#### FEDERAL COMMUNICATIONS COMMISSION (FCC) STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, Pursuant to Part 15 the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

#### **WARNING:**

You are cautioned that changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

#### INFORMATION FOR OPTICAL POINTING DEVICES ONLY:

This product has been tested to comply with international Standard IEC 60825-1:(1993), incid. Amd.2(2001). This product uses LEDs that are inherently Class 1.

Class 1 LED Product

# **Product Specification**

Frequency: 2402MHz ~ 2478 MHz (77 channel)

Modulation Type: DSSS

Frequency Deviation: 125 KHz

Power rated: 3V (Keyboard) / 3V (Mouse) / 5V (Dongle)

Battery: Keyboard – 2 pieces of AAA Batteries

Mouse – 2 pieces of AAA Batteries

**Operation distance:** Keyboard – 10M without signal disturbance and no

direction limit

Mouse – 10M without signal disturbance and no

direction limit

Mouse resolution: 800 DPI

Operating temperature:  $0^{\circ}\text{C} \sim +40^{\circ}\text{C}$ Storage temperature:  $-40^{\circ}\text{C} \sim +65^{\circ}\text{C}$ 

# **Getting Start**

## 1. Thanks for purchasing this product

This product used the latest wireless 2.4GHz solution and the most advanced optical sensor to detect the cursor movement, position and rapid.

## 2.System Requirement:

IBM PC compatible

#### 3. Important information

Before you use this product, please read the user manual in this product to avoid and reduce the operating harm of your wrist.

All the parts in keyboard, mouse and dongle are completely meet the international safety requirement. Please use this product from 0 degree to 40 degrees in Celsius (F32-F104 degrees).

Please do not disassemble the keyboard, mouse and dongle yourself or might cause you in danger.

### 4. Connect keyboard, mouse and dongle

When plug the dongle into USB port and make sure the dongle can be recognized, keep pressing the connection button for around 5 seconds, you can see the blue led twinkling. That means the keyboard had been connected with dongle and you can press windows key on the keyboard to make sure the keyboard functional or not.

After that, please keep pressing the connection button for around 5 seconds, you can see the blue led twinkling and it means the mouse had been connected with the dongle. (System requirement: Windows 98 or above, need Mac OS8.6 or updated version.)

### **Trouble shooting and Tips**

When the keyboard or mouse do not operate normally or are not recognized.

- \* Make sure the dongle is plugged into USB port already.
- \*Make sure the batteries are not too weak.

If you still can not use this product, please plug out the dongle and plug in the dongle again.