



LTE Band 48, Channel Bandwidth 15MHz

Channel 56665 (3692.50MHz)


Frequency Range : 9kHz ~ 1GHz



Frequency Range : 1GHz ~ 18GHz



Frequency Range : 18GHz ~ 40GHz




Note: The signal at 9 kHz is IF signal from spectrum analyzer.

LTE Band 48, Channel Bandwidth 20MHz
Channel 55340 (3560.0MHz)

1RB



Full RB



Channel 55990 (3625.0MHz)

1RB




Full RB



Channel 56640 (3690.0MHz)

1RB




Full RB




LTE Band 48, Channel Bandwidth 20MHz

Channel 55340 (3560.0MHz)


Frequency Range : 9kHz ~ 1GHz



Frequency Range : 1GHz ~ 18GHz



Frequency Range : 18GHz ~ 40GHz




Note: The signal at 9 kHz is IF signal from spectrum analyzer.


LTE Band 48, Channel Bandwidth 20MHz

Channel 55990 (3625.0MHz)


Frequency Range : 9kHz ~ 1GHz



Frequency Range : 1GHz ~ 18GHz



Frequency Range : 18GHz ~ 40GHz




Note: The signal at 9 kHz is IF signal from spectrum analyzer.


LTE Band 48, Channel Bandwidth 20MHz

Channel 56640 (3690.0MHz)


Frequency Range : 9kHz ~ 1GHz



Frequency Range : 1GHz ~ 18GHz



Frequency Range : 18GHz ~ 40GHz



Note: The signal at 9 kHz is IF signal from spectrum analyzer.


4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement


The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz .

4.7.2 Test Set Up

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.7.4 Test Procedures

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5 and 5.2.7
 - $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
 - $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

Test was done with 50ohm terminator on antenna port.

Below 1GHz Data


LTE Band 48, Channel Bandwidth 20MHz

| | | | |
|--------------------------|---------------------------------|-----------------|----------------|
| Mode | TX channel 55990 (3625.0MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 30.00 | -54.95 | -40.00 | -14.95 | 2.00 H | 37 | 50.63 | -105.58 |
| 2 | 79.47 | -50.82 | -40.00 | -10.82 | 1.00 H | 280 | 57.53 | -108.35 |
| 3 | 160.95 | -49.64 | -40.00 | -9.64 | 1.50 H | 110 | 53.91 | -103.55 |
| 4 | 250.19 | -53.96 | -40.00 | -13.96 | 1.00 H | 193 | 49.95 | -103.91 |
| 5 | 368.53 | -59.13 | -40.00 | -19.13 | 1.25 H | 120 | 41.37 | -100.50 |
| 6 | 551.86 | -59.96 | -40.00 | -19.96 | 1.00 H | 4 | 37.15 | -97.11 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$.
4. The other EIRP levels were very low against the limit.




| | | | |
|--------------------------|---------------------------------|-----------------|----------------|
| Mode | TX channel 55990 (3625.0MHz) | Frequency Range | Below 1000 MHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
|---|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 34.85 | -48.91 | -40.00 | -8.91 | 1.50 V | 63 | 56.57 | -105.48 |
| 2 | 65.89 | -54.50 | -40.00 | -14.50 | 1.00 V | 149 | 50.89 | -105.39 |
| 3 | 144.46 | -54.37 | -40.00 | -14.37 | 1.25 V | 115 | 49.46 | -103.83 |
| 4 | 164.83 | -53.88 | -40.00 | -13.88 | 2.00 V | 169 | 49.79 | -103.67 |
| 5 | 366.59 | -56.48 | -40.00 | -16.48 | 1.00 V | 169 | 44.08 | -100.56 |
| 6 | 426.73 | -46.11 | -40.00 | -6.11 | 1.50 V | 353 | 53.21 | -99.32 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.



Above 1GHz

LTE Band 48, Channel Bandwidth 5MHz

| | | | |
|--------------------------|---------------------------------|-----------------|--------------|
| Mode | TX channel 55265 (3552.5MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7105.00 | -44.58 | -40.00 | -4.58 | 1.16 H | 197 | 43.24 | -87.82 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7105.00 | -45.85 | -40.00 | -5.85 | 2.51 V | 84 | 41.97 | -87.82 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.

| | | | |
|--------------------------|---------------------------------|-----------------|--------------|
| Mode | TX channel 55990 (3625.0MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7250.00 | -44.19 | -40.00 | -4.19 | 1.12 H | 203 | 43.12 | -87.31 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7250.00 | -45.87 | -40.00 | -5.87 | 2.51 V | 80 | 41.44 | -87.31 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.

4. The other EIRP levels were very low against the limit.

| | | | |
|--------------------------|---------------------------------|-----------------|--------------|
| Mode | TX channel 56715 (3697.5MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7395.00 | -43.92 | -40.00 | -3.92 | 1.18 H | 197 | 43.29 | -87.21 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7395.00 | -45.20 | -40.00 | -5.20 | 2.47 V | 83 | 42.01 | -87.21 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m).$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.

LTE Band 48, Channel Bandwidth 20MHz

| | | | |
|--------------------------|---------------------------------|-----------------|--------------|
| Mode | TX channel 55340 (3560.0MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7120.00 | -44.32 | -40.00 | -4.32 | 1.12 H | 196 | 43.46 | -87.78 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7120.00 | -46.51 | -40.00 | -6.51 | 2.51 V | 78 | 41.27 | -87.78 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m).$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.

| | | | |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode | TX channel 55990 (3625.00MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7250.00 | -43.32 | -40.00 | -3.32 | 1.09 H | 200 | 43.99 | -87.31 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7250.00 | -45.04 | -40.00 | -5.04 | 2.42 V | 82 | 42.27 | -87.31 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m).$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.

| | | | |
|--------------------------|----------------------------------|-----------------|--------------|
| Mode | TX channel 56640 (3690.00MHz) | Frequency Range | 1GHz ~ 40GHz |
| Environmental Conditions | 22deg. C, 66%RH | Input Power | 120Vac, 60Hz |
| Tested By | Rex Wang | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|------------|-------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7380.00 | -43.82 | -40.00 | -3.82 | 1.19 H | 200 | 43.43 | -87.25 |
| Antenna Polarity & Test Distance : Vertical at 3m | | | | | | | | |
| No | Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 7380.00 | -45.29 | -40.00 | -5.29 | 2.42 V | 81 | 41.96 | -87.25 |

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value.
4. The other EIRP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---