

FCC Test Report

Equipment : ASUS Tablet
Marketing Name : ASUS Transformer Pad
Brand Name : ASUS
Model No. : K010
FCC ID : MSQK010
Standard : 47 CFR FCC Part 15.247
Operating Band : 5725 MHz – 5850 MHz
FCC Classification : DTS
Applicant : ASUSTeK COMPUTER INC.
4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN
Manufacturer : See section 1.1.1 for more details

The product sample received on Mar. 13, 2014 and completely tested on Mar. 19, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:


James Fan / Assistant Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	8
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	12
3.1	AC Power-line Conducted Emissions	12
3.2	6dB Bandwidth	15
3.3	RF Output Power.....	17
3.4	Power Spectral Density	21
3.5	Emissions in non-restricted frequency bands	23
3.6	Transmitter Radiated Unwanted Emissions	32
4	TEST EQUIPMENT AND CALIBRATION DATA	53

Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.3	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]:0.447MHz 46.93 (Margin 5.43dB) - AV 56.93 (Margin 12.11dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth [MHz] 20M:14.49 / 40M:35.13	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]: 11a: 21.09 HT20: 19.78 HT40: 19.82	Power [dBm]:30	Complied
3.4	15.247(d)	Power Spectral Density	PSD [dBm/3kHz]:-12.41	PSD [dBm/3kHz]:8	Complied
3.5	15.247(c)	Emissions in non-restricted frequency bands	Out-of -band emissions are 20dB below the highest power	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(c)	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 900.09MHz 37.93 (Margin 8.07dB) - PK	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



SPORTON INTERNATIONAL INC.
TEL : 886-3-3273456
FAX : 886-3-3270973

1 General Description

1.1 Information

1.1.1 Manufacturer Information

Manufacturer1	: PROTEK (SHANGHAI) LTD 3768 XIU YAN RD KANG QIAO TOWN PU DONG NEW District , Shanghai, China
Manufacturer2	: TECH-COM (SHANGHAI) COMPUTER CO., LTD 68 SANZHUANG RD, SONGJIANG EXPORT PROCESSING ZONE, SHANGHAI 201613, CHINA
Manufacturer3	: DIGITEK (CHONGQING)LIMITED B01,SECTION C, AIRPORT FUNCTION ZONE,LIANGLU CUNTAN FREE TRADE PORT AREA, YUBEI DISTRICT CHONGQING CITY, CHINA
Manufacturer4	: WISTRON INFOCOMM (SUNSHAN) CO LTD FIRST AVE KUNSHAN INTEGRATED FREE TRADE ZONE KUNSHAN JIANGSU CHINA
Manufacturer5	: COTEK ELECTRONICS (KUZHO) CO LTD 288 MAYUN RD NEW DISTRICT SUZHOU JIANGSU 215011 CHINA
Manufacturer6	: TECH-FRONT (CHONGQING)COMPUTER CO LTD 18,ZONGBAO ROAD, SHAPINGBA DISTRICT, CHONGQING, CHINA
Manufacturer7	: WISTRON INFOCOMM(CHONGQING)CO LTD No. 18-9 baohong Avenue, Wangjia Sub-district, Yubei District, Chongqing, China

1.1.2 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)	Co-location
5725-5850	a	5745-5825	149-165 [5]	1	21.09	N/A
5725-5850	n (HT20)	5745-5825	149-165 [5]	1	19.78	N/A
5725-5850	n (HT40)	5755-5795	151-159 [2]	1	19.82	N/A
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation. Note 3: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)						

1.1.3 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input type="checkbox"/>	External antenna (dedicated antennas)
<input type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).
<input type="checkbox"/>	RF connector provided
<input type="checkbox"/>	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
<input type="checkbox"/>	Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	Integral	PIFA	1.23

1.1.4 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
<input type="checkbox"/>	Other:

1.1.5 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 94.33% - IEEE 802.11a	0.25
<input checked="" type="checkbox"/> 93.99% - IEEE 802.11n (HT20)	0.27
<input checked="" type="checkbox"/> 88.56% - IEEE 802.11n (HT40)	0.53

1.1.6 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> Battery

1.2 Accessories

Accessories				
No.	Equipment	Brand Name	Model Name	Remarks
1	AC Adapter 1	ASUS	PSM06A-050Q	I/P: 100-240Vac, 0.25A O/P: 5.2Vdc, 1.35A
2	AC Adapter 2	ASUS	PA-1070-07	I/P: 100-240Vac, 0.25A O/P: 5.2Vdc, 1.35A
3	USB cable	ASUS	---	0.97m shielding cable
4	Battery	ASUS	C11P1328	Power Rating: 3.75Vdc or 3.7Vdc 19Wh

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2009
- ♦ FCC KDB 558074
- ♦ FCC KDB 662911
- ♦ FCC KDB 412172

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	Sporton Lab	ADD : No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.		
		TEL : 886-3-327-3456	FAX : 886-3-327-0973	
<input checked="" type="checkbox"/>	ICC Lab	ADD : No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)		
		TEL : 886-3-271-8666	FAX : 886-3-318-0155	
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Mark Liao	21°C / 62%	Mar. 17, 2014
AC Conduction*	CO01-WS	Skys Huang	19°C / 65%	Mar. 17, 2014
Radiated Emission*	03CH02-WS	Skys Huang	20°C / 64%	Mar. 13 ~ 19, 2014

Note: * Sporton Lab subcontracts this test item to ICC lab (TAF:2732).

ICC lab is a TAF accreditation test firm and also is an approved provider of Sporton Lab.

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.26 dB	N/A
Emission bandwidth, 6dB bandwidth		±1.42 %	N/A
RF output power, conducted		±0.63 dB	N/A
Power density, conducted		±0.81 dB	N/A
All emissions, radiated	30 – 1000 MHz	±3.90 dB	N/A
	1 – 25 GHz	±4.20 dB	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11a,6-54Mbps	1	6-54 Mbps	6 Mbps
HT20,M0-7	1	M0-7	MCS 0
HT40,M0-7	1	M0-7	MCS 0




2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (5725-5850MHz band)							
Test Software Version	adb command, version: 1.0.31						
Modulation Mode	N _{TX}	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		5745	5785	5825	5755	5795	-
11a,6-54Mbps	1	12.5	12.5	12.5	--	--	--
HT20,M0-7	1	10.5	10.5	10.5	--	--	--
HT40,M0-7	1	--	--	--	10.5	10.5	--


2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	AC Power & Radio link (WLAN)
Note: Adapter 1 and Adapter 2 had been pretested and found that Adapter 1 was the worst case and was selected for final testing (Adapter 1: PSM06A-050Q; Adapter 2: PA-1070-07).	

The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, Power Spectral Density, 6 dB Bandwidth
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11a, HT20, HT40

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
User Position	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst planes is Z.		
	<input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst planes is X.		
Operating Mode	<input checked="" type="checkbox"/> 1. AC Power & Radio link (WLAN)		
Modulation Mode	11a, HT20, HT40		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Note: Adapter 1 and Adapter 2 had been pretested and found that Adapter 1 was the worst case and was selected for final testing (Adapter 1: PSM06A-050Q; Adapter 2: PA-1070-07).			

2.4 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup




3.1.5 Test Result of AC Power-line Conducted Emissions



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	AC Power & Radio link (WLAN)		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1*	0.447	41.50	46.93	-5.43	40.90	0.55	0.05	Average
2	0.447	44.82	56.93	-12.11	44.22	0.55	0.05	QP
3	0.489	24.41	46.19	-21.78	23.79	0.57	0.05	Average
4	0.489	38.30	56.19	-17.89	37.68	0.57	0.05	QP
5	1.276	30.40	46.00	-15.60	29.49	0.83	0.08	Average
6	1.276	34.12	56.00	-21.88	33.21	0.83	0.08	QP
7	2.809	20.06	46.00	-25.94	18.82	1.04	0.20	Average
8	2.809	35.26	56.00	-20.74	34.02	1.04	0.20	QP
9	5.867	21.70	50.00	-28.30	20.18	1.33	0.19	Average
10	5.867	27.63	60.00	-32.37	26.11	1.33	0.19	QP
11	26.139	19.56	50.00	-30.44	16.93	2.13	0.50	Average
12	26.139	28.95	60.00	-31.05	26.32	2.13	0.50	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
<input checked="" type="checkbox"/>	6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/>	Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input type="checkbox"/>	Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result										
Condition			Emission Bandwidth (MHz)							
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth				6dB Bandwidth			
			Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4	Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4
11a	1	5745	16.53	--	--	--	15.13	--	--	--
11a	1	5785	16.50	--	--	--	15.71	--	--	--
11a	1	5825	16.50	--	--	--	15.13	--	--	--
HT20	1	5745	17.47	--	--	--	14.49	--	--	--
HT20	1	5785	17.47	--	--	--	14.96	--	--	--
HT20	1	5825	17.51	--	--	--	15.13	--	--	--
HT40	1	5755	36.27	--	--	--	35.13	--	--	--
HT40	1	5795	36.21	--	--	--	35.13	--	--	--
Limit			N/A				≥500 kHz			
Result			Complied							
Note 1: N _{TX} = Number of Transmit Chains										



3.3 RF Output Power

3.3.1 RF Output Power Limit

RF Output Power Limit	
Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit	
<input checked="" type="checkbox"/> 5725-5850 MHz Band:	
<input checked="" type="checkbox"/>	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/>	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30$ dBm
e.i.r.p. Power Limit:	
<input checked="" type="checkbox"/> 5725-5850 MHz Band	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): N/A
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm.	

RF Output Power Limit - IC	
Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit and e.i.r.p.	
<input checked="" type="checkbox"/> 5725-5850 MHz Band:	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{Out} \leq 30$ dBm (1 W); $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): If $P_{eirp} > 36$ dBm, $G_{TX} \leq P_{Out}$
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Maximum Peak Conducted Output Power
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.2 Option 2 (integrated band power method).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.3 Option 2 (peak power meter for VBW ≥ DTS BW)
<input checked="" type="checkbox"/>	Maximum Conducted Output Power (For reference only)
	[duty cycle ≥ 98% or external video / power trigger]
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
	RF power meter and average over on/off periods with duty factor or gated trigger
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.3 Method AVGPM (using an RF average power meter).
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup



3.3.5 Directional Gain for Power Measurement

Directional Gain (DG) Result					
Transmit Chains No.		1	--	--	--
Maximum G _{ANT} (dBi)		1.23	--	--	--
Modulation Mode	DG (dBi)	N _{TX}	N _{SS} (Min.)	STBC	Array Gain (dB)
11a,6-54Mbps	1.23	1	1	-	-
HT20,M0-7	1.23	1	1	-	-
HT40,M0-7	1.23	1	1	-	-

3.3.6 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result											
Condition			RF Output Power (dBm)								
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11a	1	5745	21.05	--	--	--	21.05	30.00	1.23	22.28	36.00
11a	1	5785	21.09	--	--	--	21.09	30.00	1.23	22.32	36.00
11a	1	5825	21.03	--	--	--	21.03	30.00	1.23	22.26	36.00
HT20	1	5745	19.64	--	--	--	19.64	30.00	1.23	20.87	36.00
HT20	1	5785	19.78	--	--	--	19.78	30.00	1.23	21.01	36.00
HT20	1	5825	19.62	--	--	--	19.62	30.00	1.23	20.85	36.00
HT40	1	5755	19.82	--	--	--	19.82	30.00	1.23	21.05	36.00
HT40	1	5795	19.74	--	--	--	19.74	30.00	1.23	20.97	36.00
Result			Complied								

3.3.7 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power											
Condition			RF Output Power (dBm)								
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11a	1	5745	11.90	--	--	--	11.90	30.00	1.23	13.13	36.00
11a	1	5785	11.94	--	--	--	11.94	30.00	1.23	13.17	36.00
11a	1	5825	11.84	--	--	--	11.84	30.00	1.23	13.07	36.00
HT20	1	5745	9.68	--	--	--	9.68	30.00	1.23	10.91	36.00
HT20	1	5785	9.70	--	--	--	9.70	30.00	1.23	10.93	36.00
HT20	1	5825	9.52	--	--	--	9.52	30.00	1.23	10.75	36.00
HT40	1	5755	9.98	--	--	--	9.98	30.00	1.23	11.21	36.00
HT40	1	5795	9.95	--	--	--	9.95	30.00	1.23	11.18	36.00
Result			Complied								

Note: Maximum conducted output power is for reference only.

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
<input checked="" type="checkbox"/>	Power Spectral Density (PSD) \leq 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak).. [duty cycle \geq 98% or external video / power trigger]
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.3 Method AVGPS-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.4 Method AVGPS-1 Alt. (slow sweep speed) duty cycle < 98% and average over on/off periods with duty factor
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.5 Method AVGPS-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.6 Method AVGPS-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N _{TX} output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/>	Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result								
Condition			Power Spectral Density (dBm/3kHz)					
Modulation Mode	N _{TX}	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit
11a	1	5745	-12.66	-	-	-	-12.66	8
11a	1	5785	-12.41	-	-	-	-12.41	8
11a	1	5825	-13.49	-	-	-	-13.49	8
HT20	1	5745	-15.76	-	-	-	-15.76	8
HT20	1	5785	-15.04	-	-	-	-15.04	8
HT20	1	5825	-15.23	-	-	-	-15.23	8
HT40	1	5755	-17.96	-	-	-	-17.96	8
HT40	1	5795	-17.14	-	-	-	-17.14	8
Result			Complied					



3.5 Emissions in non-restricted frequency bands

3.5.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.5.4 Test Setup




3.5.5 Test Result of Emissions in non-restricted frequency bands


802.11a





Reference Level




Tx 5785MHz / 30MHz~40GHz (down 20dBc)










Reference Level




Tx 5825MHz / 30MHz~40GHz (down 20dBc)









HT20





Reference Level




Tx 5785MHz / 30MHz~40GHz (down 20dBc)










Reference Level




Tx 5825MHz / 30MHz~40GHz (down 20dBc)








HT40





3.6 Transmitter Radiated Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$).
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/>	For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.6 for radiated emissions from above 1 GHz.
<input type="checkbox"/>	For conducted and cabinet radiation measurement, refer as FCC KDB 558074, clause 12.2.2.
<input type="checkbox"/>	For conducted unwanted emissions into non-restricted bands (relative emission limits). Devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.
<input type="checkbox"/>	For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB

3.6.4 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)


All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)																																																																															
Modulation Mode	11a				Test Freq. (MHz)		5785																																																																								
Polarization	V																																																																														
<div><div><div>Level (dBuV/m)</div><div></div><div>Frequency (MHz)</div></div><table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>49.40</td><td>30.84</td><td>40.00</td><td>-9.16</td><td>47.17</td><td>-16.33</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>80.44</td><td>26.75</td><td>40.00</td><td>-13.25</td><td>48.38</td><td>-21.63</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>412.18</td><td>29.08</td><td>46.00</td><td>-16.92</td><td>42.50</td><td>-13.42</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>533.43</td><td>28.46</td><td>46.00</td><td>-17.54</td><td>39.42</td><td>-10.96</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>600.36</td><td>33.45</td><td>46.00</td><td>-12.55</td><td>43.02</td><td>-9.57</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>1000.00</td><td>35.68</td><td>54.00</td><td>-18.32</td><td>40.32</td><td>-4.64</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table></div>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	49.40	30.84	40.00	-9.16	47.17	-16.33	Peak	---	---	2	80.44	26.75	40.00	-13.25	48.38	-21.63	Peak	---	---	3	412.18	29.08	46.00	-16.92	42.50	-13.42	Peak	---	---	4	533.43	28.46	46.00	-17.54	39.42	-10.96	Peak	---	---	5	600.36	33.45	46.00	-12.55	43.02	-9.57	Peak	---	---	6	1000.00	35.68	54.00	-18.32	40.32	-4.64	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	49.40	30.84	40.00	-9.16	47.17	-16.33	Peak	---	---																																																																						
2	80.44	26.75	40.00	-13.25	48.38	-21.63	Peak	---	---																																																																						
3	412.18	29.08	46.00	-16.92	42.50	-13.42	Peak	---	---																																																																						
4	533.43	28.46	46.00	-17.54	39.42	-10.96	Peak	---	---																																																																						
5	600.36	33.45	46.00	-12.55	43.02	-9.57	Peak	---	---																																																																						
6	1000.00	35.68	54.00	-18.32	40.32	-4.64	Peak	---	---																																																																						
<div>Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</div> <div>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</div> <div>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</div>																																																																															

Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
Polarization	H		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	80.44	23.03	40.00	-16.97	44.66	-21.63	Peak	---	---
2	158.04	29.85	43.50	-13.65	46.57	-16.72	Peak	---	---
3	412.18	31.77	46.00	-14.23	45.19	-13.42	Peak	---	---
4	600.36	35.61	46.00	-10.39	45.18	-9.57	Peak	---	---
5	900.09	37.93	46.00	-8.07	43.46	-5.53	Peak	---	---
6	963.14	34.39	54.00	-19.61	39.35	-4.96	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11a				Test Freq. (MHz)	5745			
N _{TX}	1				Polarization	V			




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.96	54.00	-19.04	41.43	-6.47	Average	---	---
2	1500.00	48.33	74.00	-25.67	54.80	-6.47	Peak	---	---
3	7660.00	41.87	54.00	-12.13	30.76	11.11	Average	---	---
4	7660.00	54.93	74.00	-19.07	43.82	11.11	Peak	---	---
5	11490.00	43.22	54.00	-10.78	28.02	15.20	Average	---	---
6	11490.00	56.58	74.00	-17.42	41.38	15.20	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5745
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	33.88	54.00	-20.12	40.35	-6.47	Average	---	---
2	1500.00	46.72	74.00	-27.28	53.19	-6.47	Peak	---	---
3	7660.00	40.33	54.00	-13.67	29.22	11.11	Average	---	---
4	7660.00	54.12	74.00	-19.88	43.01	11.11	Peak	---	---
5	11490.00	42.55	54.00	-11.45	27.35	15.20	Average	---	---
6	11490.00	55.86	74.00	-18.14	40.66	15.20	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N_{TX}	1	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.79	54.00	-19.21	41.26	-6.47	Average	---	---
2	1500.00	48.05	74.00	-25.95	54.52	-6.47	Peak	---	---
3	7713.30	41.40	54.00	-12.60	30.33	11.07	Average	---	---
4	7713.30	54.64	74.00	-19.36	43.57	11.07	Peak	---	---
5	11570.00	43.05	54.00	-10.95	27.90	15.15	Average	---	---
6	11570.00	56.31	74.00	-17.69	41.16	15.15	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N _{TX}	1	Polarization	H



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	33.42	54.00	-20.58	39.89	-6.47	Average	---	---
2	1500.00	46.28	74.00	-27.72	52.75	-6.47	Peak	---	---
3	7713.30	40.02	54.00	-13.98	28.95	11.07	Average	---	---
4	7713.30	53.82	74.00	-20.18	42.75	11.07	Peak	---	---
5	11570.00	42.91	54.00	-11.09	27.76	15.15	Average	---	---
6	11570.00	56.12	74.00	-17.88	40.97	15.15	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825
N_{TX}	1	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.57	54.00	-20.43	43.16	-9.59	Average	---	---
2	1031.00	46.59	74.00	-27.41	56.18	-9.59	Peak	---	---
3	1500.00	34.54	54.00	-19.46	41.01	-6.47	Average	---	---
4	1500.00	47.85	74.00	-26.15	54.32	-6.47	Peak	---	---
5	11650.00	43.33	54.00	-10.67	28.22	15.11	Average	---	---
6	11650.00	56.73	74.00	-17.27	41.62	15.11	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.86	54.00	-20.14	43.45	-9.59	Average	---	---
2	1031.00	46.79	74.00	-27.21	56.38	-9.59	Peak	---	---
3	1500.00	33.84	54.00	-20.16	40.31	-6.47	Average	---	---
4	1500.00	46.58	74.00	-27.42	53.05	-6.47	Peak	---	---
5	11650.00	43.18	54.00	-10.82	28.07	15.11	Average	---	---
6	11650.00	56.53	74.00	-17.47	41.42	15.11	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT20				Test Freq. (MHz)	5745			
N _{TX}	1				Polarization	V			




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.97	54.00	-19.03	41.44	-6.47	Average	---	---
2	1500.00	48.15	74.00	-25.85	54.62	-6.47	Peak	---	---
3	7660.00	41.82	54.00	-12.18	30.71	11.11	Average	---	---
4	7660.00	54.89	74.00	-19.11	43.78	11.11	Peak	---	---
5	11490.00	42.83	54.00	-11.17	27.63	15.20	Average	---	---
6	11490.00	55.79	74.00	-18.21	40.59	15.20	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5745
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	33.83	54.00	-20.17	40.30	-6.47	Average	---	---
2	1500.00	46.84	74.00	-27.16	53.31	-6.47	Peak	---	---
3	7660.00	40.30	54.00	-13.70	29.19	11.11	Average	---	---
4	7660.00	54.09	74.00	-19.91	42.98	11.11	Peak	---	---
5	11490.00	42.83	54.00	-11.17	27.63	15.20	Average	---	---
6	11490.00	55.91	74.00	-18.09	40.71	15.20	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5785
N _{TX}	1	Polarization	V



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.39	54.00	-19.61	40.86	-6.47	Average	---	---
2	1500.00	47.69	74.00	-26.31	54.16	-6.47	Peak	---	---
3	7713.30	41.35	54.00	-12.65	30.28	11.07	Average	---	---
4	7713.30	54.31	74.00	-19.69	43.24	11.07	Peak	---	---
5	11570.00	42.59	54.00	-11.41	27.44	15.15	Average	---	---
6	11570.00	55.93	74.00	-18.07	40.78	15.15	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5785
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	33.29	54.00	-20.71	39.76	-6.47	Average	---	---
2	1500.00	46.65	74.00	-27.35	53.12	-6.47	Peak	---	---
3	7713.30	39.84	54.00	-14.16	28.77	11.07	Average	---	---
4	7713.30	53.72	74.00	-20.28	42.65	11.07	Peak	---	---
5	11570.00	42.82	54.00	-11.18	27.67	15.15	Average	---	---
6	11570.00	55.73	74.00	-18.27	40.58	15.15	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5825
N_{TX}	1	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.67	54.00	-20.33	43.26	-9.59	Average	---	---
2	1031.00	46.35	74.00	-27.65	55.94	-9.59	Peak	---	---
3	1500.00	34.71	54.00	-19.29	41.18	-6.47	Average	---	---
4	1500.00	48.21	74.00	-25.79	54.68	-6.47	Peak	---	---
5	11650.00	42.55	54.00	-11.45	27.44	15.11	Average	---	---
6	11650.00	55.84	74.00	-18.16	40.73	15.11	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5825
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.60	54.00	-20.40	43.19	-9.59	Average	---	---
2	1031.00	46.28	74.00	-27.72	55.87	-9.59	Peak	---	---
3	1500.00	33.94	54.00	-20.06	40.41	-6.47	Average	---	---
4	1500.00	46.74	74.00	-27.26	53.21	-6.47	Peak	---	---
5	11650.00	42.57	54.00	-11.43	27.46	15.11	Average	---	---
6	11650.00	55.84	74.00	-18.16	40.73	15.11	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

3.6.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40				Test Freq. (MHz)	5755			
N _{TX}	1				Polarization	V			




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.93	54.00	-20.07	43.52	-9.59	Average	---	---
2	1031.00	46.66	74.00	-27.34	56.25	-9.59	Peak	---	---
3	1500.00	34.88	54.00	-19.12	41.35	-6.47	Average	---	---
4	1500.00	48.29	74.00	-25.71	54.76	-6.47	Peak	---	---
5	11510.00	43.39	54.00	-10.61	28.21	15.18	Average	---	---
6	11510.00	55.56	74.00	-18.44	40.38	15.18	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5755
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.94	54.00	-20.06	43.53	-9.59	Average	---	---
2	1031.00	47.20	74.00	-26.80	56.79	-9.59	Peak	---	---
3	1500.00	34.07	54.00	-19.93	40.54	-6.47	Average	---	---
4	1500.00	46.32	74.00	-27.68	52.79	-6.47	Peak	---	---
5	11510.00	43.34	54.00	-10.66	28.16	15.18	Average	---	---
6	11510.00	55.59	74.00	-18.41	40.41	15.18	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5795
N_{TX}	1	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.86	54.00	-20.14	43.45	-9.59	Average	---	---
2	1031.00	47.20	74.00	-26.80	56.79	-9.59	Peak	---	---
3	1500.00	34.91	54.00	-19.09	41.38	-6.47	Average	---	---
4	1500.00	48.38	74.00	-25.62	54.85	-6.47	Peak	---	---
5	11590.00	43.50	54.00	-10.50	28.36	15.14	Average	---	---
6	11590.00	55.71	74.00	-18.29	40.57	15.14	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5795
N_{TX}	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1031.00	33.86	54.00	-20.14	43.45	-9.59	Average	---	---
2	1031.00	47.24	74.00	-26.76	56.83	-9.59	Peak	---	---
3	1500.00	33.84	54.00	-20.16	40.31	-6.47	Average	---	---
4	1500.00	46.16	74.00	-27.84	52.63	-6.47	Peak	---	---
5	11590.00	43.56	54.00	-10.44	28.42	15.14	Average	---	---
6	11590.00	55.55	74.00	-18.45	40.41	15.14	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

4 Test Equipment and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Amplifier	Burgen	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014
Amplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014
control	EM Electronics	EM1000	060608	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Amplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2015
Note: Calibration Interval of instruments listed above is two year.					

Test Item	RF Conducted				
Test Site	TH01-HY				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV 40	101013	Jan. 25, 2014	Jan. 24, 2015
AC Power Source	G.W	APS-9102	EL920581	Jul. 16, 2013	Jul. 15, 2014
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	Nov. 20, 2013	Nov. 19, 2014
Signal Generator	R&S	SMR40	100116	Jun. 27, 2013	Jun. 26, 2014
Power Sensor	Anritsu	MA2411B	0917017	Jan. 28, 2014	Jan. 27, 2015
Power Meter	Anritsu	ML2495A	0949003	Jan. 28, 2014	Jan. 27, 2015
RF Cable-2m	HUBER+SUHNER	SUCOFLEX_104	SN 345675/4	Dec. 02, 2013	Dec. 01, 2014
RF Cable-3m	HUBER+SUHNER	SUCOFLEX_104	SN 345669/4	Dec. 02, 2013	Dec. 01, 2014
Note: Calibration Interval of instruments listed above is one year.					