



FCC Test Report

Equipment : ASUS Tablet
Brand Name : ASUS
Model No. : K013
FCC ID : MSQK013
Standard : 47 CFR FCC Part 15.247
Operating Band : 2400 MHz – 2483.5 MHz
Equipment Class : DTS
Applicant : ASUSTeK COMPUTER INC.
4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan
Manufacturer : PEGATRON CORPORATION
No. 76, Ligong St., Beitou District, Taipei City 112
COTEK ELECTRONICS (SUZHOU) CO LTD
No. 288, MaYun Rd, Suzhou, Jiangsu, PRC
zipcode:215011
WISTRON INFOCOMM (KUNSHAN) CO LTD
No.168 First Avenue, Jiangsu Province, comprehensive
free Trade Zone, Kunshan, Suzhou China
TECH-COM(SHANGHAI) COMPUTER CO. LTD
68 SANZHUANG RD, SONGJIANG EXPORT
PROCESSING ZONE, SHANGHAI 201613, CHINA

The product sample received on Feb. 27, 2014 and completely tested on Mar. 13, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:


Wayne Hsu / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter.....	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	6dB Bandwidth	16
3.3	RF Output Power.....	18
3.4	Power Spectral Density	22
3.5	Transmitter Bandedge Emissions	24
3.6	Transmitter Unwanted Emissions.....	27
4	TEST EQUIPMENT AND CALIBRATION DATA	50

APPENDIX A. TEST PHOTOS

APPENDIX B. PHOTOGRAPHS OF EUT



Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.4941090MHz 39.12 (Margin 6.98dB) - AV 44.28 (Margin 11.82dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	Bandwidth	6dB Bandwidth Unit [MHz]: 7.09	\geq 500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]: 17.92	Power [dBm]:30	Complied
3.4	15.247(d)	Power Spectral Density	PSD [dBm/100kHz]: -10.64	PSD [dBm/3kHz]:8	Complied
3.5	15.247(c)	Transmitter Radiated Bandedge Emissions	Non-Restricted Bands: 2399.94MHz: 34.05dB Restricted Bands [dBuV/m at 3m]: 2483.50MHz 68.96 (Margin 5.04dB) - PK 52.63 (Margin 1.371dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(c)	Transmitter Radiated Unwanted Emissions	[dBuV/m at 3m]: 35.820MHz 30.58 (Margin 9.42dB) - PK	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



Revision History



1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)	Co-location
2400-2483.5	b	2412-2462	1-11 [11]	1	17.82	N/A
2400-2483.5	g	2412-2462	1-11 [11]	1	17.92	N/A
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	17.82	N/A

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)

Note: The WLAN and Bluetooth didn't transmit simultaneously.

1.1.2 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	Integral	PIFA	1.19



1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input checked="" type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:	
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:	
<input type="checkbox"/> Other:	

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100% - IEEE 802.11b	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11g	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT20)	0

1.1.5 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	<input type="checkbox"/> System
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> Battery



1.2 Accessories

Accessories Information				
AC Adapter 1	Brand Name	ASUS	Model Name	PA-1070-07
	Vendor	LITE-ON		
	Power Rating	I/P: 100-240V~ 50/60Hz 0.25A ; O/P: 5.2V---1.35A		
AC Adapter 2	Brand Name	ASUS	Model Name	PSM06A-050Q
	Vendor	Phihong		
	Power Rating	I/P: 100-240V~ 50/60Hz 0.25A ; O/P: 5.2V---1.35A		
AC Adapter 3	Brand Name	ASUS	Model Name	AD2005320
	Vendor	PI		
	Power Rating	I/P: 100-240V~ 50/60Hz 0.25A ; O/P: 5.2V---1.35A		
Li-ion Battery 1	Brand Name	ASUS	Model Name	C11P1326
	Vendor	SIMPLO POLY		
	Power Rating	3.8V --- 15 Wh		
Li-ion Battery 2	Brand Name	ASUS	Model Name	C11P1326
	Vendor	CELXPERT		
	Power Rating	3.8V --- 15 Wh		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15
- ANSI C63.10-2009
- FCC KDB 558074
- FCC KDB 662911

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD	:	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
		TEL	:	886-3-327-3456 FAX : 886-3-327-0973



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty		
Test Item	Uncertainty	
AC power-line conducted emissions	±2.26 dB	
Emission bandwidth, 6dB bandwidth	±1.42 %	
RF output power, conducted	±0.63 dB	
Power density, conducted	±0.81 dB	
Unwanted emissions, conducted	9 – 150 kHz	±0.38 dB
	0.15 – 30 MHz	±0.42 dB
	30 – 1000 MHz	±0.51 dB
	1 – 18 GHz	±0.67 dB
	18 – 40 GHz	±0.83 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.49 dB
	0.15 – 30 MHz	±2.28 dB
	30 – 1000 MHz	±2.56 dB
	1 – 18 GHz	±3.59 dB
	18 – 40 GHz	±3.82 dB
	40 – 200 GHz	N/A
Temperature	±0.8 °C	
Humidity	±3 %	
DC and low frequency voltages	±3 %	
Time	±1.42 %	
Duty Cycle	±1.42 %	



2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11b,1-11Mbps	1	1-11 Mbps	1 Mbps
11g,6-54Mbps	1	6-54 Mbps	6 Mbps
HT20,M0-7	1	M0-7	MCS 0

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (2400-2483.5MHz band)					
Test Software Version	Ampak RFTestTool Ver. : 4.4				
Modulation Mode	N _{TX}	Test Frequency (MHz)			
		NCB: 20MHz			
		2412	2437	2462	
11b,1-11Mbps	1	60	60	60	
11g,6-54Mbps	1	44	52	52	
HT20,M0-7	1	48	52	52	



2.3 The Worst Case Measurement Configuration


The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	EUT via USB cable with adapter (PA-1070-07)



The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, Power Spectral Density, 6 dB Bandwidth
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11b, 11g, HT20

The Worst Case Mode for Following Conformance Tests							
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions						
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.						
User Position	<input type="checkbox"/> EUT will be placed in fixed position. <input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst planes is X. <input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.						
Operating Mode	<input checked="" type="checkbox"/> 1. EUT via USB cable with adapter (PA-1070-07)						
Modulation Mode	11b, 11g, HT20						
Orthogonal Planes of EUT	<table border="1"><thead><tr><th>X Plane</th><th>Y Plane</th><th>Z Plane</th></tr></thead><tbody><tr><td></td><td></td><td></td></tr></tbody></table>	X Plane	Y Plane	Z Plane			
X Plane	Y Plane	Z Plane					

2.4 Test Setup Diagram

Test Setup Diagram – AC Line Conducted Emission Test



Test Setup Diagram - Radiated Test (Below 1GHz)**Test Setup Diagram - Radiated Test (Above 1GHz)**

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup






3.1.5 Test Result of AC Power-line Conducted Emissions





AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line				
Operating Function	EUT via USB cable with adapter (PA-1070-07) (Transmission)						
							
Freq	Level	Over Limit	Limit	Read Line	Level	LISN Factor	Remark
MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1954980	44.88	-18.92	63.80	44.36	0.03	QP
2	0.1954980	30.99	-22.81	53.80	30.47	0.03	Average
3	0.4397440	43.87	-13.20	57.07	43.22	0.03	QP
4	0.4397440	38.90	-8.17	47.07	38.25	0.03	Average
5	0.4863180	37.10	-9.13	46.23	36.42	0.04	Average
6	0.4863180	43.06	-13.17	56.23	42.38	0.04	QP
7	0.5406800	40.92	-15.08	56.00	40.21	0.04	QP
8	0.5406800	34.81	-11.19	46.00	34.10	0.04	Average
9	0.7390970	27.43	-18.57	46.00	26.65	0.05	Average
10	0.7390970	37.86	-18.14	56.00	37.08	0.05	QP
11	0.9184250	20.99	-25.01	46.00	20.15	0.06	Average
12	0.9184250	37.61	-18.39	56.00	36.77	0.06	QP
13	20.270	24.61	-25.39	50.00	23.61	0.31	Average
14	20.270	36.26	-23.74	60.00	35.26	0.31	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<input checked="" type="checkbox"/> 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.


3.2.4 Test Setup





3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result					
Condition			Emission Bandwidth (MHz)		
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth	6dB Bandwidth	
11b	1	2412	12.20	7.18	
11b	1	2437	12.29	7.09	
11b	1	2462	12.33	7.83	
11g	1	2412	16.31	16.32	
11g	1	2437	16.28	15.07	
11g	1	2462	16.28	15.31	
HT20	1	2412	17.48	16.81	
HT20	1	2437	17.46	16.93	
HT20	1	2462	17.51	17.53	
Limit			N/A	≥500 kHz	
Result			Complied		

Note 1: N_{TX} = Number of Transmit Chains



3.3 RF Output Power

3.3.1 RF Output Power Limit

RF Output Power Limit	
Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit and e.i.r.p.	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{\text{Out}} \leq 30 \text{ dBm}$ (1 W); $P_{\text{eirp}} \leq 36 \text{ dBm}$ (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): If $P_{\text{eirp}} > 36 \text{ dBm}$, $G_{\text{TX}} \leq P_{\text{Out}}$
<input type="checkbox"/>	Smart antenna system (SAS): If $P_{\text{eirp}} > 36 \text{ dBm}$, $G_{\text{TX}} \leq P_{\text{Out}}$
	<input type="checkbox"/> Single beam: follow P2M, P2P limits
	<input type="checkbox"/> Overlap beam: follow P2M limit
	<input type="checkbox"/> Aggregate power on all beams: follow P2M limit + 8dB
P_{out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm.	

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Maximum Peak Conducted Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.1 Option 1 (RBW \geq EBW method).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.2 Option 2 (integrated band power method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.3 Option 2 (peak power meter for VBW \geq DTS BW)
<input checked="" type="checkbox"/> Maximum Conducted (Average) Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.1 Option 1 (spectral trace averaging).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.2 Option 2 (slow sweep speed).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.3 Option 3 (average power meter).
<input checked="" type="checkbox"/> For conducted measurement.	
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{\text{total}} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{\text{total}} = P_{\text{total}} + DG$



3.3.4 Test Setup






3.3.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result						
Condition			RF Output Power (dBm)			
Modulation Mode	N _{TX}	Freq. (MHz)	Output Power	Power Limit	EIRP Power	EIRP Limit
11b	1	2412	17.82	30	19.01	36
11b	1	2437	17.69	30	18.88	36
11b	1	2462	17.66	30	18.85	36
11g	1	2412	16.03	30	17.22	36
11g	1	2437	17.92	30	19.11	36
11g	1	2462	17.85	30	19.04	36
HT20	1	2412	16.89	30	18.08	36
HT20	1	2437	17.71	30	18.90	36
HT20	1	2462	17.82	30	19.01	36
Result			Complied			

3.3.6 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power						
Condition			RF Output Power (dBm)			
Modulation Mode	N _{TX}	Freq. (MHz)	Output Power	Power Limit	EIRP Power	EIRP Limit
11b	1	2412	14.70	30	15.89	36
11b	1	2437	14.74	30	15.93	36
11b	1	2462	14.63	30	15.82	36
11g	1	2412	11.04	30	12.27	36
11g	1	2437	12.84	30	14.07	36
11g	1	2462	12.79	30	14.02	36
HT20	1	2412	11.86	30	13.10	36
HT20	1	2437	12.72	30	13.96	36
HT20	1	2462	12.78	30	14.02	36
Result			Complied			





3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq 8 \text{ dBm/3kHz}$


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak).. [duty cycle $\geq 98\%$ or external video / power trigger]
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed) duty cycle $< 98\%$ and average over on/off periods with duty factor
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N_{TX} output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/> Option 2: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.

3.4.4 Test Setup




3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result				
Modulation Mode	N _{TX}	Freq. (MHz)	Power Spectral Density (dBm/100kHz)	Power Limit (dBm/3kHz)
11b	1	2412	-10.94	8
11b	1	2437	-10.69	8
11b	1	2462	-10.64	8
11g	1	2412	-15.42	8
11g	1	2437	-15.48	8
11g	1	2462	-15.28	8
HT20	1	2412	-17.54	8
HT20	1	2437	-15.77	8
HT20	1	2462	-15.19	8
Result		Complied		



3.5 Transmitter Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit




3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$)
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$).
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> For the transmitter bandedge emissions shall be measured using following options below:
<input type="checkbox"/> Refer as FCC KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2 for band-edge testing.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7 and ANSI C63.10, clause 6.6. Test distance is 3m.

3.5.4 Test Setup

Transmitter Radiated Bandedge Emissions
 <p>Electric field tests shall be performed in transmitter bandedge emissions using a calibrated horn antenna.</p>



3.5.5 Transmitter Radiated Bandedge Emissions

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Non-restricted Band)								
Modulation	N _{TX}	Test Freq. (MHz)	In-band PSD [i] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [o] (dBuV/100kHz)	[i] – [o] (dB)	Limit (dB)	Pol.
11b	1	2412	108.71	2398.14	66.31	42.4	20	V
11b	1	2462	107.43	2515.50	65.13	42.3	20	V
11g	1	2412	98.45	2395.46	64.35	34.1	20	V
11g	1	2462	101.89	2543.50	64.28	37.61	20	V
HT20	1	2412	99.24	2399.94	65.19	34.05	20	V
HT20	1	2462	101.99	2501.00	64.79	37.2	20	V

Note 1: Measurement worst emissions of receive antenna polarization

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Restricted Band)										
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11b	1	2412	3	2387.84	63.08	74	2389.97	51.33	54	V
11b	1	2462	3	2488.60	62.96	74	2487.00	50.57	54	V
11g	1	2412	3	2389.63	66.96	74	2390.00	50.70	54	V
11g	1	2462	3	2483.50	67.28	74	2483.50	52.00	54	V
HT20	1	2412	3	2389.63	70.19	74	2390.00	52.49	54	V
HT20	1	2462	3	2484.20	68.96	74	2483.50	52.63	54	V

Note 1: Measurement worst emissions of receive antenna polarization.



3.6 Transmitter Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced $VBW \geq 1/T$).
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). $VBW \geq 1/T$, where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/> All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.4 Test Setup

Transmitter Radiated Unwanted Emissions



Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna and the frequency range of 1 GHz to 40 GHz using a calibrated horn antenna.

3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)

Operating Mode	1	Polarization	V
Operating Function	EUT via USB cable with adapter (PA-1070-07) (Transmission)		

Level (dBuV/m)
Date: 2014-03-09

Freq	Level	Over Limit	Limit	Read Antenna		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				MHz	dBuV/m					
1	35.820	30.58	-9.42	40.00	41.89	15.59	0.82	27.72 Peak	---	---
2	59.100	29.39	-10.61	40.00	49.12	6.76	1.06	27.55 Peak	---	---
3	159.980	28.67	-14.83	43.50	44.24	10.16	1.83	27.56 Peak	---	---
4	622.670	28.56	-17.44	46.00	34.15	19.09	3.77	28.45 Peak	---	---
5	780.780	31.26	-14.74	46.00	35.16	19.94	4.27	28.11 Peak	---	---
6	901.060	29.25	-16.75	46.00	31.88	20.59	4.55	27.77 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.



Transmitter Radiated Unwanted Emissions (Below 1GHz)


Operating Mode	1	Polarization	H																																																																																	
Operating Function	EUT via USB cable with adapter (PA-1070-07) (Transmission)																																																																																			
Level (dBuV/m)			Date: 2014-03-09																																																																																	
			IC/IC/FCC-B																																																																																	
<table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th>Ant</th> <th>Table</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>Pos</th> <th>Pos</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>35.820</td> <td>22.06</td> <td>-17.94</td> <td>40.00</td> <td>33.37</td> <td>15.59</td> <td>0.82</td> <td>27.72</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>90.140</td> <td>17.90</td> <td>-25.60</td> <td>43.50</td> <td>35.59</td> <td>8.68</td> <td>1.34</td> <td>27.71</td> <td>Peak</td> </tr> <tr> <td>3</td> <td>137.670</td> <td>26.67</td> <td>-16.83</td> <td>43.50</td> <td>41.23</td> <td>11.39</td> <td>1.68</td> <td>27.63</td> <td>Peak</td> </tr> <tr> <td>4</td> <td>419.940</td> <td>29.38</td> <td>-16.62</td> <td>46.00</td> <td>37.57</td> <td>16.82</td> <td>3.00</td> <td>28.01</td> <td>Peak</td> </tr> <tr> <td>5</td> <td>780.780</td> <td>30.07</td> <td>-15.93</td> <td>46.00</td> <td>33.97</td> <td>19.94</td> <td>4.27</td> <td>28.11</td> <td>Peak</td> </tr> <tr> <td>6</td> <td>901.060</td> <td>28.63</td> <td>-17.37</td> <td>46.00</td> <td>31.26</td> <td>20.59</td> <td>4.55</td> <td>27.77</td> <td>Peak</td> </tr> </tbody> </table>			Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Ant	Table	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos	1	35.820	22.06	-17.94	40.00	33.37	15.59	0.82	27.72	Peak	2	90.140	17.90	-25.60	43.50	35.59	8.68	1.34	27.71	Peak	3	137.670	26.67	-16.83	43.50	41.23	11.39	1.68	27.63	Peak	4	419.940	29.38	-16.62	46.00	37.57	16.82	3.00	28.01	Peak	5	780.780	30.07	-15.93	46.00	33.97	19.94	4.27	28.11	Peak	6	901.060	28.63	-17.37	46.00	31.26	20.59	4.55	27.77	Peak	cm	deg
Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Ant	Table																																																																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos																																																																											
1	35.820	22.06	-17.94	40.00	33.37	15.59	0.82	27.72	Peak																																																																											
2	90.140	17.90	-25.60	43.50	35.59	8.68	1.34	27.71	Peak																																																																											
3	137.670	26.67	-16.83	43.50	41.23	11.39	1.68	27.63	Peak																																																																											
4	419.940	29.38	-16.62	46.00	37.57	16.82	3.00	28.01	Peak																																																																											
5	780.780	30.07	-15.93	46.00	33.97	19.94	4.27	28.11	Peak																																																																											
6	901.060	28.63	-17.37	46.00	31.26	20.59	4.55	27.77	Peak																																																																											


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.



3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Transmitter Radiated Unwanted Emissions (Above 1GHz)








Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2437
N_{TX}	1	Polarization	V



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Line	Level	Factor		Loss	Factor			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
4874.000	47.41	-26.59	74.00	43.03	34.32	4.73	34.67	Peak	---	---
4874.000	35.45	-18.55	54.00	31.07	34.32	4.73	34.67	Average	---	---
7311.000	49.61	-24.39	74.00	43.21	35.88	5.47	34.95	Peak	---	---
7311.000	37.36	-16.64	54.00	30.96	35.88	5.47	34.95	Average	---	---
9748.000	50.16			42.40	36.71	6.41	35.36	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 3: Measurement receive antenna polarization: H (horizontal), V (vertical)
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.62 dB_{UV}/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2437
N _{TX}	1	Polarization	H



Freq	Level	Over	Limit	ReadAntenna		Cable	Preamp	Ant Pos	Table Pos
		Line	dB	dB	dBuV	Factor	Loss		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4874.000	47.58	-26.42	74.00	43.20	34.32	4.73	34.67	Peak	---
2 4874.000	36.03	-17.97	54.00	31.65	34.32	4.73	34.67	Average	---
3 7311.000	49.85	-24.15	74.00	43.45	35.88	5.47	34.95	Peak	---
4 7311.000	36.47	-17.53	54.00	30.07	35.88	5.47	34.95	Average	---
5 9748.000	50.57			42.81	36.71	6.41	35.36	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.62 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (104.35 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (104.35 dBuV/m).


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2412
N_{TX}	1	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
24.000	47.49	-26.51	74.00	43.14	34.33	4.70	34.68	Peak	---	---
24.000	33.82	-20.18	54.00	29.47	34.33	4.70	34.68	Average	---	---
36.000	49.42			43.09	35.90	5.37	34.94	Peak	---	---
48.000	48.55	----	----	40.96	36.59	6.35	35.35	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 3: Measured field receive antenna polarization: H (horizontal), V (vertical)
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (108.90 dB_{UV}/m).


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
N_{TX}	1	Polarization	H



Freq	Level	Over	Limit	Read		Antenna		Cable		Preamp		Remark	Ant	Table
		Line	Limit	Level	Factor	Loss	Factor	dB	dB	cm	deg			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	cm	deg			
4874.000	48.00	-26.00	74.00	43.62	34.32	4.73	34.67	Peak		---	---			
4874.000	34.22	-19.78	54.00	29.84	34.32	4.73	34.67	Average		---	---			
7311.000	36.33	-17.67	54.00	29.93	35.88	5.47	34.95	Average		---	---			
7311.000	48.85	-25.15	74.00	42.45	35.88	5.47	34.95	Peak		---	---			
9748.000	47.63			39.87	36.71	6.41	35.36	Peak		---	---			

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected).

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.50 dB_UV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11g	Test Freq. (MHz)	2462
N _{TX}	1	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
4924.000	47.21	-26.79	74.00	42.77	34.31	4.79	34.66	Peak	---	---
4924.000	34.28	-19.72	54.00	29.84	34.31	4.79	34.66	Average	---	---
7386.000	36.55	-17.45	54.00	30.11	35.84	5.57	34.97	Average	---	---
7386.000	49.44	-24.56	74.00	43.00	35.84	5.57	34.97	Peak	---	---
9848.000	49.81			41.87	36.81	6.50	35.37	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "NF" means Nothing Found spurious emissions (No spurious emissions were detected).


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 3: Measured field receive antenna polarization: H (horizontal), V (vertical)
Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (103.43 dB_{UV}/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.








Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2437																																				
N _{TX}	1	Polarization	V																																				
Level (dBuV/m)			Date: 2014-03-08																																				
<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th rowspan="2">Remark</th> <th rowspan="2">Ant</th> <th rowspan="2">Table</th> </tr> <tr> <th>Limit</th> <th>Line</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Pos</th> <th>Pos</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV/m</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td></td> <td>cm</td> <td>deg</td> </tr> </tbody> </table>										Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant			Table																											
		Limit	Line	Level	Factor	Loss	Factor			Pos	Pos																												
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg																													
1	4874.000	47.40	-26.60	74.00	43.02	34.32	4.73	34.67 Peak	---	---																													
2	4874.000	34.13	-19.87	54.00	29.75	34.32	4.73	34.67 Average	---	---																													
3	7311.000	36.24	-17.76	54.00	29.84	35.88	5.47	34.95 Average	---	---																													
4	7311.000	48.51	-25.49	74.00	42.11	35.88	5.47	34.95 Peak	---	---																													
5	9748.000	48.20			40.44	36.71	6.41	35.36 Peak	---	---																													


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (105.50 dBuV/m).
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2462																																																																																												
N _{TX}	1	Polarization	V																																																																																												
Level (dBuV/m)			Date: 2014-03-08																																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th rowspan="2">Remark</th> <th rowspan="2">Ant</th> <th rowspan="2">Table</th> </tr> <tr> <th>Limit</th> <th>Line</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Pos</th> <th>Pos</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV/m</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td></td> <td>cm</td> <td>deg</td> </tr> <tr> <td>1</td> <td>4924.000</td> <td>48.02</td> <td>-25.98</td> <td>74.00</td> <td>43.58</td> <td>34.31</td> <td>4.79</td> <td>34.66 Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>2</td> <td>4924.000</td> <td>34.27</td> <td>-19.73</td> <td>54.00</td> <td>29.83</td> <td>34.31</td> <td>4.79</td> <td>34.66 Average</td> <td>---</td> <td>---</td> </tr> <tr> <td>3</td> <td>7386.000</td> <td>36.38</td> <td>-17.62</td> <td>54.00</td> <td>29.94</td> <td>35.84</td> <td>5.57</td> <td>34.97 Average</td> <td>---</td> <td>---</td> </tr> <tr> <td>4</td> <td>7386.000</td> <td>48.60</td> <td>-25.40</td> <td>74.00</td> <td>42.16</td> <td>35.84</td> <td>5.57</td> <td>34.97 Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>5</td> <td>9848.000</td> <td>49.65</td> <td></td> <td></td> <td>41.71</td> <td>36.81</td> <td>6.50</td> <td>35.37 Peak</td> <td>---</td> <td>---</td> </tr> </tbody> </table>				Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	1	4924.000	48.02	-25.98	74.00	43.58	34.31	4.79	34.66 Peak	---	---	2	4924.000	34.27	-19.73	54.00	29.83	34.31	4.79	34.66 Average	---	---	3	7386.000	36.38	-17.62	54.00	29.94	35.84	5.57	34.97 Average	---	---	4	7386.000	48.60	-25.40	74.00	42.16	35.84	5.57	34.97 Peak	---	---	5	9848.000	49.65			41.71	36.81	6.50	35.37 Peak	---	---							
Freq	Level	Over	Limit			Read	Antenna	Cable	Preamp	Remark	Ant				Table																																																																																
		Limit	Line	Level	Factor	Loss	Factor	Pos	Pos																																																																																						
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg																																																																																					
1	4924.000	48.02	-25.98	74.00	43.58	34.31	4.79	34.66 Peak	---	---																																																																																					
2	4924.000	34.27	-19.73	54.00	29.83	34.31	4.79	34.66 Average	---	---																																																																																					
3	7386.000	36.38	-17.62	54.00	29.94	35.84	5.57	34.97 Average	---	---																																																																																					
4	7386.000	48.60	-25.40	74.00	42.16	35.84	5.57	34.97 Peak	---	---																																																																																					
5	9848.000	49.65			41.71	36.81	6.50	35.37 Peak	---	---																																																																																					
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.) Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (102.74 dBuV/m). Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																																															





4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 25, 2013	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	JAN. 21, 2014	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	7.61183201e+012	9kHz ~ 30MHz	Oct. 30, 2013	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101013	9KHz~40GHz	Jan. 25, 2014	Conducted (TH06-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 27, 2013	Conducted (TH06-HY)
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_103	10715/4 10716/4	30MHz ~ 26.5GHz	Dec. 02, 2013	Conducted (TH06-HY)

Note: Calibration Interval of instruments listed above is one year.



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9kHz ~ 40GHz	Oct. 03, 2013	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 11, 2013	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	Jul. 18, 2013	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz ~ 26.5GHz	Aug. 28, 2013	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz ~ 18GHz	Nov. 25, 2013	Radiation (03CH02-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jan. 10, 2014	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 09, 2013	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1GHz ~ 40GHz	Mar. 05, 2014	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 10, 2013	Radiation (03CH02-HY)
Turn Table	Chaintek Instruments	3000	MF7802058	0~ 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	MF	MF7802	MF780208205	1 ~ 4 m	N/A	Radiation (03CH02-HY)
Software	Audix	E3	4.03260c	Radiate	NCR	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz - 30 MHz	Dec. 02, 2012	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.