



FCC TEST REPORT

for

47 CFR Part 22H, 24E

Equipment : Quad-band Smart Phone
Trade Name : ASUS
Model No. : P527
FCC ID : MSQP527
Tx Frequency Range : GSM850 : 824.2~848.8 MHz
PCS1900 : 1850.2~1909.8 MHz
Max. ERP/EIRP Power : GSM850(GSM) : 0.63 W
GSM850(EDGE) : 0.16 W
PCS1900(GSM) : 1.53 W
PCS1900(EDGE) : 0.53 W
Emission Designator : GSM : 300KGXW
EDGE : 300KG7W
Applicant : ASUSTek COMPUTER INC.
4F., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**
- The data shown in this test report were carried out on Oct. 02, 2007 at **Sporton International Inc. LAB.**
- Report No.: FG781408A, Report Version: Rev. 01.

Jones Tsai
Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.



Table of Contents

History of this test reportii

1. General Information.....1

 1.2 Applicant.....1

 1.3 Manufacturer1

 1.4 Basic Description of Equipment under Test.....1

 1.5 Feature of Equipment under Test.....2

 1.6 Report Date2

2. Test Configuration of Equipment under Test.....3

 2.1 Test Manner3

 2.2 Test Mode3

 2.3 Connection Diagram of Test System3

 2.4 Ancillary Equipment List4

3. General Information of Test Site5

 3.1 Test Voltage5

 3.2 Test Compliance5

 3.3 Frequency Range5

 3.4 Test Distance5

4. Test Data and Test Result.....6

 4.1 List of Measurements and Examinations6

 4.2 RF Output Power.....7

 4.3 ERP / EIRP Measurement.....9

 4.4 Occupied Bandwidth and Band Edge Measurement13

 4.5 Conducted Emission.....58

 4.6 Field Strength of Spurious Radiation77

 4.7 Frequency Stability (Temperature Variation)91

 4.8 Frequency Stability (Voltage Variation)94

5. List of Measurement Equipments96

6. Uncertainty Evaluation97

Appendix A - External Photographs

Appendix B - Internal Photographs

Appendix C - Setup Photographs



1. General Information

1.2 Applicant

ASUSTek COMPUTER INC.

4F., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

1.3 Manufacturer

1. ASUSTeK Computer Inc.

No. 5, Shing Yeh Street, 333 Kwei Shan Hsiang, Taoyuan Hsien, Taiwan

2. ProTek (Shanghai) Ltd.

No.3768, Xiu Yan Road, Nanhui District, 201315 Shanghai, People's Republic of China

3. MainTek Computer (Suzhou) Co., Ltd.

No. 233 Jing Feng Road · 215011 Suzhou New District, Jiangsu, People's Republic of China

1.4 Basic Description of Equipment under Test

Equipment		Quad-band Smart Phone
Trade Name		ASUS
Model Name		P527
FCC ID		MSQP527
AC Adapter	Brand Name	TPT
	Model Name	JSP050090UU
	ASUS P/N	04G267013800
	Power Rating	I/P:100-240Vac, 50-60Hz, 0.3A O/P: 5Vdc, 0.9A, 4.5W
	AC Power Cord Type	1.65 meter shielded cable without ferrite non-core
Car Charger	Brand Name	L&K
	Model Name	G12PCL-530-0011
	ASUS P/N	04G267011910
	Power Rating	I/P: 12V/24V; O/P: 5V, 900mA
	Power Cord Type	0.6 meter non-shielded cable without ferrite non-core
Battery	Brand Name	ASUS
	Model Name	SBP-06
	ASUS P/N	07G016043459
	Rating	3.7Vdc, 1300mAh
	Type	Li-ion
Earphone	Brand Name	ASUS
	ASUS P/N	04G170012520
	Signal line Type	1.8 meter non-shielded cable without ferrite non-core
USB Cable	Brand Name	Foxconn
	ASUS P/N	14G000506200
	Signal line Type	0.7 meter shielded cable with ferrite core
Holster	Brand Name	ASUS
	ASUS P/N	15G180904400
	Color	Black

Remark: Above EUT's information was declared by manufacturer. Please refer to the specifications of manufacturer or User's Manual for more detailed features description.



1.5 Feature of Equipment under Test

DUT Type :	Quad-band Smart Phone
Trade Name :	ASUS
Model Name :	P527
FCC ID :	MSQP527
Tx Frequency :	GSM850 : 824 ~ 849 MHz PCS1900 : 1850 ~1910 MHz WLAN / Bluetooth : 2400 ~ 2483.5 MHz
Rx Frequency :	GSM850 : 869 ~ 894 MHz PCS1900 : 1930 ~ 1990 MHz WLAN / Bluetooth : 2400 ~ 2483.5 MHz
Maximum Output Power to Antenna :	GSM850 : 32.44 dBm (GSM) / 32.49 dBm (GPRS) / 26.04 dBm (EDGE) PCS1900 : 29.39 dBm (GSM) / 29.45 dBm (GPRS) / 25.10 dBm (EDGE) WLAN : 20.57 dBm (802.11b) / 22.81 dBm (802.11g) Bluetooth : 1.35 dBm (1Mbps) Bluetooth EDR : 2.21 dBm (2Mbps) / 2.45 dBm (3Mbps)
Maximum ERP/EIRP :	GSM850(GSM) : 0.63 W (27.97 dBm) GSM850(EDGE) : 0.16 W (22.08 dBm) PCS1900(GSM) : 1.53 W (31.86 dBm) PCS1900(EDGE) : 0.53 W (27.25 dBm)
GPRS / EGPRS Multislot class :	10
HW Version :	Rev: 1.02
SW Version :	3.12.070809.000S-FTA
Antenna Type :	GSM : Fixed Internal Bluetooth : PIFA Antenna WLAN : PIFA Antenna
Type of Antenna Connector	N/A
Power Rating (DC/AC , Voltage and Current of RF element or PA) :	DC 3.8V / 270mA
Modulation Type :	GSM / GPRS : GMSK EDGE : 8PSK WLAN : DSSS / OFDM Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : Pi/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
Emission Designator :	GSM : 300KGXW EDGE : 300KG7W
Device Power Class :	GSM850 : 4 PCS1900 : 1

1.6 Report Date

EUT Received : Aug. 14, 2007

Report Date : Oct. 04, 2007

2. Test Configuration of Equipment under Test

2.1 Test Manner


1. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.
2. During all testings, EUT is in link mode with base station emulator at maximum power level.
3. Frequency range investigated: radiated emission 30 MHz to 9000 MHz for GSM850 and 30MHz to 19000 MHz for PCS1900.

2.2 Test Mode


Application	GSM850	PCS1900
Radiated Emission	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 3: GSM Link
	<input checked="" type="checkbox"/> Mode 2: EDGE Link	<input checked="" type="checkbox"/> Mode 4: EDGE Link
	<input checked="" type="checkbox"/> Mode 5: GSM Link + BT Link	
Conducted Measurement	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 3: GSM Link
	<input checked="" type="checkbox"/> Mode 2: EDGE Link	<input checked="" type="checkbox"/> Mode 4: EDGE Link

2.3 Connection Diagram of Test System

<GSM Link Mode>



<GSM with Bluetooth Link Mode>



2.4 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Cable Cord / Power Code
1.	Base Station	R&S	CMU200	N/A	Unshielded, 1.8m
2.	BT Base Station	Anritus	8852A	N/A	Unshielded, 1.8m



3. General Information of Test Site

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,
Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-318-0055

Test Site No : 03CH06-HY

The chamber meets the characteristics of ANSI C63.4-2003. This site is on file with the FCC.

3.1 Test Voltage

AC 120V / 60Hz

3.2 Test Compliance

47 CFR Part 22H, 24E, Part 2

3.3 Frequency Range

- a. Radiation: from 30MHz to 9000MHz for GSM850.
- b. Radiation: from 30 MHz to 19000 MHz for PCS1900.

3.4 Test Distance

The test distance of radiated emission from antenna to EUT is 3 m.



4. Test Data and Test Result

4.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result	Section
§2.1046	RF Output Power	Passed	4.2
§ 22.913 §24.232	ERP / EIRP	Passed	4.3
§2.1049, § 22.917, § 24.238(b)	Occupied Bandwidth & Band Edge Measurement	Passed	4.4
§2.1051	Conducted Emission	Passed	4.5
§2.1053	Field Strength of Spurious Radiation	Passed	4.6
§2.1055, § 22.355, §24.235	Frequency Stability vs. Temperature	Passed	4.7
§2.1055, §22.355, §24.235	Frequency Stability vs. Voltage	Passed	4.8

4.2 RF Output Power


4.2.1 Measurement Instruments :

As described in chapter 5 of this test report.

4.2.2 Test Procedure :

1. The transmitter output was connected to power meter and base station through power divider.
2. Set EUT at PCL=5 for GSM850 and/or PCL=0 for PCS1900 maximum power through base station.
3. Select lowest, middle, and highest channels for each band.

4.2.3 Test Setup Layout :





4.2.4 Test Result :

Bands	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GSM)	128	824.2 (Low)	32.37	1.726
	189	836.4 (Mid)	32.44	1.754
	251	848.8 (High)	32.43	1.750
GSM850 (EDGE)	128	824.2 (Low)	25.89	0.388
	189	836.4 (Mid)	25.84	0.384
	251	848.8 (High)	26.04	0.402
PCS1900 (GSM)	512	1850.2 (Low)	29.12	0.817
	661	1880.0 (Mid)	29.23	0.838
	810	1909.8 (High)	29.39	0.869
PCS1900 (EDGE)	512	1850.2 (Low)	24.82	0.303
	661	1880.0 (Mid)	25.10	0.324
	810	1909.8 (High)	25.01	0.317



4.3 ERP / EIRP Measurement

Equivalent isotropic radiated power measurements by substitution method according to ANSI/TIA/EIA-603-C.

4.3.1 Measurement Instruments

As described in chapter 5 of this test report.

4.3.2 Test Procedure

1. The EUT was placed on a table with 1.0 meter height in an fully anechoic chamber.
2. The EUT was set 1.2 meters from the receiving antenna which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is also kept at 1.0M height.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$

$E_s = R_s + AF$


AF (dB/m) : Receive antenna factor

R_t : The highest received signal in Spectrum Analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.



4.3.3 Test Setup Layout of ERP/EIRP





4.3.4 Test Result

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-30.39	-48.12	0.00	-1.08	16.65	0.05
836.40	-29.60	-48.28	0.00	-0.93	17.75	0.06
848.80	-28.82	-48.35	0.00	-0.76	18.77	0.08
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-20.89	-47.97	0.00	-1.08	26.00	0.40
836.40	-19.84	-48.01	0.00	-0.93	27.24	0.53
848.80	-19.32	-48.05	0.00	-0.76	27.97	0.63

GSM850 (EDGE) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-38.14	-48.12	0.00	-1.08	8.90	0.01
836.40	-38.12	-48.28	0.00	-0.93	9.23	0.01
848.80	-38.00	-48.35	0.00	-0.76	9.59	0.01
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-27.79	-47.97	0.00	-1.08	19.10	0.08
836.40	-25.00	-48.01	0.00	-0.93	22.08	0.16
848.80	-26.05	-48.05	0.00	-0.76	21.24	0.13



PCS1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.51	-51.88	0.00	1.96	29.33	0.86
1880.00	-25.85	-52.99	0.00	2.00	29.14	0.82
1909.80	-27.89	-54.28	0.00	1.98	28.37	0.69
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-22.23	-52.13	0.00	1.96	31.86	1.53
1880.00	-23.33	-53.17	0.00	2.00	31.84	1.53
1909.80	-25.28	-54.13	0.00	1.98	30.83	1.21

PCS1900 (EDGE) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.12	-51.88	0.00	1.96	24.72	0.30
1880.00	-30.35	-52.99	0.00	2.00	24.64	0.29
1909.80	-32.52	-54.28	0.00	1.98	23.74	0.24
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.87	-52.13	0.00	1.96	27.22	0.53
1880.00	-28.08	-53.17	0.00	2.00	27.09	0.51
1909.80	-28.86	-54.13	0.00	1.98	27.25	0.53

4.4 Occupied Bandwidth and Band Edge Measurement


4.4.1 Measurement Instruments

As described in chapter 5 of this test report.

4.4.2 Test Procedure


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% occupied bandwidth of middle channel for the highest and lowest RF powers were measured.
3. The bandedge of low and high channels for the highest RF powers within the transmitting frequency band were measured. Setting RBW as roughly $BW/100$.

4.4.3 Test Setup Layout






Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -17.54 dBm
*SWT 300 ms 823.976000000 MHz



Date: 11.SEP.2007 17:29:30




- Test Mode : GSM850 (GSM) CH128 99% Occupied Bandwidth
- Power State : High



Date: 11.SEP.2007 18:05:06



- Test Mode : GSM850 (GSM) CH189 99% Occupied Bandwidth
- Power State : High



Date: 11.SEP.2007 18:03:19




*RBW 3 kHz Marker 1 [T1]
 *VBW 30 kHz 26.26 dBm
 *SWT 300 ms 836.386000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK
VIEW




Center 836.4 MHz 100 kHz/ Span 1 MHz

Date: 11.SEP.2007 18:02:20



- Test Mode : GSM850 (GSM) CH 251 99% Occupied Bandwidth
- Power State : High



444

Date: 25.SEP.2007 18:14:04



- Test Mode : GSM850 (GSM) CH128 26dB Bandwidth
- Power State : High




*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 1.23 dB
 *SWT 300 ms 300.00000000 kHz

Ref 35 dBm

*Att 30 dB

1 PK
 VIEW




Center 824.2 MHz 100 kHz/ Span 1 MHz

Date: 11.SEP.2007 19:44:05




- Test Mode : GSM850 (GSM) CH189 26dB Bandwidth
- Power State : High



Date: 11.SEP.2007 19:45:39



- Test Mode : GSM850 (GSM) CH 251 26dB Bandwidth
- Power State : High




Date: 11.SEP.2007 19:47:19



- Test Mode : GSM850 (GSM) CH251 Higher Band Edge
- Power State : High




*RBW 3 kHz Marker 1 [T1]
*VBW 3 kHz -15.58 dBm
*SWT 300 ms 849.01800000 MHz



Date: 11.SEP.2007 17:32:36



Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -14.71 dBm
*SWT 300 ms 849.016000000 MHz



Date: 11.SEP.2007 17:30:48




*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -27.75 dBm
*SWT 300 ms 823.99000000 MHz

Ref 30 dBm

*Att 30 dB

1 AV *
VIEW




Date: 20.SEP.2007 13:15:16



- Test Mode : GSM850 (EDGE) CH128 99% Occupied Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 17.57 dBm
 *SWT 300 ms 824.20000000 MHz




Date: 20.SEP.2007 13:01:53



- Test Mode : GSM850 (EDGE) CH189 99% Occupied Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 17.70 dBm
 *SWT 300 ms 836.392000000 MHz



Date: 20.SEP.2007 13:03:01




*RBW 3 kHz Marker 1 [T1]
*VBW 30 kHz 17.15 dBm
*SWT 300 ms 836.36600000 MHz

Ref 30 dBm

*Att 30 dB

1 PK
VIEW



Center 836.4 MHz


100 kHz/

Span 1 MHz

Date: 20.SEP.2007 13:04:51



- Test Mode : GSM850 (EDGE) CH 251 99% Occupid Bandwidth
- Power State : High




Date: 20.SEP.2007 13:00:41



- Test Mode : GSM850 (EDGE) CH128 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] *VBW 10 kHz 2.94 dB *SWT 300 ms 306.00000000 kHz




Date: 20.SEP.2007 12:31:25



- Test Mode : GSM850 (EDGE) CH189 26dB Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] -1.05 dB
 *VBW 10 kHz *SWT 300 ms 298.00000000 kHz



Date: 20.SEP.2007 12:35:14



- Test Mode : GSM850 (EDGE) CH 251 26dB Bandwidth
- Power State : High



444


Date: 25.SEP.2007 18:24:26



- Test Mode : GSM850 (EDGE) CH251 Higher Band Edge
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 3 kHz -26.82 dBm
 *SWT 300 ms 849.008000000 MHz



Date: 20.SEP.2007 13:19:12




*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -27.61 dBm
*SWT 300 ms 849.004000000 MHz

Ref 30 dBm

*Att 30 dB

1 AV *
VIEW



Center 849 MHz


100 kHz/

Span 1 MHz

Date: 20.SEP.2007 13:17:40



Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -18.38 dBm
*SWT 300 ms 1.849994000 GHz




Date: 11.SEP.2007 17:27:02



- Test Mode : PCS1900 (GSM) CH512 99% Occupied Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] 21.16 dBm
 *VBW 10 kHz 1.850184000 GHz
 *SWT 300 ms



Date: 11.SEP.2007 17:18:29



- Test Mode : PCS1900 (GSM) CH661 99% Occupied Bandwidth
- Power State : High



Date: 11.SEP.2007 17:17:30




*RBW 3 kHz Marker 1 [T1]
 *VBW 30 kHz 20.87 dBm
 *SWT 300 ms 1.879980000 GHz

Ref 30 dBm

*Att 30 dB

1 PK
MAXH



Center 1.88 GHz 100 kHz/ Span 1 MHz

Date: 11.SEP.2007 17:20:37



- Test Mode : PCS1900 (GSM) CH810 99% Occupied Bandwidth
- Power State : High




*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 22.83 dBm
 *SWT 300 ms 1.909748000 GHz

Ref 30 dBm

*Att 30 dB

1 PK
MAXH



Center 1.9098 GHz


100 kHz/

Span 1 MHz

Date: 11.SEP.2007 17:16:31



- Test Mode : PCS1900 (GSM) CH512 26dB Bandwidth
- Power State : High




Date: 11.SEP.2007 17:10:50



- Test Mode : PCS1900 (GSM) CH810 26dB Bandwidth
- Power State : High



*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 1.17 dB
 *SWT 300 ms 308.00000000 kHz




Date: 11.SEP.2007 17:14:38



- Test Mode : PCS1900 (GSM) CH810 Higher Band Edge
- Power State : High



*RBW 3 kHz Marker 1 [T1]
*VBW 3 kHz -17.85 dBm
*SWT 300 ms 1.910020000 GHz



Date: 11.SEP.2007 17:24:05



Ref 30 dBm

*Att 30 dB

*RBW 3 kHz


Marker 1 [T1]

*VBW 10 kHz

-19.89 dBm

*SWT 300 ms


1.910018000 GHz



Date: 11.SEP.2007 17:25:24




*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -27.49 dBm
*SWT 300 ms 1.849982000 GHz



Date: 20.SEP.2007 14:36:53




- Test Mode : PCS1900 (EDGE) CH512 99% Occupied Bandwidth
- Power State : High



Date: 20.SEP.2007 14:20:26



- Test Mode : PCS1900 (EDGE) CH661 99% Occupied Bandwidth
- Power State : High




Date: 20.SEP.2007 14:21:30



*RBW 3 kHz Marker 1 [T1]
*VBW 30 kHz 16.01 dBm
*SWT 300 ms 1.879970000 GHz


Ref 30 dBm *Att 30 dB



Date: 20.SEP.2007 14:24:30



- Test Mode : PCS1900 (EDGE) CH810 99% Occupied Bandwidth
- Power State : High




Date: 20.SEP.2007 14:19:31



- Test Mode : PCS1900 (EDGE) CH512 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] -0.11 dB
 *VBW 10 kHz 308.00000000 kHz
 *SWT 300 ms




Date: 20.SEP.2007 14:45:41



- Test Mode : PCS1900 (EDGE) CH661 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] *VBW 10 kHz 0.46 dB *SWT 300 ms 308.00000000 kHz




Date: 20.SEP.2007 14:47:24



- Test Mode : PCS1900 (EDGE) CH810 26dB Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 1.39 dB
 *SWT 300 ms 304.00000000 kHz



Date: 20.SEP.2007 14:49:04



*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -28.64 dBm
*SWT 300 ms 1.910004000 GHz



Date: 20.SEP.2007 14:34:36

4.5 Conducted Emission


4.5.1 Measurement Instruments

As described in chapter 5 of this test report.

4.5.2 Test Procedure

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.


4.5.3 Test Setup Layout





4.5.4 Test Result

- Mode 1
- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 30M-1G



Date: 11.SEP.2007 19:19:20




- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 1G-3G



*RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -51.90 dBm
 *SWT 500 ms 2.512000000 GHz

Ref 0 dBm

*Att 0 dB



Date: 11.SEP.2007 19:24:08



- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 3G-7G




*RBW 1 MHz Marker 3 [T1]
 *VBW 3 MHz -48.01 dBm
 *SWT 500 ms 4.184000000 GHz

Ref 0 dBm

*Att 0 dB

1 PK
VIEW



Date: 11.SEP.2007 19:25:44




- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 7G-9G



*RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -44.29 dBm
 *SWT 500 ms 8.364000000 GHz

Ref 0 dBm

*Att 0 dB




Date: 11.SEP.2007 19:32:17



- Mode 2
- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 30M-1G



Ref 35 dBm *Att 30 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -33.37 dBm
 *SWT 500 ms 848.68000000 MHz




Date: 20.SEP.2007 14:59:12



- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 1G-3G




*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -59.09 dBm
*SWT 500 ms 1.96000000 GHz



Date: 20.SEP.2007 15:05:55



- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 3G-7G




Date: 20.SEP.2007 15:07:16



- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 7G-9G



*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -40.98 dBm
*SWT 500 ms 7.52800000 GHz




Date: 20.SEP.2007 15:11:06



- Mode 3
- Test Mode : PCS1900 (GSM) CH661
- Frequency Range : 30M-1G



Ref 30 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -27.96 dBm
*SWT 500 ms 140.58000000 MHz



Date: 11.SEP.2007 19:04:13



- Test Mode : PCS1900 (GSM) CH661
- Frequency Range : 1G-3G




*RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -29.56 dBm
 *SWT 500 ms 2.980000000 GHz

Ref 35 dBm

*Att 30 dB

1 PK
VIEW



A

LVL

Start 1 GHz

200 MHz/

Stop 3 GHz


Date: 11.SEP.2007 19:22:16



- Test Mode : PCS1900 (GSM) CH661
- Frequency Range : 3G-7G



*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -45.30 dBm
*SWT 500 ms 3.76000000 GHz



Date: 11.SEP.2007 19:27:16



- Test Mode : PCS1900 (GSM) CH661
- Frequency Range : 7G-13.6G




*RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -45.59 dBm
 *SWT 500 ms 9.402400000 GHz

Ref 0 dBm

*Att 0 dB

1 PK
VIEW



Start 7 GHz

660 MHz/

Stop 13.6 GHz

Date: 11.SEP.2007 19:29:18



- Test Mode : PCS1900 (GSM) CH661
- Frequency Range : 13.6G-19.1G




*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -26.56 dBm
*SWT 500 ms 15.019000000 GHz

Ref 0 dBm

*Att 0 dB

1 PK
VIEW




Date: 11.SEP.2007 19:34:11



- Mode 4
- Test Mode : PCS1900 (EDGE) CH661
- Frequency Range : 30M-1G



Ref 30 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -34.25 dBm
 *SWT 500 ms 916.58000000 MHz




Date: 20.SEP.2007 14:56:52



- Test Mode : PCS1900 (EDGE) CH661
- Frequency Range : 1G-3G



Ref 35 dBm *Att 30 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -28.72 dBm
 *SWT 500 ms 1.764000000 GHz




Date: 20.SEP.2007 15:02:22



- Test Mode : PCS1900 (EDGE) CH661
- Frequency Range : 3G-7G



*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -41.04 dBm
*SWT 500 ms 3.760000000 GHz




Date: 20.SEP.2007 15:08:18



- Test Mode : PCS1900 (EDGE) CH661
- Frequency Range : 7G-13.6G



*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -44.57 dBm
 *SWT 500 ms 7.51480000 GHz




Date: 20.SEP.2007 15:12:14



- Test Mode : PCS1900 (EDGE) CH661
- Frequency Range : 13.6G-19.1G



*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -26.53 dBm
 *SWT 500 ms 14.007000000 GHz



Date: 20.SEP.2007 15:13:05

4.6 Field Strength of Spurious Radiation

Equivalent isotropic radiated Power Measurements by substitution method according to ANSI/TIA/EIA-603-C.


4.6.1 Measurement Instruments

As described in chapter 5 of this test report.

4.6.2 Test Procedure

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to reach the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A Horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. Emission level (dBm) = output power + substitution Gain.

4.6.3 Test Setup Layout





4.6.4 Test Result

- Test Mode : Mode 1

GSM850 (GSM) Radiated Spurious ERP							
H Polarization				V Polarization			
Frequency	ERP (dBm)	Limit	Margin	Frequency	ERP (dBm)	Limit	Margin
(MHz)		(dBm)	(dB)	(MHz)		(dBm)	(dB)
30.540	-63.170	-13	-50.17	32.430	-62.930	-13	-49.93
66.180	-62.210	-13	-49.21	48.630	-66.920	-13	-53.92
99.390	-67.320	-13	-54.32	70.230	-55.350	-13	-42.35
607.300	-69.600	-13	-56.60	679.400	-66.320	-13	-53.32
1674.000	-38.990	-13	-25.99	1674.000	-44.510	-13	-31.51
2508.000	-42.210	-13	-29.21	2508.000	-42.360	-13	-29.36
3344.000	-49.800	-13	-36.80	3344.000	-47.710	-13	-34.71
6688.000	-33.190	-13	-20.19	5854.000	-42.090	-13	-29.09
7528.000	-42.270	-13	-29.27	6688.000	-32.210	-13	-19.21
				8364.000	-37.790	-13	-24.79

- Test Mode : Mode 2

GSM850 (EDGE) Radiated Spurious ERP							
H Polarization				V Polarization			
Frequency	ERP (dBm)	Limit	Margin	Frequency	ERP (dBm)	Limit	Margin
(MHz)		(dBm)	(dB)	(MHz)		(dBm)	(dB)
31.080	-63.310	-13	-50.31	32.430	-64.860	-13	-51.86
67.530	-62.550	-13	-49.55	69.690	-56.900	-13	-43.90
194.430	-66.960	-13	-53.96	97.230	-63.830	-13	-50.83
665.400	-68.840	-13	-55.84	309.800	-61.150	-13	-48.15
1674.000	-47.320	-13	-34.32	1674.000	-53.400	-13	-40.40
2508.000	-52.250	-13	-39.25	2508.000	-53.040	-13	-40.04
6688.000	-35.900	-13	-22.90	6688.000	-34.880	-13	-21.88
8364.000	-36.500	-13	-23.50	8364.000	-39.970	-13	-26.97



• Test Mode : Mode 3

PCS1900 (GSM) Radiated Spurious EIRP							
H Polarization				V Polarization			
Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)
31.080	-60.030	-13	-47.03	33.240	-57.430	-13	-44.43
70.230	-57.100	-13	-44.10	48.630	-52.770	-13	-39.77
95.340	-61.860	-13	-48.86	71.580	-47.380	-13	-34.38
616.400	-67.370	-13	-54.37	733.300	-63.790	-13	-50.79
777.400	-65.690	-13	-52.69	890.800	-61.880	-13	-48.88
962.900	-64.190	-13	-51.19	978.300	-61.190	-13	-48.19
3758.000	-47.810	-13	-34.81	3758.000	-44.630	-13	-31.63
5638.000	-38.080	-13	-25.08	5638.000	-32.930	-13	-19.93
9398.000	-39.880	-13	-26.88	9398.000	-39.920	-13	-26.92
11278.000	-36.270	-13	-23.27				

• Test Mode : Mode 4

PCS1900 (EDGE) Radiated Spurious EIRP							
H Polarization				V Polarization			
Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)
33.240	-60.950	-13	-47.95	31.890	-57.780	-13	-44.78
65.640	-53.850	-13	-40.85	71.580	-47.680	-13	-34.68
140.430	-60.110	-13	-47.11	84.540	-51.190	-13	-38.19
745.900	-65.230	-13	-52.23	633.900	-64.890	-13	-51.89
848.800	-64.590	-13	-51.59	794.900	-62.980	-13	-49.98
918.800	-63.860	-13	-50.86	901.300	-61.540	-13	-48.54
3758.000	-47.650	-13	-34.65	3758.000	-47.050	-13	-34.05
5638.000	-39.280	-13	-26.28	5638.000	-34.600	-13	-21.60
9398.000	-37.930	-13	-24.93	9398.000	-41.260	-13	-28.26



• Test Mode : Mode 5


GSM850 (GSM) with Bluetooth Co-location Radiated Spurious ERP							
H Polarization				V Polarization			
Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)
35.130	-58.320	-13	-45.32	34.590	-61.070	-13	-48.07
68.340	-54.490	-13	-41.49	66.180	-53.850	-13	-40.85
99.390	-52.910	-13	-39.91	76.980	-53.050	-13	-40.05
992.300	-65.690	-13	-52.69	974.800	-64.020	-13	-51.02
1674.000	-47.770	-13	-34.77	1674.000	-50.620	-13	-37.62
2508.000	-43.150	-13	-30.15	2508.000	-43.770	-13	-30.77
5854.000	-42.400	-13	-29.40	5854.000	-41.890	-13	-28.89
6688.000	-30.090	-13	-17.09	6688.000	-30.230	-13	-17.23
8364.000	-38.600	-13	-25.60	8364.000	-41.160	-13	-28.16



4.6.5 Test Data

4.6.5.1 Mode 1

Horizontal Polarization



Trace: (Discrete)

Site : 03CHD6-HY
 Condition : HF-SPURIOUS-060929 HORIZONTAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GFS, FM
 Power : 120V_{ac}/60Hz
 Model : FG 781408
 Memo : GSM 850 Link;Ch189+Earphone+Adaptor
 Plane : E2


	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	30.5	-61.02	-48.02	-13.00	-60.77	-0.25	Peak
2	66.2	-60.06	-47.06	-13.00	-47.69	-12.37	Peak
3	99.4	-65.17	-52.17	-13.00	-52.93	-12.24	Peak
4	607.3	-67.45	-54.45	-13.00	-63.78	-3.67	Peak
5	836.9	-44.86			-43.53	-1.33	Peak
6	880.3	-59.98			-59.07	-0.91	Peak
7	1674.0	-36.84	-23.84	-13.00	-39.20	2.36	Peak
8	2508.0	-40.06	-27.06	-13.00	-46.75	6.69	Peak
9	3344.0	-47.65	-34.65	-13.00	-57.05	9.40	Peak
10	6688.0	-31.04	-18.04	-13.00	-51.23	20.19	Peak
11	7528.0	-40.12	-27.12	-13.00	-61.43	21.31	Peak

Remark:

- #5: MS Signal
- #6: BS Signal



Vertical Polarization



Trace: (Discrete)

Site : 03CHD6-HY
 Condition : HF-SPURIOUS-060929 VERTICAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GPS, FM
 Power : 120Vac/60Hz
 Model : FG 781408
 Memo : GSM 850 Link;CH189+Earphone+Adaptor
 Plane : E2

	Freq	Level	Over	Limit	Read	Factor	Remark
	MHz	dBm	dB	dBm	dBm	dB	
1	32.4	-60.78	-47.78	-13.00	-50.89	-9.89	Peak
2	48.6	-64.77	-51.77	-13.00	-50.50	-14.27	Peak
3	70.2	-53.20	-40.20	-13.00	-41.17	-12.02	Peak
4	679.4	-64.17	-51.17	-13.00	-63.42	-0.75	Peak
5	836.9	-51.09			-52.45	1.36	Peak
6	880.3	-59.80			-61.51	1.71	Peak
7	1674.0	-42.36	-29.36	-13.00	-44.52	2.16	Peak
8	2508.0	-40.21	-27.21	-13.00	-47.39	7.18	Peak
9	3344.0	-45.56	-32.56	-13.00	-54.11	8.55	Peak
10	5854.0	-39.94	-26.94	-13.00	-58.43	18.49	Peak
11 @	6688.0	-30.06	-17.06	-13.00	-48.74	18.68	Peak
12	8364.0	-35.64	-22.64	-13.00	-58.40	22.75	Peak


Remark:

- #5: MS Signal
- #6: BS Signal
- There is no more obvious emission except the listings above.



4.6.5.2 Mode 2

Horizontal Polarization



Date: 2007-09-24

Trace: (Discrete)

Site : 08CH06-HY
 Condition : HF-SPURIOUS-060929 HORIZONTAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GFS, FM
 Power : 120V_{ac}/60Hz
 Model : FG 781408
 Memo : EDGE Link;Ch189+Earphone+Adaptor
 Plane : E2


	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	31.1	-61.16	-48.16	-13.00	-60.92	-0.25	Peak
2	67.5	-60.40	-47.40	-13.00	-48.03	-12.36	Peak
3	194.4	-64.81	-51.81	-13.00	-51.48	-13.33	Peak
4	665.4	-66.69	-53.69	-13.00	-63.62	-3.07	Peak
5	833.4	-47.29			-45.92	-1.37	Peak
6	880.3	-43.19			-42.28	-0.91	Peak
7	1674.0	-45.17	-32.17	-13.00	-47.52	2.36	Peak
8	2508.0	-50.10	-37.10	-13.00	-56.79	6.69	Peak
9 @	6688.0	-33.75	-20.75	-13.00	-53.94	20.19	Peak
10	8364.0	-34.35	-21.35	-13.00	-58.32	23.97	Peak

Remark:

1. #5: MS Signal
2. #6: BS Signal



Vertical Polarization



Site : 03CHD6-HY
 Condition : HF-SPURIOUS-060929 VERTICAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GFS, FM
 Power : 120V_{ac}/60Hz
 Model : FG 781408
 Memo : EDGE Link;Ch189+Earphone+Adaptor
 Plane : E2

	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	32.4	-62.71	-49.71	-13.00	-52.82	-9.89	Peak
2	69.7	-54.75	-41.75	-13.00	-42.73	-12.02	Peak
3	97.2	-61.68	-48.68	-13.00	-53.57	-8.11	Peak
4	309.8	-59.00	-46.00	-13.00	-52.74	-6.25	Peak
5	831.3	-50.59			-51.91	1.32	Peak
6	880.3	-45.19			-46.90	1.71	Peak
7	1674.0	-51.25	-38.25	-13.00	-53.41	2.16	Peak
8	2508.0	-50.89	-37.89	-13.00	-58.07	7.18	Peak
9 @	6688.0	-32.73	-19.73	-13.00	-51.42	18.68	Peak
10	8364.0	-37.82	-24.82	-13.00	-60.57	22.75	Peak


Remark:

- #5: MS Signal
- #6: BS Signal
- There is no more obvious emission except the listings above.



4.6.5.3 Mode 3

Horizontal Polarization



Date: 2007-09-24

Trace: (Discrete)

Site : 08CH06-HY
 Condition : HF-SPURIOUS-060929 HORIZONTAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GPS, FM
 Power : 120V_{ac}/60Hz
 Model : FG 781408
 Memo : PCS 1900 Link;Ch661+Earphone+Adaptor
 Plane : E2


	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	31.1	-60.03	-47.03	-13.00	-59.78	-0.25	Peak
2	70.2	-57.10	-44.10	-13.00	-44.74	-12.36	Peak
3	95.3	-61.86	-48.86	-13.00	-49.60	-12.26	Peak
4	616.4	-67.37	-54.37	-13.00	-63.80	-3.57	Peak
5	777.4	-65.69	-52.69	-13.00	-63.77	-1.92	Peak
6	962.9	-64.19	-51.19	-13.00	-64.08	-0.12	Peak
7	1878.0	-43.45			-47.35	3.90	Peak
8	1958.0	-36.70			-41.12	4.41	Peak
9	3758.0	-47.81	-34.81	-13.00	-58.21	10.41	Peak
10	5638.0	-38.08	-25.08	-13.00	-56.53	18.45	Peak
11	9398.0	-39.88	-26.88	-13.00	-61.28	21.40	Peak
12	11278.0	-36.27	-23.27	-13.00	-61.00	24.72	Peak

Remark:

- #7: MS Signal
- #8: BS Signal



Vertical Polarization



Trace: (Discrete)

Site : 08CHD6-HY
 Condition : HF-SPURIOUS-060929 VERTICAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 : with BT, EDR, 802.11g, GPS, FM
 Power : 120V_{ac}/60Hz
 Model : FG 781408
 Memo : PCS 1900 Link;Ch661+Earphone+Adaptor
 Plane : E2

	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	33.2	-57.43	-44.43	-13.00	-47.54	-9.89	Peak
2	48.6	-52.77	-39.77	-13.00	-38.50	-14.27	Peak
3	71.6	-47.38	-34.38	-13.00	-35.63	-11.74	Peak
4	733.3	-63.79	-50.79	-13.00	-63.86	0.07	Peak
5	890.8	-61.88	-48.88	-13.00	-63.66	1.79	Peak
6	978.3	-61.19	-48.19	-13.00	-63.68	2.49	Peak
7	1878.0	-43.51			-47.81	4.29	Peak
8	1958.0	-36.98			-41.99	5.01	Peak
9	3758.0	-44.63	-31.63	-13.00	-54.52	9.89	Peak
10 @	5638.0	-32.93	-19.93	-13.00	-49.90	16.97	Peak
11	9398.0	-39.92	-26.92	-13.00	-59.80	19.89	Peak


Remark:

- #7: MS Signal
- #8: BS Signal
- There is no more obvious emission except the listings above.



4.6.5.4 Mode 4

Horizontal Polarization



Date: 2007-09-24

Trace: (Discrete)

Site : 08CH06-HY
 Condition : HF-SPURIOUS-060929 HORIZONTAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 : with BT, EDR, 802.11g, GFS, FM
 Power : 120Vac/60Hz
 Model : FG 781408
 Memo : PCS 1900 Link;Ch661+Earphone+Adaptor
 Plane : E2


	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	33.2	-60.95	-47.95	-13.00	-59.48	-1.47	Peak
2	65.6	-53.85	-40.85	-13.00	-41.48	-12.37	Peak
3	140.4	-60.11	-47.11	-13.00	-47.40	-12.71	Peak
4	745.9	-65.23	-52.23	-13.00	-62.99	-2.25	Peak
5	848.8	-64.59	-51.59	-13.00	-63.37	-1.22	Peak
6	918.8	-63.86	-50.86	-13.00	-63.31	-0.55	Peak
7	1884.0	-44.01			-47.91	3.90	Peak
8 @	1958.0	-36.03			-40.45	4.41	Peak
9	3758.0	-47.65	-34.65	-13.00	-58.06	10.41	Peak
10	5638.0	-39.28	-26.28	-13.00	-57.72	18.45	Peak
11	9398.0	-37.93	-24.93	-13.00	-59.34	21.40	Peak

Remark:

- #7: MS Signal
- #8: BS Signal



Vertical Polarization



Trace: (Discrete)

Site : 03CHD6-HY
 Condition : HF-SPURIOUS-060929 VERTICAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 with BT, EDR, 802.11g, GFS, FM
 Power : 120Vac/60Hz
 Model : FG 781408
 Memo : PCS 1900 Link;Ch661+Earphone+Adaptor
 Plane : E2

	Freq	Level	Over	Limit	Read	Factor	Remark
	MHz	dBm	dB	dBm	dBm	dB	
1	31.9	-57.78	-44.78	-13.00	-48.16	-9.62	Peak
2	71.6	-47.68	-34.68	-13.00	-35.94	-11.74	Peak
3	84.5	-51.19	-38.19	-13.00	-41.26	-9.93	Peak
4	633.9	-64.89	-51.89	-13.00	-63.47	-1.42	Peak
5	794.9	-62.98	-49.98	-13.00	-63.97	1.00	Peak
6	901.3	-61.54	-48.54	-13.00	-63.42	1.87	Peak
7	1884.0	-40.27			-44.57	4.29	Peak
8	1958.0	-36.71			-41.71	5.01	Peak
9	3758.0	-47.05	-34.05	-13.00	-56.94	9.89	Peak
10 @	5638.0	-34.60	-21.60	-13.00	-51.57	16.97	Peak
11	9398.0	-41.26	-28.26	-13.00	-61.14	19.89	Peak


Remark:

- #7: MS Signal
- #8: BS Signal
- There is no more obvious emission except the listings above.



4.6.5.5 Mode 5

Horizontal Polarization



Trace: (Discrete)
 Site : 08CH06-HY
 Condition : HF-SPURIOUS-060929 HORIZONTAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 : with BT, EDR, 802.11g, GFS, FM
 Power : 120Vac/60Hz
 Model : FG 781408
 Memo : GSM 850 Link;Ch189 + BT Tx_Ch78
 : + Earphone + Adaptor
 Plane : E2


	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	35.1	-56.17	-43.17	-13.00	-53.48	-2.69	Peak
2	68.3	-52.34	-39.34	-13.00	-39.99	-12.36	Peak
3	99.4	-50.76	-37.76	-13.00	-38.52	-12.24	Peak
4	836.9	-46.48	-33.48	-13.00	-45.15	-1.33	Peak
5	880.3	-39.61			-38.70	-0.91	Peak
6	992.3	-63.54			-63.71	0.17	Peak
7	1674.0	-45.62	-32.62	-13.00	-47.98	2.36	Peak
8	2478.0	-6.96			-13.53	6.57	Peak
9	2508.0	-41.00	-28.00	-13.00	-47.68	6.69	Peak
10	5854.0	-40.25	-27.25	-13.00	-60.10	19.85	Peak
11	6688.0	-27.94	-14.94	-13.00	-48.12	20.19	Peak
12	8364.0	-36.45	-23.45	-13.00	-60.42	23.97	Peak

Remark:

1. #5: MS Signal
2. #6: BS Signal
3. #8: BT Signal



Vertical Polarization



Trace: (Discrete)
 Site : 08CHD6-HY
 Condition : HF-SPURIOUS-060929 VERTICAL
 EUT : GSM/EDGE 850/900/1800/1900 Smart Phone
 : with BT, EDR, 802.11g, GFS, FM
 Power : 120Vac/60Hz
 Model : FG 781408
 Memo : GSM 850 Link;Ch189 + BT Tx_Ch78
 : + Earphone + Adaptor
 Plane : E2

	Freq	Level	Over	Limit	Read		
	MHz	dBm	Limit	Line	Level	Factor	Remark
			dB	dBm	dBm	dB	
1	34.6	-58.92	-45.92	-13.00	-48.48	-10.44	Peak
2	66.2	-51.70	-38.70	-13.00	-39.11	-12.58	Peak
3	77.0	-50.90	-37.90	-13.00	-39.86	-11.05	Peak
4	836.9	-47.92	-34.92	-13.00	-49.29	1.36	Peak
5	880.3	-39.16			-40.87	1.71	Peak
6	974.8	-61.87			-64.33	2.46	Peak
7	1674.0	-48.47	-35.47	-13.00	-50.63	2.16	Peak
8 @	2478.0	-5.31			-12.42	7.11	Peak
9	2508.0	-41.62	-28.62	-13.00	-48.80	7.18	Peak
10	5854.0	-39.74	-26.74	-13.00	-58.23	18.49	Peak
11	6688.0	-28.08	-15.08	-13.00	-46.76	18.68	Peak
12	8364.0	-39.01	-26.01	-13.00	-61.76	22.75	Peak

Remark:

- #5: MS Signal
- #6: BS Signal
- #8: BT Signal
- There is no more obvious emission except the listings above.

4.7 Frequency Stability (Temperature Variation)


4.7.1 Measurement Instrument

As described in chapter 5 of this test report.

4.7.2 Test Procedure

1. The EUT and test equipment were set up as shown on the following section.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. Test data was recorded.

4.7.3 Test Setup Layout





4.7.4 Test Result

• Test Mode : GSM850 (GSM) CH189

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-33	-0.02	2.5	Passed
-20	28	0.03		
-10	-25	-0.03		
0	-24	-0.03		
10	17	0.02		
20	21	0.02		
30	13	0.02		
40	-15	-0.02		
50	-19	-0.02		

• Test Mode : GSM850 (EDGE) CH189

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-16	-0.01	2.5	Passed
-20	18	0.02		
-10	22	0.03		
0	-17	-0.02		
10	10	0.01		
20	12	0.01		
30	-20	-0.02		
40	25	0.03		
50	-19	-0.02		

• Test Mode : PCS1900 (GSM) CH661

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	44	0.02	2.5	Passed
-20	-12	-0.01		
-10	15	0.01		
0	-22	-0.01		
10	21	0.01		
20	18	0.01		
30	15	0.01		
40	-20	-0.01		
50	23	0.01		



• Test Mode : PCS1900 (EDGE) CH661

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-30	-0.02	2.5	Passed
-20	22	0.01		
-10	10	0.01		
0	15	0.01		
10	-18	-0.01		
20	-15	-0.01		
30	-17	-0.01		
40	24	0.01		
50	26	0.01		

4.8 Frequency Stability (Voltage Variation)


4.8.1 Measurement Instrument

As described in chapter 5 of this test report.

4.8.2 Test Procedure

1. The EUT was placed in a temperature chamber at 25 ± 5 °C and connected as the following section.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

4.8.3 Test Setup Layout



4.8.4 Test Result

- Test Mode : GSM850 (GSM) CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	16.0	0.02	2.5	Passed
BEP	-22.0	-0.03		
4.2	-20.0	-0.02		

- Test Mode : GSM850 (EDGE) CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	12.0	0.01	2.5	Passed
BEP	9.0	0.01		
4.2	-15.0	-0.02		



- Test Mode : PCS1900 (GSM) CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	14.0	0.01	2.5	Passed
BEP	8.0	0.00		
4.2	10.0	0.01		

- Test Mode : PCS1900 (EDGE) CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	-12.0	-0.01	2.5	Passed
BEP	10.0	0.01		
4.2	11.0	0.01		

Remark:

1. Normal Voltage=3.7V.
2. Battery End Point (BEP)= 3.4 V.



5. List of Measurement Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	Agilent	E4408B	MY44211030	9KHz-26.5GHz	Oct. 05, 2006	Oct. 04, 2007	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESCS30	100356	9KHz-2.75GHz	Jul. 26, 2007	Jul. 25, 2008	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Nov. 20, 2006	Nov. 19, 2007	Radiation (03CH06-HY)
Double Ridge Horn Antenna	Com-Power	AH118	071025	1G~18G	Jun. 04, 2007	Jun. 03, 2008	Radiation (03CH06-HY)
SHF-EHF Horn	SCHWARZBECK	BBHA 9170	9170-249	14G - 40G	Nov. 20, 2006	Nov. 19, 2008	Radiation (03CH06-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1G - 26.5G	Nov. 15, 2006	Nov. 14, 2007	Radiation (03CH06-HY)
Pre Amplifier	Mini Circuits	ZKL-2	D092004-1	10~2500MHz	Nov. 15, 2006	Nov. 14, 2007	Radiation (03CH06-HY)
Base Station Simulator	R & S	CMU200	106656	WCDMA	Nov. 20, 2006	Nov. 19, 2007	Radiation (03CH06-HY)
Controller	INN-CO	CO2000	N/A	N/A	N/A	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0 ~ 360 degree	N/A	N/A	Radiation (03CH06-HY)
Antenna Mast	INN-CO	MM3000	114/8000604/L	1 m - 4 m	N/A	N/A	Radiation (03CH06-HY)
Thermal Chamber	Tenyi technology	TTH-D35P	TBN-930701	N/A	Aug. 02, 2007	Aug. 01, 2008	Conduction (TH02-HY)
Spectrum	R&S	FSP40	100055	9KHz~40GHz	Jun. 25, 2007	Jun. 24, 2008	Conduction (TH02-HY)
Bluetooth Test	ANRITSU	MT8852A	6K00003939	N/A	N/A	N/A	Conduction (TH02-HY)
Power Divider	ARRA	5200-1	3871	N/A	Oct. 07, 2006	Oct. 06, 2007	Conduction (TH02-HY)
Dc Power Supply	TOPWARD	3303D	740889	N/A	May 25, 2007	May 24, 2009	Conduction (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	N/A	Feb. 08, 2007	Feb. 07, 2008	Conduction (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	N/A	Feb. 08, 2007	Feb. 07, 2008	Conduction (TH02-HY)



6. Uncertainty Evaluation

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2 * \Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	4.72				

END OF TEST REPORT