

FCC TEST REPORT (NFC)

REPORT NO.: RF130830C20-2

MODEL NO.: TF502T

FCC ID: MSQTF502T

RECEIVED: Aug. 30, 2013

TESTED: Sep. 09 ~ Sep. 17, 2013

ISSUED: Sep. 18, 2013

APPLICANT: ASUSTeK Computer Inc

ADDRESS: 4F, No. 150, Li-Te Rd., PEITOU, TAIPEI, TAIWAN

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

RELEASE CONTROL RECORD.....	3
1. CERTIFICATION.....	4
2. SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY.....	5
3. GENERAL INFORMATION.....	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	7
3.3 DESCRIPTION OF SUPPORT UNITS.....	8
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST.....	9
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	10
4. TEST TYPES AND RESULTS.....	11
4.1 RADIATED EMISSION MEASUREMENT.....	11
4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	11
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES.....	13
4.1.4 DEVIATION FROM TEST STANDARD.....	13
4.1.5 TEST SETUP.....	14
4.1.6 EUT OPERATING CONDITIONS.....	14
4.1.7 TEST RESULTS.....	16
4.2 CONDUCTED EMISSION MEASUREMENT.....	28
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	28
4.2.2 TEST INSTRUMENTS.....	28
4.2.3 TEST PROCEDURES.....	29
4.2.4 DEVIATION FROM TEST STANDARD.....	29
4.2.5 TEST SETUP.....	29
4.2.6 EUT OPERATING CONDITIONS.....	29
4.2.7 TEST RESULTS.....	30
4.3 FREQUENCY STABILITY.....	42
4.3.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT.....	42
4.3.2 TEST INSTRUMENTS.....	42
4.3.3 TEST PROCEDURE.....	42
4.3.4 DEVIATION FROM TEST STANDARD.....	43
4.3.5 TEST SETUP.....	43
4.3.6 EUT OPERATING CONDITION.....	43
4.3.7 TEST RESULTS.....	44
4.4 20dB BANDWIDTH.....	45
4.4.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT.....	45
4.4.2 TEST INSTRUMENTS.....	45
4.4.3 TEST PROCEDURE.....	45
4.4.4 DEVIATION FROM TEST STANDARD.....	45
4.4.5 TEST SETUP.....	45
4.4.6 EUT OPERATING CONDITION.....	45
4.4.7 TEST RESULTS.....	46
5. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	47
6. INFORMATION ON THE TESTING LABORATORIES.....	48
7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	49



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130830C20-2	Original release	Sep. 18, 2013

1. CERTIFICATION

PRODUCT: ASUS Tablet

MODEL: TF502T

BRAND: ASUS

APPLICANT: ASUSTeK Computer Inc

TESTED: Sep. 09 ~ Sep. 17, 2013


TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.225)

FCC Part 15, Subpart C (Section 15.215)

ANSI C63.10-2009

The above equipment (model: TF502T) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE :** Sep. 18, 2013
Pettie Chen / Senior Specialist

APPROVED BY : , **DATE :** Sep. 18, 2013
Ken Liu / Senior Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.225, 15.215)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	Conducted emission test	PASS	Meet the requirement of limit. Minimum passing margin is -5.78dB at 13.565250MHz.
15.225 (a)	The field strength of any emissions within the band 13.553-13.567 MHz	PASS	Meet the requirement of limit. Minimum passing margin is -65.98dB at 13.56MHz.
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band	PASS	Meet the requirement of limit. Minimum passing margin is -8.9dB at 80.35MHz.
15.225 (e)	The frequency tolerance	PASS	Meet the requirement of limit.
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted Emission	150kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	ASUS Tablet
MODEL NO.	TF502T
POWER SUPPLY	3.7Vdc from battery 15Vdc from adapter 5Vdc from host equipment
MODULATION TYPE	ASK
OPERATING FREQUENCY	13.56MHz
ANTENNA TYPE	Loop antenna
DATA CABLE	1.5m shielded USB cable without core
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Adapter, USB kit (Brand: KUANG, Model: ROR-USB60-00)

NOTE:

1. The EUT consumes power from the following battery & adapters.

NO.	PRODUCT	BRAND	MODEL	DESCRIPTION
1	Adapter 1	ASUS	ADP-18BW A	I/P: 100~240Vac, 50-60Hz, 0.5A O/P: 15Vdc, 1.2A (Class II), 40°C
2	Adapter 2	ASUS	ADP-18BW B	I/P: 100~240Vac, 50-60Hz, 0.5A O/P: 15Vdc, 1.2A (Class II), 40°C
3	Adapter 3	ASUS	AD8273	I/P: 100~240Vac, 50-60Hz, 0.5A O/P: 15Vdc, 1.2A (Class II), 40°C
4	Battery	ASUS	C12-TF600T	Rating: 3.7Vdc, 6760mAh, 25Wh

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE	PLC	FS	BW	
A	√	√	√	√	Power from Adapter 1
B	√	√	-	-	Power from Adapter 2
C	√	√	-	-	Power from Adapter 3
D	√	-	-	-	EUT with Mobile Dock
E	√	-	-	-	EUT standalone
F	√	-	-	-	EUT with USB dongle
G	√	√	-	-	EUT with Mobile Dock & Adapter 1
H	√	√	-	-	EUT with Mobile Dock & Adapter 2
I	√	√	-	-	EUT with Mobile Dock & Adapter 3

Where **RE:** Radiated Emission
FS: Frequency Stability

PLC: Power Line Conducted Emission
BW: 20dB Bandwidth

NOTE 1: “-” means no effect.

NOTE 2: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

RADIATED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A, B, C, D, E, F, G, H, I	1	1	ASK

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A, B, C, G, H, I	1	1	ASK

FREQUENCY STABILITY:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A	1	1	ASK

20dB BANDWIDTH:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A	1	1	ASK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE	24deg. C, 64%RH	120Vac, 60Hz	Alan Wu Match Tsui
PLC	26deg. C, 64%RH 25deg. C, 65%RH	120Vac, 60Hz	Jones Chang Chris Lin
FS	24deg. C, 67%RH	120Vac, 60Hz	Alan Wu
BW	24deg. C, 64%RH	120Vac, 60Hz	Alan Wu

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Mobile Dock	ASUS	AD03	NA	FCC DoC Approved
2	USB dongle	Transcend	V85	569992-8209	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA


NOTE: All power cords of the above support units are non-shielded (1.8m).

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST


Test Mode A, B, C




Test Mode D




Test Mode E



Test Mode F



Test Mode G, H, I



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RFID Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.225)

FCC Part 15, Subpart C (15.215)

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B. The test report has been issued separately.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 16, 2012	Nov. 15, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Jan. 28, 2013	Jan. 27, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Mar. 22, 2013	Mar. 21, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-404	Dec. 22, 2012	Dec. 21, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8449B	3008A01911	Oct. 25, 2012	Oct. 24, 2013
Preamplifier Agilent	8447D	2944A10638	Oct. 25, 2012	Oct. 24, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309222/4 248780/4 274392/4	Aug. 22, 2013	Aug. 21, 2014
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 11, 2013	Aug. 10, 2014
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA	NA
Turn Table ADT.	TT100.	TT93021704	NA	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 9.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 460141.
6. The IC Site Registration No. is IC 7450F-4.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

Test Mode A~C, E

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

Test Mode D, G, H, I

- Plugged the EUT into the mobile dock and placed them on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enabled the system in full functions.

Test Mode F

- a. Plugged the USB dongle into the EUT via the USB kit and placed them on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enabled the system in full functions.

4.1.7 TEST RESULTS

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	13.553 ~ 13.567MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu


ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA OPEN AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	13.56	58.02	124.0	-65.98	1.0	350	38.09	19.93

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

$$\begin{aligned}
 13.56\text{MHz} &= 15848\mu\text{V/m} & 30\text{m} \\
 &= 84\text{dBuV/m} & 30\text{m} \\
 &= 84+20\log(30/3)^2 & 3\text{m} \\
 &= 124\text{dBuV/m}
 \end{aligned}$$





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	13.553 ~ 13.567MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu


ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA CLOSE AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	13.56	53.89	124.00	-70.11	100	84	33.96	19.93

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

$$\begin{aligned} 13.56\text{MHz} &= 15848\mu\text{V/m} & 30\text{m} \\ &= 84\text{dBuV/m} & 30\text{m} \\ &= 84+20\log(30/3)^2 & 3\text{m} \\ &= 124\text{dBuV/m} \end{aligned}$$





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 30MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA OPEN AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	27.12	35.34	69.54	-34.20	100	15	15.31	20.03
ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA CLOSE AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	27.12	34.10	69.54	-35.44	100	230	14.07	20.03

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.13	24.8 QP	40.0	-15.2	1.00 H	225	38.90	-14.10
2	119.16	26.3 QP	43.5	-17.2	1.00 H	323	42.60	-16.30
3	206.48	18.9 QP	43.5	-24.6	1.75 H	184	35.40	-16.50
4	336.48	22.9 QP	46.0	-23.1	1.49 H	6	34.70	-11.80
5	431.56	23.5 QP	46.0	-22.5	1.24 H	13	33.50	-10.00
6	503.36	28.0 QP	46.0	-18.0	1.24 H	315	37.00	-9.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	123.04	24.5 QP	43.5	-19.0	1.00 V	281	40.60	-16.10
2	291.85	21.8 QP	46.0	-24.2	3.00 V	159	34.50	-12.70
3	478.13	23.4 QP	46.0	-22.6	1.49 V	117	32.80	-9.40
4	503.36	31.9 QP	46.0	-14.1	1.49 V	136	40.90	-9.00
5	602.32	24.7 QP	46.0	-21.3	1.24 V	166	31.70	-7.00
6	627.54	26.6 QP	46.0	-19.4	1.24 V	193	32.90	-6.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	80.35	31.1 QP	40.0	-8.9	1.00 H	183	49.30	-18.20
2	123.04	22.2 QP	43.5	-21.3	1.49 H	190	38.30	-16.10
3	336.48	24.3 QP	46.0	-21.7	1.75 H	16	36.10	-11.80
4	452.91	25.6 QP	46.0	-20.4	1.49 H	7	35.30	-9.70
5	503.36	30.3 QP	46.0	-15.7	1.49 H	241	39.30	-9.00
6	722.62	23.6 QP	46.0	-22.4	1.24 H	250	28.40	-4.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	59.01	19.4 QP	40.0	-20.6	1.00 V	265	34.20	-14.80
2	130.80	18.5 QP	43.5	-25.0	1.49 V	223	34.00	-15.50
3	336.48	23.4 QP	46.0	-22.6	1.00 V	109	35.20	-11.80
4	377.23	22.1 QP	46.0	-23.9	2.00 V	343	33.30	-11.20
5	503.36	24.8 QP	46.0	-21.2	1.00 V	216	33.80	-9.00
6	627.54	24.4 QP	46.0	-21.6	1.00 V	48	30.70	-6.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.07	27.8 QP	40.0	-12.2	1.49 H	203	42.50	-14.70
2	124.98	24.8 QP	43.5	-18.7	1.00 H	323	40.50	-15.70
3	175.43	21.2 QP	43.5	-22.3	1.00 H	250	36.00	-14.80
4	377.23	24.0 QP	46.0	-22.0	1.49 H	8	35.20	-11.20
5	431.56	24.0 QP	46.0	-22.0	1.49 H	7	34.00	-10.00
6	503.36	23.7 QP	46.0	-22.3	2.00 H	7	32.70	-9.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	59.01	22.3 QP	40.0	-17.8	1.49 V	104	36.99	-14.74
2	103.64	25.0 QP	43.5	-18.5	1.75 V	280	43.09	-18.09
3	124.98	25.8 QP	43.5	-17.8	1.49 V	300	41.50	-15.75
4	173.49	22.4 QP	43.5	-21.2	1.00 V	272	37.04	-14.69
5	503.36	33.1 QP	46.0	-12.9	1.49 V	144	42.14	-9.01
6	627.54	23.4 QP	46.0	-22.6	1.24 V	139	29.76	-6.35

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	D		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	101.69	17.6 QP	43.5	-25.9	1.26 H	142	36.00	-18.40
2	163.79	17.8 QP	43.5	-25.7	1.26 H	7	31.80	-14.00
3	291.85	20.4 QP	46.0	-25.6	1.49 H	163	33.10	-12.70
4	336.48	25.7 QP	46.0	-20.3	1.49 H	104	37.50	-11.80
5	377.23	21.9 QP	46.0	-24.1	1.26 H	7	33.10	-11.20
6	503.36	27.0 QP	46.0	-19.0	1.00 H	182	36.00	-9.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	194.83	17.7 QP	43.5	-25.8	1.75 V	285	34.30	-16.60
2	291.85	22.1 QP	46.0	-23.9	1.00 V	108	34.80	-12.70
3	336.48	28.6 QP	46.0	-17.4	1.00 V	285	40.40	-11.80
4	377.23	23.6 QP	46.0	-22.4	1.00 V	274	34.80	-11.20
5	503.36	30.2 QP	46.0	-15.8	1.49 V	44	39.20	-9.00
6	627.54	23.9 QP	46.0	-22.1	1.49 V	88	30.20	-6.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	E		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	103.64	15.8 QP	43.5	-27.7	1.50 H	87	33.90	-18.10
2	336.48	20.2 QP	46.0	-25.8	1.25 H	132	32.00	-11.80
3	377.23	22.5 QP	46.0	-23.5	1.00 H	205	33.70	-11.20
4	402.46	20.4 QP	46.0	-25.6	1.00 H	6	31.30	-10.90
5	503.36	29.6 QP	46.0	-16.4	1.75 H	208	38.60	-9.00
6	602.32	21.9 QP	46.0	-24.1	1.00 H	216	28.90	-7.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	251.11	18.9 QP	46.0	-27.1	1.00 V	284	33.40	-14.50
2	291.85	21.3 QP	46.0	-24.7	1.00 V	97	34.00	-12.70
3	336.48	25.5 QP	46.0	-20.5	3.00 V	296	37.30	-11.80
4	377.23	26.4 QP	46.0	-19.6	1.25 V	106	37.60	-11.20
5	402.46	23.3 QP	46.0	-22.7	1.00 V	86	34.20	-10.90
6	503.36	24.0 QP	46.0	-22.0	1.00 V	336	33.00	-9.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Alan Wu
TEST MODE	F		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	103.64	16.6 QP	43.5	-26.9	2.00 H	12	34.70	-18.10
2	295.73	18.0 QP	46.0	-28.0	1.00 H	298	30.70	-12.70
3	336.48	23.8 QP	46.0	-22.2	1.49 H	5	35.60	-11.80
4	377.23	26.0 QP	46.0	-20.0	1.24 H	7	37.20	-11.20
5	431.56	25.3 QP	46.0	-20.7	1.49 H	12	35.30	-10.00
6	503.36	27.7 QP	46.0	-18.3	1.00 H	322	36.70	-9.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	251.11	16.7 QP	46.0	-29.3	1.00 V	89	31.20	-14.50
2	377.23	22.5 QP	46.0	-23.5	1.00 V	144	33.70	-11.20
3	478.13	23.6 QP	46.0	-22.4	3.00 V	114	33.00	-9.40
4	503.36	32.8 QP	46.0	-13.2	1.49 V	154	41.80	-9.00
5	528.58	24.1 QP	46.0	-21.9	1.49 V	6	32.70	-8.60
6	726.50	24.4 QP	46.0	-21.6	1.49 V	309	29.10	-4.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Match Tsui
TEST MODE	G		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	142.52	25.6 QP	43.5	-17.9	2.00 H	38	39.80	-14.20
2	745.86	27.5 QP	46.0	-18.5	2.00 H	355	31.10	-3.60
3	871.96	29.4 QP	46.0	-16.6	1.00 H	18	30.70	-1.30
4	885.54	29.7 QP	46.0	-16.3	2.00 H	12	30.80	-1.10
5	934.04	30.2 QP	46.0	-15.8	1.00 H	146	30.30	-0.10
6	947.62	31.7 QP	46.0	-14.3	2.00 H	315	31.60	0.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	115.36	26.2 QP	43.5	-17.3	1.01 V	15	42.90	-16.70
2	761.38	28.1 QP	46.0	-17.9	1.01 V	15	31.20	-3.10
3	833.16	28.5 QP	46.0	-17.5	1.01 V	269	30.50	-2.00
4	873.90	29.5 QP	46.0	-16.5	2.00 V	231	30.70	-1.20
5	885.54	29.6 QP	46.0	-16.4	2.00 V	127	30.70	-1.10
6	937.92	31.1 QP	46.0	-14.9	1.01 V	106	31.10	0.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Match Tsui
TEST MODE	H		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	774.96	28.6 QP	46.0	-17.4	1.00 H	11	31.60	-3.00
2	806.00	28.1 QP	46.0	-17.9	1.00 H	236	30.70	-2.60
3	844.80	28.7 QP	46.0	-17.3	1.00 H	305	30.50	-1.80
4	895.24	30.1 QP	46.0	-15.9	1.00 H	320	31.00	-0.90
5	930.16	30.4 QP	46.0	-15.6	1.00 H	249	30.50	-0.10
6	939.86	30.9 QP	46.0	-15.1	1.00 H	18	31.10	-0.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	806.00	28.5 QP	46.0	-17.5	1.01 V	16	31.10	-2.60
2	838.98	29.7 QP	46.0	-16.3	1.01 V	336	31.50	-1.80
3	864.20	29.4 QP	46.0	-16.6	1.01 V	81	30.70	-1.30
4	904.94	30.1 QP	46.0	-15.9	2.00 V	16	30.80	-0.70
5	930.16	30.4 QP	46.0	-15.6	2.00 V	11	30.50	-0.10
6	957.32	30.8 QP	46.0	-15.2	1.01 V	222	30.50	0.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Match Tsui
TEST MODE	I		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	142.52	25.8 QP	43.5	-17.7	2.00 H	45	40.00	-14.20
2	813.76	28.6 QP	46.0	-17.4	2.00 H	340	30.90	-2.30
3	833.16	29.0 QP	46.0	-17.0	2.00 H	326	31.00	-2.00
4	856.44	29.4 QP	46.0	-16.6	2.00 H	110	30.90	-1.50
5	899.12	29.5 QP	46.0	-16.5	2.00 H	15	30.30	-0.80
6	941.80	31.5 QP	46.0	-14.5	1.00 H	305	31.60	-0.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	66.86	24.3 QP	40.0	-15.7	1.00 V	131	40.30	-16.00
2	774.96	28.1 QP	46.0	-17.9	1.00 V	12	31.10	-3.00
3	837.04	29.1 QP	46.0	-16.9	2.00 V	198	31.10	-2.00
4	864.20	29.4 QP	46.0	-16.6	2.00 V	26	30.70	-1.30
5	899.12	29.7 QP	46.0	-16.3	2.00 V	13	30.50	-0.80
6	934.04	30.8 QP	46.0	-15.2	2.00 V	297	30.90	-0.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 09, 2012	Nov. 08, 2013
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 21, 2012	Dec. 20, 2013
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 17, 2013	Jul. 16, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


4.2.7 TEST RESULTS

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20078	0.20	44.81	31.27	45.01	31.47	63.58	53.58	-18.57	-22.11
2	0.32578	0.21	36.09	21.00	36.30	21.21	59.56	49.56	-23.26	-28.35
3	0.40781	0.22	33.15	18.42	33.37	18.64	57.69	47.69	-24.32	-29.05
4	0.63828	0.25	29.20	15.12	29.45	15.37	56.00	46.00	-26.55	-30.63
5	0.86484	0.27	28.25	12.36	28.52	12.63	56.00	46.00	-27.48	-33.37
6	10.81641	0.51	39.31	30.04	39.82	30.55	60.00	50.00	-20.18	-19.45
7	13.56250	0.58	53.64	40.09	54.22	40.67	60.00	50.00	-5.78	-9.33

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20469	0.19	52.85	40.09	53.04	40.28	63.42	53.42	-10.38	-13.14
2	0.31016	0.23	44.00	30.03	44.23	30.26	59.97	49.97	-15.73	-19.70
3	0.41172	0.27	38.82	22.82	39.09	23.09	57.61	47.61	-18.52	-24.52
4	0.52500	0.27	32.54	17.76	32.81	18.03	56.00	46.00	-23.19	-27.97
5	10.37891	0.58	35.79	24.90	36.37	25.48	60.00	50.00	-23.63	-24.52
6	13.55859	0.66	51.95	36.34	52.61	37.00	60.00	50.00	-7.39	-13.00
7	21.08203	0.81	30.77	21.25	31.58	22.06	60.00	50.00	-28.42	-27.94

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.20	57.82	43.37	58.02	43.57	64.08	54.08	-6.06	-10.51
2	0.26328	0.21	47.47	34.02	47.68	34.23	61.33	51.33	-13.65	-17.10
3	0.31797	0.21	43.47	31.07	43.68	31.28	59.76	49.76	-16.08	-18.48
4	0.39219	0.22	37.44	23.87	37.66	24.09	58.02	48.02	-20.36	-23.93
5	0.44297	0.23	36.20	23.45	36.43	23.68	57.01	47.01	-20.58	-23.33
6	13.56115	0.58	50.16	38.91	50.74	39.49	60.00	50.00	-9.26	-10.51
7	19.11328	0.71	29.55	24.51	30.26	25.22	60.00	50.00	-29.74	-24.78

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.19	46.96	20.19	47.15	20.38	66.00	56.00	-18.85	-35.62
2	0.18906	0.19	54.98	40.96	55.17	41.15	64.08	54.08	-8.91	-12.93
3	0.25156	0.21	45.86	31.69	46.07	31.90	61.71	51.71	-15.63	-19.80
4	0.32578	0.24	40.23	27.62	40.47	27.86	59.56	49.56	-19.09	-21.70
5	0.46250	0.27	32.74	19.93	33.01	20.20	56.65	46.65	-23.64	-26.45
6	13.55987	0.66	49.44	39.98	50.10	40.64	60.00	50.00	-9.90	-9.36
7	18.84766	0.79	30.57	25.68	31.36	26.47	60.00	50.00	-28.64	-23.53

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	C		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20469	0.20	37.53	26.44	37.73	26.64	63.42	53.42	-25.69	-26.78
2	0.31406	0.21	40.96	27.43	41.17	27.64	59.86	49.86	-18.69	-22.22
3	0.63438	0.25	35.19	20.68	35.44	20.93	56.00	46.00	-20.56	-25.07
4	0.86094	0.27	34.22	16.73	34.49	17.00	56.00	46.00	-21.51	-29.00
5	1.85547	0.32	33.80	15.60	34.12	15.92	56.00	46.00	-21.88	-30.08
6	6.66016	0.44	34.80	20.01	35.24	20.45	60.00	50.00	-24.76	-29.55
7	13.56050	0.58	52.40	36.50	52.98	37.08	60.00	50.00	-7.02	-12.92

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	C		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20469	0.19	32.05	23.50	32.24	23.69	63.42	53.42	-31.18	-29.73
2	0.32188	0.24	40.29	28.32	40.53	28.56	59.66	49.66	-19.13	-21.10
3	0.42344	0.27	36.59	23.49	36.86	23.76	57.38	47.38	-20.52	-23.62
4	0.64609	0.27	36.38	21.80	36.65	22.07	56.00	46.00	-19.35	-23.93
5	1.24219	0.27	36.63	16.45	36.90	16.72	56.00	46.00	-19.10	-29.28
6	7.29688	0.52	36.58	24.58	37.10	25.10	60.00	50.00	-22.90	-24.90
7	13.56250	0.66	52.42	34.84	53.08	35.50	60.00	50.00	-6.92	-14.50

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	G		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.30625	0.21	42.74	31.60	42.95	31.81	60.07	50.07	-17.12	-18.26
2	0.52109	0.23	36.04	22.52	36.27	22.75	56.00	46.00	-19.73	-23.25
3	0.86094	0.27	34.89	18.62	35.16	18.89	56.00	46.00	-20.84	-27.11
4	1.68750	0.31	33.14	17.46	33.45	17.77	56.00	46.00	-22.55	-28.23
5	6.54297	0.44	38.76	23.27	39.20	23.71	60.00	50.00	-20.80	-26.29
6	13.56250	0.58	41.10	40.22	41.68	40.80	60.00	50.00	-18.32	-9.20

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	G		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20469	0.19	37.30	25.35	37.49	25.54	63.42	53.42	-25.93	-27.88
2	0.30234	0.23	35.74	25.32	35.97	25.55	60.18	50.18	-24.21	-24.63
3	0.52891	0.27	37.52	20.90	37.79	21.17	56.00	46.00	-18.21	-24.83
4	1.60547	0.30	36.92	20.52	37.22	20.82	56.00	46.00	-18.78	-25.18
5	6.53516	0.50	36.60	21.00	37.10	21.50	60.00	50.00	-22.90	-28.50
6	13.55859	0.66	41.10	40.51	41.76	41.17	60.00	50.00	-18.24	-8.83

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	H		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20859	0.20	45.92	33.52	46.12	33.72	63.26	53.26	-17.14	-19.54
2	0.31406	0.21	35.10	21.82	35.31	22.03	59.86	49.86	-24.55	-27.83
3	0.61875	0.25	34.17	17.64	34.42	17.89	56.00	46.00	-21.58	-28.11
4	1.31250	0.30	41.65	23.82	41.95	24.12	56.00	46.00	-14.05	-21.88
5	10.60156	0.50	40.53	31.08	41.03	31.58	60.00	50.00	-18.97	-18.42
6	13.56250	0.58	45.45	38.35	46.03	38.93	60.00	50.00	-13.97	-11.07

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	H		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20859	0.19	53.20	40.29	53.39	40.48	63.26	53.26	-9.87	-12.78
2	0.31797	0.24	42.46	28.73	42.70	28.97	59.76	49.76	-17.06	-20.79
3	0.40781	0.27	37.88	23.00	38.15	23.27	57.69	47.69	-19.54	-24.42
4	1.25000	0.28	32.37	13.11	32.65	13.39	56.00	46.00	-23.35	-32.61
5	3.26953	0.40	29.46	15.37	29.86	15.77	56.00	46.00	-26.14	-30.23
6	13.55859	0.66	41.20	38.35	41.86	39.01	60.00	50.00	-18.14	-10.99

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	I		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.20	51.24	38.29	51.44	38.49	64.08	54.08	-12.64	-15.59
2	0.25156	0.21	42.81	30.11	43.02	30.32	61.71	51.71	-18.69	-21.39
3	0.32188	0.21	36.56	26.33	36.77	26.54	59.66	49.66	-22.89	-23.12
4	0.47422	0.23	34.09	20.92	34.32	21.15	56.44	46.44	-22.12	-25.29
5	13.56250	0.58	38.20	37.99	38.78	38.57	60.00	50.00	-21.22	-11.43
6	18.83984	0.70	29.24	24.76	29.94	25.46	60.00	50.00	-30.06	-24.54

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	I		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.19	45.07	18.20	45.26	18.39	66.00	56.00	-20.74	-37.61
2	0.18906	0.19	53.23	39.62	53.42	39.81	64.08	54.08	-10.66	-14.27
3	0.25547	0.21	43.11	31.24	43.32	31.45	61.58	51.58	-18.26	-20.13
4	1.37500	0.28	29.78	17.65	30.06	17.93	56.00	46.00	-25.94	-28.07
5	4.45313	0.46	26.90	19.34	27.36	19.80	56.00	46.00	-28.64	-26.20
6	13.56250	0.66	39.52	38.48	40.18	39.14	60.00	50.00	-19.82	-10.86

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 FREQUENCY STABILITY

4.3.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
R&S SPECTRUM ANALYZER	FSP40	100039	Jan. 31, 2013	Jan. 30, 2014
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 10, 2013	Jun. 09, 2014

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITION

Same as Item 4.1.6.

4.3.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
TEMP. (°C)	POWER SUPPLY (Vdc)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
50	5	13.559956	-0.000324	13.559970	-0.000221	13.559952	-0.000354	13.559971	-0.000214
40	5	13.560066	0.000487	13.560054	0.000398	13.560054	0.000398	13.560050	0.000369
30	5	13.559943	-0.000420	13.559958	-0.000310	13.559958	-0.000310	13.559959	-0.000302
20	5	13.560057	0.000420	13.560050	0.000369	13.560059	0.000435	13.560043	0.000317
10	5	13.559957	-0.000317	13.559950	-0.000369	13.559966	-0.000251	13.559947	-0.000391
0	5	13.560055	0.000406	13.560054	0.000398	13.560054	0.000398	13.560062	0.000457
-10	5	13.560022	0.000162	13.560016	0.000118	13.560008	0.000059	13.560015	0.000111
-20	5	13.559936	-0.000472	13.559942	-0.000428	13.559946	-0.000398	13.559929	-0.000524

FREQUENCY STABILITY VERSUS VOLTAGE									
TEMP. (°C)	POWER SUPPLY (Vdc)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	5.75	13.560054	0.00040	13.560052	0.00038	13.560058	0.00043	13.560043	0.00032
	5	13.560057	0.00042	13.56005	0.00037	13.560059	0.00044	13.560043	0.00032
	4.25	13.560054	0.00040	13.560053	0.00039	13.560057	0.00042	13.560042	0.00031

4.4 20dB BANDWIDTH

4.4.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

The 20dB bandwidth shall be specified in operating frequency band.

4.4.2 TEST INSTRUMENTS

Same as Item 4.1.2.

4.4.3 TEST PROCEDURE

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1kHz RBW and 1kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP


Same as Item 4.1.5.

4.4.6 EUT OPERATING CONDITION

Same as Item 4.1.6.

4.4.7 TEST RESULTS

20dBc point (Low)	20dBc point (High)	Operating frequency band (MHz)	PASS/FAIL
13.55934 MHz	13.56192 MHz	13.553~13.567	PASS



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---