



# FCC RF Test Report

APPLICANT : ASUSTeK COMPUTER INC.  
EQUIPMENT : ASUS Phone  
BRAND NAME : ASUS  
MODEL NAME : ASUS\_Z01GD  
FCC ID : MSQZ01GD  
STANDARD : FCC 47 CFR Part 2, and 90(S)  
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 08, 2017 and testing was completed on Jun. 28, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-D-2010 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Feature of Equipment Under Test..... 5

    1.4 Modification of EUT ..... 6

    1.5 Testing Site..... 7

    1.6 Applied Standards ..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Test Mode..... 8

    2.2 Connection Diagram of Test System ..... 9

    2.3 Support Unit used in test configuration and system..... 9

    2.4 Measurement Results Explanation Example ..... 9

    2.5 Frequency List of Low/Middle/High Channels..... 10

**3 TEST RESULT ..... 11**

    3.1 Conducted Output Power Measurement..... 11

    3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 12

    3.3 Emissions Mask Measurement ..... 13

    3.4 Emissions Mask – Out Of Band Emissions Measurement..... 15

    3.5 Field Strength of Spurious Radiation Measurement ..... 16

    3.6 Frequency Stability Measurement..... 18

**4 LIST OF MEASURING EQUIPMENT ..... 20**

**5 UNCERTAINTY OF EVALUATION ..... 21**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST**

**APPENDIX C. TEST SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW740840	Rev. 01	Initial issue of report	Aug. 09, 2017



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 46.11 dB at 1638.500 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-



# 1 General Description

## 1.1 Applicant

ASUSTeK COMPUTER INC.

4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN

## 1.2 Manufacturer

COTEK ELECTRONICS (SUZHOU) CO., LTD.

No.288, Mayun Road, Suzhou Hi-and-New Tech Park, Jiangsu, PRC

## 1.3 Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, FM Receiver, NFC, and GPS

Product Specification subjective to this standard	
Sample 1	EUT with SKU 1
Sample 2	EUT with SKU 2
Sample 3	EUT with SKU 3
Sample 4	EUT with SKU 4
Sample 5	EUT with SKU 5
Sample 6	EUT with SKU 6
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC: Loop Antenna

**<Sample Information>**

SKU MB	SKU1	SKU2
DDR4X	6G/ Hynix	6G/ Hynix
UFS 2.1	128G/ Samsung	64G/ Toshiba
CPU	MSM-8998-1-885MPSP-TR-02-0-AB	
TP Module	TIANMA/TA055VVHM08-03 ON CELL	TIANMA/TA055VVHM09-03 ON CELL
Front Camera (8M)	CAMERA MODULE 8M AF (SonyIMX319, XPT 85B-BC28-SU,KT F6518)	
Rear Camera (12+16M)	DUAL CAMERA MODULE 12M+16M/SEMCO/MOMDM82PG3A V0.0	
Battery	ZS551KL BAT/ATL POLY/C11P1701/SMP/PS414997/1S1P/3.85V/13.8WH	

SKU MB	SKU3	SKU4
DDR4X	4G/ Hynix	6G/ Hynix
UFS 2.1	64G/ Toshiba	64G/ Samsung
CPU	MSM-8998-1-885MPSP-TR-02-0-AB	
TP Module	TIANMA/TA055VVHM09-03 ON CELL	TIANMA/TA055VVHM08-00 ON CELL
Front Camera (8M)	CAMERA MODULE 8M AF (SonyIMX319, XPT 85B-BC28-SU,KT F6518)	
Rear Camera (12+16M)	DUAL CAMERA MODULE 12M+16M/SEMCO/MOMDM82PG3A V0.0	
Battery	ZS551KL BAT/ATL POLY/C11P1701/SMP/PS414997/1S1P/3.85V/13.8WH	

SKU MB	SKU5	SKU6
DDR4X	6G Hynix	6G Hynix
UFS 2.1	128G Toshiba	UFS 2.0 64G Toshiba
CPU	MSM-8998-1-885MPSP-TR-02-0-AB	
TP Module	TIANMA/TA055VVHM09-05 ON CELL	
Front Camera (8M)	CAMERA MODULE 8M AF (SonyIMX319, XPT 85B-BC28-SU,KT F6518)	
Rear Camera (12+16M)	DUAL CAMERA MODULE 12M+16M/SEMCO/MOMDM82PG3A V0.0	
Battery	ZS551KL BAT/ATL POLY/C11P1701/SMP/PS414997/1S1P/3.85V/13.8WH	

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.5 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	

<b>Test Site</b>	SPORTON International (ShenZhen) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH03-SZ	565805

### 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 90
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- ♦ Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v	v			v	v	v
Frequency Stability	26				v	v	-	v					v		v	
E.R.P.	26	v	v	v	v	v	-	v	v	v	v			v		
Radiated Spurious Emission	26	v	v	v	v		-	v			v			v	v	v
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported.															



## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$Offset = RF\ cable\ loss + attenuator\ factor.$

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 Offset(dB) &= RF\ cable\ loss(dB) + attenuator\ factor(dB). \\
 &= 4.2 + 10 = 14.2\ (dB)
 \end{aligned}$$



## 2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

## 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

### 3.2.4 Test Setup



### 3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



### 3.3 Emissions Mask Measurement

#### 3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \text{ Log}_{10}(f/6.1)$  decibels or  $50 + 10 \text{ Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10\text{Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor  $10\log(1\% \text{ of OBW/measured RBW})(\text{dB})$  was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

### 3.3.4 Test Setup



### 3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

### 3.4 Emissions Mask – Out Of Band Emissions Measurement

#### 3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least  $43 + 10 \log (P)$  dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)

#### 3.4.4 Test Setup



#### 3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.



### 3.5 Field Strength of Spurious Radiation Measurement

#### 3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log_{10}(P[\text{Watts}])$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11.  $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10 \log(P)$  dB below the transmitter power P(Watts)




### 3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



### 3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.



## 3.6 Frequency Stability Measurement

### 3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency according to FCC Part 90.213.

### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.6.5 Test Setup



### 3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 04, 2016	Apr. 08, 2017 ~ Jun. 19, 2017	Nov. 03, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30°C~70°C	Sep. 01, 2016	Apr. 08, 2017 ~ Jun. 19, 2017	Aug. 31, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~5A	Oct. 03, 2016	Apr. 08, 2017 ~ Jun. 19, 2017	Oct. 02, 2017	Conducted (TH05-HY)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY5445008 3	20Hz~8.4GHz	Apr.20, 2017	Jun. 26, 2017 ~ Jun. 28, 2017	Apr.19, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 14, 2017	Jun. 26, 2017 ~ Jun. 28, 2017	May. 13, 2018	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Jul.09.2017	Jun. 26, 2017 ~ Jun. 28, 2017	Jul. 08, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Jun. 26, 2017 ~ Jun. 28, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 11, 2016	Jun. 26, 2017 ~ Jun. 28, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY3950130 2	500MHz~26.5GHz	Jan. 06, 2017	Jun. 26, 2017 ~ Jun. 28, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	6160100019 85	N/A	NCR	Jun. 26, 2017 ~ Jun. 28, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 26, 2017 ~ Jun. 28, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 26, 2017 ~ Jun. 28, 2017	NCR	Radiation (03CH03-SZ)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.6dB
---	-------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.8dB
---	-------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	<b>23.06</b>	-	-
15	1	37		22.82	-	-
15	1	74		22.59	-	-
15	36	0		21.98	-	-
15	36	20		21.96	-	-
15	36	39		21.74	-	-
15	75	0		21.91	-	-
15	1	0	16-QAM	22.26	-	-
15	1	37		22.14	-	-
15	1	74		21.91	-	-
15	36	0		20.98	-	-
15	36	20		20.94	-	-
15	36	39		20.72	-	-
15	75	0		20.91	-	-
15	1	0	64-QAM	21.20	-	-
15	1	37		21.04	-	-
15	1	74		20.79	-	-
15	36	0		20.00	-	-
15	36	20		19.97	-	-
15	36	39		19.73	-	-
15	75	0		19.92	-	-
10	1	0	QPSK	-	22.62	-
10	1	25		-	22.51	-
10	1	49		-	22.71	-
10	25	0		-	21.61	-
10	25	12		-	21.59	-
10	25	25		-	21.63	-
10	50	0		-	21.58	-
10	1	0	16-QAM	-	22.00	-
10	1	25		-	21.83	-
10	1	49		-	21.98	-
10	25	0		-	20.61	-
10	25	12		-	20.62	-
10	25	25		-	20.61	-
10	50	0		-	20.59	-
10	1	0	64-QAM	-	20.84	-
10	1	25		-	20.74	-
10	1	49		-	20.90	-
10	25	0		-	19.66	-
10	25	12		-	19.64	-
10	25	25		-	19.64	-
10	50	0		-	19.60	-



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.88	22.55	23.05
5	1	12		22.82	22.50	23.04
5	1	24		22.79	22.53	23.00
5	12	0		21.96	21.58	22.13
5	12	7		21.94	21.58	22.13
5	12	13		21.88	21.64	22.10
5	25	0		21.91	21.56	22.16
5	1	0	16-QAM	22.18	21.91	22.42
5	1	12		22.11	21.83	22.29
5	1	24		22.04	21.82	22.19
5	12	0		20.98	20.63	21.17
5	12	7		20.94	20.60	21.16
5	12	13		20.89	20.66	21.09
5	25	0		20.93	20.58	21.14
5	1	0	64-QAM	21.10	20.77	21.26
5	1	12		21.05	20.70	21.27
5	1	24		21.00	20.71	21.24
5	12	0		20.00	19.63	20.21
5	12	7		19.99	19.64	20.22
5	12	13		19.95	19.70	20.18
5	25	0		19.92	19.57	20.16
3	1	0	QPSK	22.87	22.52	23.05
3	1	8		22.83	22.49	23.04
3	1	14		22.82	22.56	22.98
3	8	0		21.94	21.57	22.12
3	8	4		21.94	21.58	22.16
3	8	7		21.90	21.53	22.13
3	15	0		21.90	21.53	22.11
3	1	0	16-QAM	22.14	21.87	22.30
3	1	8		22.13	21.83	22.21
3	1	14		22.04	21.85	22.19
3	8	0		21.01	20.61	21.19
3	8	4		21.02	20.64	21.18
3	8	7		20.98	20.59	21.17
3	15	0		20.95	20.59	21.13
3	1	0	64-QAM	21.07	20.73	21.28
3	1	8		21.06	20.73	21.25
3	1	14		21.02	20.75	21.23
3	8	0		19.97	19.59	20.17
3	8	4		20.00	19.62	20.18
3	8	7		19.96	19.57	20.16
3	15	0		19.94	19.56	20.17



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.80	22.45	22.94
1.4	1	3		22.82	22.50	22.96
1.4	1	5		22.78	22.43	22.90
1.4	3	0		22.86	22.49	23.03
1.4	3	1		22.90	22.51	22.75
1.4	3	3		22.84	22.49	23.01
1.4	6	0		21.88	21.49	22.04
1.4	1	0	16-QAM	22.07	21.79	22.09
1.4	1	3		22.13	21.82	22.18
1.4	1	5		22.03	21.72	22.09
1.4	3	0		21.88	21.51	22.04
1.4	3	1		21.90	21.57	22.08
1.4	3	3		21.83	21.52	22.01
1.4	6	0		20.93	20.57	21.12
1.4	1	0	64-QAM	21.00	20.66	21.17
1.4	1	3		21.04	20.70	21.24
1.4	1	5		21.00	20.62	21.18
1.4	3	0		20.99	20.63	21.14
1.4	3	1		21.03	20.70	21.18
1.4	3	3		20.98	20.61	21.15
1.4	6	0		19.89	19.52	20.01





# LTE Band 26\_Part 90S

## Peak-to-Average Ratio

Mode	LTE Band 26 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	<b>PASS</b>
Middle CH	4.29	4.87	5.1	5.83	
Highest CH	-	-	-	-	
Mode	LTE Band 26 / 10MHz				
Mod.			64QAM		Limit: 13dB
RB Size			1RB	Full RB	Result
Lowest CH	-	-	-	-	<b>PASS</b>
Middle CH	-	-	4.9	5.8	
Highest CH	-	-	-	-	




LTE Band 26 / 10MHz / QPSK

Middle Channel / 1RB



Date: 15 JUN 2017 00:45:23

Middle Channel / Full RB



Date: 15 JUN 2017 00:46:09

LTE Band 26 / 10MHz / 16QAM

Middle Channel / 1RB



Date: 15 JUN 2017 00:45:33


Middle Channel / Full RB



Date: 15 JUN 2017 00:45:59


LTE Band 26 / 10MHz / 64QAM

Middle Channel / 1RB



Date: 15 JUN 2017 15:13:28

Middle Channel / Full RB



Date: 15 JUN 2017 15:13:37




**26dB Bandwidth**

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.214	1.225	3.045	3.027	4.895	4.895	-	-	14.326	14.176	-	-
Middle CH	1.22	1.228	2.997	2.997	4.895	4.855	9.65	9.65	-	-	-	-
Highest CH	1.231	1.225	3.033	2.979	4.845	4.865	-	-	-	-	-	-
Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.		64QAM		64QAM		64QAM		64QAM		64QAM		64QAM
Lowest CH	-	1.217	-	2.991	-	4.865	-	-	-	14.146	-	-
Middle CH	-	1.228	-	2.961	-	4.855	-	9.75	-	-	-	-
Highest CH	-	1.228	-	3.033	-	4.875	-	-	-	-	-	-




LTE Band 26

Lowest Channel / 1.4MHz / QPSK




Date: 14 JUN 2017 22:56:49

Lowest Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 22:56:38

Middle Channel / 1.4MHz / QPSK




Date: 14 JUN 2017 22:58:11

Middle Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 22:59:22

Highest Channel / 1.4MHz / QPSK



Date: 14 JUN 2017 23:01:44

Highest Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 23:01:55




LTE Band 26

Lowest Channel / 3MHz / QPSK




Date: 14 JUN 2017 23:46:00

Lowest Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:46:10

Middle Channel / 3MHz / QPSK




Date: 14 JUN 2017 23:48:33

Middle Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:48:43

Highest Channel / 3MHz / QPSK



Date: 14 JUN 2017 23:51:06

Highest Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:51:16




LTE Band 26

Lowest Channel / 5MHz / QPSK




Date: 14 JUN 2017 23:53:39

Lowest Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:53:49

Middle Channel / 5MHz / QPSK




Date: 14 JUN 2017 23:56:12

Middle Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:56:22

Highest Channel / 5MHz / QPSK



Date: 14 JUN 2017 23:58:45

Highest Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:58:55




LTE Band 26

Middle Channel / 10MHz / QPSK




Date: 15 JUN 2017 00:01:18

Middle Channel / 10MHz / 16QAM




Date: 15 JUN 2017 00:01:28

Lowest Channel / 15MHz / QPSK



Date: 15 JUN 2017 00:03:51

Lowest Channel / 15MHz / 16QAM




Date: 15 JUN 2017 00:04:02




LTE Band 26


Lowest Channel / 1.4MHz / 64QAM



Middle Channel / 1.4MHz / 64QAM



Highest Channel / 1.4MHz / 64QAM









LTE Band 26

Lowest Channel / 3MHz / 64QAM




Date: 15 JUN 2017 14:57:46

Middle Channel / 3MHz / 64QAM



Date: 15 JUN 2017 14:59:02

Highest Channel / 3MHz / 64QAM




Date: 15 JUN 2017 15:00:18




LTE Band 26

Lowest Channel / 5MHz / 64QAM




Date: 15 JUN 2017 15:01:34

Middle Channel / 5MHz / 64QAM



Date: 15 JUN 2017 15:02:51

Highest Channel / 5MHz / 64QAM




Date: 15 JUN 2017 15:04:07




LTE Band 26

Middle Channel / 10MHz / 64QAM



Lowest Channel / 15MHz / 64QAM






**Occupied Bandwidth**

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.71	2.7	4.45	4.48	-	-	13.46	13.46	-	-
Middle CH	1.09	1.09	2.72	2.72	4.47	4.5	9.03	8.99	-	-	-	-
Highest CH	1.09	1.09	2.72	2.72	4.49	4.49	-	-	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.		64QAM		64QAM		64QAM		64QAM		64QAM		64QAM
Lowest CH	-	1.09	-	2.72	-	4.48	-	-	-	13.49	-	-
Middle CH	-	1.08	-	2.73	-	4.49	-	8.97	-	-	-	-
Highest CH	-	1.09	-	2.73	-	4.51	-	-	-	-	-	-




LTE Band 26

Lowest Channel / 1.4MHz / QPSK




Date: 14 JUN 2017 22:56:18

Lowest Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 22:56:28

Middle Channel / 1.4MHz / QPSK




Date: 14 JUN 2017 22:58:50

Middle Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 22:59:01

Highest Channel / 1.4MHz / QPSK



Date: 14 JUN 2017 23:01:24

Highest Channel / 1.4MHz / 16QAM




Date: 14 JUN 2017 23:01:34




LTE Band 26

Lowest Channel / 3MHz / QPSK




Date: 14 JUN 2017 23:45:39

Lowest Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:45:50

Middle Channel / 3MHz / QPSK




Date: 14 JUN 2017 23:48:12

Middle Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:48:23

Highest Channel / 3MHz / QPSK



Date: 14 JUN 2017 23:50:45

Highest Channel / 3MHz / 16QAM




Date: 14 JUN 2017 23:50:56




LTE Band 26

Lowest Channel / 5MHz / QPSK




Date: 14 JUN 2017 23:53:18

Lowest Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:53:29

Middle Channel / 5MHz / QPSK




Date: 14 JUN 2017 23:55:51

Middle Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:56:02

Highest Channel / 5MHz / QPSK



Date: 14 JUN 2017 23:58:24

Highest Channel / 5MHz / 16QAM




Date: 14 JUN 2017 23:58:35




LTE Band 26

Middle Channel / 10MHz / QPSK



Date: 15 JUN 2017 00:00:57


Middle Channel / 10MHz / 16QAM



Date: 15 JUN 2017 00:01:08


LTE Band 26

Lowest Channel / 15MHz / QPSK



Date: 15 JUN 2017 00:03:31

Lowest Channel / 15MHz / 16QAM




Date: 15 JUN 2017 00:03:41






LTE Band 26

Lowest Channel / 1.4MHz / 64QAM




Date: 15 JUN 2017 15:09:37

Middle Channel / 1.4MHz / 64QAM



Date: 15 JUN 2017 15:10:54

Highest Channel / 1.4MHz / 64QAM




Date: 15 JUN 2017 15:12:10




LTE Band 26


Lowest Channel / 3MHz / 64QAM



Middle Channel / 3MHz / 64QAM




Highest Channel / 3MHz / 64QAM






LTE Band 26

Lowest Channel / 5MHz / 64QAM




Date: 15 JUN 2017 15:01:24

Middle Channel / 5MHz / 64QAM



Date: 15 JUN 2017 15:02:40

Highest Channel / 5MHz / 64QAM




Date: 15 JUN 2017 15:03:57




LTE Band 26

Middle Channel / 10MHz / 64QAM



LTE Band 26

Lowest Channel / 15MHz / 64QAM






**Conducted Band Edge**




LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB




Date: 14 JUN 2017 23:04:55

Highest Band Edge / 1RB




Date: 14 JUN 2017 23:09:33

Lowest Band Edge / Full RB



Date: 14 JUN 2017 23:07:14

Highest Band Edge / Full RB




Date: 14 JUN 2017 23:11:52




LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 14 JUN 2017 23:06:04

Highest Band Edge / 1 RB




Date: 14 JUN 2017 23:10:42

Lowest Band Edge / Full RB



Date: 14 JUN 2017 23:08:23

Highest Band Edge / Full RB




Date: 14 JUN 2017 23:13:01




LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 15 JUN 2017 15:15:07

Highest Band Edge / 1 RB




Date: 15 JUN 2017 14:40:01

Lowest Band Edge / Full RB



Date: 15 JUN 2017 14:38:52

Highest Band Edge / Full RB



Date: 15 JUN 2017 14:41:11