



## Test Report

Prepared for: Time Keeping Systems Inc.

Model: TAG-006

Description: Body Worn Location Device

Serial Number: N/A

FCC ID: MTD-0006  
IC: 12375A-0006

To

FCC Part 15.247  
IC RSS-247 Issue 2

Date of Issue: June 25, 2018

On the behalf of the applicant:

Time Keeping Systems Inc.  
30700 Bainbridge Rd  
Cleveland, OH 44139

Attention of:

Blair Hamilton, Hardware Engineer  
Ph: (216)595-1026  
E-Mail: [dchriss@guard1.com](mailto:dchriss@guard1.com)

Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1850027

**Kenneth Lee**  
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing.  
All results contained herein relate only to the sample tested.



**Test Report Revision History**

<b>Revision</b>	<b>Date</b>	<b>Revised By</b>	<b>Reason for Revision</b>
1.0	June 19, 2018	Kenneth Lee	Original Document
2.0	June 25, 2018	Kenneth Lee	Updated the term BLE to GFSK in additional Information



## Table of Contents

<b><u>Description</u></b>	<b><u>Page</u></b>
Standard Test Conditions Engineering Practices .....	6
Output Power .....	8
Radiated Spurious Emissions .....	9
Conducted Spurious Emissions .....	13
Emissions at Band Edges .....	15
DTS Bandwidth .....	19
Transmitter Power Spectral Density (PSD).....	22
Test Equipment Utilized .....	25

**ILAC / A2LA**

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

**The applicant has been cautioned as to the following**

15.21 - Information to User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) - Special Accessories

Equipment marked to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



**Standard Test Conditions Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.10-2013 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F) unless the particular equipment requirements specified testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Measurement results, unless otherwise noted, are worst-case measurements.

Environmental Conditions		
Temperature (°C)	Humidity (%)	Pressure (mbar)
20-27	26-37	942-989

**EUT Description**

**Model:** TAG-006

**Description:** Body Worn Location Device

**Firmware:** N/A

**Software:** N/A

**Serial Number:** N/A

**Antenna Gain:** -1.6 dBi

**Additional Information:** The EUT implements GFSK.

**EUT Operation during Tests**

The EUT was set to transmit at 100% duty cycle on the low, middle and highest channel of operation at the maximum available power level.

**Accessories:** None

**Cables:** None

**Modifications:** None

**15.203: Antenna Requirement:**

- The antenna is permanently attached to the EUT
- The antenna uses a unique coupling
- The EUT must be professionally installed
- The antenna requirement does not apply



### Test Results Summary

FCC 15.247 Specification	RSS-247 Specification	Test Name	Pass, Fail, N/A	Comments
15.247(b)	Section 5.4(d)	Peak Output Power	Pass	
15.247(d)	Section 5.5	Conducted Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Section 5.5	Radiated Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Section 5.5	Emissions At Band Edges	Pass	
15.247(a)(2)	Sections 5.2(a)	Occupied Bandwidth	Pass	
15.247(e)	Section 5.2(b)	Transmitter Power Spectral Density	Pass	
15.207	RSS-GEN Section 8.8	A/C Powerline Conducted Emissions	N/A	EUT is Battery Powered

References	Description
CFR47, Part 15, Subpart B	Unintentional Radiators
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63.10-2013	American National standard for testing Unlicensed Wireless Devices
ANSI C63.4-2014	Method and Measurements of Radio-Noise Emissions from low-Voltage Electrical and Electronic Equipment in the range 9kHz to 40GHz.
ISO/IEC 17025:2005	General requirements for the Competence of Testing and Calibrations Laboratories
KDB 558074 D01 v04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under §15.247

**Output Power**
**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018

**Test Procedure**

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

 RBW  $\geq$  DTS Bandwidth

 VBW  $\geq$  3 x RBW


 Span  $\geq$  3 x RBW

Sweep time = auto couple

Detector = peak

Trace Mode = max hold

The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. The RF output power was measured using the spectrum analyzer's marker peak function

**Test Setup**

**Transmitter Output Power**

Tuned Frequency (MHz)	Measured Value (dBm)	Specification Limit	Result
2402	3.327	1 W (30 dBm)	Pass
2426	3.549	1 W (30 dBm)	Pass
2480	2.433	1 W (30 dBm)	Pass





### Radiated Spurious Emissions

**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018

#### **Test Procedure Radiated Spurious Emissions: 30 – 1000 MHz**

The EUT was setup in a semi-anechoic test chamber set 3m from the receiving antenna. The EUT was set to transmit on the lowest, middle and highest frequency of operation at the maximum power level. The EUT was tested, in 3 orthogonal axis, by rotating it 360° with the receive antenna in both the vertical and horizontal orientation while raised from 1 to 4 meters to ensure the TX signal levels were maximized. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Spurious Emissions.

All emissions from 30 MHz to 1 GHz were examined.

Measured Level includes antenna and receiver cable correction factors.


Correction factors were input into the spectrum analyzer before recording "Measured Level".

RBW = 100 KHz

VBW = 300 KHz

Detector – Quasi Peak

#### **Test Setup**



#### **Test Procedure for Radiated Spurious Emissions above 1 GHz**


The EUT was setup in a semi-anechoic test chamber set 3m from the receiving antenna. The EUT was set to transmit on the lowest, middle and highest frequency of operation at the maximum power level. The EUT was tested, in 3 orthogonal axis, by rotating it 360° with the receive antenna in both the vertical and horizontal orientation while raised from 1 to 4 meters to ensure the TX signal levels were maximized. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Spurious Emissions.

RBW = 1 MHz

VBW = 3 MHz

Detector – Peak


#### **Test Setup**






### Radiated Spurious Emissions Plots

#### Low Channel – 30-1000 MHz




#### Mid Channel – 30-1000 MHz






### High Channel – 30-1000 MHz




### Low Channel – 1-18 GHz






### Mid Channel – 1-18 GHz



### High Channel – 1-18 GHz



Testing was performed to the 10<sup>th</sup> harmonic of the device, only noise floor was discovered above 18 GHz.



## Conducted Spurious Emissions

**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018

### Test Procedure

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

RBW = 100 kHz

VBW  $\geq$  3 x RBW

Peak Detector


Trace mode = max hold

Sweep = auto couple


Frequency Range = 30MHz – 10<sup>th</sup> Harmonic of the fundamental

The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. The trace was allowed to stabilize. All emissions were investigated to insure they were attenuated from the peak fundamental by at least 20dB. If the average power levels were measured then the out-of-band emissions needed to be attenuated by 30dB. In addition, emissions were investigated at the band edges to insure all out-of-band emissions were attenuated 20 or 30dB as necessary.

### Test Setup




### Conducted Spurious Emissions Plots






### Mid Channel



### High Channel



## Emissions at Band Edges


**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018

### Test Procedure

The EUT was connected directly to a spectrum analyzer. The spectrum analyzer was used to verify that the EUT met the requirements for band edges.

### Test Setup




### Band Edge Emissions Summary

Tuned Frequency (MHz)	Emission Frequency (MHz)	Monitored Level	Detector	Limit	Result
2402	2400	-52.49	Peak	-20 dBc	Pass
2480	2483.5	-48.27	Peak	-20 dBc	Pass

### Restricted Band Edge Test Procedure

The EUT was tested in a semi-anechoic test chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Restricted Band Edges. The EUT was tested in 3 orthogonal axis by rotating it 360° with the antenna in both the vertical and horizontal orientation and was raised from 1 to 4 meters to ensure the TX signal levels were maximized.


### Test Setup






### Band Edge Plots

#### Low Channel



#### High Channel









### Restricted Band Edge Plots

#### Low Channel




#### High Channel – Peak





### High Channel – Average





**DTS Bandwidth**

**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018


**Test Procedure**

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

- RBW = 100 kHz
- VBW ≥ 3 x RBW
- Peak Detector
- Trace mode = max hold
- Sweep = auto couple
- Span = 1.5 x EBW

The EUT was set to transmit at the lowest, middle and highest channels of the band at the maximum power levels. The maximum width of the emission that was determined by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that were attenuated by 6db and this value was used to determine the width of the carrier. Alternatively, the spectrum analyzer’s automatic bandwidth capability was used.

**Test Setup**



**6 dB Occupied Bandwidth Summary**

Frequency (MHz)	Measured Bandwidth (kHz)	Specification Limit (kHz)	Result
2402	731.947	≥ 500	Pass
2426	716.654	≥ 500	Pass
2480	735.127	≥ 500	Pass


**99% Bandwidth Summary**

Frequency (MHz)	Measured Bandwidth (MHz)	Result
2402	1.0763	Pass
2426	1.0826	Pass
2480	1.0905	Pass





### High Channel





## Transmitter Power Spectral Density (PSD)

**Engineer:** Kenneth Lee

**Test Date:** 6/19/2018


### Test Procedure

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

DTS channel center frequency  
Span 1.5 x DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz  
VBW ≥ 3 x RBW  
Peak Detector  
Sweep time = auto couple  
Trace mode = max hold

The EUT was set to transmit at the lowest, middle and highest channels of the band at the maximum power levels. Once the trace has stabilized the peak marker was used to determine the peak power spectral density.

### Test Setup




### PSD Summary

Frequency (MHz)	Measured Data (dBm)	Specification Limit (dBm)	Result
2402	-11.46	8	Pass
2426	-10.44	8	Pass
2480	-10.27	8	Pass




### PSD Plots

#### Low Channel




#### Mid Channel





### High Channel







### Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
EMI Receiver	HP	8546A	i00033	3/26/18	3/26/19
Horn Antenna	EMCO	3115	i00103	2/3/17	2/3/19
Bi-Log antenna	Chase	CBL6111C	i00267	3/8/18	3/8/20
Humidity / Temp Meter	Newport	IBTHX-W-5	i00282	6/9/17	6/9/18
Bi-Log Antenna	Schaffner	CBL 6111D	i00349	8/3/16	8/3/18
EMI Analyzer	Agilent	E7405A	i00379	2/13/18	2/13/19
3 Meter Semi-Anechoic Chamber	Panashield	3 Meter Semi-Anechoic Chamber	i00428	8/15/16	8/15/19
Spectrum Analyzer	Agilent	E4407B	i00331	11/21/17	11/21/18
Preamplifier for 1-18GHz horn antenna	Miteq	AFS44 00101 400 23-10P-44	i00509	N/A	N/A

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT