



FCC / ISED Test Report

For:
Telular AMETEK

Model:
SHB6510

Product Description:
Asset tracking.

FCC ID: MTFSHB6510
IC ID: 2175D-SHB6510

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)
RSS-247 Issue 2 (DTSS) & RSS-Gen Issue 5

REPORT #: EMC_TELUL-101-21001_FCC_15.247_BLE

DATE: 2022-01-12



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: contact@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571



TABLE OF CONTENTS

1 ASSESSMENT 3

2 ADMINISTRATIVE DATA 4

2.1 IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT 4

2.2 IDENTIFICATION OF THE CLIENT 4

2.3 IDENTIFICATION OF THE MANUFACTURER..... 4

3 EQUIPMENT UNDER TEST (EUT)..... 5

3.1 EUT SPECIFICATIONS 5

3.2 EUT SAMPLE DETAILS 6

3.3 ACCESSORY EQUIPMENT (AE) DETAILS..... 6

3.4 TEST SAMPLE CONFIGURATION 6

3.5 JUSTIFICATION FOR WORST CASE MODE OF OPERATION..... 6

4 SUBJECT OF INVESTIGATION 7

5 MEASUREMENT RESULTS SUMMARY 7

6 MEASUREMENT UNCERTAINTY..... 8

6.1 ENVIRONMENTAL CONDITIONS DURING TESTING:..... 8

6.2 DATES OF TESTING: 8

7 MEASUREMENT PROCEDURES 9

7.1 RADIATED MEASUREMENT..... 9

7.2 POWER LINE CONDUCTED MEASUREMENT PROCEDURE 11

7.3 RF CONDUCTED MEASUREMENT PROCEDURE 11

8 TEST RESULT DATA 12

8.1 RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS 12

9 TEST SETUP PHOTOS 26

10 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING 26

11 HISTORY 27



1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Telular AMETEK	Asset tracking.	SHB6510

Responsible for Testing Laboratory:

2022-01-12	Compliance	Kevin Wang (EMC Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2022-01-12	Compliance	Cheng Song (EMC Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Kevin Wang
Responsible Project Leader:	Cathy Palacios

2.2 Identification of the Client

Client's Name:	Telular AMETEK
Street Address:	3225 Cumberland Blvd, Suite 300
City/Zip Code	Atlanta, GA, 30339
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	SHB6510
HW Version :	A
SW Version :	EM.00.01.1096,BM.00.01.0061,CM.00.01.1026
FCC-ID :	MTFSHB6510
IC-ID:	2175D-SHB6510
PMN:	Kinnect
Product Description:	Asset tracking.
Radio Information:	<p>Cellular:</p> <ul style="list-style-type: none"> • Module: Telit ME910G1-W1 (CAT-M1 only) • FCC ID: RI7ME910G1W1, IC ID: 5131A-ME910G1W1 • Bands: LTE 1, 2, 3, 4, 5, 8, 12, 13, 18, 19, 20, 25, 26, 27, 28, 66, 71, 75 <p>Bluetooth:</p> <ul style="list-style-type: none"> • Module: Laird BL654 (Bluetooth 5 LE) • FCC ID: SQGBL654, IC ID: 3147A-BL654 <p>ISM:</p> <ul style="list-style-type: none"> • Module: EFR32FG1P131F256GM32-C0 • Operating Frequency: 902-928 MHz <p>GPS / GNSS:</p> <ul style="list-style-type: none"> • Module: Quectel GNSS L86
Antenna Information:	<p>Cellular:</p> <ul style="list-style-type: none"> • Type: PCB Trace • Max Gain: LTE 2 (4.4 dBi), LTE 4 (4.4 dBi), LTE 12 (2.6 dBi) <p>Bluetooth:</p> <ul style="list-style-type: none"> • Type: PCB Trace • Max Gain: 0 dBi <p>ISM:</p> <ul style="list-style-type: none"> • Type: Pulse W3113, small helica • Max Gain: 0.8 dBi
Power Supply/ Rated Operating Voltage Range:	Battery Vmin: 6 VDC/ Vnom: 7 VDC / Vmax: 8.2 VDC
Operating Temperature Range	-40 °C to 70 °C
Sample Revision	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	SHB7ACHI213600010	A	EM.00.01.1096,BM.00.01.0061,CM.00.01.1026	Radiated Emissions

3.3 Accessory Equipment (AE) details

AE #	Type
1	Communication Cable

3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1 + AE#1	Radiated Emissions

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and highest possible duty cycle. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

This test report is to support a request for new equipment authorization under the

- FCC ID: MTFSHB6510
- IC ID: 2175D-SHB6510

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(a)	Emission Bandwidth	Nominal	-	■	□	□	Note 2
§15.247(e) RSS-247 5.2(b)	Power Spectral Density	Nominal	-	■	□	□	Note 2
§15.247(b)(1) RSS-247 5.4(d)	Maximum Conducted Output Power and EIRP	Nominal	-	■	□	□	Note 2
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	-	■	□	□	Note 2
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	-	■	□	□	Note 2
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BLE	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	-	□	□	■	Note 3

Note: NA= Not Applicable; NP= Not Performed.

Note 2: Leveraged from module certification report under FCC ID: SQGBL654

Note 3: EUT powered by battery

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

Measurement System	EMC 1	EMC 2
Conducted Emissions (mains port)	1.12 dB	0.46 dB
Radiated Emissions		
(<30 MHz)	3.66 dB	3.88 dB
(30 MHz – 1 GHz)	3.17 dB	3.34 dB
(1 GHz – 3 GHz)	5.01 dB	4.45 dB
(> 3 GHz)	4.0 dB	4.79 dB

RF conducted measurement ± 0.5 dB

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


11/15/2021 - 11/30/2021

7 Measurement Procedures


7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dBμV
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:


Frequency (MHz)	Measured SA (dBμV)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dBμV/m)
1000	80.5	3.5	14	98.0

7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

8 Test Result Data

8.1 Radiated Transmitter Spurious Emissions and Restricted Bands

8.1.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing frequencies below 30 MHz at distance other than the specified in the standard, the limit conversion is calculated by using the FCC materials for the ANSI 63 committee issued on January, 27 1991.

8.1.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (µV/m)	Measurement Distance (m)	Field strength @ 3m (dBµV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBµV/m
88–216	150	3	43.5 dBµV/m
216–960	200	3	46 dBµV/m
Above 960	500	3	54 dBµV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
 - *PEAK LIMIT= 74 dBµV/m
 - *AVG. LIMIT= 54 dBµV/m

8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	Power Input
22° C	1	Battery


8.1.4 Measurement result:

Plot #	Channel #	Scan Frequency	Result
1-3	Low	30 MHz – 18 GHz	Pass
4-8	Mid	9 kHz – 18 GHz	Pass
9-11	High	30 MHz – 18 GHz	Pass

8.1.5 Measurement Plots:

Plot # 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
71.903	20.15	40.00	19.85	500.0	120.000	178.0	V	22.0	11.7	
168.251	25.04	43.50	18.46	500.0	120.000	248.0	H	270.0	13.9	
818.951	26.20	46.02	19.82	500.0	120.000	233.0	H	311.0	30.0	




— Preview Result 1-PK+
 — FCC 15.209 QP at 3m
 ◆ Final_Result QPK



Plot # 2

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---




- Preview Result 2-AVG
- Preview Result 1-PK+
- FCC 15.209 PK at 3m
- FCC 15.209 AVG at 3m
- * Critical_Freqs AVG
- ♦ Final_Result PK+
- ♦ Final_Result CAV



Plot # 3


Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6000.000	44.13	---	73.98	29.84	500.0	1000.000	179.0	V	-1.0	-1.9
6000.000	---	35.39	53.98	18.59	500.0	1000.000	179.0	V	-1.0	-1.9
7206.500	52.36	---	73.98	21.62	500.0	1000.000	100.0	H	277.0	-0.6
7206.500	---	40.73	53.98	13.25	500.0	1000.000	100.0	H	277.0	-0.6



— Preview Result 2-AVG — Preview Result 1-PK+ — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 4


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
20.133	19.81	55.95	36.14	500.0	0.200	153.0	V	353.0	16.4	



— Preview Result 1-PK+
 — FCC 15.209 QP at 3m
 ◆ Final_Result QPK

Plot # 5


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
48.016	23.96	40.00	16.04	500.0	120.000	167.0	V	-34.0	10.8	
144.276	24.90	43.50	18.60	500.0	120.000	186.0	H	238.0	13.3	
884.599	25.91	46.02	20.11	500.0	120.000	197.0	H	19.0	29.4	



— Preview Result 1-PK+
 — FCC 15.209 QP at 3m
 ◆ Final_Result QPK

Plot # 6

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---




- Preview Result 2-AVG
- Preview Result 1-PK+
- FCC 15.209 PK at 3m
- FCC 15.209 AVG at 3m
- * Critical_Freqs AVG
- ♦ Final_Result PK+
- ♦ Final_Result CAV



Plot # 7


Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5999.750	56.75	---	73.98	17.23	500.0	1000.000	174.0	V	347.0	-1.9
5999.750	---	43.79	53.98	10.19	500.0	1000.000	174.0	V	347.0	-1.9
7319.000	50.74	---	73.98	23.24	500.0	1000.000	167.0	H	271.0	-0.4
7319.000	---	37.63	53.98	16.35	500.0	1000.000	167.0	H	271.0	-0.4



— Preview Result 2-AVG — Preview Result 1-PK+ — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 8


Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
22701.250	---	53.25	63.50	10.25	500.0	1000.000	100.0	H	21.0	19.9
22701.250	65.78	---	83.50	17.72	500.0	1000.000	100.0	H	21.0	19.9



— Preview Result 2-AVG — Preview Result 1-PK+ — FCC 15.209 PK at 1m
— FCC 15.209 AVG at 1m ◆ Final_Result PK+ ◆ Final_Result CAV

Plot # 9


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
72.102	20.23	40.00	19.77	500.0	120.000	154.0	V	-29.0	11.8	
96.128	24.63	43.50	18.87	500.0	120.000	155.0	V	14.0	12.6	
312.019	26.21	46.02	19.81	500.0	120.000	125.0	H	49.0	19.4	



— Preview Result 1-PK+ — FCC 15.209 QP at 3m ◆ Final_Result QPK

Plot # 10

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---




- Preview Result 2-AVG
- Preview Result 1-PK+
- FCC 15.209 PK at 3m
- FCC 15.209 AVG at 3m
- * Critical_Freqs AVG
- * Critical_Freqs PK+
- ◆ Final_Result PK+
- ◆ Final_Result CAV



Plot # 11

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5999.750	43.98	---	73.98	30.00	500.0	1000.000	260.0	V	-16.0	-1.9
5999.750	---	31.29	53.98	22.69	500.0	1000.000	260.0	V	-16.0	-1.9
7439.250	53.22	---	73.98	20.76	500.0	1000.000	201.0	H	273.0	0.2
7439.250	---	41.13	53.98	12.85	500.0	1000.000	201.0	H	273.0	0.2



— Preview Result 2-AVG
 — Preview Result 1-PK+
 — FCC 15.209 PK at 3m
— FCC 15.209 AVG at 3m
 ◆ Final_Result PK+
 ◆ Final_Result CAV

9 Test setup photos

Setup photos are included in supporting file name: "EMC_TELUL-101-21001_FCC_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

Equipment Name/Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Biconilog Antenna	A.H. Systems	BiLA2G	569343	2 years	12/01/2020
Horn Antenna	ETS Lindgren	3115	35114	2 years	10/10/2020
Horn Antenna	ETS Lindgren	3117-PA	215984	2 years	01/31/2021
Active Loop Antenna	ETS Lindgren	6507	161344	2 years	10/30/2020
Horn Antenna	ETS Lindgren	3116C	70497	2 years	11/23/2020
Spectrum Analyzer	R&S	ESU40	100251	2 years	09/13/2021
Thermometer Humidity Monitor	CONTROL COMPANY	36934-164	191871986	2 years	10/20/2021

Note:

1. Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.



11 History

Date	Template Revision	Changes to report	Prepared by
2022-01-12	EMC_TELUL-101-21001_FCC_15.247_BLE	Initial Version	Cheng Song

<<< The End >>>