SPECIFICATION OF THE LF921U-004-0

空白文件

ITEM	TEST CONDITION
1.	SUPPLY VOLTAGE 8V DC

2.UHF MODULE		UNIT	TYP.	MIN.	MAX.
2.1 OPERATING VOLTAGE		V	8	7	9
2.2 CURRENT DRAIN		mA	50	35	60
2.3 CARRIER FREQUENCY	#1	MHz	912.00	911.980	912.020
	#2	MHz	912.500	912.480	912.520
	#3	MHz	913.00	912.980	913.020
2.4 RF OUTPUT POWER (W/O ANT .& MAIN BOARD) (THE 50 Ohm CABLE CONNECT TO THE ANT.PIN DIRECTLY W/SOLDER)		dBm	-7	-12	-3
2.5 THE 2nd HARMONIC POWER (W/O ANT) (THE 50 Ohm CABLE CONNECT TO THE ANT.PIN DIRECTLY W/SOLDER)		dBm	-58		-55

Prepared/ Drawn by	Description : SPECIFICATION	修改 2.2			
Checked by :					
Approved by :	Model No. : LF921U-004-0				
Ref No. : SPS 0211	Model Name: UHF MODULE	Revision	Chg. by	App'd by	Date
UNI-ART PRECISE PRODUCTS LTD.		DE. DEPT.		Page: 1 OF 1	