



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: MWC406WIFI**

**FCC Rule Part: 47 CFR Part 2.1091**

**ACS Project Number: 16-3095**

Applicant: Sealevel Systems Inc.  
Model: 406

**General Information:**

Applicant: Sealevel Systems Inc.  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: quarter wave vertical dipole antenna  
 Antenna Gain: 2 dBi  
 Maximum Transmitter Conducted Power: 802.11g 14.64 dBm, 29.11 mW  
 Maximum System EIRP: 16.64 dBm, 46.13 mW  
 Exposure Conditions: Greater than 20 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
2412	14.64	1.00	29.11	2	1.585	20	0.009

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.