



# FCC TEST REPORT

**REPORT NO.:** RF910722R01

**MODEL NO.:** P380A, P390A

**RECEIVED:** July 6, 2002

**TESTED:** Aug. 9 ~ Aug. 14, 2002

**APPLICANT:** GEMTEK TECHNOLOGY CO., LTD.

**ADDRESS:** No.1, Jen Ai Road, Hsinchu Industrial Park  
Hukou, Hsinchu, Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14<sup>th</sup> Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 51 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



Lab Code: 200102-0



## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	8
4	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS.....	10
4.1.3	TEST PROCEDURES .....	11
4.1.4	DEVIATION FROM TEST STANDARD .....	11
4.1.5	TEST SETUP .....	12
4.1.6	EUT OPERATING CONDITIONS.....	13
4.1.7	TEST RESULTS .....	14
4.2	RADIATED EMISSION MEASUREMENT .....	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	20
4.2.2	TEST INSTRUMENTS.....	21
4.2.3	TEST PROCEDURES .....	22
4.2.4	DEVIATION FROM TEST STANDARD .....	22
4.2.5	TEST SETUP .....	23
4.2.6	EUT OPERATING CONDITIONS.....	23
4.2.7	TEST RESULTS .....	24
4.3	6dB BANDWIDTH MEASUREMENT .....	29
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	29
4.3.2	TEST INSTRUMENTS.....	29
4.3.3	TEST PROCEDURE.....	30
4.3.4	DEVIATION FROM TEST STANDARD .....	30
4.3.5	TEST SETUP .....	30
4.3.6	EUT OPERATING CONDITIONS.....	30
4.3.7	TEST RESULTS .....	31
4.4	MAXIMUM PEAK OUTPUT POWER.....	35



4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT ..... 35

4.4.2 INSTRUMENTS ..... 35

4.4.3 TEST PROCEDURES ..... 36

4.4.4 DEVIATION FROM TEST STANDARD ..... 36

4.4.5 TEST SETUP ..... 36

4.4.6 EUT OPERATING CONDITIONS ..... 36

4.4.7 TEST RESULTS ..... 37

4.5 POWER SPECTRAL DENSITY MEASUREMENT ..... 38

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT ..... 38

4.5.2 TEST INSTRUMENTS ..... 38

4.5.3 TEST PROCEDURE ..... 39

4.5.4 DEVIATION FROM TEST STANDARD ..... 39

4.5.5 TEST SETUP ..... 39

4.5.6 EUT OPERATING CONDITION ..... 39

4.5.7 TEST RESULTS ..... 40

4.6 BAND EDGES MEASUREMENT ..... 44

4.6.1 LIMITS OF BAND EDGES MEASUREMENT ..... 44

4.6.2 TEST INSTRUMENTS ..... 44

4.6.3 TEST PROCEDURE ..... 44

4.6.4 DEVIATION FROM TEST STANDARD ..... 44

4.6.5 EUT OPERATING CONDITION ..... 45

4.6.6 TEST RESULTS ..... 45

4.7 ANTENNA REQUIREMENT ..... 48

4.7.1 STANDARD APPLICABLE ..... 48

4.7.2 ANTENNA CONNECTED CONSTRUCTION ..... 48

5 PHOTOGRAPHS OF THE TEST CONFIGURATION ..... 49

6 INFORMATION ON THE TESTING LABORATORIES ..... 51



# 1 CERTIFICATION

**PRODUCT :** WLAN Inter-Building Router  
**MODEL NO. :** P380A, P390A  
**BRAND :** Gemtek  
**APPLICANT :** GEMTEK TECHNOLOGY CO., LTD.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Aug. 9 ~ Aug. 14, 2002. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY : Emily Lu , DATE : Sep. 5, 2002  
Emily Lu

APPROVED BY : Alan Lane , DATE : Sep. 5, 2002  
Dr. Alan Lane, Manager

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is $-2.06\text{dBuV}$ at 16.169MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is $-2.90\text{dBuV}$ at 250.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	WLAN Inter-Building Router
<b>MODEL NO.</b>	P380A, P390A
<b>POWER SUPPLY</b>	48VDC from POE (Power over Ethernet)
<b>MODULATION TYPE</b>	BPSK, QPSK, CCK
<b>RADIO TECHNOLOGY</b>	DSSS
<b>TRANSFER RATE</b>	1/2/5.5/11Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	22.20dBm
<b>DATA CABLE</b>	NA
<b>ANTENNA TYPE</b>	Patch Antenna
<b>I/O PORTS</b>	RJ45
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT was powered by the following POE:

<b>Brand :</b>	Gemtek Systems Inc.
<b>Model No.:</b>	E110
<b>Input power :</b>	100 - 240Vac 50/60 Hz 0.25A
<b>Output power :</b>	48Vdc 0.35A 16W (Max)

2. Two identical models with different softwares were included in this application.
3. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a WLAN Inter-Building Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR 47 Part 15, Subpart C. (15.247)**

**ANSI C63.4 : 1992**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-190-B220	FCC DoC APPROVED
2	FAST ETHERNET PC CARD	D-Link	DFE-680TXD	RE1A044413	MQ4FE2K5MX

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

**NOTE:** All power cords of the above support units are non shielded (1.8m).





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 12, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	Jul. 23, 2003
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 25, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 2, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 2, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	Jul. 23, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	Jul. 23, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. "\*": These equipment are used for conducted telecom port test only (if tested).
  4. The test was performed in ADT Open Site No. 5.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

## 4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency via an RJ 45 cable.
- d. The communication partner sent data to EUT by command "PIN".




4.1.7 TEST RESULTS

<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. (MHz)	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	1.293	0.20	38.35	-	38.55	-	56.00	46.00	-17.45	-
2	1.293	0.20	38.39	-	38.59	-	56.00	46.00	-17.41	-
3	15.004	0.70	48.18	-	48.88	-	60.00	50.00	-11.12	-
4	16.469	0.79	47.08	-	47.87	-	60.00	50.00	-12.13	-
5	17.691	0.86	50.35	46.89	51.21	47.75	60.00	50.00	-8.79	-2.25
6	23.131	1.13	48.64	-	49.77	-	60.00	50.00	-10.23	-

- Remarks:
1. "\*\*": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. (MHz)	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	0.263	0.10	49.79	-	49.89	-	61.33	51.33	-11.44	-
2	0.384	0.10	39.28	-	39.38	-	58.18	48.18	-18.80	-
3	1.441	0.20	40.60	-	40.80	-	56.00	46.00	-15.20	-
4	15.255	0.52	46.26	-	46.78	-	60.00	50.00	-13.22	-
5	16.171	0.57	48.33	-	48.90	-	60.00	50.00	-11.10	-
6	16.473	0.59	48.68	-	49.27	-	60.00	50.00	-10.73	-
7	18.305	0.70	49.96	46.06	50.66	46.76	60.00	50.00	-9.34	-3.24
8	22.578	0.75	49.51	45.08	50.26	45.83	60.00	50.00	-9.74	-4.17
9	23.132	0.74	48.54	-	49.28	-	60.00	50.00	-10.72	-

- Remarks:
1. "\*\*": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. (MHz)	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	0.400	0.10	40.36	-	40.46	-	57.85	47.85	-17.39	-
2	1.320	0.20	40.19	-	40.39	-	56.00	46.00	-15.61	-
3	1.473	0.20	40.05	-	40.25	-	56.00	46.00	-15.75	-
4	3.023	0.30	35.53	-	35.83	-	56.00	46.00	-20.17	-
5	3.023	0.30	35.87	-	36.17	-	56.00	46.00	-19.83	-
6	18.244	0.89	50.87	46.89	51.76	47.78	60.00	50.00	-8.24	-2.22
7	23.131	1.13	48.25	-	49.38	-	60.00	50.00	-10.62	-
8	26.484	1.23	46.65	-	47.88	-	60.00	50.00	-12.12	-

- Remarks:
1. "": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.








<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. (MHz)	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	0.263	0.10	49.71	-	49.81	-	61.33	51.33	-11.52	-
2	1.343	0.20	40.90	-	41.10	-	56.00	46.00	-14.90	-
3	1.453	0.20	40.38	-	40.58	-	56.00	46.00	-15.42	-
4	14.699	0.49	47.95	-	48.44	-	60.00	50.00	-11.56	-
5	16.231	0.57	48.52	-	49.09	-	60.00	50.00	-10.91	-
6	16.231	0.57	47.62	-	48.19	-	60.00	50.00	-11.81	-
7	21.477	0.77	42.10	-	42.87	-	60.00	50.00	-17.13	-
8	24.043	0.72	47.80	-	48.52	-	60.00	50.00	-11.48	-

- Remarks:
1. "": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. (MHz)	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	0.275	0.10	40.00	-	40.10	-	60.97	50.97	-20.87	-
2	0.404	0.10	39.80	-	39.90	-	57.77	47.77	-17.87	-
3	1.434	0.20	41.86	-	42.06	-	56.00	46.00	-13.94	-
4	2.387	0.24	34.52	-	34.76	-	56.00	46.00	-21.24	-
5	13.355	0.67	44.86	-	45.53	-	60.00	50.00	-14.47	-
6	16.169	0.77	50.39	47.17	51.16	47.94	60.00	50.00	-8.84	-2.06
7	17.387	0.84	47.76	-	48.60	-	60.00	50.00	-11.40	-
8	18.246	0.89	48.85	-	49.74	-	60.00	50.00	-10.26	-
9	23.132	1.13	48.99	45.03	50.12	46.16	60.00	50.00	-9.88	-3.84

- Remarks:
1. "\*\*": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 50 %RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	QP.	AV.	QP.	AV.	QP.	AV.	QP.	AV.
1	0.256	0.10	46.98	-	47.08	-	61.57	51.57	-14.49	-
2	1.332	0.20	40.30	-	40.50	-	56.00	46.00	-15.50	-
3	1.438	0.20	40.59	-	40.79	-	56.00	46.00	-15.21	-
4	3.125	0.26	34.75	-	35.01	-	56.00	46.00	-20.99	-
5	3.125	0.26	34.24	-	34.50	-	56.00	46.00	-21.50	-
6	14.211	0.48	48.70	-	49.18	-	60.00	50.00	-10.82	-
7	17.387	0.64	41.77	-	42.41	-	60.00	50.00	-17.59	-
8	18.242	0.69	47.43	-	48.12	-	60.00	50.00	-11.88	-
9	19.707	0.78	46.85	-	47.63	-	60.00	50.00	-12.37	-
10	22.458	0.75	49.76	46.49	50.51	47.24	60.00	50.00	-9.49	-2.76
11	23.132	0.74	48.50	-	49.24	-	60.00	50.00	-10.76	-

- Remarks:
1. "\*\*": Undetectable
  2. QP. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": NA
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Oct. 30, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 7, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 3, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 9, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
  2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  3. "\*" = These equipment are used for the final measurement.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The test was performed in ADT Open Site No. 5.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

## 4.2.7 TEST RESULTS

<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	35 deg. C, 60%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	125.00	29.3 QP	43.50	-14.20	1.86H	174	15.54	11.47	2.29	0.00	-13.76
2	150.00	29.3 QP	43.50	-14.20	1.00H	138	16.33	10.30	2.66	0.00	-12.97
3	200.00	27.5 QP	43.50	-16.00	1.40H	181	14.95	8.98	3.57	0.00	-12.56
4	225.00	30.3 QP	46.00	-15.70	1.66H	287	15.98	10.41	3.92	0.00	-14.32
5	250.00	43.1 QP	46.00	-2.90	1.34H	192	26.80	12.02	4.29	0.00	-16.32
6	275.00	31.0 QP	46.00	-15.00	1.60H	221	13.73	12.59	4.68	0.00	-17.27
7	300.00	38.8 QP	46.00	-7.20	1.64H	180	20.63	13.18	4.94	0.00	-18.13
8	325.00	30.0 QP	46.00	-16.00	1.00H	221	10.97	13.72	5.31	0.00	-19.03
9	350.00	37.3 QP	46.00	-8.70	1.48H	260	17.44	14.21	5.65	0.00	-19.86
10	375.00	27.1 QP	46.00	-18.90	1.00H	318	6.03	15.13	5.94	0.00	-21.07
11	400.00	37.2 QP	46.00	-8.80	1.26H	286	14.83	16.11	6.27	0.00	-22.37
12	425.00	28.9 QP	46.00	-17.10	1.03H	53	6.02	16.24	6.64	0.00	-22.89
13	450.00	33.0 QP	46.00	-13.00	1.01H	114	9.61	16.37	7.02	0.00	-23.39
14	475.00	31.0 QP	46.00	-15.00	1.02H	205	6.91	16.83	7.26	0.00	-24.09
15	500.00	35.0 QP	46.00	-11.00	1.00H	164	10.28	17.26	7.47	0.00	-24.72
16	525.00	31.6 QP	46.00	-14.40	1.00H	230	6.22	17.59	7.79	0.00	-25.38
17	600.00	33.1 QP	46.00	-12.90	1.00H	129	6.00	18.61	8.49	0.00	-27.10
18	700.00	34.6 QP	46.00	-11.40	1.01H	167	5.60	19.31	9.69	0.00	-29.00
19	875.00	35.4 QP	46.00	-10.60	1.00H	327	3.52	20.63	11.25	0.00	-31.88

- NOTE:**
- 1 Emission level = Raw Value - Correction Factor
  - 2 Correction Factor = External Preamp. Gain - Ant. Factor - Cable loss  
(External Preamp. Gain = 0, when the test receiver is used for the test.)
  - 3 The other emission levels were very low against the limit.
  - 4 Margin value = Emission level - Limit value





<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	35 deg. C, 60%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>												
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)	
1	125.00	31.1 QP	43.50	-12.40	1.06V	2	17.34	11.47	2.29	0.00	-13.76	
2	200.00	29.5 QP	43.50	-14.00	1.00V	218	16.95	8.98	3.57	0.00	-12.56	
3	225.00	32.6 QP	46.00	-13.40	1.00V	177	18.28	10.41	3.92	0.00	-14.32	
4	250.00	40.4 QP	46.00	-5.60	1.17V	201	24.08	12.02	4.29	0.00	-16.32	
5	275.00	27.8 QP	46.00	-18.20	1.28V	217	10.53	12.59	4.68	0.00	-17.27	
6	300.00	40.9 QP	46.00	-5.10	1.00V	241	22.78	13.18	4.94	0.00	-18.13	
7	325.00	30.5 QP	46.00	-15.50	1.56V	182	11.47	13.72	5.31	0.00	-19.03	
8	350.00	37.7 QP	46.00	-8.30	1.23V	208	17.84	14.21	5.65	0.00	-19.86	
9	375.00	26.0 QP	46.00	-20.00	1.14V	170	4.93	15.13	5.94	0.00	-21.07	
10	400.00	38.1 QP	46.00	-7.90	1.19V	261	15.73	16.11	6.27	0.00	-22.37	
11	500.00	35.3 QP	46.00	-10.70	1.22V	310	10.58	17.26	7.47	0.00	-24.72	
12	525.00	31.5 QP	46.00	-14.50	1.00V	263	6.12	17.59	7.79	0.00	-25.38	
13	550.00	31.1 QP	46.00	-14.90	1.59V	237	5.07	17.93	8.11	0.00	-26.03	
14	600.00	34.4 QP	46.00	-11.60	1.00V	201	7.30	18.61	8.49	0.00	-27.10	
15	625.00	32.4 QP	46.00	-13.60	1.00V	43	4.69	18.91	8.80	0.00	-27.71	
16	700.00	38.3 QP	46.00	-7.70	1.61V	160	9.30	19.31	9.69	0.00	-29.00	

- NOTE:**
- 1 Emission level = Raw Value - Correction Factor
  - 2 Correction Factor = External Preamp. Gain - Ant. Factor - Cable loss  
(External Preamp. Gain = 0, when the test receiver is used for the test.)
  - 3 The other emission levels were very low against the limit.
  - 4 Margin value = Emission level - Limit value



<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	35 deg. C, 60%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2412.00	108.5 PK			1.45H	3	115.00	27.67	2.53	36.72	6.52
2	*2412.00	100.5 AV			1.45H	3	107.00	27.67	2.53	36.72	6.52
3	4824.00	47.3 PK	74.00	-26.70	1.16H	126	48.50	31.52	4.01	36.70	1.18
4	7235.00	53.8 PK	74.00	-20.20	1.61H	359	49.00	36.20	5.58	37.00	-4.78
5	7235.00	44.3 AV	54.00	-9.70	1.61H	359	39.50	36.20	5.58	37.00	-4.78
6	9648.00	50.6 PK	54.00	-3.40	1.26H	11	44.00	38.45	5.76	37.63	-6.59

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2412.00	104.5 PK			1.51V	114	111.00	27.67	2.53	36.72	6.52
2	*2412.00	98.5 AV			1.51V	114	105.00	27.67	2.53	36.72	6.52
3	4824.00	45.8 PK	74.00	-28.20	1.00V	2	47.00	31.52	4.01	36.70	1.18
4	7238.00	48.3 AV	54.00	-5.70	1.28V	23	43.50	36.20	5.58	37.00	-4.78
5	7238.00	52.8 PK	74.00	-21.20	1.28V	23	48.00	36.20	5.58	37.00	-4.78

- NOTE:**
1. Emission level = Raw Value - Correction Factor
  2. Correction Factor = External Preamp. Gain - Ant. Factor - Cable loss  
(External Preamp. Gain = 0, when the test receiver is used for the test.)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency



<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	35 deg. C, 60%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2437.00	106.8 PK			1.07H	47	113.00	27.81	2.66	36.71	6.24
2	*2437.00	100.8 AV			1.07H	88	107.00	27.81	2.66	36.71	6.24
3	4874.00	46.1 PK	74.00	-27.90	1.54H	327	47.20	31.59	4.03	36.70	1.08
4	7311.00	53.1 PK	74.00	-20.90	1.23H	30	48.20	36.26	5.65	37.02	-4.90
5	7311.00	45.9 AV	54.00	-8.10	1.23H	30	41.00	36.26	5.65	37.02	-4.90

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2437.00	103.8 PK			1.04V	3	110.00	27.81	2.66	36.71	6.24
2	*2437.00	94.8 AV			1.04V	3	101.00	27.81	2.66	36.71	6.24
3	4874.00	47.8 PK	74.00	-26.20	1.04V	44	48.90	31.59	4.03	36.70	1.08
4	7313.00	54.0 PK	74.00	-20.00	1.36V	337	49.00	36.33	5.72	37.03	-5.03
5	7313.00	47.0 AV	54.00	-7.00	1.36V	311	42.00	36.33	5.72	37.03	-5.02
6	9748.00	50.6 PK	74.00	-23.40	1.38V	48	44.10	38.50	5.66	37.65	-6.51

- NOTE:**
1. Emission level = Raw Value - Correction Factor
  2. Correction Factor = External Preamp. Gain - Ant. Factor - Cable loss  
(External Preamp. Gain = 0, when the test receiver is used for the test.)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	35 deg. C, 60%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2463.00	109.6 PK			1.59H	3	115.80	27.81	2.66	36.71	6.24
2	*2463.00	100.6 AV			1.59H	3	106.80	27.81	2.66	36.71	6.24
3	4924.00	46.0 PK	74.00	-28.00	1.59H	81	47.00	31.66	4.06	36.70	0.99
4	7387.00	54.0 PK	74.00	-20.00	1.33H	3	48.85	36.40	5.79	37.05	-5.14
5	7387.00	47.8 AV	54.00	-6.20	1.33H	3	42.70	36.40	5.79	37.05	-5.14
6	9848.00	47.5 PK	74.00	-26.50	1.33H	102	41.00	38.54	5.59	37.67	-6.46

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	*2462.00	96.8 AV			1.05V	11	103.00	27.81	2.66	36.71	6.24
2	*2462.00	105.8 PK			1.05V	11	112.00	27.81	2.66	36.71	6.24
3	4924.00	47.1 PK	74.00	-26.90	1.50V	307	48.10	31.66	4.06	36.70	0.99
4	7385.00	50.5 AV	54.00	-3.50	1.48V	68	45.40	36.40	5.79	37.05	-5.14
5	7385.00	58.6 PK	74.00	-15.40	1.48V	68	53.50	36.40	5.79	37.05	-5.14
6	9848.00	50.3 PK	74.00	-23.70	1.19V	233	43.80	38.54	5.59	37.67	-6.46

- NOTE:**
1. Emission level= Raw Value - Correction Factor
  2. Correction Factor = External Preamp. Gain - Ant. Factor - Cable loss  
(External Preamp. Gain = 0, when the test receiver is used for the test.)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.7 TEST RESULTS

<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 55%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	10.64	0.5	PASS
6	2437	10.64	0.5	PASS
11	2462	10.64	0.5	PASS




CH1








CH6





CH11





#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SINGLE CHANNEL POWER METER	NRVS	100026	Feb. 23, 2003
PEAK POWER SENSOR	NRV-Z32	100013	Feb. 23, 2003

**NOTE:**

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




#### 4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



## 4.4.7 TEST RESULTS

<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	30deg.C, 55%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	22.03	29	PASS
6	2437	22.20	29	PASS
11	2462	22.05	29	PASS

**NOTE:** According to 15.247(b)(3), the maximum antenna gain 10dBi is higher than 6dBi, so the limit of peak power shall be reduced by 1dBi.



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

**NOTE:**

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



## 4.5.7 TEST RESULTS


<b>EUT</b>	WLAN Inter-Building Router	<b>MODEL</b>	P380A
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 55%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-3.22	8	PASS
6	2437	-3.00	8	PASS
11	2462	-3.16	8	PASS






CH1






CH6





CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

**NOTE:**

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation




#### 4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6

#### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:** The band edge emission plot on the following 2 pages shows 49.41dB / 48.42dB delta between carrier maximum power and local maximum emission in restrict band (2.4884GHz / 2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 (Page 26) is 100.5dBuV/m, so the maximum field strength in restrict band is  $100.5 - 48.42 = 52.08$ dBuV/m which is under 54dBuV/m limit.







## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**


The antennas used in this product is Patch Antenna with Reversed N Type connector. The maximum Gain of the antenna is 10dBi.



## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.