



RF EXPOSURE REPORT

REPORT NO.: SA970918L05

MODEL NO.: AR725W

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Gemtek Technology Co., Ltd.

ADDRESS: No. 15-1, Zhonghua Rd, Hsinchu Industrial
Park , Hsinchu County, Taiwan, R.O.C. 303

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



RF EXPOSURE MEASUREMENT (MOBILE DEVICE)

1. INTRODUCTION

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF EXPOSURE LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
(A)LIMITS FOR OCCUPATIONAL / CONTROL EXPOSURES				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz



3. FRIIS FORMULA

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance r .

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,

Page 640, Eq. (11-133).

4. EUT OPERATING CONDITION

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



6. TEST RESULTS

6.1 ANTENNA GAIN

The maximum Gain measured in Fully Anechoic Chamber is 0dBi or 1(numeric).

6.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE VALUE AT DISTANCE 20cm:

For 2.400 ~ 2.4385GHz band:

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm ²)	LIMIT OF POWER DENSITY (mW/cm ²)
1	2412	63.973	18.06	0.013	1.0
6	2437	100.925	20.04	0.020	1.0
11	2462	102.094	20.09	0.020	1.0

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm ²)	LIMIT OF POWER DENSITY (mW/cm ²)
1	2412	180.717	22.57	0.036	1.0
6	2437	252.930	24.03	0.050	1.0
11	2462	254.097	24.05	0.051	1.0

DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
1	2422	21.52	21.55	284.795	24.55	0.057	1.000
4	2437	22.57	22.59	362.269	25.59	0.072	1.000
7	2452	22.53	22.07	340.125	25.32	0.068	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
1	2422	19.02	18.58	151.910	21.82	0.030	1.000
4	2437	22.07	22.06	321.759	25.08	0.064	1.000
7	2452	21.53	21.57	285.782	24.56	0.057	1.000



For 5.150 ~ 5.250GHz band:

802.11a OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm ²)	LIMIT OF POWER DENSITY (mW/cm ²)
36	5180	7.980	9.02	0.002	1.0
40	5200	10.116	10.05	0.002	1.0
48	5240	10.186	10.08	0.002	1.0

DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
36	5180	8.04	8.06	12.765	11.06	0.003	1.000
40	5200	8.53	8.59	14.356	11.57	0.003	1.000
48	5240	8.06	8.02	12.736	11.05	0.003	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
38	5190	12.06	12.51	33.893	15.30	0.007	1.000
46	5230	9.03	9.08	16.089	12.07	0.003	1.000



For 5.725 ~ 5.850GHz band:

802.11a OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm ²)	LIMIT OF POWER DENSITY (mW/cm ²)
149	5745	79.799	19.02	0.016	1.0
157	5785	159.956	22.04	0.032	1.0
165	5825	161.808	22.09	0.032	1.0

DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
149	5745	19.03	18.56	151.763	21.81	0.030	1.000
157	5785	22.06	22.03	320.282	25.06	0.064	1.000
165	5825	22.04	21.57	303.505	24.82	0.060	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
151	5755	20.06	20.08	203.250	23.08	0.040	1.000
159	5795	20.54	21.53	255.473	24.07	0.051	1.000