


FCC RF Exposure Report

FCC ID : MXF-W1701K
Equipment : Tri-Band AP
Model No. : W1701K
Brand Name : Q Fiber
Applicant : Gemtek Technology Co., Ltd.
Address : No. 15-1 Zhonghua Road, Hsinchu Industrial
Park, Hukou, Hsinchu, Taiwan, 30352.
Standard : 47 CFR FCC Part 2.1091
Received Date : Jun. 27, 2023
Tested Date : Aug. 01 ~ Sep. 11, 2023

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:



Along Chen / Assistant Manager



Gary Chang / Manager

Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	4
1.2	MPE EVALUATION FORMULA	4
1.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	4
1.4	MEASUREMENT UNCERTAINTY	4
1.5	MPE EVALUATION RESULTS	5
1.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	6
2	TEST LABORATORY INFORMATION	7

Release Record

Report No.	Version	Description	Issued Date
FA362701	Rev. 01	Initial issue	Sep. 25, 2023

1 MPE EVALUATION OF MOBILE DEVICES

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm ²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

1.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.4 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1.5 MPE EVALUATION RESULTS

Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
WLAN								
2412-2462	28.20	28.5	1.09	25	0.116	1	0.116	Pass
5180-5240	29.71	30	2.58	25	0.231	1	0.231	Pass
5745-5825	29.89	30	2.81	25	0.243	1	0.243	Pass
5925-6425	24.97	25	4.01	25	0.101	1	0.101	Pass
6425-6525	20.18	20.5	1.29	25	0.019	1	0.019	Pass
6525-6875	23.98	24	2.84	25	0.062	1	0.062	Pass
6875-7125	23.99	24	3.03	25	0.064	1	0.064	Pass
BT								
2402-2480 (BT-LE)	9.79	10	2.40	25	0.002	1	0.002	Pass
Thread								
2405-2480	9.79	10	2.40	25	0.002	1	0.002	Pass

*Ratio = Power density / Limit.

Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
WLAN								
2412-2462	27.83	28	3.21	25	0.168	1	0.168	Pass
5180-5240	29.36	29.5	5.23	25	0.378	1	0.378	Pass
5745-5825	29.86	30	3.39	25	0.278	1	0.278	Pass
5925-6425	24.60	25	4.20	25	0.106	1	0.106	Pass
6425-6525	19.84	20	3.90	25	0.031	1	0.031	Pass
6525-6875	23.70	24	5.31	25	0.109	1	0.109	Pass
6875-7125	21.86	22	4.78	25	0.061	1	0.061	Pass

*Ratio = Power density / Limit.

1.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Non-beamforming mode

Max Ratio of Each Mode

Mode	Wi-Fi 2.4G	BT	Thread	Wi-Fi 5G	Wi-Fi 6G	Sum	Limit	Pass / Fail
1	0.116	-	-	0.243	-	0.359	1	Pass
2	0.116	-	-	-	0.101	0.217	1	Pass
3	0.116	-	-	0.243	0.101	0.46	1	Pass
4	-	0.002	-	0.243	-	0.245	1	Pass
5	-	0.002	-	-	0.101	0.103	1	Pass
6	-	0.002	-	0.243	0.101	0.346	1	Pass
7	-	-	0.002	0.243	-	0.245	1	Pass
8	-	-	0.002	-	0.101	0.103	1	Pass
9	-	-	0.002	0.243	0.101	0.346	1	Pass

Beamforming mode

Max Ratio of Each Mode

Mode	Wi-Fi 2.4G	BT	Thread	Wi-Fi 5G	Wi-Fi 6G	Sum	Limit	Pass / Fail
1	0.168	-	-	0.378	-	0.546	1	Pass
2	0.168	-	-	-	0.109	0.277	1	Pass
3	0.168	-	-	0.378	0.109	0.655	1	Pass
4	-	0.002	-	0.378	-	0.380	1	Pass
5	-	0.002	-	-	0.109	0.111	1	Pass
6	-	0.002	-	0.378	0.109	0.489	1	Pass
7	-	-	0.002	0.378	-	0.380	1	Pass
8	-	-	0.002	-	0.109	0.111	1	Pass
9	-	-	0.002	0.378	0.109	0.489	1	Pass

2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==