

# **FCC RF Exposure Report**

FCC ID : MXF-WAPD246ACN

**Equipment** : WAPD-246ACN\_LoRa gateway

Model No. : WAPD-246ACN

**Brand Name** : Gemtek

: Gemtek Technology Co., Ltd. **Applicant** 

**Address** : No.15-1 Zhonghua Road, Hsinchu Industrial

Park, Hukou, Hsinchu, Taiwan, 30352

: 47 CFR FCC Part 2.1091 Standard

**Received Date** : Mar. 06, 2018

**Tested Date** : Mar. 07 ~ May 04, 2018

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chew/ Assistant Manager

Testing Laboratory

2732

Report No.: FA780201-01 Page: 1 of 6



# **Table of Contents**

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
	MPE EVALUATION FORMULA	
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	6

Report No.: FA780201-01 Page: 2 of 6



# **Release Record**

Report No. Version		Description	Issued Date	
FA780201-01	Rev. 01	Initial issue	May 24, 2018	

Report No.: FA780201-01 Page: 3 of 6



## 1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

### 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

### 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

Report No.: FA780201-01 Page: 4 of 6



### 1.3 MPE EVALUATION RESULTS

Mode	Maximum Conducted Power (dBm)	Rated Power(dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
LoRa Card 0 923.3 ~ 927.5 MHz	24.36	24.5	8	23	0.268	0.616
LoRa Card 1 923.3 ~ 927.5 MHz	24.34	24.5	8	23	0.268	0.616

The device contains a certified wireless LTE module as below

FCC ID	QISME936
Operating Frequency Band and Channel Bandwidth	1850 MHz – 1910 MHz: 1.4 / 3 / 5 / 10 / 15 / 20 MHz 1710 MHz – 1755 MHz: 1.4 / 3 / 5 / 10 / 15 / 20 MHz 2500 MHz – 2570 MHz: 5 / 10 / 15 / 20 MHz
Antenna Type and Gain	Dipole antenna 1850 MHz – 1910 MHz: -0.05 dBi 1710 MHz – 1755 MHz: 0.34 dBi 2500 MHz – 2570 MHz: 1.89 dBi

Frequency Band (MHz)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
1850 MHz – 1910 MHz	24	-0.05	23	0.037	1
1710 MHz – 1755 MHz	24	0.34	23	0.041	1
2500 MHz – 2570 MHz	24	1.89	23	0.058	1

#### **MPE Evaluation of Simultaneous Transmission**

The device supports simultaneous transmission as below configurations Lora Card 0 + Lora Card 1 + LTE

MPE evaluation is as below formula

PD1 / Limit1 + PD2 / Limit 2 + ..... < 1, PD = Power density

MPE Evaluation = 0.268 / 0.616 + 0.268 / 0.616 + 0.058 / 1 = 0.928 < 1

#### Conclusion

MPE evaluations of single and simultaneous transmission meet the requirement of standard.

Report No.: FA780201-01 Page: 5 of 6



# 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END===

Report No.: FA780201-01 Page: 6 of 6