

FCC Co-Location Test Report

FCC ID : MXF-WAPQ-245

Equipment : Router

Model No. : AC3000

Brand Name : Onelink

Applicant : Gemtek Technology Co., Ltd.

Address : No.15-1 Zhoughua Rd, Hsinchu Industrial

Park, Hukou, Hsinchu, Taiwan, R.O.C

Standard : 47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

Received Date : Mar. 29, 2019

Tested Date : Nov. 01 ~ Nov. 09, 2018 (for original test)

Apr. 12 ~ Apr. 15, 2019 (for new test)

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

ong Chen / Assistant Manager Gary Chang / Manager

2732

Report No.: FR8O3101-01CO Page: 1 of 16



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	The Equipment List	6
1.3	Test Standards	7
1.4	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Condition	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS	9
3.1	Unwanted Emissions into Restricted Frequency Bands	g
4	TEST LABORATORY INFORMATION	16



Release Record

Report No.	Version	Description	Issued Date
FR8O3101-01CO	Rev. 01	Initial issue	Aug. 02, 2019

Report No.: FR8O3101-01CO Page: 3 of 16



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 6420.00MHz 51.43 (Margin -2.57dB) - AV	Pass
15.209		2.0.1.0 (a.g 2.0.1.a2) 7.11	

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR8O3101-01CO Page: 4 of 16



1 General Description

1.1 Information

This report is issued as a duplicate report to the original ICC report no. FR8O3101CO. . The difference is concerned with following items:

- Antenna change and enable beamforming function for 2.4G and 5GHz UNII band 1 and 3 by software setting
- ♦ Hardware minor change of non-RF PCB layout is to reserve coexistence function.

Note:

Previous version of hardware: V03A

Current version (Re-layout) of hardware: V04

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5745 ~ 5825 MHz Bluetooth EDR: 2402 ~ 2480 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth EDR: GFSK / π/4-DQPSK / 8DPSK

1.1.2 Antenna Details of Platform

Wi-Fi antenna

Ant. No.	Model	Tuno	Connector	Operating Fr	equency (MHz) / Gain (dBi)
AIII. NO.	Wodel	Туре	Connector	2400~2483.5	5150~5250	5725~5850
1	2.4GHz,G1	PIFA	UFL	2.8		
2	2.4GHz,G2	PIFA	UFL	2.5		
3	5GHz, Low Band,A1	PIFA	UFL		5.3	
4	5GHz, Low Band,A2	PIFA	UFL		3.7	
5	5GHz, high Band,A3	PIFA	UFL			4.8
6	5GHz, high Band,A4	PIFA	UFL			3.8
7	5GHz, high Band,A5	PIFA	UFL			3.6
8	5GHz, high Band,A6	PIFA	UFL			4.2

Bluetooth Antenna

Ant. No.	Туре	Gain (dBi)	Connector	Remark
1	Chip	0.7	UFL	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter
-------------------	--------------------

Report No.: FR8O3101-01CO Page: 5 of 16



1.2 The Equipment List

Test Item	Radiated Emission						
Test Site	966 chamber 1/ (03CH01-WS)						
Tested Date	Apr. 12 ~ Apr. 15, 2019						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019		
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019		
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019		
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019		
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019		
RF Cable	EMC	EMC104-SM-SM-80 00	181106	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019		
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 08, 2018	Oct. 07, 2019		
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019		
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 08, 2018	Oct. 07, 2019		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		
Note: Calibration Inter	val of instruments listed	d above is one year.					

Test Item	RF Conducted	F Conducted						
Test Site	(TH01-WS)	TH01-WS)						
Tested Date	Nov. 01 ~ Nov. 09, 20	18						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101063	Apr. 16, 2018	Apr. 15, 2019			
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019			
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019			
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 01, 2017	Nov. 30, 2018			
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA			
Note: Calibration Inter	Note: Calibration Interval of instruments listed above is one year.							

Report No.: FR8O3101-01CO Page: 6 of 16



1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.4 Deviation from Test Standard and Measurement Procedure

None

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty				
Parameters Ur				
Radiated emission ≤ 1GHz	±3.66 dB			
Radiated emission > 1GHz	±5.37 dB			

Report No.: FR8O3101-01CO Page: 7 of 16



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	22-23°C / 64-65%	Akun Chung
Conducted Emissions	TH01-WS	24°C / 66%	Akun Chung

FCC Designation No.: TW2732
 FCC site registration No.: 181692
 ISED#: 10807A

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Channel	Data Rate	Test Configuration
Radiated Emissions	2.4G 11b + 5G B1 11ac VHT40 +	CH11 + CH46 +	1Mbps + MCS 0 +	
Conducted Emissions	5G B4 11a	CH165	6Mbps	

NOTE:

1. The selected channel is the maximum power channel of Wi-Fi mode.

2. Only 2.4GHz Wi-Fi and 5 GHz Wi-Fi can transmit simultaneously.

Report No.: FR8O3101-01CO Page: 8 of 16



3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit							
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)				
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300				
0.490~1.705	24000/F(kHz)	33.8 - 23	30				
1.705~30.0	30	29	30				
30~88	100	40	3				
88~216	150	43.5	3				
216~960	200	46	3				
Above 960	500	54	3				

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR8O3101-01CO Page: 9 of 16




3.1.3 Test Setup



Report No.: FR8O3101-01CO Page: 10 of 16



3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR8O3101-01CO Page: 11 of 16



Modulation	2.4G 11b + 5G B4 11a	5G B1 11ac VHT	10 + Test Cha	annel	CH11	+ CH46 + CH ²		
Polarization	Vertical	Vertical						
90 Level 80 70 60 50 40 123	(dBuV/m) 4 5	6			FCC CLAS	SS-B		
20 10 0 30	100. 200. 3	00. 400. 500 Frequen		700. 800.	900.	1000		
	level	n Limit Margin			ANT High cm	Turn Table deg		
1 2 3 4 5	146.40 33.87		44.10 -7. 43.86 -8. 45.45 -8. 42.26 -8. 40.87 -8.	00 QP 61 QP 39 Peak	100 100 	20 21		
6	506.27 31.78	46.00 -14.22	34.37 -2.	59 Peak				

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR8O3101-01CO Page: 12 of 16



3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR8O3101-01CO Page: 13 of 16



Modulation	2.4G 11b + 5G B1 11ac VHT40 + 5G B4 11a	Test Channel	CH11 + CH46 + CH165
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		CM	deg
1	6420.00	48.03	54.00	-5.97	40.95	7.08	Average	100	238
2	6420.00	60.76	74.00	-13.24	53.68	7.08	Peak	100	238
3	7692.00	37.35	54.00	-16.65	28.93	8.42	Average	100	115
4	7692.00	51.26	74.00	-22.74	42.84	8.42	Peak	100	115
5	8287.00	38.37	54.00	-15.63	29.22	9.15	Average	100	147
6	8287.00	52.12	74.00	-21.88	42.97	9.15	Peak	100	147

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR8O3101-01CO Page: 14 of 16



3.1.6 Conducted Emissions (30MHz~40GHz)



Report No.: FR8O3101-01CO

Page: 15 of 16



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

___END___

Report No.: FR8O3101-01CO Page: 16 of 16