

FCC Test Report

FCC ID : MXF-WLRGFM100
Equipment : IOT Femto Gateway
Model No. : WLRGFM-100
Brand Name : Gemtek
Applicant : Gemtek Technology Co., Ltd.
Address : No. 15-1 Zhonghua Road, Hsinchu Industrial
Park, Hukou, Hsinchu, Taiwan, 30352.
Standard : 47 CFR FCC Part 15.247
Received Date : Apr. 10, 2017
Tested Date : May 05 ~ May 16, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	17
3.4	Power Spectral Density	19
3.5	Unwanted Emissions into Restricted Frequency Bands	21
3.6	Emissions in Non-Restricted Frequency Bands	43
4	TEST LABORATORY INFORMATION	53

Release Record

Report No.	Version	Description	Issued Date
FR741001AC	Rev. 01	Initial issue	May 31, 2017

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.579MHz 34.88 (Margin -11.12dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2390.00MHz 52.62 (Margin -1.38dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 26.78	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	2	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remark
1	Monopole	R-SMA	3.6	---
2	Monopole	R-SMA	3.42	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from adapter
--------------------------	-------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter 1	Brand: PHIHONG Model: PSAF10A-050Q Power Rating: I/P: 100-240Vac, 50/60Hz, 0.28A O/P: 5Vdc, 2A MAX
2	AC adapter 2	Brand: Tenbao Model: SO10WU0500200 Power Rating: I/P: 100-240Vac, 50/60Hz, 0.4A O/P: 5Vdc, 2A MAX
3	AC adapter 3	Brand: ChenYang Model: CC10-050200U Power Rating: I/P: 100-240Vac, 50/60Hz, 0.35A O/P: 5Vdc, 2A MAX
4	USB cable (for charging use)	1.5m non-shielded without core
5	RJ45 cable	0.95m non-shielded without core

1.1.5 Channel List

Channel	Frequency(MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

1.1.6 Test Tool and Duty Cycle

Test Tool	Tera Term, V4.8		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	88.24%	0.54
	HT20	87.38%	0.59


1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	11/10
11b	2437	11/10
11b	2462	10/9
11g	2412	9/7
11g	2437	10/8
11g	2462	10/8
HT20	2412	6/4
HT20	2437	10/9
HT20	2462	10/9

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	DoC	RJ45, 0.95m non-shielded.
2	USB 3.0 Flash	Kingston	DTSE9G2	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Dec. 21, 2016	Dec. 20, 2017
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 08, 2016	Nov. 07, 2017
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 20, 2016	Dec. 19, 2017
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Nov. 25, 2016	Nov. 24, 2017
Receiver	R&S	ESR3	101658	Nov. 24, 2016	Nov. 23, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 04, 2016	Aug. 03, 2017
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 21, 2016	Dec. 20, 2017
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017
Preamplifier	EMC	EMC02325	980225	Aug. 05, 2016	Aug. 04, 2017
Preamplifier	Agilent	83017A	MY39501308	Oct. 06, 2016	Oct. 05, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 09, 2016	Dec. 08, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 09, 2016	Dec. 08, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 09, 2016	Dec. 08, 2017
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	16052	Dec. 09, 2016	Dec. 08, 2017
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 09, 2016	Dec. 08, 2017
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 09, 2016	Dec. 08, 2017
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 60%	Alex Tsai
Radiated Emissions	03CH01-WS	24°C / 62%	Kevin Lee Vincent Yeh
RF Conducted	TH01-WS	22°C / 64%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	11g	2437	6 Mbps	---
Radiated Emissions ≤1GHz	11g	2437	6 Mbps	---
Radiated Emissions >1GHz				
Maximum Output Power	11b	2412 / 2437 / 2462	1 Mbps	
6dB bandwidth	11g	2412 / 2437 / 2462	6 Mbps	---
Power spectral density	HT20	2412 / 2437 / 2462	MCS 0	

Note:

1. Three adapters (PHIHONG, Tenbao and ChenYang) had been covered during the pre-test and found that PHIHONG adapter was the worst case for radiated emission and ChenYang adapter was the worst case for conducted emission test.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions


Modulation	11g	Test Freq. (MHz)	2437
Power Phase	Line		



	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	LISN factor dB	cable loss dB	Remark
1	0.150	24.69	56.00	-31.31	24.58	0.07	0.04	Average
2	0.150	39.03	66.00	-26.97	38.92	0.07	0.04	QP
3	0.165	23.76	55.21	-31.45	23.64	0.08	0.04	Average
4	0.165	37.39	65.21	-27.82	37.27	0.08	0.04	QP
5	0.579	34.88	46.00	-11.12	34.78	0.06	0.04	Average
6	0.579	44.25	56.00	-11.75	44.15	0.06	0.04	QP
7	1.269	22.90	46.00	-23.10	22.77	0.09	0.04	Average
8	1.269	31.93	56.00	-24.07	31.80	0.09	0.04	QP
9	2.448	20.34	46.00	-25.66	20.13	0.14	0.07	Average
10	2.448	28.85	56.00	-27.15	28.64	0.14	0.07	QP
11	18.244	37.36	50.00	-12.64	36.74	0.37	0.25	Average
12	18.244	41.63	60.00	-18.37	41.01	0.37	0.25	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).

Modulation	11g	Test Freq. (MHz)	2437
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.165	20.92	55.21	-34.29	20.78	0.10	0.04	Average
2	0.165	36.60	65.21	-28.61	36.46	0.10	0.04	QP
3	0.207	20.25	53.32	-33.07	20.12	0.09	0.04	Average
4	0.207	34.44	63.32	-28.88	34.31	0.09	0.04	QP
5	0.589	26.00	46.00	-20.00	25.85	0.11	0.04	Average
6	0.589	39.50	56.00	-16.50	39.35	0.11	0.04	QP
7	1.296	13.90	46.00	-32.10	13.74	0.12	0.04	Average
8	1.296	24.99	56.00	-31.01	24.83	0.12	0.04	QP
9	5.333	20.74	50.00	-29.26	20.37	0.19	0.18	Average
10	5.333	31.69	60.00	-28.31	31.32	0.19	0.18	QP
11	16.226	29.62	50.00	-20.38	29.00	0.38	0.24	Average
12	16.226	37.07	60.00	-22.93	36.45	0.38	0.24	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup




3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	2	2412	10.09	10.09	---	---	500
11b	2	2437	10.09	10.09	---	---	500
11b	2	2462	10.09	10.09	---	---	500
11g	2	2412	16.35	16.35	---	---	500
11g	2	2437	16.35	16.41	---	---	500
11g	2	2462	16.35	16.35	---	---	500
HT20	2	2412	17.57	17.57	---	---	500
HT20	2	2437	17.10	17.10	---	---	500
HT20	2	2462	17.57	17.10	---	---	500



Modulation Mode	N _{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	2	2412	12.29	12.24	---	---
11b	2	2437	12.32	12.31	---	---
11b	2	2462	12.24	12.27	---	---
11g	2	2412	16.95	16.96	---	---
11g	2	2437	16.93	16.95	---	---
11g	2	2462	16.92	16.95	---	---
HT20	2	2412	17.73	17.72	---	---
HT20	2	2437	17.76	17.77	---	---
HT20	2	2462	17.72	17.79	---	---



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain \leq 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain $>$ 6dBi
 - Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
 - Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power (For reference only)
 - Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Peak conducted Output Power (dBm)							Ant. Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3	Total Power (mW)	Total Power (dBm)	Limit (dBm)			
11b	2	2412	18.89	18.65	---	---	150.729	21.78	30.00	3.60	25.38	36.00
11b	2	2437	19.04	18.93	---	---	158.331	22.00	30.00	3.60	25.60	36.00
11b	2	2462	19.03	18.72	---	---	154.457	21.89	30.00	3.60	25.49	36.00
11g	2	2412	23.88	23.61	---	---	473.958	26.76	30.00	3.60	30.36	36.00
11g	2	2437	23.75	23.79	---	---	476.469	26.78	30.00	3.60	30.38	36.00
11g	2	2462	23.76	23.05	---	---	439.521	26.43	30.00	3.60	30.03	36.00
HT20	2	2412	22.41	21.85	---	---	327.289	25.15	30.00	3.60	28.75	36.00
HT20	2	2437	23.67	23.24	---	---	443.672	26.47	30.00	3.60	30.07	36.00
HT20	2	2462	23.66	23.18	---	---	440.243	26.44	30.00	3.60	30.04	36.00

Modulation Mode	N _{TX}	Freq. (MHz)	Conducted (Average) Output Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	2	2412	15.38	15.18	---	---	67.475	18.29	---
11b	2	2437	15.52	15.47	---	---	70.882	18.51	---
11b	2	2462	15.54	15.28	---	---	69.538	18.42	---
11g	2	2412	15.89	15.33	---	---	72.934	18.63	---
11g	2	2437	15.78	15.5	---	---	73.326	18.65	---
11g	2	2462	15.77	15.23	---	---	71.100	18.52	---
HT20	2	2412	14.57	13.81	---	---	52.685	17.22	---
HT20	2	2437	15.63	15.42	---	---	71.393	18.54	---
HT20	2	2462	15.68	15.48	---	---	72.301	18.59	---

Note: Conducted average output power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup


Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz




3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	HT20	Test Freq. (MHz)	2437						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 200 MHz, and 50 dBuV/m from 200 to 1000 MHz. Six blue vertical lines represent emission peaks labeled 1 through 6, with their corresponding data listed in the table below.</p>									
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB				
1	101.78	32.91	43.50	-10.59	45.48	-12.57	Peak	---	---
2	171.62	35.91	43.50	-7.59	44.65	-8.74	Peak	---	---
3	249.22	35.58	46.00	-10.42	44.81	-9.23	Peak	---	---
4	267.65	32.56	46.00	-13.44	41.08	-8.52	Peak	---	---
5	499.48	31.47	46.00	-14.53	34.29	-2.82	Peak	---	---
6	579.99	34.31	46.00	-11.69	35.44	-1.13	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	35.42	40.00	-4.58	43.43	-8.01	Peak	---	---
2	58.13	36.33	40.00	-3.67	45.02	-8.69	Peak	---	---
3	76.56	32.74	40.00	-7.26	44.66	-11.92	Peak	---	---
4	171.62	31.55	43.50	-11.95	40.29	-8.74	Peak	---	---
5	232.73	29.89	46.00	-16.11	39.27	-9.38	Peak	---	---
6	579.99	36.70	46.00	-9.30	37.83	-1.13	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

Modulation	11b	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	42.30	54.00	-11.70	45.48	-3.18	Average	148	193
2	2390.00	55.71	74.00	-18.29	58.89	-3.18	Peak	148	193
3	4824.00	43.40	54.00	-10.60	39.62	3.78	Average	298	309
4	4824.00	46.07	74.00	-27.93	42.29	3.78	Peak	298	309
5	12060.00	41.60	54.00	-12.40	28.02	13.58	Average	100	242
6	12060.00	54.07	74.00	-19.93	40.49	13.58	Peak	100	242
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.27	54.00	-10.73	46.45	-3.18	Average	380	144
2	2390.00	56.50	74.00	-17.50	59.68	-3.18	Peak	380	144
3	4824.00	45.76	54.00	-8.24	41.98	3.78	Average	105	130
4	4824.00	48.74	74.00	-25.26	44.96	3.78	Peak	105	130
5	12060.00	41.73	54.00	-12.27	28.15	13.58	Average	100	205
6	12060.00	54.01	74.00	-19.99	40.43	13.58	Peak	100	205

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.11	54.00	-10.89	46.29	-3.18	Average	149	186
2	2390.00	55.90	74.00	-18.10	59.08	-3.18	Peak	149	186
3	2483.50	39.80	54.00	-14.20	42.60	-2.80	Average	149	186
4	2483.50	53.01	74.00	-20.99	55.81	-2.80	Peak	149	186
5	4874.00	44.32	54.00	-9.68	40.38	3.94	Average	322	298
6	4874.00	46.88	74.00	-27.12	42.94	3.94	Peak	322	298
7	7311.00	48.02	54.00	-5.98	39.61	8.41	Average	100	319
8	7311.00	54.34	74.00	-19.66	45.93	8.41	Peak	100	319

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.67	54.00	-10.33	46.85	-3.18	Average	360	143
2	2390.00	56.07	74.00	-17.93	59.25	-3.18	Peak	360	143
3	2483.50	41.17	54.00	-12.83	43.97	-2.80	Average	360	143
4	2483.50	54.72	74.00	-19.28	57.52	-2.80	Peak	360	143
5	4874.00	48.63	54.00	-5.37	44.69	3.94	Average	283	118
6	4874.00	51.33	74.00	-22.67	47.39	3.94	Peak	283	118
7	7311.00	49.36	54.00	-4.64	40.95	8.41	Average	285	228
8	7311.00	55.17	74.00	-18.83	46.76	8.41	Peak	285	228

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.50	54.00	-13.50	43.30	-2.80	Average	172	185
2	2483.50	53.26	74.00	-20.74	56.06	-2.80	Peak	172	185
3	4924.00	44.23	54.00	-9.77	40.13	4.10	Average	343	289
4	4924.00	48.49	74.00	-25.51	44.39	4.10	Peak	343	289
5	7386.00	45.19	54.00	-8.81	36.75	8.44	Average	100	315
6	7386.00	52.27	74.00	-21.73	43.83	8.44	Peak	100	315

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	41.56	54.00	-12.44	44.36	-2.80	Average	350	146
2	2483.50	54.31	74.00	-19.69	57.11	-2.80	Peak	350	146
3	4924.00	47.73	54.00	-6.27	43.63	4.10	Average	308	121
4	4924.00	49.95	74.00	-24.05	45.85	4.10	Peak	308	121
5	7386.00	47.84	54.00	-6.16	39.40	8.44	Average	309	231
6	7386.00	53.21	74.00	-20.79	44.77	8.44	Peak	309	231

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412						
Polarization	Horizontal								
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	51.19	54.00	-2.81	54.37	-3.18	Average	154	187
2	2390.00	70.32	74.00	-3.68	73.50	-3.18	Peak	154	187
3	4824.00	34.83	54.00	-19.17	31.05	3.78	Average	296	309
4	4824.00	48.69	74.00	-25.31	44.91	3.78	Peak	296	309
5	12060.00	41.64	54.00	-12.36	28.06	13.58	Average	100	262
6	12060.00	54.18	74.00	-19.82	40.60	13.58	Peak	100	262

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.62	54.00	-1.38	55.80	-3.18	Average	380	142
2	2390.00	71.31	74.00	-2.69	74.49	-3.18	Peak	380	142
3	4824.00	37.06	54.00	-16.94	33.28	3.78	Average	304	119
4	4824.00	50.44	74.00	-23.56	46.66	3.78	Peak	304	119
5	12060.00	42.80	54.00	-11.20	29.22	13.58	Average	100	221
6	12060.00	55.70	74.00	-18.30	42.12	13.58	Peak	100	221

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.02	54.00	-10.98	46.20	-3.18	Average	146	186
2	2390.00	55.66	74.00	-18.34	58.84	-3.18	Peak	146	186
3	2483.50	40.48	54.00	-13.52	43.28	-2.80	Average	146	186
4	2483.50	52.71	74.00	-21.29	55.51	-2.80	Peak	146	186
5	4874.00	33.16	54.00	-20.84	29.22	3.94	Average	285	310
6	4874.00	44.51	74.00	-29.49	40.57	3.94	Peak	285	310
7	7311.00	49.18	54.00	-4.82	40.77	8.41	Average	100	321
8	7311.00	63.73	74.00	-10.27	55.32	8.41	Peak	100	321

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.19	54.00	-10.81	46.37	-3.18	Average	390	230
2	2390.00	56.37	74.00	-17.63	59.55	-3.18	Peak	390	230
3	2483.50	40.95	54.00	-13.05	43.75	-2.80	Average	390	230
4	2483.50	53.98	74.00	-20.02	56.78	-2.80	Peak	390	230
5	4874.00	34.61	54.00	-19.39	30.67	3.94	Average	305	288
6	4874.00	45.13	74.00	-28.87	41.19	3.94	Peak	305	288
7	7311.00	49.43	54.00	-4.57	41.02	8.41	Average	306	121
8	7311.00	63.29	74.00	-10.71	54.88	8.41	Peak	306	121

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.84	54.00	-9.16	47.64	-2.80	Average	149	185
2	2483.50	63.43	74.00	-10.57	66.23	-2.80	Peak	149	185
3	4924.00	34.26	54.00	-19.74	30.16	4.10	Average	282	316
4	4924.00	46.68	74.00	-27.32	42.58	4.10	Peak	282	316
5	7386.00	38.58	54.00	-15.42	30.14	8.44	Average	100	326
6	7386.00	52.82	74.00	-21.18	44.38	8.44	Peak	100	326

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	45.95	54.00	-8.05	48.75	-2.80	Average	360	142
2	2483.50	64.02	74.00	-9.98	66.82	-2.80	Peak	360	142
3	4924.00	35.04	54.00	-18.96	30.94	4.10	Average	289	122
4	4924.00	48.52	74.00	-25.48	44.42	4.10	Peak	289	122
5	7386.00	40.39	54.00	-13.61	31.95	8.44	Average	340	124
6	7386.00	54.84	74.00	-19.16	46.40	8.44	Peak	340	124

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	51.59	54.00	-2.41	54.77	-3.18	Average	148	182
2	2390.00	70.82	74.00	-3.18	74.00	-3.18	Peak	148	182
3	4824.00	34.28	54.00	-19.72	30.50	3.78	Average	283	297
4	4824.00	48.19	74.00	-25.81	44.41	3.78	Peak	283	297
5	12060.00	40.68	54.00	-13.32	27.10	13.58	Average	100	240
6	12060.00	53.80	74.00	-20.20	40.22	13.58	Peak	100	240
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.45	54.00	-1.55	55.63	-3.18	Average	383	143
2	2390.00	71.08	74.00	-2.92	74.26	-3.18	Peak	383	143
3	4824.00	35.58	54.00	-18.42	31.80	3.78	Average	302	124
4	4824.00	49.36	74.00	-24.64	45.58	3.78	Peak	302	124
5	12060.00	41.51	54.00	-12.49	27.93	13.58	Average	100	223
6	12060.00	54.64	74.00	-19.36	41.06	13.58	Peak	100	223

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.94	54.00	-10.06	47.12	-3.18	Average	149	188
2	2390.00	56.38	74.00	-17.62	59.56	-3.18	Peak	149	188
3	2483.50	38.94	54.00	-15.06	41.74	-2.80	Average	149	188
4	2483.50	51.85	74.00	-22.15	54.65	-2.80	Peak	149	188
5	4874.00	34.92	54.00	-19.08	30.98	3.94	Average	282	313
6	4874.00	48.63	74.00	-25.37	44.69	3.94	Peak	282	313
7	7311.00	48.67	54.00	-5.33	40.26	8.41	Average	100	317
8	7311.00	63.42	74.00	-10.58	55.01	8.41	Peak	100	317

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	44.66	54.00	-9.34	47.84	-3.18	Average	388	239
2	2390.00	57.16	74.00	-16.84	60.34	-3.18	Peak	388	239
3	2483.50	39.62	54.00	-14.38	42.42	-2.80	Average	388	239
4	2483.50	52.63	74.00	-21.37	55.43	-2.80	Peak	388	239
5	4874.00	35.04	54.00	-18.96	31.10	3.94	Average	297	294
6	4874.00	48.80	74.00	-25.20	44.86	3.94	Peak	297	294
7	7311.00	49.81	54.00	-4.19	41.40	8.41	Average	322	121
8	7311.00	64.50	74.00	-9.50	56.09	8.41	Peak	322	121

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.68	54.00	-7.32	49.48	-2.80	Average	146	198
2	2483.50	65.16	74.00	-8.84	67.96	-2.80	Peak	146	198
3	4924.00	33.57	54.00	-20.43	29.47	4.10	Average	279	315
4	4924.00	46.13	74.00	-27.87	42.03	4.10	Peak	279	315
5	7386.00	38.30	54.00	-15.70	29.86	8.44	Average	100	333
6	7386.00	52.91	74.00	-21.09	44.47	8.44	Peak	100	333

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	47.90	54.00	-6.10	50.70	-2.80	Average	356	141
2	2483.50	66.11	74.00	-7.89	68.91	-2.80	Peak	356	141
3	4924.00	35.34	54.00	-18.66	31.24	4.10	Average	287	123
4	4924.00	48.77	74.00	-25.23	44.67	4.10	Peak	287	123
5	7386.00	39.64	54.00	-14.36	31.20	8.44	Average	304	123
6	7386.00	54.97	74.00	-19.03	46.53	8.44	Peak	304	123

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in Non-Restricted Frequency Bands

3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.3 Test Setup





3.6.4 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding $10 \log(N_{ANT})$ since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

3.6.5 Unwanted Emissions into Non-Restricted Frequency Bands


802.11b










802.11g









802.11n HT20







4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==