

FCC Test Report

FCC ID : MXF-WLTFSM13643
Equipment : LTE B43 Cat 6 Single-Mode Indoor CPE
Model No. : WLTFSM-136ACN
Brand Name : Gemtek
Applicant : Gemtek Technology Co., Ltd.
Address : No.15-1 Zhonghua Road, Hsinchu Industrial
Park, Hukou, Hsinchu, Taiwan, 30352
Standard : 47 CFR FCC Part 90 Subpart Z
Received Date : Dec. 02, 2016
Tested Date : Dec. 22, 2016 ~ Feb. 20, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition and Location Information.....	10
2.2	The Worst Test Modes and Channel Details	10
3	TEST RESULTS.....	11
3.1	Equivalent Isotropically Radiated Power and Peak EIRP Power Density	11
3.2	Radiated Emissions.....	19
3.3	Conducted Emissions.....	27
3.4	Emission Mask	32
3.5	26dBc Bandwidth	37
3.6	Frequency Stability.....	42
4	TEST LABORATORY INFORMATION	45

Release Record

Report No.	Version	Description	Issued Date
FW6D0201	Rev. 01	Initial issue	Mar. 13, 2017

Summary of Test Results

FCC Rules	Test Items	Measured	Result
2.1046 / 90.1321	Equivalent Isotropically Radiated Power	Maximum EIRP: 0.173 W / 5MHz 0.164 W / 10MHz 0.163 W / 15MHz 0.170 W / 20MHz	Pass
2.1046 / 90.1321	Peak EIRP Power Density	Meet the requirement of limit	Pass
2.1053 / 90.1323	Radiated Emissions	Meet the requirement of limit	Pass
2.1051 / 90.1323	Conducted Emissions	Meet the requirement of limit	Pass
90.210	Emission Mask	Meet the requirement of limit	Pass
2.1049(h) / 90.1323	26dBc Bandwidth	Meet the requirement of limit	Pass
2.1055 / 90.213	Frequency Stability	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	Channel Bandwidth: 5MHz: 3652.5 MHz ~ 3697.5 MHz Channel Bandwidth: 10MHz: 3655.0 MHz ~ 3695.0 MHz Channel Bandwidth: 15MHz: 3657.5 MHz ~ 3692.5 MHz Channel Bandwidth: 20MHz: 3660.0 MHz ~ 3690.0 MHz
Modulation Type	QPSK, 16QAM (Uplink)
Duplex Mode	TDD
UE Category	Cat. 5 / Cat. 6
Release	9
H/W Version	Mother board: V00; daughter board: V01
S/W Version	01.01.02.115

1.1.2 Maximum EIRP & Emission Designator

Channel Bandwidth	Modulation	Maximum EIRP (W)	Emission Designator
5MHz	QPSK	0.173	4M52G7D
5MHz	16QAM	0.172	4M50W7D
10MHz	QPSK	0.164	8M94G7D
10MHz	16QAM	0.163	8M95W7D
15MHz	QPSK	0.163	13M4G7D
15MHz	16QAM	0.161	13M4W7D
20MHz	QPSK	0.170	17M9G7D
20MHz	16QAM	0.166	17M9W7D

1.1.3 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)
1	Internal antenna: Dipole	UFL	0
2	External antenna: Dipole	SMA	-0.5

1.1.4 EUT Operational Condition

Power Supply Type	12Vdc from adapter		
Operational Voltage	<input checked="" type="checkbox"/> Vnom (120 V)	<input checked="" type="checkbox"/> Vmax (138 V)	<input checked="" type="checkbox"/> Vmin (102 V)
Operational Climatic	<input checked="" type="checkbox"/> Tnom (20°C)	<input checked="" type="checkbox"/> Tmax (50°C)	<input checked="" type="checkbox"/> Tmin (-30°C)

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Adapter 1	Brand: SHENZHEN FRECOM Model: F18W8-120150SPAU Power Rating: I/P: 100-240Vac, 50/60Hz, 0.6A O/P: 12Vdc, 1.5A Power Line: 1.2m non-shielded without core
2	Adapter 2	Brand: Leader Model: MU18AY120150-A1 Power Rating: I/P: 100-240Vac, 50/60Hz, 0.6A O/P: 12Vdc, 1.5A Power Line: 1.5m non-shielded without core


1.1.6 Operating Channel List

Channel Bandwidth (MHz)	Channel	Frequency (MHz)
5	44115	3652.5
5	44340	3675.0
5	44565	3697.5
10	44140	3655.0
10	44340	3675.0
10	44540	3695.0
15	44165	3657.5
15	44340	3675.0
15	44515	3692.5
20	44190	3660.0
20	44340	3675.0
20	44490	3690.0

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	9ZFB4X1	DoC	RJ45, 10m non-shielded.
2	Telephone	HTT	HTT-806	187118	---	RJ11, 2m non-shielded.
3	USB Flash	SONY	USM16GU	0000020	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Nov. 25, 2016	Nov. 24, 2017
Receiver	R&S	ESR3	101658	Nov. 24, 2016	Nov. 23, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 04, 2016	Aug. 03, 2017
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 21, 2016	Dec. 20, 2017
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017
Preamplifier	EMC	EMC02325	980225	Aug. 05, 2016	Aug. 04, 2017
Preamplifier	Agilent	83017A	MY39501308	Oct. 06, 2016	Oct. 05, 2017
Preamplifier	EMC	EMC184045B	980192	Aug. 24, 2016	Aug. 23, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 09, 2016	Dec. 08, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 09, 2016	Dec. 08, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 09, 2016	Dec. 08, 2017
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	16052	Dec. 09, 2016	Dec. 08, 2017
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 09, 2016	Dec. 08, 2017
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 09, 2016	Dec. 08, 2017
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 28, 2016	Mar. 27, 2017
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 09, 2016	Sep. 08, 2017
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 21, 2016	Nov. 20, 2017
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 28, 2016	Mar. 27, 2017
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards.

47 CFR FCC Part 90 Subpart Z

FCC KDB 965270 D01 PwrMeas Part 90 Z Equipment v01

ANSI C63.4-2014

ANSI/TIA-603-D 2010

FCC KDB 971168 D01 Power Meas License Digital Systems v02r02

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor $k=2$)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Frequency error	± 34.134 Hz
Conducted emission	± 2.670 dB
Radiated emission ≤ 1 GHz	± 3.66 dB
Radiated emission > 1 GHz	± 5.63 dB
Temperature	± 0.6 °C

2 Test Configuration

2.1 Testing Condition and Location Information

Test Item	Test Site	Ambient Condition	Tested By
RF Conducted	TH01-WS	22°C / 61%	Alex Huang
Radiated Emissions	03CH01-WS	23°C / 62%	Vincent Yeh

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Channel Bandwidth	Modulation	Test channel (MHz)
Equivalent Isotropically Radiated Power	5 MHz	QPSK / 16QAM	3652.5 / 3675.0 / 3697.5
	10 MHz	QPSK / 16QAM	3655.0 / 3675.0 / 3695.0
	15 MHz	QPSK / 16QAM	3657.5 / 3675.0 / 3692.5
	20 MHz	QPSK / 16QAM	3660.0 / 3675.0 / 3690.0
Radiated Emission ≤ 1GHz	5 MHz	QPSK	3652.5
	10 MHz	QPSK	3655.0
	15 MHz	QPSK	3657.5
	20 MHz	QPSK	3660.0
Radiated Emission > 1GHz	5 MHz	QPSK	3652.5 / 3675.0 / 3697.5
	10 MHz	QPSK	3655.0 / 3675.0 / 3695.0
	15 MHz	QPSK	3657.5 / 3675.0 / 3692.5
	20 MHz	QPSK	3660.0 / 3675.0 / 3690.0
Conducted Emissions Emission Mask 26dBc Bandwidth	5 MHz	QPSK / 16QAM	3652.5 / 3675.0 / 3697.5
	10 MHz	QPSK / 16QAM	3655.0 / 3675.0 / 3695.0
	15 MHz	QPSK / 16QAM	3657.5 / 3675.0 / 3692.5
	20 MHz	QPSK / 16QAM	3660.0 / 3675.0 / 3690.0
Frequency Stability	5 MHz	Un-modulation	3675.0
	10 MHz		3675.0
	15 MHz		3675.0
	20 MHz		3675.0

NOTE:

1. Two adapters had been covered during the pretest and found that **Adapter 1** was the worst case and was selected for final testing (Adapter 1: SHENZHEN FRECOM adapter; Adapter 2: Leader adapter).

3 Test Results

3.1 Equivalent Isotropically Radiated Power and Peak EIRP Power Density

3.1.1 Limit of Equivalent Isotropically Radiated Power and Peak EIRP Power Density

Base and fixed stations are limited to 25 watts/25 MHz equivalent isotropically radiated power (EIRP), the peak EIRP power density shall not exceed 1 Watt in any one-mega hertz slice of spectrum.

Mobile and portable stations are limited to 1 watt/25 MHz EIRP. The peak EIRP density shall not exceed 40 milli watts in any one-megahertz slice of spectrum.

3.1.2 Test Procedures


For EIRP

1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than occupied bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power
2. Determine the EIRP by adding the effective antenna gain to the adjusted power level.

For Peak EIRP Power Density

1. Connect the transmitter to the spectrum analyzer via coaxial cable (i.e., conducted measurement) while ensuring proper impedance matching.
2. Tune the analyzer to the nominal center frequency of the emission bandwidth.
3. Set the span to twice the nominal EBW (span = 2 x EBW).
4. Set the resolution bandwidth (RBW) to 1 MHz.
5. Set the video bandwidth (VBW) to 3 MHz
6. Select the average power (RMS) display detector.
7. Set the number of measurement points to ≥ 1001 .
8. Use auto-coupled sweep time.
9. Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
10. Utilize trace averaging over 100 traces in the power averaging.
11. Find the maximum trace amplitude (peak search) and record.
12. Adjust the recorded level by applying appropriate correction factors for the measurement set-up.
13. Determine the EIRP by adding the effective antenna gain to the adjusted power level.

3.1.3 Test Setup



3.1.4 Duty cycle and duty factor

Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	QPSK	41.27	3.84
	16QAM	41.27	3.84

3.1.5 Test Result of EIRP

Channel Bandwidth: 5MHz

Modulation	Channel	Channel Frequency (MHz)	Conducted Power (dBm)	Max. Ant. Gain(dBi)	EIRP (dBm)	EIRP (W)	LIMIT (W)
QPSK	44115	3652.5	22.39	0	22.39	0.173	0.2
QPSK	44340	3675.0	22.38	0	22.38	0.173	0.2
QPSK	44565	3697.5	22.27	0	22.27	0.169	0.2
16QAM	44115	3652.5	22.16	0	22.16	0.164	0.2
16QAM	44340	3675.0	22.35	0	22.35	0.172	0.2
16QAM	44565	3697.5	22.26	0	22.26	0.168	0.2

Channel Bandwidth: 10MHz

Modulation	Channel	Channel Frequency (MHz)	Conducted Power (dBm)	Max. Ant. Gain(dBi)	EIRP (dBm)	EIRP (W)	LIMIT (W)
QPSK	44140	3655.0	22.16	0	22.16	0.164	0.4
QPSK	44340	3675.0	22.11	0	22.11	0.163	0.4
QPSK	44540	3695.0	22.02	0	22.02	0.159	0.4
16QAM	44140	3655.0	22.13	0	22.13	0.163	0.4
16QAM	44340	3675.0	22.08	0	22.08	0.161	0.4
16QAM	44540	3695.0	22.01	0	22.01	0.159	0.4

Channel Bandwidth: 15MHz

Modulation	Channel	Channel Frequency (MHz)	Conducted Power (dBm)	Max. Ant. Gain(dBi)	EIRP (dBm)	EIRP (W)	LIMIT (W)
QPSK	44165	3657.5	22.12	0	22.12	0.163	0.6
QPSK	44340	3675.0	22.09	0	22.09	0.162	0.6
QPSK	44515	3692.5	22.04	0	22.04	0.160	0.6
16QAM	44165	3657.5	22.06	0	22.06	0.161	0.6
16QAM	44340	3675.0	22.05	0	22.05	0.160	0.6
16QAM	44515	3692.5	22.01	0	22.01	0.159	0.6

Channel Bandwidth: 20MHz

Modulation	Channel	Channel Frequency (MHz)	Conducted Power (dBm)	Max. Ant. Gain(dBi)	EIRP (dBm)	EIRP (W)	LIMIT (W)
QPSK	44190	3660.0	22.30	0	22.30	0.170	0.8
QPSK	44340	3675.0	22.22	0	22.22	0.167	0.8
QPSK	44490	3690.0	22.16	0	22.16	0.164	0.8
16QAM	44190	3660.0	22.21	0	22.21	0.166	0.8
16QAM	44340	3675.0	22.14	0	22.14	0.164	0.8
16QAM	44490	3690.0	22.07	0	22.07	0.161	0.8

3.1.6 Test Result of Peak EIRP Density

Channel Bandwidth: 5MHz- QPSK

Modulation	Channel	Channel Freq. (MHz)	Conducted Power Density (dBm/MHz)	Duty Factor (dB)	Max. Ant. Gain (dBi)	EIRP Peak Density (dBm/MHz)	EIRP Peak Density (mW/MHz)	LIMIT (mW/MHz)
QPSK	44115	3652.5	11.604	3.84	0	15.444	35.03	40.00
QPSK	44340	3675.0	11.414	3.84	0	15.254	33.53	40.00
QPSK	44565	3697.5	11.470	3.84	0	15.310	33.96	40.00
16QAM	44115	3652.5	11.453	3.84	0	15.293	33.83	40.00
16QAM	44340	3675.0	11.479	3.84	0	15.319	34.03	40.00
16QAM	44565	3697.5	11.332	3.84	0	15.172	32.90	40.00

Channel Bandwidth: 10MHz

Modulation	Channel	Channel Freq. (MHz)	Conducted Power Density (dBm/MHz)	Duty Factor (dB)	Max. Ant. Gain (dBi)	EIRP Peak Density (dBm/MHz)	EIRP Peak Density (mW/MHz)	LIMIT (mW/MHz)
QPSK	44140	3655.0	8.540	3.84	0	12.380	17.30	40.00
QPSK	44340	3675.0	8.463	3.84	0	12.303	16.99	40.00
QPSK	44540	3695.0	8.387	3.84	0	12.227	16.70	40.00
16QAM	44140	3655.0	8.386	3.84	0	12.226	16.70	40.00
16QAM	44340	3675.0	8.391	3.84	0	12.231	16.71	40.00
16QAM	44540	3695.0	8.357	3.84	0	12.197	16.58	40.00


Channel Bandwidth: 15MHz

Modulation	Channel	Channel Freq. (MHz)	Conducted Power Density (dBm/MHz)	Duty Factor (dB)	Max. Ant. Gain (dBi)	EIRP Peak Density (dBm/MHz)	EIRP Peak Density (mW/MHz)	LIMIT (mW/MHz)
QPSK	44165	3657.5	6.364	3.84	0	10.204	10.48	40.00
QPSK	44340	3675.0	6.242	3.84	0	10.082	10.19	40.00
QPSK	44515	3692.5	6.297	3.84	0	10.137	10.32	40.00
16QAM	44165	3657.5	6.295	3.84	0	10.135	10.32	40.00
16QAM	44340	3675.0	6.240	3.84	0	10.080	10.19	40.00
16QAM	44515	3692.5	6.319	3.84	0	10.159	10.37	40.00


Channel Bandwidth: 20MHz

Modulation	Channel	Channel Freq. (MHz)	Conducted Power Density (dBm/MHz)	Duty Factor (dB)	Max. Ant. Gain (dBi)	EIRP Peak Density (dBm/MHz)	EIRP Peak Density (mW/MHz)	LIMIT (mW/MHz)
QPSK	44190	3660.0	5.257	3.84	0	9.097	8.12	40.00
QPSK	44340	3675.0	5.404	3.84	0	9.244	8.40	40.00
QPSK	44490	3690.0	5.357	3.84	0	9.197	8.31	40.00
16QAM	44190	3660.0	5.320	3.84	0	9.160	8.24	40.00
16QAM	44340	3675.0	5.244	3.84	0	9.084	8.10	40.00
16QAM	44490	3690.0	5.325	3.84	0	9.165	8.25	40.00


Test Plots




Test Plots



Test Plots



Test Plots



3.2 Radiated Emissions

3.2.1 Limit of Radiated Emissions


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. E.I.R.P = output power of step 4 + gain of substitution antenna – cable loss of RF cable.

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Test Result of Radiated Emissions below 1GHz

Mode		LTE Band 43, CB:5MHz, Channel: 44115					
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
30.97	H	-56.02	-13.00	-43.02	-63.94	-42.05	-13.97
87.23	H	-56.68	-13.00	-43.68	-54.76	-56.60	-0.08
158.04	H	-53.88	-13.00	-40.88	-53.56	-53.51	-0.37
207.51	H	-58.88	-13.00	-45.88	-55.04	-63.23	4.35
354.95	H	-57.29	-13.00	-44.29	-59.44	-61.63	4.34
540.22	H	-59.29	-13.00	-46.29	-64.21	-63.29	4.00
48.43	V	-54.19	-13.00	-41.19	-52.25	-43.17	-11.02
89.17	V	-51.62	-13.00	-38.62	-51.72	-52.15	0.53
140.58	V	-54.41	-13.00	-41.41	-55.72	-53.08	-1.33
221.09	V	-57.34	-13.00	-44.34	-59.42	-61.72	4.38
291.90	V	-60.20	-13.00	-47.20	-62.26	-64.51	4.31
540.22	V	-58.09	-13.00	-45.09	-65.11	-62.09	4.00

Mode		LTE Band 43, CB:10MHz, Channel:44140					
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
30.97	H	-56.20	-13.00	-43.20	-64.12	-42.23	-13.97
87.23	H	-56.92	-13.00	-43.92	-55.00	-56.84	-0.08
148.34	H	-54.23	-13.00	-41.23	-54.02	-53.33	-0.90
211.39	H	-57.27	-13.00	-44.27	-53.55	-61.63	4.36
353.01	H	-57.96	-13.00	-44.96	-60.08	-62.30	4.34
540.22	H	-60.28	-13.00	-47.28	-65.20	-64.28	4.00
49.40	V	-54.50	-13.00	-41.50	-52.58	-43.67	-10.83
89.17	V	-48.89	-13.00	-35.89	-48.99	-49.42	0.53
139.61	V	-54.26	-13.00	-41.26	-55.51	-52.91	-1.35
221.09	V	-58.34	-13.00	-45.34	-60.42	-62.72	4.38
293.84	V	-60.03	-13.00	-47.03	-62.07	-64.33	4.30
540.22	V	-58.60	-13.00	-45.60	-65.62	-62.60	4.00

Mode							
LTE Band 43, CB:15MHz, Channel:44165							
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
30.97	H	-55.65	-13.00	-42.65	-63.57	-41.68	-13.97
89.17	H	-56.29	-13.00	-43.29	-54.80	-56.82	0.53
163.86	H	-53.65	-13.00	-40.65	-53.16	-53.88	0.23
211.39	H	-58.98	-13.00	-45.98	-55.26	-63.34	4.36
353.01	H	-57.58	-13.00	-44.58	-59.70	-61.92	4.34
540.22	H	-59.57	-13.00	-46.57	-64.49	-63.57	4.00
48.43	V	-53.98	-13.00	-40.98	-52.04	-42.96	-11.02
87.23	V	-48.43	-13.00	-35.43	-48.18	-48.35	-0.08
140.58	V	-54.78	-13.00	-41.78	-56.09	-53.45	-1.33
223.03	V	-55.99	-13.00	-42.99	-58.10	-60.38	4.39
302.57	V	-60.52	-13.00	-47.52	-62.52	-64.80	4.28
600.36	V	-57.24	-13.00	-44.24	-66.71	-60.78	3.54

Mode							
LTE Band 43, CB:20MHz, Channel:44190							
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
30.97	H	-56.13	-13.00	-43.13	-64.05	-42.16	-13.97
87.23	H	-58.59	-13.00	-45.59	-56.67	-58.51	-0.08
163.86	H	-55.02	-13.00	-42.02	-54.53	-55.25	0.23
211.39	H	-60.44	-13.00	-47.44	-56.72	-64.80	4.36
357.86	H	-57.34	-13.00	-44.34	-59.54	-61.67	4.33
661.47	H	-60.32	-13.00	-47.32	-66.87	-64.14	3.82
48.43	V	-54.66	-13.00	-41.66	-52.72	-43.64	-11.02
89.17	V	-47.29	-13.00	-34.29	-47.39	-47.82	0.53
163.86	V	-55.54	-13.00	-42.54	-58.14	-55.77	0.23
211.39	V	-57.91	-13.00	-44.91	-59.85	-62.27	4.36
302.57	V	-60.10	-13.00	-47.10	-62.10	-64.38	4.28
540.22	V	-58.28	-13.00	-45.28	-65.30	-62.28	4.00

3.2.5 Test Result of Radiated Emissions above 1GHz

Mode							
LTE Band 43, CB:5MHz, Channel:44115							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7305.00	H	-32.81	-13.00	-19.81	-53.60	-36.06	3.25
10957.50	H	-35.56	-13.00	-22.56	-59.20	-36.18	0.62
14610.00	H	-39.44	-13.00	-26.44	-63.58	-39.56	0.12
7305.00	V	-38.27	-13.00	-25.27	-60.56	-41.52	3.25
10957.50	V	-39.11	-13.00	-26.11	-63.25	-39.73	0.62
14610.00	V	-35.88	-13.00	-22.88	-62.96	-36.00	0.12
Mode							
LTE Band 43, CB:5MHz, Channel:44340							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7350.00	H	-33.41	-13.00	-20.41	-54.35	-36.50	3.09
11025.00	H	-34.81	-13.00	-21.81	-58.45	-35.39	0.58
14700.00	H	-39.29	-13.00	-26.29	-63.65	-39.53	0.24
7350.00	V	-37.70	-13.00	-24.70	-59.98	-40.79	3.09
11025.00	V	-38.15	-13.00	-25.15	-62.39	-38.73	0.58
14700.00	V	-36.45	-13.00	-23.45	-63.89	-36.69	0.24
Mode							
LTE Band 43, CB:5MHz, Channel:44565							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7395.00	H	-33.28	-13.00	-20.28	-54.38	-36.21	2.93
11092.50	H	-35.16	-13.00	-22.16	-58.94	-35.79	0.63
14790.00	H	-39.68	-13.00	-26.68	-64.27	-40.04	0.36
7395.00	V	-37.96	-13.00	-24.96	-60.22	-40.89	2.93
11092.50	V	-38.65	-13.00	-25.65	-63.09	-39.28	0.63
14790.00	V	-36.83	-13.00	-23.83	-64.63	-37.19	0.36

Mode							
LTE Band 43, CB:10MHz, Channel:44140							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7310.00	H	-33.84	-13.00	-20.84	-54.65	-37.07	3.23
10965.00	H	-35.63	-13.00	-22.63	-59.26	-36.24	0.61
14620.00	H	-40.08	-13.00	-27.08	-64.24	-40.21	0.13
7310.00	V	-38.26	-13.00	-25.26	-60.56	-41.49	3.23
10965.00	V	-38.81	-13.00	-25.81	-62.95	-39.42	0.61
14620.00	V	-37.21	-13.00	-24.21	-64.33	-37.34	0.13
Mode							
LTE Band 43, CB:10MHz, Channel:44340							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7350.00	H	-33.71	-13.00	-20.71	-54.65	-36.80	3.09
11025.00	H	-35.20	-13.00	-22.20	-58.84	-35.78	0.58
14700.00	H	-39.68	-13.00	-26.68	-64.04	-39.92	0.24
7350.00	V	-38.16	-13.00	-25.16	-60.44	-41.25	3.09
11025.00	V	-38.65	-13.00	-25.65	-62.89	-39.23	0.58
14700.00	V	-36.89	-13.00	-23.89	-64.33	-37.13	0.24
Mode							
LTE Band 43, CB:10MHz, Channel:44540							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7390.00	H	-33.52	-13.00	-20.52	-54.60	-36.47	2.95
11085.00	H	-36.03	-13.00	-23.03	-59.80	-36.65	0.62
14780.00	H	-39.82	-13.00	-26.82	-64.38	-40.17	0.35
7390.00	V	-38.23	-13.00	-25.23	-60.48	-41.18	2.95
11085.00	V	-38.82	-13.00	-25.82	-63.24	-39.44	0.62
14780.00	V	-40.14	-13.00	-27.14	-67.90	-40.49	0.35

Mode							
LTE Band 43, CB:15MHz, Channel:44165							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7315.00	H	-33.62	-13.00	-20.62	-54.44	-36.83	3.21
10972.50	H	-35.89	-13.00	-22.89	-59.52	-36.49	0.60
14630.00	H	-39.87	-13.00	-26.87	-64.06	-40.02	0.15
7315.00	V	-37.95	-13.00	-24.95	-60.24	-41.16	3.21
10972.50	V	-39.29	-13.00	-26.29	-63.44	-39.89	0.60
14630.00	V	-37.55	-13.00	-24.55	-64.71	-37.70	0.15
Mode							
LTE Band 43, CB:15MHz, Channel:44340							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7350.00	H	-33.95	-13.00	-20.95	-54.89	-37.04	3.09
11025.00	H	-34.86	-13.00	-21.86	-58.50	-35.44	0.58
14700.00	H	-40.65	-13.00	-27.65	-65.01	-40.89	0.24
7350.00	V	-37.87	-13.00	-24.87	-60.15	-40.96	3.09
11025.00	V	-38.83	-13.00	-25.83	-63.07	-39.41	0.58
14700.00	V	-39.28	-13.00	-26.28	-66.72	-39.52	0.24
Mode							
LTE Band 43, CB:15MHz, Channel:44515							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7385.00	H	-34.15	-13.00	-21.15	-55.22	-37.11	2.96
11077.50	H	-35.89	-13.00	-22.89	-59.64	-36.51	0.62
14770.00	H	-40.21	-13.00	-27.21	-64.75	-40.55	0.34
7385.00	V	-38.56	-13.00	-25.56	-60.82	-41.52	2.96
11077.50	V	-39.04	-13.00	-26.04	-63.44	-39.66	0.62
14770.00	V	-39.82	-13.00	-26.82	-67.54	-40.16	0.34

Mode							
LTE Band 43, CB:20MHz, Channel:44190							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7320.00	H	-33.06	-13.00	-20.06	-53.91	-36.25	3.19
10980.00	H	-35.39	-13.00	-22.39	-59.00	-35.98	0.59
14640.00	H	-38.94	-13.00	-25.94	-63.16	-39.10	0.16
7320.00	V	-38.56	-13.00	-25.56	-60.85	-41.75	3.19
10980.00	V	-38.86	-13.00	-25.86	-63.01	-39.45	0.59
14640.00	V	-36.31	-13.00	-23.31	-63.51	-36.47	0.16
Mode							
LTE Band 43, CB:20MHz, Channel:44340							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7350.00	H	-33.21	-13.00	-20.21	-54.15	-36.30	3.09
11025.00	H	-35.41	-13.00	-22.41	-59.05	-35.99	0.58
14700.00	H	-39.74	-13.00	-26.74	-64.10	-39.98	0.24
7350.00	V	-38.23	-13.00	-25.23	-60.51	-41.32	3.09
11025.00	V	-38.58	-13.00	-25.58	-62.82	-39.16	0.58
14700.00	V	-36.88	-13.00	-23.88	-64.32	-37.12	0.24
Mode							
LTE Band 43, CB:20MHz, Channel:44490							
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)
7380.00	H	-33.66	-13.00	-20.66	-54.70	-36.64	2.98
11070.00	H	-34.81	-13.00	-21.81	-58.54	-35.42	0.61
14760.00	H	-39.82	-13.00	-26.82	-64.33	-40.14	0.32
7380.00	V	-38.32	-13.00	-25.32	-60.58	-41.30	2.98
11070.00	V	-38.41	-13.00	-25.41	-62.78	-39.02	0.61
14760.00	V	-37.17	-13.00	-24.17	-64.85	-37.49	0.32

3.3 Conducted Emissions


3.3.1 Limit of Conducted Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.


3.3.2 Test Procedures

1. Lowest, middle and highest operating channels are tested for this item.
2. Scan frequency range is from 30MHz~40GHz.
3. Set RBW = 1MHz, VBW = 3MHz, detector = RMS, sweep time = auto.
4. Record the max trace value and capture the test plot of each sub frequency band.


3.3.3 Test Setup




3.3.4 Test Result of Conducted Emissions



Worst Plots



Worst Plots



Worst Plots

