


FCC C2PC Test Report

FCC ID : MXF-WMDS183
Equipment : LoRa RF Board
Model No. : WMDS-183
Brand Name : Gemtek
Applicant : Gemtek Technology Co., Ltd.
Address : No.15-1 Zhonghua Rd, Hsinchu Industrial
Park, Hukou, Hsinchu, Taiwan, R.O.C
Standard : 47 CFR FCC Part 15.247
Received Date : Oct. 24, 2018
Tested Date : Oct. 26 ~ Oct. 30, 2018


We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	Unwanted Emissions into Restricted Frequency Bands	16
4	TEST LABORATORY INFORMATION	26

Release Record

Report No.	Version	Description	Issued Date
FR782401-06	Rev. 01	Initial issue	Nov. 14, 2018

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.300MHz 41.67 (Margin -8.57dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 110.14MHz 38.65 (Margin -4.85dB) - PK	Pass

1 General Description

1.1 Information

This report is prepared for FCC class II change.

This report is issued as a supplementary report to original ICC report no. FR782401. The difference is concerned with following items:

- ✧ Adding 2nd baseband IC, Model name: SX1308 (pin for pin compatible)
- ✧ Adding components on exist path to switch transmission path

In this report, conducted emission and radiated emission tests had been re-tested and only its data was presented in the following sections.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	Ch. Freq. (MHz)	Channel Number	Data Rate (bit/sec)	Spread Factor	Channel Bandwidth (kHz)
902 ~ 928	923.3 ~ 927.5	1 ~ 8 [8]	980 ~ 21900	12 ~ 7	500
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					
Note 2: The device uses CSS modulation.					

1.1.2.1 Antenna of Host

Ant. No.	Brand	Part Number	Type	Connector	Gain (dBi)
1	GSC-TECH	OMA-G04A	Dipole	N-Type	3
2	GSC-TECH	OMA-G03A	Dipole	N-Type	5
3	GSC-TECH	OMA-G01	Dipole	N-Type	8
4	Auden	A40816-90	Dipole	N-Type	3
5	Lynwave	OOX17X-021030-00	Dipole	N-Type	3
6	Lynwave	OOX17X-021050-00	Dipole	N-Type	5
7	Lynwave	OOX17X-021080-00	Dipole	N-Type	8

Note: The Ant. 3 with highest gain was selected for final testing

1.1.2.2 Power Supply Type of Host

Power Supply Type	5Vdc from host
-------------------	----------------

1.1.2.3 Accessories of Host

N/A


1.1.2 Channel List

Channel	Frequency(MHz)
1	923.3
2	923.9
3	924.5
4	925.1
5	925.7
6	926.3
7	926.9
8	927.5

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Test box	machineQ	HXQX1AM0S	---	Provided by applicant.
2	Test box Power source	PHIHONG	PSAC24A-120L 6	---	Provided by applicant.
3	Fixture	---	---	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Oct. 30, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 05, 2018	Jan. 04, 2019
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2017	Nov. 12, 2018
RF Cable-CON	EMC	EMCCFD300-BM-B M-6000	50821	Dec. 18, 2017	Dec. 17, 2018
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Oct. 26, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2017	Dec. 03, 2018
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 20, 2017	Dec. 19, 2018
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	May 09, 2018	May 08, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 07, 2017	Dec. 06, 2018
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	16052	Dec. 07, 2017	Dec. 06, 2018
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 07, 2017	Dec. 06, 2018
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 07, 2017	Dec. 06, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Power density	± 0.463 dB
Conducted emission	± 2.670 dB
AC conducted emission	± 2.90 dB
Radiated emission ≤ 1 GHz	± 3.66 dB
Radiated emission > 1 GHz	± 5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 57%	Alex Tsai
Radiated Emissions	03CH01-WS	26°C / 60%	Akun Chung

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Test Frequency (MHz)	Channel Bandwidth (kHz)	Modulation / SF	Test Configuration
Conducted Emissions	923.3 / 927.5	500	CSS / 12	---
Radiated Emissions	923.3 / 927.5	500	CSS / 12	---

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report. .

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions


Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	25.02	56.00	-30.98	24.74	0.27	0.01	Average
2	0.150	41.89	66.00	-24.11	41.61	0.27	0.01	QP
3*	0.300	41.67	50.24	-8.57	41.33	0.32	0.02	Average
4	0.300	43.46	60.24	-16.78	43.12	0.32	0.02	QP
5	0.853	25.15	46.00	-20.85	24.74	0.38	0.03	Average
6	0.853	26.98	56.00	-29.02	26.57	0.38	0.03	QP
7	4.574	16.91	46.00	-29.09	16.20	0.48	0.23	Average
8	4.574	22.47	56.00	-33.53	21.76	0.48	0.23	QP
9	10.290	18.93	50.00	-31.07	18.03	0.58	0.32	Average
10	10.290	24.63	60.00	-35.37	23.73	0.58	0.32	QP
11	14.313	18.78	50.00	-31.22	17.78	0.68	0.32	Average
12	14.313	24.27	60.00	-35.73	23.27	0.68	0.32	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.171	23.51	54.90	-31.39	23.35	0.14	0.02	Average
2	0.171	38.67	64.90	-26.23	38.51	0.14	0.02	QP
3*	0.300	40.05	50.24	-10.19	39.86	0.17	0.02	Average
4	0.300	42.21	60.24	-18.03	42.02	0.17	0.02	QP
5	0.598	24.31	46.00	-21.69	24.07	0.22	0.02	Average
6	0.598	26.15	56.00	-29.85	25.91	0.22	0.02	QP
7	0.853	24.63	46.00	-21.37	24.35	0.25	0.03	Average
8	0.853	26.67	56.00	-29.33	26.39	0.25	0.03	QP
9	3.901	13.78	46.00	-32.22	13.21	0.35	0.22	Average
10	3.901	21.97	56.00	-34.03	21.40	0.35	0.22	QP
11	13.479	18.41	50.00	-31.59	17.56	0.53	0.32	Average
12	13.479	23.63	60.00	-36.37	22.78	0.53	0.32	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	25.71	55.69	-29.98	25.43	0.27	0.01	Average
2	0.156	38.88	65.69	-26.81	38.60	0.27	0.01	QP
3*	0.300	41.66	50.24	-8.58	41.32	0.32	0.02	Average
4	0.300	43.41	60.24	-16.83	43.07	0.32	0.02	QP
5	0.598	24.81	46.00	-21.19	24.43	0.36	0.02	Average
6	0.598	26.68	56.00	-29.32	26.30	0.36	0.02	QP
7	1.790	19.30	46.00	-26.70	18.79	0.42	0.09	Average
8	1.790	26.34	56.00	-29.66	25.83	0.42	0.09	QP
9	10.397	19.13	50.00	-30.87	18.23	0.58	0.32	Average
10	10.397	24.70	60.00	-35.30	23.80	0.58	0.32	QP
11	13.841	19.17	50.00	-30.83	18.18	0.67	0.32	Average
12	13.841	24.35	60.00	-35.65	23.36	0.67	0.32	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.186	27.63	54.20	-26.57	27.45	0.15	0.03	Average
2	0.186	37.48	64.20	-26.72	37.30	0.15	0.03	QP
3*	0.297	39.74	50.32	-10.58	39.55	0.17	0.02	Average
4	0.297	42.14	60.32	-18.18	41.95	0.17	0.02	QP
5	0.601	22.45	46.00	-23.55	22.21	0.22	0.02	Average
6	0.601	26.25	56.00	-29.75	26.01	0.22	0.02	QP
7	0.880	17.96	46.00	-28.04	17.68	0.25	0.03	Average
8	0.880	25.88	56.00	-30.12	25.60	0.25	0.03	QP
9	3.840	14.28	46.00	-31.72	13.72	0.35	0.21	Average
10	3.840	22.49	56.00	-33.51	21.93	0.35	0.21	QP
11	13.989	18.51	50.00	-31.49	17.65	0.54	0.32	Average
12	13.989	23.82	60.00	-36.18	22.96	0.54	0.32	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.2.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	110.14	38.65	43.50	-4.85	50.22	-11.57	Peak	---	---
2	249.60	32.78	46.00	-13.22	42.27	-9.49	Peak	---	---
3	448.00	37.08	46.00	-8.92	41.31	-4.23	Peak	---	---
4	479.20	40.18	46.00	-5.82	43.78	-3.60	Peak	---	---
5	664.80	37.42	46.00	-8.58	37.58	-0.16	Peak	---	---
6	960.20	38.02	54.00	-15.98	33.81	4.21	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	68.25	35.12	40.00	-4.88	45.57	-10.45	QP	108	200
2	230.40	33.39	46.00	-12.61	43.78	-10.39	Peak	---	---
3	243.20	34.84	46.00	-11.16	44.47	-9.63	Peak	---	---
4	352.00	33.77	46.00	-12.23	40.38	-6.61	Peak	---	---
5	479.20	35.33	46.00	-10.67	38.93	-3.60	Peak	---	---
6	960.30	40.86	54.00	-13.14	36.65	4.21	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	110.75	38.35	43.50	-5.15	49.85	-11.50	Peak	---	---
2	249.60	32.19	46.00	-13.81	41.68	-9.49	Peak	---	---
3	448.00	35.28	46.00	-10.72	39.51	-4.23	Peak	---	---
4	479.20	38.22	46.00	-7.78	41.82	-3.60	Peak	---	---
5	704.00	37.35	46.00	-8.65	36.82	0.53	Peak	---	---
6	960.60	36.03	54.00	-17.97	31.82	4.21	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	68.25	35.09	40.00	-4.91	45.54	-10.45	QP	107	198
2	249.60	24.21	46.00	-21.79	33.70	-9.49	Peak	---	---
3	448.00	32.66	46.00	-13.34	36.89	-4.23	Peak	---	---
4	479.20	35.71	46.00	-10.29	39.31	-3.60	Peak	---	---
5	531.20	33.72	46.00	-12.28	36.15	-2.43	Peak	---	---
6	965.60	36.00	54.00	-18.00	31.74	4.26	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2769.90	32.48	54.00	-21.52	34.39	-1.91	Average	254	344
2	2769.90	43.45	74.00	-30.55	45.36	-1.91	Peak	254	344
3	3693.20	32.39	54.00	-21.61	31.90	0.49	Average	100	50
4	3693.20	42.72	74.00	-31.28	42.23	0.49	Peak	100	50
5	7386.40	44.29	54.00	-9.71	35.52	8.77	Average	241	5
6	7386.40	54.57	74.00	-19.43	45.80	8.77	Peak	241	5
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation / SF	CSS / 12	Test Freq. (MHz)	923.3
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2769.90	30.23	54.00	-23.77	32.14	-1.91	Average	100	162
2	2769.90	40.55	74.00	-33.45	42.46	-1.91	Peak	100	162
3	3693.20	30.94	54.00	-23.06	30.45	0.49	Average	100	32
4	3693.20	42.96	74.00	-31.04	42.47	0.49	Peak	100	32
5	7386.40	43.41	54.00	-10.59	34.64	8.77	Average	100	359
6	7386.40	54.57	74.00	-19.43	45.80	8.77	Peak	100	359

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2782.50	32.32	54.00	-21.68	34.18	-1.86	Average	256	339
2	2782.50	43.36	74.00	-30.64	45.22	-1.86	Peak	256	339
3	3710.00	32.21	54.00	-21.79	31.68	0.53	Average	100	49
4	3710.00	42.67	74.00	-31.33	42.14	0.53	Peak	100	49
5	7420.00	43.85	54.00	-10.15	35.04	8.81	Average	242	3
6	7420.00	54.46	74.00	-19.54	45.65	8.81	Peak	242	3

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation / SF	CSS / 12	Test Freq. (MHz)	927.5
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2782.50	30.23	54.00	-23.77	32.09	-1.86	Average	100	159
2	2782.50	40.46	74.00	-33.54	42.32	-1.86	Peak	100	159
3	3693.20	30.80	54.00	-23.20	30.31	0.49	Average	100	28
4	3693.20	42.76	74.00	-31.24	42.27	0.49	Peak	100	28
5	7386.40	43.38	54.00	-10.62	34.61	8.77	Average	100	3
6	7386.40	52.78	74.00	-21.22	44.01	8.77	Peak	100	3

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==