


FCC Test Report

FCC ID : MXF-WLTMQ117
Equipment : LTE Mini Card
Model No. : WLTMQ-117
Brand Name : Gemtek
Applicant : Gemtek Technology Co., Ltd.
Address : No. 15-1 Zhanghua Road, Hsinchu Industrial
Park, Hukou, Hsinchu, Taiwan, 30352
Standard : 47 CFR FCC Part 22 Subpart H
Received Date : Dec. 30, 2015
Tested Date : Jan. 14 ~ Feb. 02, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List.....	7
1.3	Test Setup Chart.....	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION.....	10
2.1	Testing Condition and Location Information.....	10
2.2	The Worst Test Modes and Channel Details.....	10
3	TEST RESULTS	11
3.1	Effective Radiated Power	11
3.2	Radiated Emissions	22
3.3	Conducted Emissions	32
3.4	Band Edge.....	43
3.5	Occupied and 26 dB Bandwidth	59
3.6	Peak to Average Ratio	65
3.7	Frequency Stability.....	71
4	TEST LABORATORY INFORMATION	75

Release Record

Report No.	Version	Description	Issued Date
FG5D3001P22	Rev. 01	Initial issue	Feb. 22, 2016
FG5D3001P22	Rev. 02	Corrected category and height of table of test diagram	Feb. 24, 2016

Summary of Test Results

FCC Rules	Test Items	Measured	Result
2.1046 / 22.913(a)(2)	Effective Radiated Power	Max ERP [dBm]: 21.77	Pass
2.1053 / 22.917(a)	Radiated Emissions	Meet the requirement of limit	Pass
2.1051 / 22.917(a)	Conducted Emissions	Meet the requirement of limit	Pass
2.1051 / 22.917(a)	Band Edge	Meet the requirement of limit	Pass
2.1049	Occupied Bandwidth	Meet the requirement of limit	Pass
-	Peak to average ratio	Meet the requirement of limit	Pass
2.1055 / 22.355	Frequency Stability	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency (MHz)	Channel Bandwidth: 1.4MHz: 824.7~848.3 Channel Bandwidth: 3MHz: 825.5~847.5 Channel Bandwidth: 5MHz: 826.5~846.5 Channel Bandwidth: 10MHz: 829~844 Channel Bandwidth: 15MHz: 831.5~841.5
Modulation	Uplink: QPSK, 16QAM, 64QAM Downlink: QPSK, 16QAM, 64QAM, 256QAM
Duplex Mode	FDD
Category	Cat 5 & Cat 6
Release Version	11
H/W Version	V01
S/W Version	LE5166215.12052
TX/RX function	1TX / 4RX

1.1.2 Maximum Conducted Power and Emission Designator

Mode	Modulation	Maximum Conducted Power (W)	Emission Designator
LTE Band 26, CB: 1.4MHz	QPSK	0.179	1M08G7D
LTE Band 26, CB: 1.4MHz	16QAM	0.144	1M08W7D
LTE Band 26, CB: 1.4MHz	64QAM	0.139	1M08W7D
LTE Band 26, CB: 3MHz	QPSK	0.177	2M68G7D
LTE Band 26, CB: 3MHz	16QAM	0.142	2M68W7D
LTE Band 26, CB: 3MHz	64QAM	0.139	2M69W7D
LTE Band 26, CB: 5MHz	QPSK	0.183	4M47G7D
LTE Band 26, CB: 5MHz	16QAM	0.156	4M47W7D
LTE Band 26, CB: 5MHz	64QAM	0.163	4M47W7D
LTE Band 26, CB: 10MHz	QPSK	0.175	8M93G7D
LTE Band 26, CB: 10MHz	16QAM	0.152	8M91W7D
LTE Band 26, CB: 10MHz	64QAM	0.147	8M93W7D
LTE Band 26, CB: 15MHz	QPSK	0.191	13M5G7D
LTE Band 26, CB: 15MHz	16QAM	0.172	13M4W7D
LTE Band 26, CB: 15MHz	64QAM	0.169	13M4W7D

1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	Dipole	1.1	SMA	---

1.1.4 EUT Operational Condition

Power Supply Type	3.3Vdc from host		
Operational Climatic	☒ Tnom (20°C)	☒ Tmax (60°C)	☒ Tmin (-40°C)

1.1.5 Accessories

N/A


1.1.6 Operating Channel List

LTE Band 26		
Channel Bandwidth (MHz)	Channel	Frequency (MHz)
1.4	26797	824.7
1.4	26915	836.5
1.4	27033	848.3
3	26805	825.5
3	26915	836.5
3	27025	847.5
5	26815	826.5
5	26915	836.5
5	27015	846.5
10	26840	829.0
10	26915	836.5
10	26990	844.0
15	26865	831.5
15	26915	836.5
15	26965	841.5

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E5420	B6FT9T1	DoC	USB, 1m shielded.
2	Fixture	---	---	---	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 13, 2015	Dec. 12, 2016
Receiver	R&S	ESR3	101658	Nov. 04, 2015	Nov. 03, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 20, 2015	Aug. 19, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 16, 2015	Dec. 15, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 10, 2015	Dec. 09, 2016
Preamplifier	Burgeon	BPA-530	SN:100219	Sep. 10, 2015	Sep. 09, 2016
Preamplifier	Agilent	83017A	MY39501308	Oct. 02, 2015	Oct. 01, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 10, 2015	Dec. 09, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 27, 2015	Nov. 26, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 19, 2015	Mar. 18, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards.

47 CFR FCC Part 22 Subpart H

ANSI C63.4-2014

ANSI/TIA-603-D 2010

FCC KDB 971168 D01 Power Meas License Digital Systems v02r02

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Frequency error	± 34.134 Hz
Conducted emission	± 2.670 dB
Radiated emission ≤ 1 GHz	± 3.66 dB
Radiated emission > 1 GHz	± 5.63 dB
Temperature	± 0.6 °C

2 Test Configuration

2.1 Testing Condition and Location Information

Test Item	Test Site	Ambient Condition	Tested By
RF conducted	TH01-WS	20°C / 62%	Felix Sung
Radiated Emissions	03CH01-WS	22°C / 64%	Aska Huang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Channel Bandwidths	Modulation	Test channel
Effective Radiated Power	1.4 MHz	QPSK / 16QAM / 64QAM	824.7 / 836.5 / 848.3
Conducted Emissions	3 MHz	QPSK / 16QAM / 64QAM	825.5 / 836.5 / 847.5
	5 MHz	QPSK / 16QAM / 64QAM	826.5 / 836.5 / 846.5
Occupied Bandwidth	10 MHz	QPSK / 16QAM / 64QAM	829.0 / 836.5 / 844.0
Peak to Average Ratio	15 MHz	QPSK / 16QAM / 64QAM	831.5 / 836.5 / 841.5
Radiated Emission ≤ 1GHz	1.4 MHz	QPSK	824.7
	3 MHz	QPSK	825.5
	5 MHz	QPSK	826.5
	10 MHz	QPSK	829.0
	15 MHz	QPSK	831.5
Radiated Emission > 1GHz	1.4 MHz	QPSK	824.7 / 836.5 / 848.3
	3 MHz	QPSK	825.5 / 836.5 / 847.5
	5 MHz	QPSK	826.5 / 836.5 / 846.5
	10 MHz	QPSK	829.0 / 836.5 / 844.0
	15 MHz	QPSK	831.5 / 836.5 / 841.5
Band Edge	1.4 MHz	QPSK / 16QAM / 64QAM	824.7 / 848.3
	3 MHz	QPSK / 16QAM / 64QAM	825.5 / 847.5
	5 MHz	QPSK / 16QAM / 64QAM	826.5 / 846.5
	10 MHz	QPSK / 16QAM / 64QAM	829.0 / 844.0
	15 MHz	QPSK / 16QAM / 64QAM	831.5 / 841.5
Frequency Stability	1.4 MHz	QPSK	836.5
	3 MHz	QPSK	836.5
	5 MHz	QPSK	836.5
	10 MHz	QPSK	836.5
	15 MHz	QPSK	836.5

3 Test Results

3.1 Effective Radiated Power

3.1.1 Limit of Effective Radiated Power

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

3.1.2 Test Procedures

For Conducted power measurement:


1. The EUT links up with simulator and is set to maximum output power level at low / middle / high channel.
2. Measure the output power of low / middle / high channel of the EUT.

For ERP measurement:

ERP can be calculated by below formula from KDB 412172 D01.

1. $EIRP = P_T + G_T - L_C$
 P_T = transmitter output power, in dBm.
 G_T = gain of the transmitting antenna, in dBi (EIRP).
 L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.
2. $ERP = EIRP - 2.15 \text{ dB}$.

3.1.3 Test Setup



3.1.4 Test Result of Conducted Output Power (dBm)

Band / Channel Bandwidth			LTE Band 26 / CB: 1.4MHz		
Channel			26797	26915	27033
Frequency (MHz)			824.7	836.5	848.3
Mode	RB	RB Offset	Maximum AV Power (dBm)		
QPSK	1	0	22.54	22.43	22.11
	1	2	22.45	22.45	21.77
	1	5	22.41	22.29	22.10
	3	0	22.45	22.36	21.86
	3	1	22.46	22.43	21.73
	3	2	22.45	22.38	21.57
	6	0	21.43	21.44	21.08
16QAM	1	0	21.59	21.48	21.06
	1	2	21.43	21.43	20.83
	1	5	21.41	21.44	20.25
	3	0	21.30	21.45	20.81
	3	1	21.33	21.55	20.68
	3	2	21.34	21.29	20.54
	6	0	20.48	20.45	20.12
64QAM	1	0	21.43	21.43	21.11
	1	2	21.35	21.35	20.76
	1	5	21.35	21.39	20.43
	3	0	21.22	21.44	20.76
	3	1	21.29	21.38	20.59
	3	2	21.31	21.19	20.38
	6	0	20.29	20.53	20.09

Band / Channel Bandwidth			LTE Band 26 / CB: 3MHz		
Channel			26805	26915	27025
Frequency (MHz)			825.5	836.5	847.5
Mode	RB	RB Offset	Maximum AV Power (dBm)		
QPSK	1	0	22.49	22.21	22.49
	1	7	22.43	22.18	22.46
	1	14	22.25	21.98	21.87
	8	0	21.37	21.29	21.37
	8	4	21.43	21.19	21.07
	8	7	21.38	21.09	20.63
	15	0	21.41	21.21	21.02
16QAM	1	0	21.51	21.26	21.35
	1	7	21.39	21.11	21.09
	1	14	21.31	21.06	21.02
	8	0	20.40	20.42	20.38
	8	4	20.46	20.32	20.22
	8	7	20.40	20.13	20.04
	15	0	20.40	20.18	20.13
64QAM	1	0	21.43	21.22	21.22
	1	7	21.32	21.03	21.15
	1	14	21.22	21.08	21.01
	8	0	20.32	20.35	20.24
	8	4	20.39	20.26	20.18
	8	7	20.28	20.08	20.15
	15	0	20.35	20.11	20.03

Band / Channel Bandwidth			LTE Band 26 / CB: 5MHz		
Channel			26815	26915	27015
Frequency (MHz)			826.5	836.5	846.5
Mode	RB	RB Offset	Maximum AV Power (dBm)		
QPSK	1	0	22.63	22.42	22.62
	1	12	22.42	22.36	22.43
	1	24	22.40	22.10	21.29
	12	0	21.51	21.47	21.34
	12	6	21.56	21.46	21.65
	12	11	21.52	21.31	21.46
	25	0	21.57	21.46	21.33
16QAM	1	0	21.93	21.87	21.54
	1	12	21.91	21.81	21.29
	1	24	21.87	21.58	21.18
	12	0	20.56	20.52	20.33
	12	6	20.59	20.51	20.67
	12	11	20.47	20.40	20.48
	25	0	20.57	20.46	20.25
64QAM	1	0	21.88	21.89	22.13
	1	12	21.77	21.87	21.29
	1	24	21.76	21.58	21.12
	12	0	20.65	20.52	20.33
	12	6	20.51	20.51	20.67
	12	11	20.43	20.40	20.48
	25	0	20.43	20.46	20.25

Band / Channel Bandwidth			LTE Band 26 / CB: 10MHz		
Channel			26840	26915	26990
Frequency (MHz)			829	836.5	844
Mode	RB	RB Offset	Maximum AV Power (dBm)		
QPSK	1	0	22.42	22.35	22.25
	1	24	22.39	22.26	22.16
	1	49	22.31	22.04	21.39
	25	0	21.51	21.56	21.17
	25	12	21.62	21.58	21.32
	25	24	21.58	21.36	21.37
	50	0	21.50	21.34	21.28
16QAM	1	0	21.73	21.82	21.32
	1	24	21.69	21.76	21.22
	1	49	21.68	21.39	20.81
	25	0	20.48	20.52	20.18
	25	12	20.61	20.56	20.31
	25	24	20.55	20.36	20.32
	50	0	20.53	20.39	20.33
64QAM	1	0	21.66	21.62	21.43
	1	24	21.59	21.55	21.11
	1	49	21.59	21.32	20.79
	25	0	20.32	20.43	20.16
	25	12	20.55	20.49	20.25
	25	24	20.43	20.32	20.29
	50	0	20.39	20.33	20.21

Band / Channel Bandwidth			LTE Band 26 / CB: 15MHz		
Channel			26865	26915	26965
Frequency (MHz)			831.5	836.5	841.5
Mode	RB	RB Offset	Maximum AV Power (dBm)		
QPSK	1	0	22.82	22.81	22.79
	1	24	22.64	22.49	22.25
	1	49	22.76	22.67	22.21
	25	0	21.67	21.63	21.34
	25	12	21.72	21.63	21.34
	25	24	21.72	21.30	21.51
	50	0	21.70	21.55	21.46
16QAM	1	0	22.36	22.27	22.23
	1	24	22.11	21.98	21.76
	1	49	22.28	22.17	21.77
	25	0	20.64	20.58	20.37
	25	12	20.70	20.62	20.38
	25	24	20.69	20.45	20.53
	50	0	20.62	20.54	20.47
64QAM	1	0	22.29	22.18	22.16
	1	24	22.03	22.03	21.89
	1	49	22.19	22.05	21.83
	25	0	20.53	20.49	20.22
	25	12	20.65	20.55	20.32
	25	24	20.62	20.32	20.49
	50	0	20.59	20.46	20.35

3.1.5 Test Result of Effective Radiated Power (dBm)

LTE Band 26, CB: 1.4MHz

Mode	LTE Band 26, CB: 1.4MHz, QPSK						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26797	824.7	22.54	1.1	23.64	21.49	0.141	7
26915	836.5	22.45	1.1	23.55	21.40	0.138	7
27033	848.3	22.11	1.1	23.21	21.06	0.128	7

Mode	LTE Band 26, CB: 1.4MHz, 16QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26797	824.7	21.59	1.1	22.69	20.54	0.113	7
26915	836.5	21.55	1.1	22.65	20.50	0.112	7
27033	848.3	21.06	1.1	22.16	20.01	0.100	7

Mode	LTE Band 26, CB: 1.4MHz, 64QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26797	824.7	21.43	1.1	22.53	20.38	0.109	7
26915	836.5	21.44	1.1	22.54	20.39	0.109	7
27033	848.3	21.11	1.1	22.21	20.06	0.101	7

NOTE: ERP = EIRP - 2.15 dB.

LTE Band 26, CB: 3MHz

Mode	LTE Band 26, CB: 3MHz, QPSK						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26805	825.5	22.49	1.1	23.59	21.44	0.139	7
26915	836.5	22.21	1.1	23.31	21.16	0.131	7
27025	847.5	22.49	1.1	23.59	21.44	0.139	7

Mode	LTE Band 26, CB: 3MHz, 16QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26805	825.5	21.51	1.1	22.61	20.46	0.111	7
26915	836.5	21.26	1.1	22.36	20.21	0.105	7
27025	847.5	21.35	1.1	22.45	20.30	0.107	7

Mode	LTE Band 26, CB: 3MHz, 64QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26805	825.5	21.43	1.1	22.53	20.38	0.109	7
26915	836.5	21.22	1.1	22.32	20.17	0.104	7
27025	847.5	21.22	1.1	22.32	20.17	0.104	7

NOTE: ERP = EIRP - 2.15 dB.

LTE Band 26, CB: 5MHz

Mode	LTE Band 26, CB: 5MHz, QPSK						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26815	826.5	22.63	1.1	23.73	21.58	0.144	7
26915	836.5	22.42	1.1	23.52	21.37	0.137	7
27015	846.5	22.62	1.1	23.72	21.57	0.144	7

Mode	LTE Band 26, CB: 5MHz, 16QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26815	826.5	21.93	1.1	23.03	20.88	0.122	7
26915	836.5	21.87	1.1	22.97	20.82	0.121	7
27015	846.5	21.54	1.1	22.64	20.49	0.112	7

Mode	LTE Band 26, CB: 5MHz, 64QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26815	826.5	21.88	1.1	22.98	20.83	0.121	7
26915	836.5	21.89	1.1	22.99	20.84	0.121	7
27015	846.5	22.13	1.1	23.23	21.08	0.128	7

NOTE: ERP = EIRP - 2.15 dB.

LTE Band 26, CB: 10MHz

Mode	LTE Band 26, CB: 10MHz, QPSK						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26840	829.0	22.42	1.1	23.52	21.37	0.137	7
26915	836.5	22.35	1.1	23.45	21.30	0.135	7
26990	844.0	22.25	1.1	23.35	21.20	0.132	7

Mode	LTE Band 26, CB: 10MHz, 16QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26840	829.0	21.73	1.1	22.83	20.68	0.117	7
26915	836.5	21.82	1.1	22.92	20.77	0.119	7
26990	844.0	21.32	1.1	22.42	20.27	0.106	7

Mode	LTE Band 26, CB: 10MHz, 64QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26840	829.0	21.66	1.1	22.76	20.61	0.115	7
26915	836.5	21.62	1.1	22.72	20.57	0.114	7
26990	844.0	21.43	1.1	22.53	20.38	0.109	7

NOTE: ERP = EIRP - 2.15 dB.

LTE Band 26, CB: 15MHz

Mode	LTE Band 26, CB: 15MHz, QPSK						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26865	831.5	22.82	1.1	23.92	21.77	0.150	7
26915	836.5	22.81	1.1	23.91	21.76	0.150	7
26965	841.5	22.79	1.1	23.89	21.74	0.149	7

Mode	LTE Band 26, CB: 15MHz, 16QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26865	831.5	22.36	1.1	23.46	21.31	0.135	7
26915	836.5	22.27	1.1	23.37	21.22	0.132	7
26965	841.5	22.23	1.1	23.33	21.18	0.131	7

Mode	LTE Band 26, CB: 15MHz, 64QAM						
Channel	Frequency (MHz)	Max Conducted Output Power (dBm)	Max Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)
26865	831.5	22.29	1.1	23.39	21.24	0.133	7
26915	836.5	22.18	1.1	23.28	21.13	0.130	7
26965	841.5	22.16	1.1	23.26	21.11	0.129	7

NOTE: ERP = EIRP - 2.15 dB.

3.2 Radiated Emissions

3.2.1 Limit of Radiated Emissions


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. $E.I.R.P = \text{output power of step 4} + \text{gain of substitution antenna} - \text{cable loss of RF cable}$. ERP can be calculated by below formula:
 $E.R.P = E.I.R.P - 2.15dB$.

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Test Result of Radiated Emissions below 1GHz

Mode	LTE Band 26, CB: 1.4MHz, 1RB, Offset 0,Channel: 26797						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
30.97	H	-67.86	-13.00	-54.86	-64.39	-51.69	-14.02
158.04	H	-65.70	-13.00	-52.70	-54.71	-62.94	-0.61
239.52	H	-54.87	-13.00	-41.87	-41.33	-57.17	4.45
296.75	H	-57.74	-13.00	-44.74	-45.92	-59.87	4.28
334.58	H	-55.05	-13.00	-42.05	-45.22	-57.26	4.36
411.21	H	-70.58	-13.00	-57.58	-62.74	-72.62	4.19
45.52	V	-63.24	-13.00	-50.24	-51.88	-49.45	-11.64
102.75	V	-65.62	-13.00	-52.62	-54.39	-63.64	0.17
156.10	V	-62.79	-13.00	-49.79	-54.64	-59.93	-0.71
239.52	V	-60.70	-13.00	-47.70	-52.39	-63.00	4.45
337.49	V	-61.77	-13.00	-48.77	-53.63	-63.99	4.37
540.22	V	-65.13	-13.00	-52.13	-61.08	-67.07	4.09

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 3MHz, 1RB, Offset 0,Channel: 26805						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
30.00	H	-67.89	-13.00	-54.89	-64.74	-51.53	-14.21
159.01	H	-65.04	-13.00	-52.04	-54.05	-62.34	-0.55
239.52	H	-54.63	-13.00	-41.63	-41.09	-56.93	4.45
295.78	H	-57.56	-13.00	-44.56	-45.72	-59.69	4.28
334.58	H	-55.05	-13.00	-42.05	-45.22	-57.26	4.36
417.03	H	-70.37	-13.00	-57.37	-62.58	-72.38	4.16
43.58	V	-61.92	-13.00	-48.92	-50.31	-47.84	-11.93
102.75	V	-64.98	-13.00	-51.98	-53.75	-63.00	0.17
151.25	V	-62.50	-13.00	-49.50	-53.97	-59.37	-0.98
240.49	V	-60.38	-13.00	-47.38	-52.11	-62.68	4.45
336.52	V	-62.89	-13.00	-49.89	-54.74	-65.10	4.36
540.22	V	-65.12	-13.00	-52.12	-61.07	-67.06	4.09

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 5MHz, 1RB, Offset 0,Channel: 26815						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
32.91	H	-68.49	-13.00	-55.49	-64.38	-52.69	-13.65
158.04	H	-64.66	-13.00	-51.66	-53.67	-61.90	-0.61
237.58	H	-54.95	-13.00	-41.95	-4135.00	-57.25	4.45
293.84	H	-58.06	-13.00	-45.06	-46.15	-60.20	4.29
336.52	H	-54.78	-13.00	-41.78	-45.06	-56.99	4.36
412.18	H	-70.84	-13.00	-57.84	-63.02	-72.88	4.19
32.91	V	-66.20	-13.00	-53.20	-52.82	-50.40	-13.65
104.69	V	-63.72	-13.00	-50.72	-52.47	-61.62	0.05
158.04	V	-62.28	-13.00	-49.28	-54.27	-59.52	-0.61
237.58	V	-60.15	-13.00	-47.15	-51.76	-62.45	4.45
336.52	V	-61.80	-13.00	-48.80	-53.65	-64.01	4.36
542.16	V	-65.50	-13.00	-52.50	-61.54	-67.43	4.08

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 10MHz, 1RB, Offset 0,Channel: 26840						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
32.91	H	-69.14	-13.00	-56.14	-65.03	-53.34	-13.65
102.75	H	-70.69	-13.00	-57.69	-58.44	-68.71	0.17
156.10	H	-65.47	-13.00	-52.47	-54.50	-62.61	-0.71
237.58	H	-55.30	-13.00	-42.30	-41.70	-57.60	4.45
296.75	H	-56.64	-13.00	-43.64	-44.82	-58.77	4.28
334.58	H	-54.85	-13.00	-41.85	-45.02	-57.06	4.36
44.55	V	-65.28	-13.00	-52.28	-53.97	-51.33	-11.80
102.75	V	-63.48	-13.00	-50.48	-52.25	-61.50	0.17
156.10	V	-62.66	-13.00	-49.66	-54.51	-59.80	-0.71
239.52	V	-60.30	-13.00	-47.30	-51.99	-62.60	4.45
336.52	V	-63.18	-13.00	-50.18	-55.03	-65.39	4.36
540.22	V	-66.11	-13.00	-53.11	-62.06	-68.05	4.09

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 15MHz, 1RB, Offset 0,Channel: 26865						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
30.97	H	-68.17	-13.00	-55.17	-64.70	-52.00	-14.02
126.03	H	-67.22	-13.00	-54.22	-55.34	-63.98	-1.09
158.04	H	-64.54	-13.00	-51.54	-53.55	-61.78	-0.61
237.58	H	-55.32	-13.00	-42.32	-41.72	-57.62	4.45
296.75	H	-57.90	-13.00	-44.90	-46.08	-60.03	4.28
333.61	H	-54.75	-13.00	-41.75	-44.87	-56.96	4.36
45.52	V	-62.56	-13.00	-49.56	-51.20	-48.77	-11.64
102.75	V	-65.92	-13.00	-52.92	-54.69	-63.94	0.17
156.10	V	-63.48	-13.00	-50.48	-55.30	-60.62	-0.71
237.58	V	-59.81	-13.00	-46.81	-51.36	-62.11	4.45
334.58	V	-62.24	-13.00	-49.24	-54.08	-64.45	4.36
540.22	V	-67.50	-13.00	-54.50	-63.45	-69.44	4.09

NOTE: ERP = S.G power value + correction factor - 2.15.

3.2.5 Test Result of Radiated Emissions above 1GHz

Mode	LTE Band 26, CB: 1.4MHz, 1RB, Offset 0, Channel:26797						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1648.60	H	-48.18	-13.00	-35.18	-49.55	-51.20	5.17
2472.90	H	-53.01	-13.00	-40.01	-59.26	-57.17	6.31
3297.20	H	-51.14	-13.00	-38.14	-60.26	-55.71	6.72
1648.60	V	-44.33	-13.00	-31.33	-45.10	-47.35	5.17
2472.90	V	-51.50	-13.00	-38.50	-58.49	-55.66	6.31
3297.20	V	-51.65	-13.00	-38.65	-60.37	-56.22	6.72

Mode	LTE Band 26, CB: 1.4MHz, 1RB, Offset 0, Channel:26915						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1672.10	H	-47.89	-13.00	-34.89	-49.38	-50.96	5.22
2508.15	H	-53.07	-13.00	-40.07	-59.41	-57.24	6.32
3344.20	H	-51.29	-13.00	-38.29	-60.18	-55.92	6.78
1672.10	V	-44.55	-13.00	-31.55	-45.39	-47.62	5.22
2508.15	V	-52.15	-13.00	-39.15	-59.21	-56.32	6.32
3344.20	V	-51.77	-13.00	-38.77	-60.47	-56.40	6.78

Mode	LTE Band 26, CB: 1.4MHz, 1RB, Offset 0, Channel:27033						
Frequency (MHz)	Antenna Polarity.	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1695.70	H	-48.24	-13.00	-35.24	-49.86	-51.37	5.28
2543.55	H	-53.85	-13.00	-40.85	-60.28	-58.04	6.34
3391.40	H	-51.82	-13.00	-38.82	-60.47	-56.50	6.83
1695.70	V	-43.36	-13.00	-30.36	-44.29	-46.49	5.28
2543.55	V	-51.93	-13.00	-38.93	-59.05	-56.12	6.34
3391.40	V	-51.80	-13.00	-38.80	-60.48	-56.48	6.83

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 3MHz, 1RB, Offset 0, Channel: 26805						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1648.50	H	-48.02	-13.00	-35.02	-49.39	-51.04	5.17
2472.75	H	-53.32	-13.00	-40.32	-59.57	-57.48	6.31
3297.00	H	-51.11	-13.00	-38.11	-60.24	-55.68	6.72
1648.50	V	-44.59	-13.00	-31.59	-45.35	-47.61	5.17
2472.75	V	-52.25	-13.00	-39.25	-59.24	-56.41	6.31
3297.00	V	-51.72	-13.00	-38.72	-60.44	-56.29	6.72

Mode	LTE Band 26, CB: 3MHz, 1RB, Offset 0, Channel: 26915						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1670.48	H	-51.96	-13.00	-38.96	-49.81	-55.03	5.22
2505.72	H	-61.99	-13.00	-48.99	-59.84	-66.16	6.32
3340.96	H	-62.48	-13.00	-49.48	-60.33	-67.10	6.77
1670.48	V	-44.64	-13.00	-31.64	-45.48	-47.71	5.22
2505.72	V	-52.24	-13.00	-39.24	-59.29	-56.41	6.32
3340.96	V	-51.77	-13.00	-38.77	-60.47	-56.39	6.77

Mode	LTE Band 26, CB: 3MHz, 1RB, Offset 0, Channel: 27025						
Frequency (MHz)	Antenna Polarity.	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1692.48	H	-48.23	-13.00	-35.23	-49.83	-51.35	5.27
2538.72	H	-53.09	-13.00	-40.09	-59.51	-57.28	6.34
3384.96	H	-51.65	-13.00	-38.65	-60.33	-56.32	6.82
1692.48	V	-44.25	-13.00	-31.25	-45.16	-47.37	5.27
2538.72	V	-52.71	-13.00	-39.71	-59.82	-56.90	6.34
3384.96	V	-51.65	-13.00	-38.65	-60.33	-56.32	6.82

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 5MHz, 1RB, Offset 0, Channel: 26815						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1648.70	H	-48.07	-13.00	-35.07	-49.44	-51.09	5.17
2473.05	H	-52.99	-13.00	-39.99	-59.24	-57.15	6.31
3297.40	H	-51.35	-13.00	-38.35	-60.47	-55.92	6.72
1648.70	V	-44.17	-13.00	-31.17	-44.93	-47.19	5.17
2473.05	V	-52.17	-13.00	-39.17	-59.16	-56.33	6.31
3297.40	V	-51.75	-13.00	-38.75	-60.47	-56.32	6.72

Mode	LTE Band 26, CB: 5MHz, 1RB, Offset 0, Channel: 26915						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1668.70	H	-48.25	-13.00	-35.25	-49.73	-51.31	5.21
2503.05	H	-53.56	-13.00	-40.56	-59.89	-57.73	6.32
3337.40	H	-51.42	-13.00	-38.42	-60.34	-56.04	6.77
1668.70	V	-44.33	-13.00	-31.33	-45.16	-47.39	5.21
2503.05	V	-52.19	-13.00	-39.19	-59.24	-56.36	6.32
3337.40	V	-52.61	-13.00	-39.61	-61.31	-57.23	6.77

Mode	LTE Band 26, CB: 5MHz, 1RB, Offset 0, Channel: 27015						
Frequency (MHz)	Antenna Polarity.	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1688.70	H	-48.63	-13.00	-35.63	-50.22	-51.74	5.26
2533.05	H	-54.33	-13.00	-41.33	-60.74	-58.51	6.33
3377.40	H	-51.72	-13.00	-38.72	-60.44	-56.38	6.81
1688.70	V	-43.96	-13.00	-30.96	-44.86	-47.07	5.26
2533.05	V	-52.11	-13.00	-39.11	-59.22	-56.29	6.33
3377.40	V	-51.62	-13.00	-38.62	-60.30	-56.28	6.81

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 10MHz, 1RB, Offset 0, Channel: 26840						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1649.20	H	-49.69	-13.00	-36.69	-51.06	-52.71	5.17
2473.80	H	-54.19	-13.00	-41.19	-60.44	-58.35	6.31
3298.40	H	-52.05	-13.00	-39.05	-61.17	-56.62	6.72
1649.20	V	-45.78	-13.00	-32.78	-46.55	-48.80	5.17
2473.80	V	-52.16	-13.00	-39.16	-59.15	-56.32	6.31
3298.40	V	-52.63	-13.00	-39.63	-61.35	-57.20	6.72

Mode	LTE Band 26, CB: 10MHz, 1RB, Offset 0, Channel: 26915						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1664.20	H	-49.83	-13.00	-36.83	-51.28	-52.88	5.20
2496.30	H	-54.08	-13.00	-41.08	-60.39	-58.25	6.32
3328.40	H	-52.59	-13.00	-39.59	-61.56	-57.20	6.76
1664.20	V	-45.75	-13.00	-32.75	-46.57	-48.80	5.20
2496.30	V	-52.31	-13.00	-39.31	-59.35	-56.48	6.32
3328.40	V	-53.61	-13.00	-40.61	-62.32	-58.22	6.76

Mode	LTE Band 26, CB: 10MHz, 1RB, Offset 0, Channel: 26990						
Frequency (MHz)	Antenna Polarity.	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1679.18	H	-49.49	-13.00	-36.49	-51.02	-52.58	5.24
2518.77	H	-53.91	-13.00	-40.91	-60.28	-58.09	6.33
3358.36	H	-52.56	-13.00	-39.56	-61.37	-57.20	6.79
1679.18	V	-44.66	-13.00	-31.66	-45.52	-47.75	5.24
2518.77	V	-52.13	-13.00	-39.13	-59.21	-56.31	6.33
3358.36	V	-52.79	-13.00	-39.79	-61.48	-57.43	6.79

NOTE: ERP = S.G power value + correction factor - 2.15.

Mode	LTE Band 26, CB: 15MHz, 1RB, Offset 0, Channel: 26865						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1649.70	H	-48.31	-13.00	-35.31	-49.68	-51.33	5.17
2474.55	H	-53.16	-13.00	-40.16	-59.41	-57.32	6.31
3299.40	H	-52.05	-13.00	-39.05	-61.16	-56.62	6.72
1649.70	V	-44.49	-13.00	-31.49	-45.26	-47.51	5.17
2474.55	V	-52.36	-13.00	-39.36	-59.35	-56.52	6.31
3299.40	V	-52.80	-13.00	-39.80	-61.52	-57.37	6.72

Mode	LTE Band 26, CB: 15MHz, 1RB, Offset 0, Channel: 26915						
Frequency (MHz)	Antenna Polarity	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1659.70	H	-49.07	-13.00	-36.07	-50.49	-52.11	5.19
2489.55	H	-54.12	-13.00	-41.12	-60.41	-58.29	6.32
3319.40	H	-51.90	-13.00	-38.90	-60.91	-56.50	6.75
1659.70	V	-44.91	-13.00	-31.91	-45.71	-47.95	5.19
2489.55	V	-52.38	-13.00	-39.38	-59.40	-56.55	6.32
3319.40	V	-52.56	-13.00	-39.56	-61.27	-57.16	6.75

Mode	LTE Band 26, CB: 15MHz, 1RB, Offset 0, Channel: 26965						
Frequency (MHz)	Antenna Polarity.	E.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
1669.70	H	-48.77	-13.00	-35.77	-50.25	-51.84	5.22
2504.55	H	-53.98	-13.00	-40.98	-60.31	-58.15	6.32
3339.40	H	-51.41	-13.00	-38.41	-60.32	-56.03	6.77
1669.70	V	-44.45	-13.00	-31.45	-45.29	-47.52	5.22
2504.55	V	-52.26	-13.00	-39.26	-59.31	-56.43	6.32
3339.40	V	-52.55	-13.00	-39.55	-61.25	-57.17	6.77

NOTE: ERP = S.G power value + correction factor - 2.15.

3.3 Conducted Emissions


3.3.1 Limit of Conducted Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.3.2 Test Procedures







1. Lowest, middle and highest operating channels are tested for this item.
2. Scan frequency range is from 30MHz ~ 9GHz.
3. Set RBW = 1MHz, VBW = 3MHz, detector = RMS, sweep time = auto.
4. Record the max trace value and capture the test plot of each sub frequency band.




3.3.3 Test Setup









3.3.4 Test Result of Conducted Emissions




LTE Band 26, CB: 1.4MHz

Mode	LTE Band 26, CB: 1.4MHz, QPSK	Mode	LTE Band 26, CB: 1.4MHz, 16QAM
Channel	Low	Channel	Low
			
Channel	Middle	Channel	Middle
			
Channel	High	Channel	High
			







Mode	LTE Band 26, CB: 1.4MHz, 64QAM	Mode	---
Channel	Low	Channel	Low
		---	
Channel	Middle	Channel	Middle
		---	
Channel	High	Channel	High
		---	




LTE Band 26, CB: 3MHz

Mode	LTE Band 26, CB: 3MHz, QPSK	Mode	LTE Band 26, CB: 3MHz, 16QAM
Channel	Low	Channel	Low
			
Channel	Middle	Channel	Middle
			
Channel	High	Channel	High
			







Mode	LTE Band 26, CB: 3MHz, 64QAM	Mode	---
Channel	Low	Channel	Low
		---	
Channel	Middle	Channel	Middle
		---	
Channel	High	Channel	High
		---	




LTE Band 26, CB: 5MHz

Mode	LTE Band 26, CB: 5MHz, QPSK	Mode	LTE Band 26, CB: 5MHz, 16QAM
Channel	Low	Channel	Low
			
Channel	Middle	Channel	Middle
			
Channel	High	Channel	High
			







Mode	LTE Band 26, CB: 5MHz, 64QAM	Mode	---
Channel	Low	Channel	Low
		---	
Channel	Middle	Channel	Middle
		---	
Channel	High	Channel	High
		---	




LTE Band 26, CB: 10MHz

Mode	LTE Band 26, CB: 10MHz, QPSK	Mode	LTE Band 26, CB: 10MHz, 16QAM
Channel	Low	Channel	Low
			
Channel	Middle	Channel	Middle
			
Channel	High	Channel	High
			

Mode	LTE Band 26, CB: 10MHz, 64QAM	Mode	---
Channel	Low	Channel	Low
		---	
Channel	Middle	Channel	Middle
		---	
Channel	High	Channel	High
		---	

LTE Band 26, CB: 15MHz

Mode	LTE Band 26, CB: 15MHz, QPSK	Mode	LTE Band 26, CB: 15MHz, 16QAM
Channel	Low	Channel	Low
			
Channel	Middle	Channel	Middle
			
Channel	High	Channel	High
			

Mode	LTE Band 26, CB: 15MHz, 64QAM	Mode	---
Channel	Low	Channel	Low
		---	
Channel	Middle	Channel	Middle
		---	
Channel	High	Channel	High
		---	