

Initially Compliant EIRP Table (not considering FCC Part 15.247(b)(3)(i))

Antenna Model	Gain (dBi)	Amplifier Power Rating (dB)							Card Alone 17.5
		29.2	27	24	20	18	17	14	
HG2401U	1	30.2	28.0	25.0	21.0	19.0	18.0	15.0	
HG2402RD	2	31.2	29.0	26.0	22.0	20.0	19.0	16.0	
HG2403RD	3	32.2	30.0	27.0	23.0	21.0	20.0	17.0	
HG2403UR	3	32.2	30.0	27.0	23.0	21.0	20.0	17.0	
HG2404CU	3	32.2	30.0	27.0	23.0	21.0	20.0	17.0	
RE05E	5	34.2	32.0	29.0	25.0	23.0	22.0	19.0	
RE05U	5	34.2	32.0	29.0	25.0	23.0	22.0	19.0	22.5
HG2405	5	34.2	32.0	29.0	25.0	23.0	22.0	19.0	
HG2406U	6	35.2	33.0	30.0	26.0	24.0	23.0	20.0	
HG2407U	7	36.2	34.0	31.0	27.0	25.0	24.0	21.0	
HG2408U	8	37.2	35.0	32.0	28.0	26.0	25.0	22.0	
HG2409U	8.5	37.7	35.5	32.5	28.5	26.5	25.5	22.5	
HGV-2409U	8.5	37.7	35.5	32.5	28.5	26.5	25.5	22.5	
HG2410U	10	39.2	37.0	34.0	30.0	28.0	27.0	24.0	
HG2412U	12	41.2	39.0	36.0	32.0	30.0	29.0	26.0	
HG2415U-PRO	15	44.2	42.0	39.0	35.0	33.0	32.0	29.0	
HG2409P	8	37.2	35.0	32.0	28.0	26.0	25.0	22.0	
HG2408P	8	37.2	35.0	32.0	28.0	26.0	25.0	22.0	
HG2412P	12	41.2	39.0	36.0	32.0	30.0	29.0	26.0	
HG2414P	14	43.2	41.0	38.0	34.0	32.0	31.0	28.0	
HG2416P	16	45.2	43.0	40.0	36.0	34.0	33.0	30.0	
HG2409Y	9	38.2	36.0	33.0	29.0	27.0	26.0	23.0	
HG2412Y	12	41.2	39.0	36.0	32.0	30.0	29.0	26.0	
HG2415Y	14.5	43.7	41.5	38.5	34.5	32.5	31.5	28.5	

Configurations in RED have an EIRP > 36 dBm

NOTE: This table does not necessarily indicate compliant configurations, as FCC 15.247(b)(3)(i) has not yet been considered. Please see the Approved Configurations exhibit for a complete listing of FCC/IC compliant configurations and the channels in which they may operate.

Maximum Permissible Amplifier Power Rating Table per FCC Part 15.247(b)(3)(i)

Antenna Model	Gain (dBi)	Amplifier Power Rating (dB)							Card Alone 17.5
		29.2	27	24	20	18	17	14	
HG2401U	1	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2402RD	2	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2403RD	3	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2403UR	3	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2404CU	3	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
RE05E	5	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
RE05U	5	29.2	27.0	24.0	20.0	18.0	17.0	14.0	17.5
HG2405	5	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2406U	6	29.2	27.0	24.0	20.0	18.0	17.0	14.0	
HG2407U	7	29.1	27.0	24.0	20.0	18.0	17.0	14.0	
HG2408U	8	28.8	27.0	24.0	20.0	18.0	17.0	14.0	
HG2409U	8.5	28.6	27.0	24.0	20.0	18.0	17.0	14.0	
HGV-2409U	8.5	28.6	27.0	24.0	20.0	18.0	17.0	14.0	
HG2410U	10	28.1	26.7	24.0	20.0	18.0	17.0	14.0	
HG2412U	12	27.5	26.0	24.0	20.0	18.0	17.0	14.0	
HG2415U-PRO	15	26.5	25.0	23.0	20.0	18.0	17.0	14.0	
HG2409P	8	28.8	27.0	24.0	20.0	18.0	17.0	14.0	
HG2408P	8	28.8	27.0	24.0	20.0	18.0	17.0	14.0	
HG2412P	12	27.5	26.0	24.0	20.0	18.0	17.0	14.0	
HG2414P	14	26.8	25.3	23.3	20.0	18.0	17.0	14.0	
HG2416P	16	26.1	24.7	22.7	20.0	18.0	17.0	14.0	
HG2409Y	9	28.5	27.0	24.0	20.0	18.0	17.0	14.0	
HG2412Y	12	27.5	26.0	24.0	20.0	18.0	17.0	14.0	
HG2415Y	14.5	26.6	25.2	23.2	20.0	18.0	17.0	14.0	

Configurations in RED must have Amplifier Power Reduced to the values indicated

NOTE: This table does not necessarily indicate compliant configurations, as FCC 15.247(b)(3)(i) has not yet been considered. Please see the Approved Configurations exhibit for a complete listing of FCC/IC compliant configurations and the channels in which they may operate.