Hyperlink Extended Range WLAN Kit Installation Manual Rev. B Page 5

Caution: Exposure to Radio Frequency Radiation.

The radiated output power of this product is below the FCC radio exposure limits. Nevertheless, this product shall be used in such a manner that the potential for human contact during normal operation is minimized.

Antenna shall be mounted in such a manner as to minimize the potential for human contact during normal operation. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antenna shall not be less than 20 cm (8 inches) during normal operation.

Hyperlink Technologies is not responsible for any radio or television interference caused by unauthorized modification of this device or the substitution or attachment of connecting cables and equipment other than specified by Hyperlink Technologies. The correction of interference caused by such unauthorized modification, substitution or attachment will be the responsibility of the user.

Antenna	Specified	Maximum Output	Total EIRP	Minimum RF
Type	Antenna Gain	Power at Antenna	(dBm)	Exposure
	(dBi)	Terminal (dBm)		Separation
				Distance (cm)
HG2403MU	3.0	24	27.0	6.5
HG2405MU	5.0	24	29.0	8.0
HG2408P	7.5	24	31.5	10.6
HG2408U	8.0	24	32.0	11.2
HG2412P	12.0	20	32.2	11.5
HG2415Y	14.5	20	34.7	15.3
HG2415U	15.0	20	35.2	16.2
HG2415G	15.0	20	35.2	16.2
HG2419G	19.0	17	36.0	17.8
HG2424G	23.5	11	35.1	16.0

WARNING: It is the responsibility of the professional installer to ensure that when using the outdoor antenna kits in the United States (or where the FCC rules apply), only these antenna configurations shown in the table above and which are described in this document are used. The use of any other than those listed is expressly forbidden in accordance to FCC rules CFR47 part 15.204.