# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## 1.1 Standard Applicable

According to § 1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

## (a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times $ E ^2$ , $ H ^2$ or S (minutes) |
|-----------------------|---|---|---|--|
| 0.3-3.0               | 614                                     | 1.63                                    | (100)*                                  | 6  |
| 3.0-30                | 1842/f                                  | 4.89/f                                  | (900/f)*                                | 6  |
| 30-300                | 61.4                                    | 0.163                                   | 1.0                                     | 6  |
| 300-1500              | /                                       | /                                       | F/300                                   | 6  |
| 1500-100000           | /                                       | /                                       | 5                                       | 6  |

## (b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times $ E ^2$ , $ H ^2$ or $S$ (minutes) |
|-----------------------|---|---|---|--|
| 0.3-1.34              | 614                                     | 1.63                                    | (100)*                                  | 30   |
| 1.34-30               | 824/f                                   | 2.19/f                                  | (180/f)*                                | 30   |
| 30-300                | 27.5                                    | 0.073                                   | 0.2                                     | 30   |
| 300-1500              | /                                       | /                                       | F/1500                                  | 30   |
| 1500-100000           | /                                       | /                                       | 1                                       | 30   |

Note: f = frequency in MHz: \* = Plane-wave equivalents power density

### 1.2 MPE Calculation Method

 $S = (30*P*G) / (377*R^2)$ 

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.3 MPE Calculation Result

Since the maximum eirp power is used as the output power to antenna, so the Gain of the antenna can be assumed as -3dBi.

Maximum peak output power: 16.88 (dBm)

Maximum peak output power at antenna input terminal: 48.75 (mW)

Prediction distance: >10 (cm)
Prediction frequency: 2412 (MHz)
Antenna gain (typical): -3 (dBi)
Antenna gain (typical): 0.5 (numeric)

The worst case is power density at prediction frequency at 10cm: <u>0.0194 (mw/cm<sup>2</sup>)</u> MPE limit for general population exposure at prediction frequency: <u>1 (mw/cm<sup>2</sup>)</u>

0.0194 (mw/cm2) < 1 (mw/cm2)

Result: Pass