## TABLE OF CONTENTS LIST

APPLICANT: WILD PLANET TOYS INC.

FCC ID: N3E11311WRISTTALK

## TEST REPORT CONTAINING:

PAGE	1-3TES	EQUIPMEN'	r LIST		
PAGE	4TES	r PROCEDURI	Ξ		
PAGE	5	TATION INT	ERFERENCE	TEST	DATA

### EXHIBITS CONTAINING:

EXHIBIT	1BLOCK DIAGRAM
EXHIBIT	2SCHEMATIC
EXHIBIT	3 INSTRUCTION MANUAL
EXHIBIT	4SAMPLE OF FCC ID LABEL
EXHIBIT	5LOCATION OF FCC ID LABEL
EXHIBIT	6EXTERNAL PHOTOGRAPHS
EXHIBIT	7INTERNAL PHOTOGRAPHS
EXHIBIT	8CIRCUIT DESCRIPTION
EXHIBIT	9TEST SET UP PHOTO

APPLICANT: WILD PLANET TOYS INC. FCC ID: N3E11311WRISTTALK

REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

TABLE OF CONTENTS

# **EMC Equipment List**

Ī	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	3-Meter OATS	TEI	N/A	N/A	Listed 12/22/99	12/22/02
	3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
	Receiver, Beige Tower Spectrum Analyzer (Tan)	НР	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03
	RF Preselector (Tan)	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
	Quasi-Peak Adapter (Tan)	НР	85650A	3303A01690	CAL 8/31/01	8/31/03
X X	Receiver, Blue Tower Spectrum Analyzer (Blue)	НР	8568B	2928A04729 2848A18049	CHAR 10/22/01	10/22/03
X	RF Preselector (Blue)	НР	85685A	2926A00983	CHAR 10/22/01	10/22/03
X	Quasi-Peak Adapter (Blue)	НР	85650A	2811A01279	CHAR 10/22/01	10/22/03
X	Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
	Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
	Biconnical Antenna	Eaton	94455-1	1057	CHAR 3/15/00	3/15/02
	BiconiLog Antenna	EMCO	3143	9409-1043		
X	Log-Periodic Antenna	Electro-Metrics	LPA-25	1122	CAL 10/2/01	10/2/03
	Log-Periodic Antenna	Electro-Metrics	EM-6950	632	CHAR 10/15/01	10/15/03
	Log-Periodic Antenna	Electro-Metrics	LPA-30	409	CHAR 10/16/01	10/16/03
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/21/01	3/21/04
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 11/24/00	11/24/03
	Double-Ridged Horn Antenna	Electro-Metrics	RGA-180	2319	CAL 12/19/01	12/19/03
	Horn Antenna	Electro-Metrics	EM-6961	6246	CAL 3/21/01	3/21/03
	Horn Antenna	ATM	19-443-6R	None	No Cal Required	
П	Passive Loop Antenna	EMC Test Systems	EMCO 6512	9706-1211	CHAR 7/10/01	7/10/03
	Line Impedance Stabilization	Electro-Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03

APPLICANT: WILD PLANET TOYS INC. FCC ID: N3E11311WRISTTALK

REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

Page 1 of 5

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
	Line Impedance Stabilization	Electro-Metrics	EM-7820	2682	CAL 3/16/01	3/16/03
	Termaline Wattmeter	Bird Electronic Corporation	611	16405	CAL 5/25/99	5/25/01
	Termaline Wattmeter	Bird Electronic Corporation	6104	1926	CAL 12/12/01	12/12/03
	Oscilloscope	Tektronix	2230	300572	CHAR 2/1/01	2/1/03
	Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 1/22/02	1/22/04
	AC Voltmeter	НР	400FL	2213A14499	CAL 10/9/01	10/9/03
	AC Voltmeter	НР	400FL	2213A14261	CHAR 10/15/01	10/15/03
	AC Voltmeter	НР	400FL	2213A14728	CHAR 10/15/01	10/15/03
X	Digital Multimeter	Fluke	77	35053830	CHAR 1/8/02	1/8/04
	Digital Multimeter	Fluke	77	43850817	CHAR 1/8/02	1/8/04
	Digital Multimeter	НР	E2377A	2927J05849	CHAR 1/8/02	1/8/04
	Multimeter	Fluke	FLUKE-77-3	79510405	CAL 9/26/01	9/26/03
	Peak Power Meter	НР	8900C	2131A00545	CHAR 1/26/01	1/26/03
	Digital Thermometer	Fluke	2166A	42032	CAL 1/16/02	1/16/04
	Thermometer	Traulsen	SK-128		CHAR 1/22/02	1/22/04
X	Temp/Humidity gauge	EXTech	44577F	E000901	CHAR 1/22/02	1/22/04
	Frequency Counter	НР	5352B	2632A00165	CAL 11/28/01	11/28/03
	Power Sensor	Agilent Technologies	84811A	2551A02705	CAL 1/26/01	1/26/03
Щ	Service Monitor	IFR	FM/AM 500A	5182	CAL 11/22/00	11/22/02
	Comm. Serv. Monitor	IFR	FM/AM 1200S	6593	CAL 5/12/02	5/12/04
Щ	Signal Generator	НР	8640B	2308A21464	CAL 11/15/01	11/15/03
	Modulation Analyzer	НР	8901A	3435A06868	CAL 9/5/01	9/5/03
$\Box$	Near Field Probe	НР	HP11940A	2650A02748	CHAR 2/1/01	2/1/03
	BandReject Filter	Lorch Microwave	5BR4-2400/ 60-N	Z1	CHAR 3/2/01	3/2/03

APPLICANT: WILD PLANET TOYS INC.

FCC ID: N3E11311WRISTTALK
REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

Page 2 of 5

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
BandReject Filter	Lorch Microwave	6BR6-2442/ 300-N	Z1	CHAR 3/2/01	3/2/03
BandReject Filter	Lorch Microwave	5BR4-10525/ 900-S	Z1	CHAR 3/2/01	3/2/03
High Pas Filter	Microlab	HA-10N		CHAR 10/4/01	10/4/03
Audio Oscillator	НР	653A	832-00260	CHAR 3/1/01	3/1/03
Frequency Counter	НР	5382A	1620A03535	CHAR 3/2/01	3/2/03
Frequency Counter	НР	5385A	3242A07460	CHAR 12/11/01	12/11/03
Preamplifier	НР	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
Amplifier	НР	11975A	2738A01969	CHAR 3/1/01	3/1/03
Egg Timer	Unk			CHAR 8/31/01	8/31/03
Measuring Tape, 20M	Kraftixx	0631-20		CHAR 2/1/02	2/1/04
Measuring Tape, 7.5M	Kraftixx	7.5M PROFI		2/1/02	2/1/04
Coaxial Cable #51	Insulated Wire Inc.	NPS 2251-2880	Timco #51	CHAR 1/23/02	1/23/04
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 1/24/02	1/24/04
Coaxial Cable #65	General Cable Co.	E9917 RG233/U	Timco #65	CHAR 1/23/02	1/23/04
Coaxial Cable #106	Unknown	Unknown	Timco #106	CHAR 1/23/02	1/23/04

APPLICANT: WILD PLANET TOYS INC.

FCC ID: N3E11311WRISTTALK
REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

Page 3 of 5

### TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHZ with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHZ and the video bandwidth was 300KHZ. The ambient temperature of the UUT was 80°F with a humidity of 70%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

### Example:

Freq (MHz) METER READING + ACF = FS 33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.4-1992 12.1.1.1 SUPERREGENERATIVE RECEIVER: A signal Generator was set to the unit under test operating frequency. An un-Modulated continuous wave (CW) signal was radiated at the superregenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

APPLICANT: WILD PLANET TOYS INC. FCC ID: N3E11311WRISTTALK

REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

Page 4 of 5

APPLICANT: WILD PLANET TOYS INC.

FCC ID: N3E11311WRISTTALK

NAME OF TEST: RADIATION INTERFERENCE

**RULES PART NO.:** 15.109

REQUIREMENTS:

30 to 88 MHz: 40.0 dBuV/M @ 3 METERS 88 to 216 MHz: 43.5 dBuV/M 216 to 960 MHz: 46.0 dBuV/M ABOVE 960 MHz: 54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000MHz and the measurements indicate that the unit DOES meet the FCC requirements.

### TEST DATA:

Tuned	Emission	Meter	ANT.	Coax		Field	
Frequency MHz	Frequency MHz	Reading dBuV	POLARITY	Loss dB	Correction Factor dB	Strength dBuV/m	Margin dB
49.9	48.03	8.4	н	0.60	10.92	19.92	20.08
49.9	48.13	8.7	H	0.61	10.93	20.24	19.76
49.9	48.24	9.0	H	0.62	10.93	20.55	19.45
49.9	48.43	8.8	H	0.64	10.94	20.38	19.62
49.9	48.52	8.4	H	0.65	10.94	19.99	20.01
49.9	49.60	9.0	H	0.76	10.98	20.74	19.26

**SAMPLE CALCULATION:** FSdBuV/m = MR (dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: JOSEPH SCOGLIO **DATE:** MARCH 28, 2003

> APPLICANT: WILD PLANET TOYS INC. FCC ID: N3E11311WRISTTALK

REPORT #: W/WILD\_N3E/411BUT3/411BUT3TestReport.doc

Page 5 of 5