

***Electromagnetic Emissions Test Report
and
Application for Grant of Equipment Authorization
pursuant to
FCC Part 15, Subpart C Specifications for an
Intentional Radiator on the
Wild Planet Toys
Model: Spy Tracker***


FCC ID: N3ESPYTRACKR70044

GRANTEE: Wild Planet Toys
98 Battery St., Suite 300
San Francisco, CA 94111

TEST SITE: Elliott Laboratories, Inc.
684 W. Maude Avenue
Sunnyvale, CA 94086

REPORT DATE: June 14, 2002

FINAL TEST DATE: June 3, 2002

AUTHORIZED SIGNATORY: 
Juan Martinez
Sr. EMC Engineer

This report shall not be reproduced, except in its entirety, without the written approval of Elliott Laboratories, Inc.

TABLE OF CONTENTS

COVER PAGE.....	1
TABLE OF CONTENTS.....	2
SCOPE.....	3
OBJECTIVE.....	3
STATEMENT OF COMPLIANCE.....	3
EMISSION TEST RESULTS	4
LIMITS OF CONDUCTED INTERFERENCE VOLTAGE.....	4
LIMITS OF RADIATED INTERFERENCE FIELD STRENGTH.....	4
MEASUREMENT UNCERTAINTIES.....	5
EQUIPMENT UNDER TEST (EUT) DETAILS	6
GENERAL.....	6
ENCLOSURE.....	6
MODIFICATIONS.....	6
SUPPORT EQUIPMENT.....	6
EXTERNAL I/O CABLING.....	6
TEST SOFTWARE	6
TEST SITE.....	7
GENERAL INFORMATION.....	7
RADIATED EMISSIONS CONSIDERATIONS.....	7
MEASUREMENT INSTRUMENTATION.....	8
RECEIVER SYSTEM.....	8
INSTRUMENT CONTROL COMPUTER	8
LINE IMPEDANCE STABILIZATION NETWORK (LISN)	8
POWER METER.....	9
FILTERS/ATTENUATORS	9
ANTENNAS.....	9
ANTENNA MAST AND EQUIPMENT TURNTABLE	9
INSTRUMENT CALIBRATION.....	9
TEST PROCEDURES	10
EUT AND CABLE PLACEMENT.....	10
RADIATED EMISSIONS.....	10
SPECIFICATION LIMITS AND SAMPLE CALCULATIONS	11
RADIATED EMISSIONS SPECIFICATION LIMITS, SECTION 15.209.....	11
SAMPLE CALCULATIONS - RADIATED EMISSIONS.....	12
EXHIBIT 1: Test Equipment Calibration Data.....	1
EXHIBIT 2: Test Data Log Sheets	2

SCOPE

An electromagnetic emissions test has been performed on the Wild Planet Toys model SPY TRACKER pursuant to Subpart C of Part 15 of FCC Rules for intentional radiators. Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in ANSI C63.4-1992 as outlined in Elliott Laboratories test procedures.

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant FCC performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

The test results recorded herein are based on a single type test of the Wild Planet Toys model SPY TRACKER and therefore apply only to the tested sample. The sample was selected and prepared by Don Marini of Wild Planet Toys

OBJECTIVE

The primary objective of the manufacturer is compliance with Subpart C of Part 15 of FCC Rules for the radiated and conducted emissions of intentional radiators. Certification of these devices is required as a prerequisite to marketing as defined in Part 2 the FCC Rules.

Certification is a procedure where the manufacturer or a contracted laboratory makes measurements and submits the test data and technical information to the FCC. The FCC issues a grant of equipment authorization upon successful completion of their review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

STATEMENT OF COMPLIANCE

The tested sample of Wild Planet Toys model SPY TRACKER complied with the requirements of Subpart C of Part 15 of the FCC Rules for low power intentional radiators.

Maintenance of FCC compliance is the responsibility of the manufacturer. Any modification of the product, which may result in increased emissions, should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

EMISSION TEST RESULTS

The following emissions tests were performed on the Wild Planet Toys model SPY TRACKER. The actual test results are contained in an exhibit of this report.

LIMITS OF CONDUCTED INTERFERENCE VOLTAGE

The EUT was not tested to the limits detailed in FCC Rules Part 15 Section 15.207, as the unit is battery operated.

LIMITS OF RADIATED INTERFERENCE FIELD STRENGTH

The EUT tested complied with the limits detailed in FCC Rules Part 15 Section 15.235 and 15.209 in the case of emissions falling within the frequency bands specified in Section 15.205.

The following measurement was extracted from the data recorded during the radiated electric field emissions scan and represents the highest amplitude emission relative to the specification limit. The actual test data and any correction factors are contained in an exhibit of this report.

Fundamental

Frequency MHz	Level dBuV/m	Pol v/h	FCC 15.235 Limit Margin		Detector Pk/QP/Avg	Azimuth degrees	Height meters	Comments
49.860	77.2	v	80.0	-2.8	Pk	305	1.0	Peak Reading, Average Limit

Harmonics

Frequency MHz	Level dBuV/m	Pol v/h	FCC 15.235 Limit Margin		Detector Pk/QP/Avg	Azimuth degrees	Height meters	Comments
99.720	40.0	h	43.5	-3.5	Pk	310	1.0	

MEASUREMENT UNCERTAINTIES

ISO Guide 25 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with NAMAS document NIS 81.

Measurement Type	Frequency Range (MHz)	Calculated Uncertainty (dB)
Conducted Emissions	0.15 to 30	± 2.4
Radiated Emissions	30 to 1000	± 3.2

EQUIPMENT UNDER TEST (EUT) DETAILS**GENERAL**

The Wild Planet Toys model SPY TRACKER is a field sensor transmitter, which is activated when tripped by any motion. The EUT operates from a dc voltage of 3V supplied by internal batteries

The sample was received on May 31, 2002 and tested on May 31 and June 3, 2002. The EUT consisted of the following component(s):

Manufacturer/Model/Description	Serial Number
Wild Planet Toys/SPY TRACKER/Field Sensor	-

ENCLOSURE

The EUT enclosure is primarily constructed of non-conductive polycarbonate plastic. It measures approximately 4 cm deep by 4 cm wide at the widest point by 2 cm high.

MODIFICATIONS

The EUT did not require modifications during testing in order to comply with the emission specifications.

SUPPORT EQUIPMENT

No support equipment was used during emissions testing.

EXTERNAL I/O CABLING

The I/O cabling configuration during emissions testing was as follows:

Cable Description	Length (m)	From Unit/Port	To Unit/Port
None	-	-	-

TEST SOFTWARE

The EUT was set to continuously transmit during testing.

TEST SITE**GENERAL INFORMATION**

Final test measurements were taken on June 3, 2002 at the Elliott Laboratories Open Area Test Site #3 located at 684 West Maude Avenue, Sunnyvale, California. The test site contains separate areas for radiated and conducted emissions testing. Pursuant to section 2.948 of the Rules, construction, calibration, and equipment data has been filed with the Commission.

The FCC recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement with the exception of predictable local TV, radio, and mobile communications traffic. The test site contains separate areas for radiated and conducted emissions testing. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent FCC requirements.

RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment. The test site is maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4 guidelines.

MEASUREMENT INSTRUMENTATION**RECEIVER SYSTEM**

An EMI receiver as specified in CISPR 16-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz.

INSTRUMENT CONTROL COMPUTER

The receivers utilize either a Rohde & Schwarz EZM Spectrum Monitor/Controller or contain an internal Spectrum Monitor/Controller to view and convert the receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers.

The Spectrum Monitor provides a visual display of the signal being measured. In addition, the controller or a personal computer run automated data collection programs which control the receivers. This provides added accuracy since all site correction factors, such as cable loss and antenna factors are added automatically.

LINE IMPEDANCE STABILIZATION NETWORK (LISN)

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

POWER METER

A power meter and thermister mount are used for all direct output power measurements from transmitters as they provide a broadband indication of the power output.

FILTERS/ATTENUATORS

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

ANTENNAS

A biconical antenna is used to cover the range from 30 MHz to 300 MHz and a log periodic antenna is utilized from 300 MHz to 1000 MHz. Narrowband tuned dipole antennas are used over the entire 30 to 1000 MHz ranges for precision measurements of field strength. Above 1000 MHz, a horn antenna is used. The antenna calibration factors are included in site factors programmed into the test receivers.

ANTENNA MAST AND EQUIPMENT TURNTABLE

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor drive to vary the antenna height.

ANSI C63.4 specifies that the test height above ground for table-mounted devices shall be 80 centimeters. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

INSTRUMENT CALIBRATION

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

TEST PROCEDURES**EUT AND CABLE PLACEMENT**

The FCC requires that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.4, and the worst-case orientation is used for final measurements.

RADIATED EMISSIONS

Radiated emissions measurements are performed in two phases as well. A preliminary scan of emissions is conducted in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed from 30 MHz up to the frequency required by the regulation specified on page 1. One or more of these is with the antenna polarized vertically while the one or more of these is with the antenna polarized horizontally. During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied and cable positions are varied to determine the highest emission relative to the limit.

A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.

Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth, which results in the highest emission, is then maintained while varying the antenna height from one to four meters. The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain. Emissions, which have values close to the specification limit, may also be measured with a tuned dipole antenna to determine compliance.

SPECIFICATION LIMITS AND SAMPLE CALCULATIONS

The limits for conducted emissions are given in units of microvolts, and the limits for radiated emissions are given in units of microvolts per meter at a specified test distance. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

For reference, converting the specification limits from linear to decibel form is accomplished by taking the base ten logarithms, then multiplying by 20. These limits in both linear and logarithmic form are as follows:

RADIATED EMISSIONS SPECIFICATION LIMITS, SECTION 15.209

Frequency Range (MHz)	Limit (uV/m @ 3m)	Limit (dBuV/m @ 3m)
0.009-0.490	$2400/F_{\text{KHz}} @ 300\text{m}$	$67.6-20*\log_{10}(F_{\text{KHz}}) @ 300\text{m}$
0.490-1.705	$24000/F_{\text{KHz}} @ 30\text{m}$	$87.6-20*\log_{10}(F_{\text{KHz}}) @ 30\text{m}$
1.705 to 30	30 @ 30m	29.5 @ 30m
30 to 88	100	40
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

SAMPLE CALCULATIONS - RADIATED EMISSIONS

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements. A distance factor, when used for electric field measurements, is calculated by using the following formula:

$$F_d = 20 * \text{LOG}_{10} (D_m/D_s)$$

where:

$$F_d = \text{Distance Factor in dB}$$

$$D_m = \text{Measurement Distance in meters}$$

$$D_s = \text{Specification Distance in meters}$$

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_c - L_s$$

where:

$$R_r = \text{Receiver Reading in dBuV/m}$$

$$F_d = \text{Distance Factor in dB}$$

$$R_c = \text{Corrected Reading in dBuV/m}$$

$$L_s = \text{Specification Limit in dBuV/m}$$

$$M = \text{Margin in dB Relative to Spec}$$

EXHIBIT 1: Test Equipment Calibration Data

Radiated Emissions, 49.86 - 498.6 MHz, 04-Jun-02

Engineer: Rafael

<u>Manufacturer</u>	<u>Description</u>	<u>Model #</u>	<u>Assett #</u>	<u>Cal interval</u>	<u>Last Calibrated</u>	<u>Cal Due</u>
EMCO	Biconical Antenna, 30-300 MHz	3110B	801	12	5/13/2002	5/13/2003
EMCO	Log Periodic Antenna, 0.3-1 GHz	3146A	364	12	8/28/2001	8/28/2002
Rohde & Schwarz	Test Receiver, 0.009-2000 MHz	ESN	1332	12	4/16/2002	4/16/2003

EXHIBIT 2: Test Data Log Sheets

ELECTROMAGNETIC EMISSIONS

TEST LOG SHEETS

AND

MEASUREMENT DATA

T47416 5 Pages



EMC Test Data

Client:	Wild Planet Toys Inc.	Job Number:	J47339
Model:	Spy Tracker Transmitter	T-Log Number:	T47416
		Proj Eng:	David Bare
Contact:	Don Marini		
Emissions Spec:	15.235	Class:	-
Immunity Spec:	-	Environment:	-

EMC Test Data

For The

Wild Planet Toys Inc.

Model

Spy Tracker Transmitter



EMC Test Data

Client:	Wild Planet Toys Inc.	Job Number:	J47339
Model:	Spy Tracker Transmitter	T-Log Number:	T47416
		Proj Eng:	David Bare
Contact:	Don Marini		
Emissions Spec:	15.235	Class:	-
Immunity Spec:	-	Environment:	-

EUT INFORMATION

General Description

The EUT is a transmitter which is designed to transmit the encoded signal to a receiver which displays when the transmitter is activated. Normally, the EUT would be placed on a table top during operation. The EUT was, therefore, treated as table-top equipment during testing to simulate the end user environment. The electrical rating of the EUT is 3vdc.

Equipment Under Test

Manufacturer	Model	Description	Serial Number	FCC ID
Wild Planet Toys Inc.	Spy Tracker	Transmitter	-	-

Other EUT Details

EUT Enclosure

The EUT enclosure is primarily constructed of fabricated plastic. It measures approximately 4 cm wide by 4 cm deep by 2 cm high.

Modification History

Mod. #	Test	Date	Modification
1	-	-	None



EMC Test Data

Client:	Wild Planet Toys Inc.	Job Number:	J47339
Model:	Spy Tracker Transmitter	T-Log Number:	T47416
		Proj Eng:	David Bare
Contact:	Don Marini		
Emissions Spec:	15.235	Class:	-
Immunity Spec:	-	Environment:	-

Test Configuration #1

Local Support Equipment

Manufacturer	Model	Description	Serial Number	FCC ID
None				

Remote Support Equipment

Manufacturer	Model	Description	Serial Number	FCC ID
None				

Interface Ports

Port	Connected To	Cable(s)		
		Description	Shielded or Unshielded	Length(m)
None				

EUT Operation During Emissions

The EUT was transmitting continuously during testing.



EMC Test Data

Client: Wild Planet Toys Inc.	Job Number: J47339
Model: Spy Tracker Transmitter	T-Log Number: T47416
	Proj Eng: David Bare
Contact: Don Marini	
Spec: 15.235	Class: -

Radiated Emissions

Test Specifics

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 6/3/2002

Test Engineer: Rafael

Test Location: SVOATS #2

Config. Used: 1

Config Change: None

EUT Voltage: 3Vdc

General Test Configuration

The EUT was located on the turntable for radiated emissions testing.

On the OATS, the measurement antenna was located 3 meters from the EUT for the measurement range 30 - 1000 MHz.

Ambient Conditions:

Temperature: 14°C

Rel. Humidity: 72%

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1	RE, Fundamental Frequency, 49.86 MHz	15.235	Pass	-2.8dB @ 49.86MHz
2	RE, Maximized Emissions, 49.86 - 498.6 MHz	15.235	Pass	-3.5dB @ 99.72MHz

Modifications Made During Testing:

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client: Wild Planet Toys Inc.	Job Number: J47339
Model: Spy Tracker Transmitter	T-Log Number: T47416
Contact: Don Marini	Proj Eng: David Bare
Spec: 15.235	Class: -

Run #1: Fundamental Frequency, 49.86 MHz

EUT upright

Frequency	Level	Pol	15.235		Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
49.860	77.2	v	80.0	-2.8	Pk	305	1.0	Peak Reading, Average Limit
49.860	61.5	h	80.0	-18.5	Pk	40	3.4	Peak Reading, Average Limit

Run #2: Maximized Radiated Emissions, 49.86-498.6 MHz


EUT upright

Frequency	Level	Pol	FCC 15.235/15.209		Detector	Azimuth	Height	Comments
MHz	dBμV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
99.720	40.0	h	43.5	-3.5	Pk	310	1.0	
448.760	39.8	v	46.0	-6.2	Pk	315	1.1	
299.174	38.7	v	46.0	-7.3	Pk	160	2.1	
349.037	38.2	v	46.0	-7.8	Pk	130	1.4	
398.897	35.5	v	46.0	-10.5	Pk	225	1.3	
149.586	30.9	v	43.5	-12.6	Pk	280	1.0	
498.620	32.1	v	46.0	-13.9	Pk	120	1.0	
99.720	28.5	v	43.5	-15.0	Avg	300	1.0	Duty cycle applied to emission (Note 1)
299.174	30.4	h	46.0	-15.6	Pk	200	1.0	
448.760	29.1	h	46.0	-16.9	Pk	20	1.0	
149.586	25.1	h	43.5	-18.4	Pk	200	2.0	
349.037	25.9	h	46.0	-20.1	Pk	345	1.0	
398.897	25.6	h	46.0	-20.4	Pk	140	1.0	
249.312	22.7	v	46.0	-23.3	Pk	150	2.0	
249.312	22.2	h	46.0	-23.8	Pk	265	1.3	
498.620	19.8	h	46.0	-26.2	Pk	240	2.5	

Note 1: DutAll average measurements calculated from the peak measurement. Avergae correction factor of -20dB was used based on a maximum "on-time" of less than 1.63 mS in any 100mS period cycle correction applied to PK measurement to get average reading. Duty Cycle applied was -20 dB.




◇ Mkr : 49.8623 MHz 71.8 dB



C1: MaxHold
C2: Blank

tek Stopped: Single Seq



tek Stopped: Single Seq

