RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
11111	(A) Limits	for Occupational/Controlled	Exposures	1111
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	1111	111111	f/300	6
1500–100,000	1 1 1 1 1	1111111	5	6
11111	(B) Limits for	General Population/Uncontro	lled Exposure	1111
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	6 1 1 3 1	1 1 3 1 4 1 3	f/1500	30
1500–100,000	5 5 5 8 8 8	1 1 8 1 1 1 1 1	1.0	30

f = frequency in MHz

Friis transmission formula: Pd = (Pout*G)/(4*pi*r²)

Where

 $Pd = power density in mW/cm^2$, **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, Pi = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
Lowest	22.23	0.0056	1.0	PASS
Middle	22.59	0.0057	1.0	PASS
Highest	24.04	0.0060	1.0	PASS

Remark: antenna gain=1dBi