

FCC Report

Applicant: FLYSKY RC MODEL TECHNOLOGY CO., LTD
Address of Applicant: West building3, Huangjianyuan Ind, Park QIAOLI North Gate Changping Town, Dongguan, China
Manufacturer: ShenZhen FLYSKY Technology Co.,Ltd
Address of Manufacturer: ADD 16F, Huafeng Building, No. 6006 Shennan Road, Futian District, Shenzhen, Guangdong, China
Factory: Dongguan Flysky RC Model technology Co.,Ltd
Address of Factory: West building3, Huangjianyuan Ind, Park QIAOLI North Gate Changping Town, China

Equipment Under Test (EUT)

Product Name: 16 Channel Receiver
Model No.: FTr16S
Trade Mark: FLYSKY

FCC ID: N4ZFTR16S00
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt: June 13, 2019
Date of Test: June 14-24, 2019
Date of report issued: June 24, 2019
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	June 24, 2019	Original

Prepared By: Bill. Yuan **Date:** June 24, 2019
Project Engineer

Check By: Robinson **Date:** June 24, 2019
Reviewer

3 Contents

Page

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
4.1	MEASUREMENT UNCERTAINTY	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE	7
5.3	TEST FACILITY	7
5.4	TEST LOCATION	7
5.5	OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
5.6	DESCRIPTION OF SUPPORT UNITS	7
5.7	ADDITIONAL INSTRUCTIONS.....	7
6	TEST INSTRUMENTS LIST	8
7	TEST RESULTS AND MEASUREMENT DATA	10
7.1	ANTENNA REQUIREMENT.....	10
7.2	CONDUCTED PEAK OUTPUT POWER.....	11
7.3	20dB EMISSION BANDWIDTH	13
7.4	CARRIER FREQUENCIES SEPARATION.....	15
7.5	HOPPING CHANNEL NUMBER	17
7.6	DWELL TIME	18
7.7	PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	26
7.8	BAND EDGE	27
7.8.1	Conducted Emission Method	27
7.8.2	Radiated Emission Method	30
7.9	SPURIOUS EMISSION	35
7.9.1	Conducted Emission Method	35
7.9.2	Radiated Emission Method	37
8	TEST SETUP PHOTO	48
9	EUT CONSTRUCTIONAL DETAILS.....	48

4 Test Summary

Test Item	Section	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	N/A
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(iii)	Pass
Dwell Time	15.247 (a)(iii)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(a)(1)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d) 15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.10:2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	16 Channel Receiver
Model No.:	FTr16S
Serial No.:	N/A
Hardware Version:	FTr16S-V1.3A
Software Version:	FTr16S V1.0.2
Test sample(s) ID:	GTS201902000062-1
Sample(s) Status	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	63
Modulation technology:	GMSK
Antenna Type:	Integral Antenna
Antenna gain:	ANT 1/ANT 2: 2.0dBi(Max)
Power supply:	DC 3.5-8.4V

Remark: The system works in the frequency range of 2402MHz to 2480MHz. This band has been divided to 63 independent channels. radio system uses 32 different channels; the minimum channel separation is ≥ 1.5 MHz. By using various switch-on times, hopping scheme and channel frequencies, the system can guarantee a jamming free radio transmission. The channel list is below.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	17	2422	33	2441	49	2462
2	2404	18	2423	34	2443	50	2463
3	2405	19	2424	35	2445	51	2464
4	2406	20	2425	36	2446	52	2466
5	2407	21	2427	37	2447	53	2467
6	2409	22	2428	38	2448	54	2468
7	2410	23	2429	39	2449	55	2469
8	2411	24	2430	40	2451	56	2471
9	2412	25	2432	41	2452	57	2472
10	2413	26	2433	42	2454	58	2473
11	2415	27	2434	43	2455	59	2474
12	2416	28	2435	44	2456	60	2475
13	2417	29	2437	45	2457	61	2477
14	2418	30	2438	46	2458	62	2478
15	2419	31	2439	47	2460	63	2480
16	2420	32	2440	48	2461		

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402.0MHz
The middle channel	2440.0MHz
The Highest channel	2480.0MHz

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode.
Remark: DC 3.5 to 8.4V all have been pretested, only worse case DC 8.4V is reported	

5.3 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. ● Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2. ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0
--

5.4 Test Location

All other tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

5.5 Other Information Requested by the Customer

None.

5.6 Description of Support Units

None.

5.7 Additional Instructions

EUT Software Settings:

Mode	Special test firmware was pre-built-in by manufacturer		
GFSK	Channel	Frequency (MHz)	Level Set
	Lowest	2402.0MHz	TX level: 10
	Middle	2440.0MHz	
	Highest	2480.0MHz	

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 27 2018	June. 26 2019

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
EUT Antenna:	
<i>Two antennas can transmit at the same time and the antenna is integral Antenna, the best case gain of the antenna is 2.0dBi, reference to the appendix II for details</i>	

7.2 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	20.97dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Antenna	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
ANT 1	Lowest	10.57	20.97	Pass
	Middle	10.29		Pass
	Highest	9.66		Pass
ANT 2	Lowest	10.68		Pass
	Middle	10.36		Pass
	Highest	9.74		Pass


Note: Highest PK output power = $10^{(10.57/10)} + 10^{(10.68/10)} = 11.402 + 11.695 = 23.097\text{mW}$
 $10 \times \log(23.097) = 13.64\text{dBm} < 20.97\text{dBm}$

Test plot as follows:



ANT 1





ANT 2



Lowest channel




Middle channel



Highest channel

7.3 20dB Emission Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Antenna	Test channel	20dB Emission Bandwidth (MHz)	Result
ANT 1	Lowest	0.365	Pass
	Middle	0.369	Pass
	Highest	0.363	Pass
ANT2	Lowest	0.365	Pass
	Middle	0.375	Pass
	Highest	0.364	Pass

Test plot as follows:



ANT 1





ANT 2



Lowest channel




Middle channel



Highest channel

7.4 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Antenna	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
ANT 1	Lowest	1360	369	Pass
	Middle	1355	369	Pass
	Highest	910	369	Pass
ANT 2	Lowest	1360	375	Pass
	Middle	1355	375	Pass
	Highest	910	375	Pass

Note: According to section 7.4


Antenna	Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
ANT 1	GMSK	369	369
ANT 2	GMSK	375	375

Test plot as follows:



ANT 1





ANT 2



Lowest channel




Middle channel





Highest channel

7.5 Hopping Channel Number


Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data:

Antenna	Hopping channel numbers	Limit	Result
ANT 1	32	15	Pass
ANT 2	32	15	Pass



7.6 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

ANT 1

Frequency	Ton (ms)	Dwell time(ms)	Limit(ms)	Result
2.402GHz	2.400	61.44	400	Pass
2.440GHz	2.392	61.235	400	Pass
2.480GHz	2.392	61.235	400	Pass

The formula as below:

2402MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.4ms*2*0.4*32=61.44ms

2440MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.392ms*2*0.4*32=61.235ms

2480MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.392ms*2*0.4*32=61.235ms

ANT 2

Frequency	Ton (ms)	Dwell time(ms)	Limit(ms)	Result
2.402GHz	2.400	61.44	400	Pass
2.440GHz	2.392	61.235	400	Pass
2.480GHz	2.392	61.235	400	Pass

The formula as below:

2402MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.4ms*2*0.4*32=61.44ms


2440MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.392ms*2*0.4*32=61.235ms

2480MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.392ms*2*0.4*32=61.235ms


Test plot as follows:

ANT 1

Frequency:	2402MHz
------------	---------




Ton




Ton times in 1s

Frequency: 2440MHz




Ton




Ton times in 1s

Frequency: 2480MHz




Ton




Ton times in 1s

ANT 2

Frequency:	2402MHz
------------	---------




Ton




Ton times in 1s

Frequency: 2440MHz




Ton




Ton times in 1s

Frequency: 2480MHz



Ton




Ton times in 1s

7.7 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement:
<p>a(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</p> <p>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> <p>(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p> <p>(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p>	
<h3>EUT Pseudorandom Frequency Hopping Sequence</h3>	
<p>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none"> • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <div data-bbox="244 1274 1295 1424" style="text-align: center;"> </div> <p style="text-align: center;"><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <div data-bbox="244 1525 1238 1675" style="text-align: center;"> </div> <p>Each frequency used equally on the average by each transmitter.</p> <p>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</p> <p>it permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted.</p>	



7.8 Band Edge

7.8.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

ANT 1:




ANT 2:



No-hopping mode


Hopping mode



No-hopping mode

Hopping mode

7.8.2 Radiated Emission Method


Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				

Temp. / Hum.	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Test voltage:	DC 8.4V					
Test results:	Pass					

Remarks:


1. ANT 1 siso ,ANT2 siso and ANT 1+ANT 2 TX mode all have been tested,The test data show only the worst dual antenna simultaneous transmission mode.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Test channel:	Lowest -2402MHz	Polarziation:	Vertical
---------------	-----------------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	36.76	27.14	6.19	42.04	28.05	54.00	-25.95	Average
2310.000	47.10	27.14	6.19	42.04	38.39	74.00	-35.61	Peak
2390.000	49.63	27.37	6.31	42.11	41.20	54.00	-12.80	Average
2390.000	64.30	27.37	6.31	42.11	55.87	74.00	-18.13	Peak
2400.000	59.33	27.41	6.33	42.12	50.95	54.00	-3.05	Average
2400.000	78.57	27.41	6.33	42.12	70.19	74.00	-3.81	Peak

Test channel:	Lowest -2402MHz	Polarization:	Horizontal
---------------	-----------------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	36.78	27.14	6.19	42.04	28.07	54.00	-25.93	Average
2310.000	48.43	27.14	6.19	42.04	39.72	74.00	-34.28	Peak
2390.000	46.14	27.37	6.31	42.11	37.71	54.00	-16.29	Average
2390.000	63.10	27.37	6.31	42.11	54.67	74.00	-19.33	Peak
2400.000	59.15	27.41	6.33	42.12	50.77	54.00	-3.23	Average
2400.000	78.15	27.41	6.33	42.12	69.77	74.00	-4.23	Peak

Test channel:	Highest-2480	Polarization:	Vertical
---------------	--------------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	58.45	27.66	6.45	42.01	50.55	54.00	-3.45	Average
2483.500	78.23	27.66	6.45	42.01	70.33	74.00	-3.67	Peak
2500.000	39.95	27.70	6.47	42.00	32.12	54.00	-21.88	Average
2500.000	63.84	27.70	6.47	42.00	56.01	74.00	-17.99	Peak

Test channel:	Highest-2480	Polarization:	Horizontal
---------------	--------------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	57.78	27.66	6.45	42.01	49.88	54.00	-4.12	Average
2483.500	77.35	27.66	6.45	42.01	69.45	74.00	-4.55	Peak
2500.000	44.15	27.70	6.47	42.00	36.32	54.00	-17.68	Average
2500.000	59.44	27.70	6.47	42.00	51.61	74.00	-22.39	Peak

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*



7.9 Spurious Emission

7.9.1 Conducted Emission Method



Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

ANT 1



ANT 2



Lowest channel: 30MHz~25GHz





Middle channel: 30MHz~25GHz




Highest channel: 30MHz~25GHz

7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Test setup:	<p>For radiated emissions from 9kHz to 30MHz</p>  <p>For radiated emissions from 30MHz to 1GHz</p>				



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:	Refer to section 5.8 for details					
Test mode:	Refer to section 5.2 for details					
Temp. / Hum.	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Test voltage:	DC 8.4V					
Test results:	Pass					

Remark:

- 1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*
- 2. ANT 1 siso ,ANT2 siso and ANT 1+ANT 2 TX mode all have been tested,The test data show only the worst dual antenna simultaneous transmission mode.The test data show only the worst dual antenna simultaneous transmission mode.*


Measurement data:

■ **Below 30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


■ 30MHz ~ 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
30.962	41.48	11.22	0.56	35.07	18.19	40.00	-21.81	QP
37.680	39.53	11.80	0.64	35.53	16.44	40.00	-23.56	QP
54.452	38.27	11.85	0.81	36.25	14.68	40.00	-25.32	QP
78.139	42.53	7.42	1.01	36.53	14.43	40.00	-25.57	QP
96.775	37.66	11.72	1.17	36.69	13.86	43.50	-29.64	QP
191.745	41.59	9.99	1.80	37.29	16.09	43.50	-27.41	QP


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
31.843	54.69	11.24	0.57	35.14	31.36	40.00	-8.64	QP
37.680	44.90	11.80	0.64	35.53	21.81	40.00	-18.19	QP
78.139	43.79	7.42	1.01	36.53	15.69	40.00	-24.31	QP
96.099	39.71	11.65	1.16	36.69	15.83	43.50	-27.67	QP
167.824	39.27	8.46	1.67	37.18	12.22	43.50	-31.28	QP
191.745	41.05	9.99	1.80	37.29	15.55	43.50	-27.95	QP


■ Above 1GHz

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	37.80	31.20	9.36	37.73	40.63	54.00	-13.37	Average
4804.000	43.97	31.20	9.36	37.73	46.80	74.00	-27.20	Peak
7206.000	34.97	36.16	11.21	35.63	46.71	54.00	-7.29	Average
7206.000	41.25	36.16	11.21	35.63	52.99	74.00	-21.01	Peak
9608.000	36.76	37.93	12.91	34.94	52.66	54.00	-1.34	Average
9608.000	42.25	37.93	12.91	34.94	58.15	74.00	-15.85	Peak

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	35.88	31.20	9.36	37.73	38.71	54.00	-15.29	Average
4804.000	42.62	31.20	9.36	37.73	45.45	74.00	-28.55	Peak
7206.000	33.38	36.16	11.21	35.63	45.12	54.00	-8.88	Average
7206.000	40.61	36.16	11.21	35.63	52.35	74.00	-21.65	Peak
9608.000	34.86	37.93	12.91	34.94	50.76	54.00	-3.24	Average
9608.000	39.67	37.93	12.91	34.94	55.57	74.00	-18.43	Peak

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	35.50	31.31	9.42	37.75	38.48	54.00	-15.52	Average
4880.000	41.95	31.31	9.42	37.75	44.93	74.00	-29.07	Peak
7320.000	28.98	36.43	11.30	35.60	41.11	54.00	-12.89	Average
7320.000	37.43	36.43	11.30	35.60	49.56	74.00	-24.44	Peak
9760.000	35.08	38.10	13.01	35.03	51.16	54.00	-2.84	Average
9760.000	40.36	38.10	13.01	35.03	56.44	74.00	-17.56	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	32.49	31.31	9.42	37.75	35.47	54.00	-18.53	Average
4880.000	39.73	31.31	9.42	37.75	42.71	74.00	-31.29	Peak
7320.000	28.27	36.43	11.30	35.60	40.40	54.00	-13.60	Average
7320.000	35.65	36.43	11.30	35.60	47.78	74.00	-26.22	Peak
9760.000	34.49	38.10	13.01	35.03	50.57	54.00	-3.43	Average
9760.000	39.51	38.10	13.01	35.03	55.59	74.00	-18.41	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	32.07	31.44	9.48	37.78	35.21	54.00	-18.79	Average
4960.000	40.87	31.44	9.48	37.78	44.01	74.00	-29.99	Peak
7440.000	28.94	36.66	11.39	35.56	41.43	54.00	-12.57	Average
7440.000	37.66	36.66	11.39	35.56	50.15	74.00	-23.85	Peak
9920.000	28.96	38.30	13.13	35.14	45.25	54.00	-8.75	Average
9920.000	40.12	38.30	13.13	35.14	56.41	74.00	-17.59	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	31.11	31.44	9.48	37.78	34.25	54.00	-19.75	Average
4960.000	38.72	31.44	9.48	37.78	41.86	74.00	-32.14	Peak
7440.000	27.63	36.66	11.39	35.56	40.12	54.00	-13.88	Average
7440.000	37.46	36.66	11.39	35.56	49.95	74.00	-24.05	Peak
9920.000	27.14	38.30	13.13	35.14	43.43	54.00	-10.57	Average
9920.000	36.97	38.30	13.13	35.14	53.26	74.00	-20.74	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

---End---