

TEST REPORT

FCC MPE Test for ADVX-L-23N77HM-P
Certification

APPLICANT
ADRF KOREA, Inc.

REPORT NO.
HCT-RF-2404-FC002

DATE OF ISSUE
April 1, 2024

Tested by
Kyung Soo Kang



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO



HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

**TEST
REPORT**

REPORT NO.
HCT-RF-2404-FC002

DATE OF ISSUE
April 01, 2024

Applicant	ADRF KOREA, Inc. 5-5, Mojeon-Ri, Backsa-Myun, Icheon-Citi, Kyunggi-Do, Korea
Product Name	REPEATER
Model Name	ADXV-L-23N77HM-P
FCC ID	N52-ADL-N77HP
Date of Test	February 20, 2024 ~ March 26, 2024
Location of Test	<input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
Test Standard Used	Part 2.1091
Test Results	PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 01, 2024	Initial Release

Notice

Content

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

RF Exposure Statement

1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#(100)	30
1.34 - 30.....	824/f	2.19/f	#(180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

= Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. Result

[SISO]

- 3.7 GHz Service 5G NR 100 MHz (Downlink)

Max output Power at antenna input terminal	24.00	dBm
Max output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	3 700.00	MHz
Antenna Gain(typical)	5.00	dBi
Antenna Gain(numeric)	3.16	-
Power density at prediction frequency(S)	0.1580	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

[MIMO]

- 3.7 GHz Service 5G NR 100 MHz (Downlink)

Max output Power at antenna input terminal	24.00	dBm
Max output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	3 700.00	MHz
Directional Antenna Gain(typical)	8.01	dBi
Directional Antenna Gain(numeric)	6.32	-
Power density at prediction frequency(S)	0.3160	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²