

# TEST REPORT

FCC MPE Test for ADVX-L-20PAWBT-P  
Certification

**APPLICANT**  
ADRF KOREA, Inc.

**REPORT NO.**  
HCT-RF-2404-FC004

**DATE OF ISSUE**  
April 5, 2024

**Tested by**  
Kyung Soo Kang



**Technical Manager**  
Jong Seok Lee



**HCT CO., LTD.**  
*Bongjai Huh*  
BongJai Huh / CEO



**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 645 6300 Fax. +82 31 645 6401

**TEST  
REPORT**

**REPORT NO.**  
HCT-RF-2404-FC004

**DATE OF ISSUE**  
April 05, 2024

<b>Applicant</b>	<b>ADRF KOREA, Inc.</b> 5-5, Mojeon-Ri, Backsa-Myun, Icheon-Citi, Kyunggi-Do, Korea
<b>Product Name</b>	DAS
<b>Model Name</b>	ADXV-L-20PAWBTP
<b>FCC ID</b>	N52-ADL-PAWBTP
<b>Date of Test</b>	February 07, 2024 ~ April 01, 2024
<b>Location of Test</b>	<input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
<b>Test Standard Used</b>	CFR 47 Part 2.1091
<b>Test Results</b>	PASS

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 05, 2024	Initial Release

## Notice

### Content

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked \*.

Information provided by the applicant is marked \*\*.

Test results provided by external providers are marked \*\*\*.

When confirmation of authenticity of this test report is required, please contact [www.hct.co.kr](http://www.hct.co.kr)

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

## RF Exposure Statement

### 1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#)(100)	30
1.34 - 30.....	824/f	2.19/f	#)(180/f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

# = Plane-wave equivalent power density

### 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 3. RESULTS

#### - AWS (Downlink)

Max output Power at antenna input terminal	21.00	dBm
Max output Power at antenna input terminal	125.89	W
Prediction distance	20.00	cm
Prediction frequency	2 110.00	MHz
Antenna Gain(typical)	4.20	dBi
Antenna Gain(numeric)	2.63	-
Power density at prediction frequency(S)	0.0659	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

#### - PCS (Downlink)

Max output Power at antenna input terminal	21.00	dBm
Max output Power at antenna input terminal	125.89	W
Prediction distance	20.00	cm
Prediction frequency	1 930.00	MHz
Antenna Gain(typical)	4.20	dBi
Antenna Gain(numeric)	2.63	-
Power density at prediction frequency(S)	0.0659	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

## - WCS (Downlink)

Max output Power at antenna input terminal	21.00	dBm
Max output Power at antenna input terminal	125.89	W
Prediction distance	20.00	cm
Prediction frequency	2 350.00	MHz
Antenna Gain(typical)	4.50	dBi
Antenna Gain(numeric)	2.82	-
Power density at prediction frequency(S)	0.0706	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

## - BRS/EBS (Downlink)

Max output Power at antenna input terminal	21.00	dBm
Max output Power at antenna input terminal	125.89	mW
Prediction distance	20.00	cm
Prediction frequency	2 500.00	MHz
Antenna Gain(typical)	4.50	dBi
Antenna Gain(numeric)	2.82	-
Power density at prediction frequency(S)	0.0706	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

**Simultaneous band emission conditions**

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
AWS	0.0659	0.2729	≤ 1
PCS	0.0659		
WCS	0.0706		
BRS/EBS	0.0706		

**Note:**

1. The result of each band was applied to the worst value.
2. MPE ratios are calculated as  
$$[(\text{Power density}_1 / \text{MPE Limit}) + [(\text{Power density}_2 / \text{MPE Limit}) + \dots]] \leq 1$$