

STATEMENT ON MAXIMUM PERMISSIBLE EXPOSURE

No. 811673-2

EQUIPMENT

Type of equipment: Remote Control
Brand name: Scanreco
Type / Model: DRC-CAN D2
Manufacturer: Scanreco AB
By request of: Scanreco AB

DIRECTIVE

OET Bulletin 65, supplement C

CALCULATIONS

The product has an EIRP of 15.1 dBm = 33mW
The manual recommends that the operator is not closer than (r) 20 cm to the transmitter's antenna.

A worst case calculation is as follows (assuming dutycycle is 100%):

$$S = \frac{4 \times dc \times EIRP}{4 \times \pi \times r^2} = \frac{4 \times 100\% \times 33}{4 \times \pi \times 20^2} = 0.026mW / cm^2$$

Reference level limit (General Population/Uncontrolled Exposure) according to OET Bulletin 65, supplement C for power density at 928 MHz is $928 / 1500 = 0.619 mW/cm^2$.

Considering the calculations above it is determined that the requirements according to the referred directive are fulfilled without testing.

Intertek Semko AB
Date of issue: 19 January 2009



Niklas Boström



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address