

D3 DRC-J RF Exposure Exemption Analysis

Products: 2,4 GHz Transceivers D3 DRC-J

The transceivers are designed for using as industrial hand-held / hand-operated remote control devices. The distance from the user to the antenna should be at least 20 cm. Therefore the body SAR is not required. Extremity SAR exclusion is based on 40mm separation distance.

Minimum test separation distance “d”: see 4.3.1 of 447498 “The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1.” The closest distance from the antenna to the user’s hand is 40,0mm

The maximum duty cycle is 8.52 %.

FCC SAR Exclusion Analysis

Section 4.3.1 of 447498 D01 General RF Exposure Guidance v05r02
 Extremity SAR exclusion based on 40 mm separation distance and 8.52 %
 maximum duty cycle for this hand-hand operated device is documented
 below.

P	20,20	dBm
Tune-up tolerance	0,50	dB
Duty Cycle	8,54	%
P average	10,03	mW
d	40	mm
f	2480	MHz
x	7,5	for 1-g SAR
SAR exclusion	0,40	<7.5
Limit	7,5	
Pmax	191	mW

* calculated using 447498 D01 General RF Exposure
 Guidance v05r02 section 4.3.1 1) [(max. power of channel,
 including tune-up tolerance, mW)/(min. test separation
 distance, mm)] · [vf(GHz)]

Scanreco AB

Industry Canada SAR Exclusion Analysis

RSS-102 Issue 4

2.5.1 Exemption from Routine Evaluation Limits – SAR Evaluation

SAR evaluation is required if the separation distance between the user and the radiating element of the device is less than or equal to 20 cm, except when the device operates as follows:

- above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;

The maximum radiated (e.i.r.p) source-based time averaged output power is 10,01 mW. This is based on 8.52 % % duty cycle.

RSS-102 exemption Notice_2013DRS0911 Extremity SAR Evaluation:

SAR evaluation – exemption limits for routine evaluation based on frequency and separation distance at 2450 MHz, 40 mm, extremity = $173 \times 2,5 = 432,5$ mW.

Revision history

Release	Date: YYYY-MM-DD	Edited By	Changes
A	2019-11-06	Elnaz Farzaneh	First creation of document

Scanreco AB

Stensåtravägen 13, SE-127 39 Skärholmen
Box 90304, SE-120 25 Stockholm, Sweden
Tel +46 8 556 32 800
www.scanreco.com