

G5 CU M RF Exposure Exemption Analysis

Product: 2,4 GHz Transceivers G5 CU M19, G5 CU M21

Company: ScanrecoIndustrielektronik AB, Box 47144/ÅrstaSkolgränd 22, S-10074, Stockholm, Sweden

According to RSS-102 exemption 2.5.2 “Exemption from Routine Evaluation Limits – SAR Evaluation”:

RF exposure evaluation is required if the separation distance between the user and the device’s radiating element is greater than 20 cm, except when the device operates as follows:

- *at or above 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 5 W*

Prediction of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density
P = power input to the antenna
G = antenna gain
R = distance

Conducted output power:	18,52	(dBm)
Tune up tolerance	0,5	(dB)
Number of carriers	1	(N)
	79,8	(mW)
	0,0798	(W)
P Average	0,0578	(W)
Antenna gain:	3,3	(dBi)
Maximum antenna gain:	2,14	(numeric)
EIRP Average	0,123	(W)
ERP Average	0,0755	(W)
Distance:	20	(cm)
Duty Cycle:	72,38	(%)
Frequency:	2400	(MHz)
MPE Limit:	1	(mW/cm ²)
Power density:	0,0246	(mW/cm ²)
	0,246	(W/m ²)
Margin	16,1	(dB)

Conclusion: The product satisfies the OET Bulletin 65 Edition 97-1 and RSS-102 Issue 4.

April 23, 2014



Andrei Sazonov, PhD

Senior RF Specialist