

# Test Report

## INTENTIONAL RADIATOR TESTS ACCORDING TO FCC PART 15 C and INDUSTRY CANADA REQUIREMENTS

Equipment Under Test: 2.4 GHz Transceiver

Type/ Model: G5 RF10 Display, G5 RF12, G5 RF12 Display,  
G5 RF14 and G5 RF14 Display

Manufacturer: Scanreco AB  
Årsta Skolgränd 22  
SE-47144 Stockholm  
SWEDEN

Customer: Scanreco AB  
Årsta Skolgränd 22  
SE-47144 Stockholm  
SWEDEN

FCC Rule Part: 15.247

Date: June 3, 2015

Issued by:

  
Pekka Kälviäinen  
Testing Engineer

Date: June 3, 2015

Checked by:

  
Janne Nyman  
Compliance Specialist

**Table of Contents**

---

PRODUCT DESCRIPTION .....	3
Equipment Under Test (EUT) .....	3
Ratings and declarations .....	3
Power Supply .....	3
GENERAL REMARKS .....	4
Disclaimer .....	4
SUMMARY OF TESTING .....	5
EUT Test Conditions during Testing .....	5
TEST RESULTS .....	6
Conducted Emissions In The Frequency Range 150 kHz - 30 MHz .....	6
Transmitter Radiated Emissions 30 MHz to 26.5 GHz .....	8
Duty cycle correction factor, Transmit time in 100 ms .....	11
LIST OF TEST EQUIPMENT .....	13
Conducted Emissions .....	13
Radiated Emissions .....	13

## Equipment Under Test (EUT)

Wireless Radio  
Type/ Model: G5 RF14 Display  
Serial Number: 1675

G5 RF14 Display, is a 2.4 GHz radio that supports frequency hopping.

This report covers models G5 RF10, G5 RF10 Display, G5 RF12, G5 RF12 Display, G5 RF14 and G5 RF14 Display. Electrical structure is similar in all models. Only model G5 RF14 Display was tested. The test results of G5 RF14 Display are sufficient also for models G5 RF10 Display, G5 RF12, G5 RF12 Display and G5 RF14, G5 RF14 Display.

## Classification of the device

Fixed device	<input type="checkbox"/>
Mobile Device (Human body distance > 20cm)	<input checked="" type="checkbox"/>
Portable Device (Human body distance < 20cm)	<input type="checkbox"/>

## Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

## Ratings and declarations

Operating Frequency Range (OFR): 2405 – 2480 MHz  
Channels: 16  
Channel separation: 5 MHz  
Conducted power: 19.25 dBm  
Transmission technique: FHSS  
Modulation: GFSK  
Integrated antenna gain: 0 dBi

## Power Supply

The following wall charger was used during the tests (supplied with 115 V/ 60 Hz).

Charger:

Manufacturer: CMP  
Model: S008CM0900090FW7600/05  
Serial number: -  
Input voltage: 100-240V AC  
Rated current: 250mA  
Rated frequency: 50/60Hz  
Output current: 900mA

Adapter Scanreco Part Nr: 51070

:

**Disclaimer**

*This document is issued by the Company under its General Conditions of service accessible at [http://www.sgs.com/terms and conditions.htm](http://www.sgs.com/terms_and_conditions.htm). attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.*

*Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.*

*Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This document cannot be reproduced except in full, without prior approval of the Company.*

## SUMMARY OF TESTING

Test Specification	Description of Test	Result
§15.207(a)	Conducted Emissions on Power Supply Lines	<b>PASS</b>
§15.209(a), §15.247(d)	Radiated Emissions Within The Restricted Bands	<b>PASS</b>
§15.209	Unintentional Radiated Emissions	<b>PASS</b>

### EUT Test Conditions during Testing

The EUT was configured into the wanted channel and was in continuous transmit mode during all the tests.

Following channels were used during the tests:

Channel	Frequency/ MHz
LOW	2405
MID	2440
HIGH	2480

### Test Facility

<input type="checkbox"/>	Testing Location / address: FCC registration number: <b>90598</b>	SGS Fimko Ltd Särkiniementie 3 FI-00210, HELSINKI FINLAND
<input checked="" type="checkbox"/>	Testing Location / address: FCC registration number: <b>178986</b> Industry Canada registration number: <b>8708A-2</b>	SGS Fimko Ltd Karakaarenkuja 4 FI-02610, ESPOO FINLAND

**Conducted Emissions In The Frequency Range 150 kHz - 30 MHz.**

**Standard:** ANSI C63.10 (2009)  
**Tested by:** PKA  
**Date:** 18.05.2015  
**Temperature:** 20 °C  
**Humidity:** 37 % RH  
**Barometric pressure:** 1004 hPa  
**Measurement uncertainty:** ± 2.9 dB Level of confidence 95 % (k = 2)

**FCC Rule: 15.207 (a)**

Conducted disturbance voltage was measured with an artificial main network from 150 kHz to 30 MHz with 4.5 kHz steps and a resolution bandwidth of 9 kHz. Measurements were carried out with peak and average detectors.

During the test the EUT was powered from the separate power supply (115VAC / 60 Hz) through the LISN.


Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

**Conducted Emissions In The Frequency Range 150 kHz – 30 MHz**

Final results 0.15 – 30 MHz: MID channel

Conducted Emission Mains FCC Part 15 Class B with ESH3-Z5 8019



**Figure 1.** The measured curves with peak- and average detector

**Final measurements from the worst frequencies**

**Table 1.** Final results (QP).

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.150000	56.2	1000.0	9.000	GN	L1	10.7	9.8	66.0	PASS
0.156750	46.1	1000.0	9.000	GN	N	10.7	19.6	65.6	PASS
0.253500	35.3	1000.0	9.000	GN	N	10.8	26.4	61.6	PASS
9.055000	29.5	1000.0	9.000	GN	N	10.9	30.5	60.0	PASS

**Table 2.** Final results (AV).

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.150000	40.8	1000.0	9.000	GN	N	10.6	15.2	56.0	PASS
0.298500	22.6	1000.0	9.000	GN	N	10.5	27.7	50.3	PASS
0.609000	19.0	1000.0	9.000	GN	N	10.1	27.0	46.0	PASS

**Transmitter Radiated Emissions 30 MHz to 26.5 GHz**

<b>Standard:</b>	ANSI C63.10	(2009)
<b>Tested by:</b>	PKAE	
<b>Date:</b>	18.05.2015	
<b>Temperature:</b>	20 °C	
<b>Humidity:</b>	37 % RH	
<b>Measurement uncertainty</b>	± 4.51 dB	Level of confidence 95 % (k = 2)

**FCC Rule: 15.247(d), 15.209(a)**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

The correction factor in the final result table contains the sum of the transducers (antenna + amplifier + cables). The result value is the measured value corrected with the correction factor.


The measurements above 1 GHz were performed by using a peak detector and a Duty Cycle correction factor(dB) -25.19 dB, see chapter: Duty cycle correction factor, Transmit time in 100 ms.

The measurements were performed with the EUT being in three orthogonal positions (X, Y, Z). Below 1 GHz the measurements were performed at MID channel, above 1 GHz the measurements were performed at LOW, MID and HIGH channels..



Final results 30 – 1000 MHz: MID channel

Radiated Emission FCC Part 15 Class B 30-1000MHz 3m



- FCC Part 15 Class B Electric Field Strength 3 m QP [..NEMI radiated]
- Preview Result 1V-PK+ [Preview Result 1V.Result:1]
- Preview Result 1H-PK+ [Preview Result 1H.Result:1]
- ◆ Final Result 1-QPK [Final Result 1.Result:1]

**Figure 2.** Measured curve with peak-detector. Channel MID.

**Final measurements from the worst frequencies**

**Table 3.** Final results 30 – 1000 MHz (QP).

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
30.020000	26.3	1000.0	120.000	100.0	V	122.0	12.9	13.7	40.0	PASS
46.295000	34.5	1000.0	120.000	100.0	V	47.0	14.5	5.5	40.0	PASS
70.645000	33.8	1000.0	120.000	100.0	V	222.0	12.3	6.2	40.0	PASS
123.925000	25.4	1000.0	120.000	100.0	V	55.0	12.7	18.1	43.5	PASS
161.245000	31.2	1000.0	120.000	175.0	H	279.0	14.4	12.3	43.5	PASS
210.305000	21.4	1000.0	120.000	193.0	V	50.0	11.4	22.1	43.5	PASS
288.805000	16.0	1000.0	120.000	100.0	H	323.0	14.9	30.0	46.0	PASS
948.135000	29.3	1000.0	120.000	304.0	H	251.0	27.5	16.7	46.0	PASS

Final results 1.0 – 26.5 GHz:

**Table 4.** LOW channel (RBW 1000 kHz, VBW 3000 kHz)

Frequency (MHz)	Peak			Average		
	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB
7214.1	65.2	74.0	8.8	40.0	54.0	14.0
9618.8	70.3	74.0	3.7	45.1	54.0	8.9

**Table 5.** MID channel (RBW 1000 kHz, VBW 3000 kHz)

Frequency (MHz)	Peak			Average		
	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB
7319.1	65.9	74.0	8.1	40.7	54.0	13.3
9758.8	66.5	74.0	7.5	41.3	54.0	12.7

**Table 6.** HIGH channel (RBW 1000 kHz, VBW 3000 kHz)

Frequency (MHz)	Peak			Average		
	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin dB
7439.1	66.1	74.0	7.9	40.9	54.0	13.9
9918.8	68.1	74.0	5.9	42.9	54.0	11.1

**Duty cycle correction factor, Transmit time in 100 ms**

**Standard:** ANSI C63.10 (2009)  
**Tested by:** PKA  
**Date:** 18.05.2013  
**Temperature:** 20 °C  
**Humidity:** 37 % RH

Spectrum analyzer with zero span was used to investigate spectrum.

15.35(c) Unless otherwise specified, e.g. § 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

**Test data**


Pulse period (T) = 6.4s/89=71.9ms

Pulses/100ms=2

Length of one pulse = 2.750ms


DutyCycleCorrectionFactor=20\*log(Tocc/100)=20\*log(2\*2.750/100)=-25.19dB

## Duty cycle correction factor, Transmit time in 100 ms



Date: 18.MAY.2015 15:15:28

Figure 3. One channel dwell time.



Date: 18.MAY.2015 15:10:46

Figure 4. Hopping on, number of transmissions, channel 2440MHz, 89 transmissions

## LIST OF TEST EQUIPMENT

### Conducted Emissions

Equipment	Manufacturer	Type	Serial no	Inv.no
TEST RECEIVER	ROHDE & SCHWARZ	ESU 26	100185	8453
TEST SOFTWARE	ROHDE & SCHWARZ	EMC-32	-	-
PULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	#1	8359
LISN	ROHDE & SCHWARZ	ESH3-Z5	863794/014	8019
AC Power Source	CALIFORNIA INSTRUMENTS	5001 iX Series II	58209	7826

### Radiated Emissions

Equipment	Manufacturer	Type	Serial no	Inv.no
TEST RECEIVER	ROHDE & SCHWARZ	ESU 26	100185	8453
TEST SOFTWARE	ROHDE & SCHWARZ	EMC-32	-	-
ANTENNA (30-1000 MHz)	SCHWARZBECK	VULB 9168	8168-503	8911
ANTENNA MAST	DEISEL	MA240	240/455	5017
TURNTABLE	DEISEL	DS420	-	5015
CONTROLLER	COMTEST	HD100	100/457	5018
ANTENNA (1-18 GHz)	EMCO	3117	29617	7293
PREAMPLIFIER (0.5-26GHz)	HP	83017A	3950M00102	5226
ATTENUATOR 10 dB	HUBER & SUHNER	6810.17B	-	-
HIGH PASS FILTER	WAINWRIGHT	WHKX	10	8267
ANTENNA (18-26.5 GHz)	EMCO	3160- 09	030232-022	7294

All used measurement equipment was calibrated (if required).