SOS Key

Long press SOS for 2S until red LED blinking if there is a risk, tracker will send the alarm to the urgent contact.



Charging

- · Connect the adapter
- Red LED on, Charging
- Red LED off, Power full



Back clip assembly method

According to below guidance operation assembly back clip.





Country/Region -



Accessories







Micro USB cable

FQA

1.Why can't power on?

An: The power may run out during transportation, please charge it before turn it on .

2. Why bind device failure?

An: Binding device need high quality GSM network, please keep the device in a suitable environment.

3. Why can't position successfully?

An: The device should work in the open area, especially the first time. The position speed and accuracy will be affected by the surroundings.

4. Why not provide adapter?

An: For two reason : (1) The device support the popular cell phone adapter to charge, such as iPhone, sansumg etc. (2) Environmental protection considering. Please select a suitable one for charging.

Cautions

1. The device only be bound by one account . an the account can authorize the other three accounts to check the status. The authorized accounts can check the device status and setting the parameters about tracking, but cann't change the main parameters such as APN etc..

2. Keep the product away from the fire, high temperature surroundings.

3. The function of location won't work when the power turn off or out of GSM network

Customer service

Please contact salesman or consultation service center which authorized by China Aerospace Telecommunications(shenzhen) Ltd. to obtain the service.

Contact information

Welcome to contact with us if you have any queries and recommends

China

Official WeChat: Lit guardian Service QQ:3106893070

Service Tel.: 0755-8618 5110

Hongkong

Service Tel.: +852-2627 3336

Overseas

E-mail: sales@castelecom.com Website: www.castelecom.com Service Tel.:+86-755-8601 8742

Warranty

User	_ Tel
Address	
Post code F	Purchase date
Product Model	Product ID code
Domost	

Repair Record

Date	Fault and repair record Repairman		Repairman	User
Date	Fault	Repair Record	Терантап	User
				·

CASTEL

PT-718 Personal Tracker



China Aerospace Telecommunications (ShenZhen) Limited

Download the mobile application

1.Scan the QR code and download the APP.





Hongkong&Overseas

Note:If Scan the QR code via Wechat ,please open the link by browser.

2. Search "Lit Guardian" in Google Play Store/ App Store and download.

Notes: App display language depends on the default language of cell phone .Ex. the cell phone language is English , and then APP's language is English even you are in China.

Bind Tracker

1.Install SIM card , device support Micro SIM card , unsupport CDMA. Please ensure the device switch off when install SIM card.



2.Turn on the device: Long press Power Key for 3 second to turn on /off the device.



3.Start APP : Lit Guardian.

4.Register new account or log in exist account.5.Scan the QR code on the back of device.


Model No.:PT-718

FC (China Aerospace Telecommunications Ltc

 $6. \\ System will bind the tracker automatically in a minute.$

Tracker Instruction

1.Led Instruction



2.Led Status Instruction

type	Color	LED Color	status	
	Red	off	Positioning success	
		on	charging	
D		OII	on& Not positioning	
Power LED		Sharp blinking (1 seconds blinking once, lasting 20S)	SOS Alarm	
		Slow blinking (8 seconds blinking once)	low power	
	Orange	off	no power	
GSM LED		011	No GSM network	
GSWILED		blinking (2 seconds blinking once)	Login success	
	Green	on	on& Not positioning	
GPS LED		blinking (2 seconds blinking once)	Positioning success	

3.Technical Parameters

Rated voltage:3.7V --Product specification:63*40*16.5mm
Product weight:50g

APN SETTING

If you don't use the SIM card which along with the device ,please set the correct APN at the APP at first, avoiding tramitting data failure as APN is incorrect.

Setting: APP \rightarrow Setting \rightarrow APN Setting \rightarrow Fill in APN(get APN parameters from the carrier).

 $Notes: Ensure \ the \ device \ stays \ online \ and \ under \ a \ stable \ network \\ connection \ before \ setting \ APN \ the \ yellow \ led \ blinking.$

SIM Card Installation

- Turn on the cover of SIM interface
- Insert SIM card
- Close the cover of interface

China Aerospace Telecommunications(ShenZhen)Limited

Add:5/F 5th Bulding, Software Park, No. 2 Gaoxin C, 3rd Road, Nanshan, Shenzhen