

RF Exposure Evaluation Declaration

Product Name : Wireless LAN Access Point
Trade Name : SILEX TECHNOLOGY
Model No. : AP-200AC
FCC ID : N6C-AP200AC

Applicant : Silex Technology, Inc.
Address : 2-3-1 Hikaridai, Seika-cho, Soraku-gun,
Kyoto 619-0237, Japan

Date of Receipt : Feb. 01, 2021
Date of Declaration : May 26, 2021
Report No. : 2120022R-E3082100013
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

RF Exposure Evaluation Declaration

Issued Date : May 26, 2021

Report No. : 2120022R-E3082100013



Product Name : Wireless LAN Access Point
Applicant : Silex Technology, Inc.
Address : 2-3-1 Hikaridai, Seika-cho, Soraku-gun, Kyoto 619-0237, Japan
Manufacturer : Amigo Technology Inc.
Address : No.82, Gongye 2nd Rd., Annan District, Tainan City 70955, Taiwan (R.O.C.)
Trade Name : SILEX TECHNOLOGY
Model No. : AP-200AC
FCC ID : N6C-AP200AC
EUT Voltage : AC 100-240V, 50/60Hz
Testing Voltage : AC 120V/60Hz
Applicable Standard : FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Test Lab : Hsin Chu Laboratory
Address : No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 310, Taiwan, R.O.C.
TEL: +886-3-582-8001 / FAX: +886-3-582-8958
Test Result : Complied

Tested By :

Clemens Fang

(Clemens Fang / Senior Engineer)

Approved By :

Louis Hsu

(Louis Hsu / Deputy Manager)

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	May 26, 2021

1.1. Test Facility

Ambient conditions in the laboratory:

Items	Test Item	Required	Test Site
Temperature (°C)	Peak Output Power	15 - 35	1
Humidity (%RH)		25 - 75	

Note: Test site information refers to Laboratory Information.

Laboratory Information

USA : FCC Registration Number: TW3024
Canada : IC Registration Number: 22397-1 / 22397-2 / 22397-3

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: <http://www.dekra.com.tw>

If you have any comments, please don't hesitate to contact us. Our test sites as below:

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
Address	1. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. 2. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
Phone number	1. +886-3-582-8001 2. +886-3-582-8001
Fax number	1. +886-3-582-8958 2. +886-3-582-8958
Email address	info.tw@dekra.com
Website	http://www.dekra.com.tw

1.2. List of Test Equipment

Peak Output Power / SR12-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
High Speed Peak Power Meter Dual Input	Anritsu	ML2496A	1602004	2020/11/30	2021/11/29
Pulse Power Sensor	Anritsu	MA2411B	1531043	2020/11/30	2021/11/29
Pulse Power Sensor	Anritsu	MA2411B	1531044	2020/11/30	2021/11/29
Power Meter	Keysight	8990B	MY51000248	2020/05/20	2021/05/19
Power Sensor	Keysight	N1923A	MY57240005	2020/05/20	2021/05/19

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

1.3. Uncertainty

Test item	Uncertainty
Peak Output Power	± 2.26 dB

Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-1023	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> 0.5	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> 0.25	0.3444/ <i>f</i> 0.25	44.72/ <i>f</i> 0.5	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> 0.25	0.04138 <i>f</i> 0.25	0.6455 <i>f</i> 0.5	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> 1.2
150000-300000	0.354 <i>f</i> 0.5	9.40 x 10 ⁻⁴ <i>f</i> 0.5	3.33 x 10 ⁻⁴ <i>f</i>	616000/ <i>f</i> 1.2

Note: *f* is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.3. Test Result of RF Exposure Evaluation

Directional Gain:

Band	Gain (dBi)
2.4GHz	5.22
5GHz Band 1	6.32
5GHz Band 4	6.32

Output Power into Antenna & RF Exposure Evaluation Distance:

WLAN Function 2.4GHz Band					
Mode	Evaluation Frequency (MHz)	Maximum Conducted Output Power		Maximum Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
		(dBm)	(mW)		
Non-Beamforming	2412 ~ 2462	24.86	306.196	0.203	1.000
Beamforming		21.85	153.123	0.101	1.000

WLAN Function 5GHz Band 1					
Mode	Evaluation Frequency (MHz)	Maximum Conducted Output Power		Maximum Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
		(dBm)	(mW)		
Non-Beamforming	5180 ~ 5240	22.478	176.947	0.151	1.000
Beamforming		19.468	88.480	0.075	1.000

WLAN Function 5GHz Band 4					
Mode	Evaluation Frequency (MHz)	Maximum Conducted Output Power		Maximum Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
		(dBm)	(mW)		
Non-Beamforming	5745 ~ 5825	23.513	224.538	0.191	1.000
Beamforming		20.503	112.277	0.096	1.000

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz=0.203+0.191=0.394, therefore the maximum calculations of above situations are less than the "1" limit.

Note:

1. The EUT description is from the customer declaration.
2. The product specification and testing instructions for the EUT declared in the report are provided by the manufacturer who will take all responsibilities for the accuracy.
3. The results are evaluated using the maximum power.