

RF Exposure / MPE Calculation

No. : 32LE0279-HO-01

Applicant : silex technology, Inc.
Type of Equipment : SX-DS-3000EWB
Model No. : SX-DS-3000EWB
FCC ID : N6C-DS3000EWB
IC Number : 4908A-DS3000EWB

silex technology, Inc. declares that Model : SX-DS-3000EWB
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "SX-DS-3000EWB" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 28.48 mW (Maximum peak output power)
G = 3.17 Numerical Antenna gain; equal to 5.01 dBi (including Correlated Gain)
r = 20.0 cm

For: SX-DS-3000EWB

$$S = 0.01796 \text{ mW/cm}^2$$

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124