

RF Exposure / MPE Calculation

No. : 32IE0154-HO-01

Applicant : silex technology, Inc.
Type of Equipment : SDIO Wireless Module (11b/g, 11n-20(2.4GHz/5745-5825MHz),
11n-40(5755-5795MHz), 11a(5745-5825MHz))
Model No. : SX-SDMAN
FCC ID : N6C-SDMAN
IC Number : 4908B-SDMAN

silex technology, Inc. declares that Model : SX-SDMAN
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "SX-SDMAN" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 197.96 mW (Maximum peak output power)
G = 1.78 Numerical Antenna gain; equal to 2.50 dBi
r = 20.0 cm

For: SX-SDMAN

$$S = 0.07003 \text{ mW/cm}^2$$

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124