

RF Exposure / MPE Calculation

No. : 29EE0161-HO-01

| | | |
|--------------------------|---|-------------------------------------------------------|
| Applicant | : | silex technology, Inc. |
| Type of Equipment | : | Wireless 11abg Adapter (11a Lower/Middle Band) |
| Model No. | : | SX-10WAG-IT |
| FCC ID | : | N6C-SX10WAGIT |
| IC Number | : | 4908B-SX10WAGIT |

silex technology, Inc. declares that Model : SX-10WAG-IT
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "SX-10WAG-IT" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

| | |
|------------|----------------------------------------------------|
| P = | 19.05 mW (Maximum peak output power) |
| G = | 1.62 Numerical Antenna gain; equal 2.10 dBi |
| r = | 20.0 cm |

For: SX-10WAG-IT

$$S = 0.00615 \text{ mW/cm}^2$$

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124