Date: December 2, 2011

## **UNII Declaration Letter**

We have declared below featured for FCC equipment authorization, Device FCC ID: N6C-SXDS3000WAN DFS Device -- Master , Client with Radar detection capability , Client without radar detection capability, N/A (2) Active / Passive Scanning, adhoc mode access point capability Frequency Band Active Scanning Ad Hoc Mode Access point passive scanning (MHz) (the device can (where the device is capability capability transmit a probe can listen only with no (beacon)) probes) 2412 - 2462 X Yes, [ No Yes, No X Yes, No Yes, No 2422 - 2452 Yes, No Yes,[ Yes, No Yes, No No Yes, No M ⊠ No 5745 - 5825 Yes, Yes, Yes, No Νo Yes , ⊠ No Yes , ⊠ No ⊠ No 5755 - 5795 Yes, Yes, No Yes, No No Yes. ⊠ No 5180 - 5240 Yes, No Yes, \_\_ No Yes , 🔀 No ⊠ No No Yes, Yes, 5190 - 5230 Yes, Yes , 🔀 No 5260 - 5320Yes, ⊠ No Yes, No Yes, 🛛 No 5270 - 5310Yes, ⊠ No Yes, No Yes, No Yes, No (3) Country code selection ability - Yes, No If no, pls explain how was implemented: It is implemented at the production test via the Ethernet port by our original protocol which is not opened for end user. (4) Meet 15.202 requirement - 

✓ Yes , 

No , pls check below: A master device is defined as a device operating in a mode in which it has the capability to transmit without receiving an enabling signal. In this mode it is able to select a channel and initiate a network by sending enabling signals to other devices A client device is defined as a device operating in a mode in which the transmissions of the device are under control of the master. A device in client mode is not able to initiate a network. (5) For client devices that have software configuration control to operate in different modes (active scanning in some and passive scanning in others) in different bands (devices with multiple equipment classes or those that operate on non-DFS frequencies) or modular devices which configure the modes of operations through software, the application must provide software and operations description on how the software and / or hardware is implemented to ensure that proper operations modes can not be modified by end user or an installer. Apply, I No Apply, (If apply, pls help to provide explanation on how it was implement (By hardware or software, and how software was controlled) It implemented as a software option and set at the production test via the Ethernet port by our original protocol which is not opened for end user. Applicant : SILEX TECHNOLOGY INC. Address : 2-3-1 Hikaridai, Seika-cho, Kyoto 617-0237 Japan Trosti rickometan' Signature

Name and Job Title. : Toshiro Kometani / Manager