



FCC 1.1310(b), Maximum Permissible Exposure Calculations RSS133 Sub Clause 8 Exposure of Humans to RF Field

Date of Report: February 9, 2010

Report No.: 90303-10-R

Calculations prepared for:

Silex Technology America, Inc.
15661 Red Hill Ave. Suite 120
Tustin CA 92780

Calculations prepared by:

Eddie Wong
110 N. Olinda Place
Brea, CA 92823

Model Number: SX-SDCAG

Fundamental Operating Frequency:

5.15 - 5.25GHz, 5.725 - 5.825GHz

Maximum Rated Output Power:

0.0214 W

Measured Output Power:

0.0214 W

Maximum Antenna Gain:

4.2 dBi (2.6 linear gain)

Power Output and Operating Frequency Information used for these calculations were from:
CKC Laboratories, Test Report: **90303-10**

Device and Antenna Operating Configuration:

Transmitting continuously. Power measured conducted at the antenna port Max antenna gain is 4.2 dBi.

Test Procedure:

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65.

MPE Limit in accordance with 1.1310(b): Limits for general population/uncontrolled exposure

$$\text{MPE Limit for 5150 – 5250MHz, 5725 – 5825MHz} = 1 \text{ mW/cm}^2 \text{ (10 W/m}^2\text{)}$$

(B) Limits for General Population/Uncontrolled Exposure

Frequency	density (mW/cm ²)	Averaging time (minute)
1500-100,000	1.0	30

Power Output (Watts)	Power Density Limit (mW/cm ²)	Minimum Distance (Meters)
0.0214	1	0.021

$$\text{Power Density (W/m}^2\text{)} = \frac{30 \times P_t \times G}{d^2 \times Z_0}$$

P_t = Power Delivered to the Antenna
 d = Distance in meters

G = Antenna Gain
 Z_0 = Impedance of Free Space

Statement of Compliance:

This device demonstrates compliance under the operating conditions specified in this document. Under normal operating conditions, the antenna is designed to be installed in accordance with the manufacturer's instructions in such a manor to maintain the minimum separation distance. The MPE calculations shown above demonstrate compliance to the provisions of 1.1310 in accordance with the guidelines of OET 65.

Under normal operation, the antennas to be used with the EUT a maintain a distance of 20 cm (0.2 meter) from the user. As can be seen from the MPE result, this device passes the limit specified in 1.1310 at a distance of 0.021 meter.

Calculation:

$$d = \sqrt{\frac{30 \times 0.0214 \times 2.6}{10 \times 377}}$$

$$= 0.021\text{m}$$