

RF Exposure Report

Test Report Number	STA-24041661-LC-FCC-IC-MPE
FCC ID ISED ID	N6C-USBAC 4908A-USBAC
Applicant Applicant Address Product Name Model Number Date of Receipt Date of Test Report Issue Date Test Standards	Silex technology, Inc. 2-3-1 Hikaridai, Seika-cho, Kyoto 619-0237, Japan Embedded Wireless Module SX-USBAC 04/26/2024 04/30/2024- 05/08/2024 05/20/2024 47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 6 Dec 2023
Test Result	PASS
	<p>Issued by:</p> <p>Vista Compliance Laboratories 1261 Puerta Del Sol, San Clemente, CA 92673 USA www.vista-compliance.com</p>
<p><i>Lining</i></p> <hr/> <p>Lining Li (Test Engineer)</p>	<p><i>David Zhang</i></p> <hr/> <p>David Zhang (Technical Manager)</p>
<p><small>This report is for the exclusive use of the applicant. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Note that the results contained in this report pertain only to the test samples identified herein, and the results relate only to the items tested and the results that were obtained in the period between the date of initial receipt of samples and the date of issue of the report. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested and the results thereof based upon the information provided to us. The applicant has 60 days from date of issuance of this report to notify us of any material error or omission. Failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies. This report is not to be reproduced by any means except in full and in any case not without the written approval of Vista Laboratories.</small></p>	

REVISION HISTORY

Report Number	Version	Description	Issued Date
STA-24041661-LC-FCC-IC-MPE	01	Initial report	05/20/2024

TABLE OF CONTENTS

1 GENERAL INFORMATION.....4

1.1 Applicant4

1.2 Product information4

1.3 Test standard and method.....5

2 TEST SITE INFORMATION.....5

3 FCC RF EXPOSURE EVALUATION.....6

3.1 Limits for Maximum Permissible Exposure (MPE)6

3.2 MPE Calculation Formula6

3.3 Classification6

3.4 Antenna Gain6

3.5 FCC RF Exposure Evaluation Results6

4 ISED RF EXPOSURE EVALUATION7

4.1 Limits for Maximum Permissible Exposure (MPE)7

4.2 MPE Calculation Formula8

4.3 Classification8

4.4 Antenna Gain8

4.5 ISED RF Exposure Evaluation Results8

1 General Information

1.1 Applicant

Applicant	Silex technology,Inc.
Applicant Address	2-3-1 Hikaridai, Seika-cho, Kyoto 619-0237, Japan
Manufacturer	Silex technology,Inc.
Manufacturer Address	2-3-1 Hikaridai, Seika-cho, Kyoto 619-0237, Japan

1.2 Product information

Product Name	Embedded Wireless Module
Model Number	SX-USBAC
Family Models	N/A
Serial Number	N/A
Frequency Band	Bluetooth_Classic: 2402-2480MHz BLE: 2402-2480MHz WLAN 2.4G: 2412-2462MHz WLAN 5G: U-NII-1: 5150-5250MHz, U-NII-2A: 5250-5350MHz U-NII-2C: 5470-5725MHz, U-NII-3: 5725-5850MHz
Type of modulation	BT BDR/EDR: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g: OFDM-CCK (BPSK, QPSK, 16QAM, 64QAM) 802.11a/n/ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Equipment Class	DTS
Antenna Information	Hercules Wi-Fi 6 Permanent Mount Antenna (Part No.: WS.03.B.205151.vj) (omni-directional with cable) Peak Gain: 3.43 dBi for 2 GHz, 5.02 dBi for 5 GHz
Clock Frequencies	N/A
Input Power	3.3VDC
Power Adapter Manufacturer/Model	N/A
Power Adapter SN	N/A
Hardware version	N/A
Software version	N/A
Additional Info	N/A

1.3 Test standard and method

Test standard	47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 6 Dec 2023
Test method	47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 6 Dec 2023

2 Test Site Information

Lab performing tests	Vista Laboratories, Inc.
Lab Address	1261 Puerta Del Sol, San Clemente, CA 92673 USA
Phone Number	+1 (949) 393-1123
Website	www.vista-compliance.com

3 FCC RF Exposure Evaluation

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3.4 Antenna Gain

Please see section 1.2 product information for antenna gain details.

3.5 FCC RF Exposure Evaluation Results

Band	Conducted Average Output Power (mW)	Antenna Gain (dBi)	Separation distance (cm)	Power Density (mW/ cm ²)	MPE Limit (mW/ cm ²)
BDR/EDR	1.99 (2.99)	3.43	20	0.00087	1
BLE	1.2 (0.76)	3.43	20	0.00053	1
WLAN 2.4G	101.86 (20.08)	3.43	20	0.04464	1
WLAN 5G	25.41 (14.05)	5.02	20	0.01114	1

The above results show that the device complies with the MPE requirement.

4 ISED RF Exposure Evaluation

4.1 Limits for Maximum Permissible Exposure (MPE)

1. Per RSS-102 issue 5, section 2.5.2 as reproduced below:

2.5.2 Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- Below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- At or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}W$ (adjusted for tune-up tolerance), where f is in MHz;
- At or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} W$ (adjusted for tune-up tolerance), where f is in MHz;
- At or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field Strength (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
Limits For General Population / Uncontrolled Exposure				
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$
<p>Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).</p>				

4.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

4.4 Antenna Gain

Please see section 1.2 product information for antenna gain details.

4.5 ISED RF Exposure Evaluation Results

Band (MHz)	Conducted Average Output Power (mW)	Antenna Gain (dBi)	Separation distance (cm)	Power Density (W/ m ²)	MPE Limit (W/ m ²)
BDR/EDR	1.99	3.43	20	0.0087	5.35
BLE	1.2	3.43	20	0.0053	5.35
WLAN 2.4G	101.86	3.43	20	0.4464	5.37
2. WLAN 5G	25.41	5.02	20	0.1114	9.01

The above results show that the device complies with the ISED MPE requirement.

---END---