



## MPE TEST REPORT

### FCC Per 47 CFR 2.1091(b)

Report Reference No.: TRE1203014502

FCC ID: N6QPT7131W

Compiled by

( position+printed name+signature): File administrators Tim Zhang

Tim Zhang

Supervised by

( position+printed name+signature): Test Engineer Eric Zhang

Eric Zhang

Approved by

( position+printed name+signature): Manager Wenliang Li

Wenliang Li

Date of issue: July 06, 2012

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd

Address: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name: TENNIS TECHNOLOGY CO LTD

Address: 301. building 6 No:3 Pu Xia Xia'an street, LiuYue Community.  
HengGang Town LongGang District Shenzhen China

#### Test specification:

Standard: FCC Per 47 CFR 2.1091(b)

TRF Originator: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF: Dated 2006-06

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: IP CAMERA

Trade Mark: /

Model/Type reference: PT7131W

Listed Models: JPT3815W

Operation Frequency: From 2400MHz to 2483.5MHz

Result: Positive

**T E S T   R E P O R T**

<b>Test Report No. :</b> <b>TRE1203014502</b>	July 06, 2012 Date of issue
---	--------------------------------

Equipment under Test                      :            IP CAMERA

Model /Type                                        :            PT7131W

Listed Models                                        :            JPT3815W

**Applicant**    :            **TENVIS TECHNOLOGY CO LTD**

Address    :            301.building 6 No:3 Pu Xia Xia'an street,LiuYue  
Community. HengGang Town LongGang District  
Shenzhen China

**Manufacturer**    :            **TENVIS TECHNOLOGY CO LTD**

Address    :            301.building 6 No:3 Pu Xia Xia'an street,LiuYue  
Community. HengGang Town LongGang District  
Shenzhen China

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

<b><u>1.</u></b>	<b><u>SUMMARY .....</u></b>	<b><u>4</u></b>
1.1.	EUT configuration	4
1.2.	Power supply system utilised	4
1.3.	Description of the test mode	4
1.4.	NOTE	4
<b><u>2.</u></b>	<b><u>TEST ENVIRONMENT.....</u></b>	<b><u>6</u></b>
2.1.	Address of the test laboratory	6
2.2.	Environmental conditions	6
2.3.	Statement of the measurement uncertainty	6
<b><u>3.</u></b>	<b><u>METHOD OF MEASUREMENT .....</u></b>	<b><u>7</u></b>
3.1.	Applicable Standard	7
3.2.	Limit	7
3.3.	MPE Calculation Method	7
<b><u>4.</u></b>	<b><u>CONCLUSION .....</u></b>	<b><u>8</u></b>

## 1. SUMMARY

### 1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○ Power Cable	Length (m) :	/
	Shield :	/
	Detachable :	/
○ Multimeter	Manufacturer :	/
	Model No. :	/

### 1.2. Power supply system utilised

Power supply voltage	:	● 120V / 60 Hz	○ 115V / 60Hz
		○ 12 V DC	○ 24 V DC
		○ Other (specified in blank below)	

/

### 1.3. Description of the test mode

IEEE 802.11b/g/n: Eleven channels are provided to the EUT.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

### 1.4. NOTE

1. The EUT is an 802.11b/g/n IP CAMERA ,The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN 802.11b/g/n	FCC Part 15 Subpart C (Section15.247)	TRE1203014501
MPE REPORT	FCC Per 47 CFR 2.1091(b)	TRE1203014502
EMC REPORT	FCC PART 15 Subpart B	TRE1203014503

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
802.11b	√	—	—	—
802.11g	√	—	—	—
802.11n(20MHz)	√	—	—	—
802.11n(40MHz)	√	—	—	—

3. The EUT incorporates a SISO function,Physically,the EUT provides one completed transmitter and one completed receiver.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

## **2. TEST ENVIRONMENT**

### **2.1. Address of the test laboratory**

Shenzhen Huatongwei International Inspection Co., Ltd  
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China  
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

### **2.2. Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Temperature:	<u>15-35 ° C</u>
Humidity:	<u>30-60 %</u>
Atmospheric pressure:	<u>950-1050mbar</u>

### **2.3. Statement of the measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

<b>Test Items</b>	<b>Measurement Uncertainty</b>	<b>Notes</b>
Transmitter power conducted	0.57 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

### 3. Method of measurement

#### 3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

#### 3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna is 2dBi, the RF power density can be obtained.

**TEST RESULTS****For 802.11 b**

Test Frequency (MHz)	Minimum Separation Distance	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2412	20.00	16.29	42.56	1.585	1.000	0.0134	Pass
2437	20.00	16.32	42.85	1.585	1.000	0.0135	Pass
2462	20.00	16.45	44.16	1.585	1.000	0.0139	Pass

**For 802.11 g**

Test Frequency (MHz)	Minimum Separation Distance	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2412	20.00	16.27	42.36	1.585	1.000	0.0134	Pass
2437	20.00	16.35	43.15	1.585	1.000	0.0136	Pass
2462	20.00	16.75	47.31	1.585	1.000	0.0149	Pass

**For 802.11 n(20MHz)**

Test Frequency (MHz)	Minimum Separation Distance (20cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2412	20.00	15.61	36.39	1.585	1.000	0.0115	Pass
2437	20.00	16.02	39.99	1.585	1.000	0.0126	Pass
2462	20.00	16.23	41.98	1.585	1.000	0.0132	Pass

**For 802.11 n(40MHz)**

Test Frequency (MHz)	Minimum Separation Distance (20cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2422	20.00	16.46	44.26	1.585	1.000	0.0140	Pass
2437	20.00	16.23	41.98	1.585	1.000	0.0132	Pass
2452	20.00	16.33	42.95	1.585	1.000	0.0136	Pass

**4. Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 (b) for the controlled RF Exposure.

.....**End of Report**.....