

**FCC PART 90 TYPE APPROVAL  
EMI MEASUREMENT AND TEST REPORT  
ABOUT BLOCK DIAGRAM FOR  
COMMUNICATION NETWORK INTERFACE, INC.**

51-2, SungSan 1-dong, Mapo-gu  
SEOUL 121-251, KOREA

**FCC ID: N79CNI-800D**

May 2, 1999

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Radio Packet Modem
<b>Test Engineer:</b> John Chan	
<b>Test Date:</b> May 2, 1999	
<b>Certified By:</b> John Y. Chan - Director, Compliance Engineering	
<b>Prepared By:</b> Bay Area Compliance Laboratory Corporation 230 Commercial Street, Suite 2 Sunnyvale, CA 94086 (408) 732-9162	

**Note:** This report may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

**TABLE OF CONTENTS**

**1 - GENERAL INFORMATION ..... 3**  
    1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... 3  
**APPENDIX A –EUT BLOCK DIAGRAM..... 4**

## 1 - GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

The *Communication Network Interface, Inc.*, FCC ID *N79CNI-800D*, *RPM (RADIO PACKET MODEM)* or the "EUT" as referred to in this report is a digital data communication equipment in accordance with Motorola DataTac 5000 RD-LAP 19.2 specification. The frequency it uses ranges from 806 MHz to 821 MHz for transmission and from 851 MHz to 866 MHz for reception. The EUT measures 68.5mm L x 46.6 mm W x 10.4mm H.

Basic Specification include:

- Weight: 45g
- Power: 4.2 V from Host
- RF protocol: RD-LAP 19.2 on DataTAC 5000
- Host protocol: DataTAC NCL 1.2
- Etc.

**Appendix A –EUT BLOCK DIAGRAM**

---

