

INTERTEK TESTING SERVICES

RF Exposure

The Equipment Under Test (EUT) is a Wireless Pee Alarm operating at 433.92MHz. The EUT is powered by DC 3V by battery. For more detailed features description, please refer to the user's manual.

Modulation Type: ASK

Antenna Type: Integral antenna.

Antenna Gain: 0 dBi Max

The nominal conducted output power specified: -20dBm (+/-3dB).

The nominal radiated output power (e.i.r.p) specified: -20dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 74dB μ V/m at 3m in the frequency 433.92MHz.

The EIRP = $[(FS * D)^2 / 30]$ mW = -21.23dBm

which is within the production variation.

The maximum conducted output power specified is -17dBm = 0.02mW

The source-based time-averaging conducted output power

= 0.02 * Duty factor mW (where Duty Factor \leq 1)

= 0.02 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt(0.43392) mW

= 22.77 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.