



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20201201519E-02  
**Applicant:** KINGTA TECHNOLOGY CO., LTD  
**Address of Applicant:** 4F, Building 2, HaoJingDa Science Park, Shangmugu, Shenzhen China  
**Equipment Under Test (EUT):**  
**EUT Name:** BLUETOOTH SPEAKER  
**Model No.:** BS01, IJOY TIKI +, IJTISP03-BJ, IJTISP03, IJTISP03-MC  
**Test Model No.:** BS01  
**Brand Name:** N/A  
**FCC ID:** N7KBS01  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-12-22  
**Date of Test:** 2020-12-22 to 2020-12-29  
**Date of Issue:** 2020-12-29  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Martin Lee

( Martin Lee )

**Reviewed By:** Ares Liu

( Ares Liu )

**Approved By:** Sheek Luo

( Sheek Luo )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20201201519E-02	Rev.01	Initial report	2020-12-29

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	KINGTA TECHNOLOGY CO., LTD
Address of Applicant:	4F, Building 2, HaoJingDa Science Park, Shangmugu, Shenzhen China
Manufacturer:	KINGTA TECHNOLOGY CO., LTD
Address of Manufacturer:	4F, Building 2, HaoJingDa Science Park, Shangmugu, Shenzhen China
Factory:	KINGTA TECHNOLOGY CO., LTD
Address of Factory:	4F, Building 2, HaoJingDa Science Park, Shangmugu, Shenzhen China

#### 3.2 General Description of EUT

Product Name:	BLUETOOTH SPEAKER
Model No.:	BS01, IJOY TIKI +, IJTISP03-BJ, IJTISP03, IJTISP03-MC
Test Model No.:	BS01
Trade Mark:	N/A
Hardware Version:	V3.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	1Mbps/2Mbps/3Mbps
Transfer Rate:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	BT_Tool (manufacturer declare )
Test Software of EUT:	PCB antenna
Antenna Type:	2.0dBi
Power Supply:	lithium battery:DC3.7V, 2000mAh, Charge by DC5.0V

Note:

Model No.: BS01, IJOY TIKI +, IJTISP03-BJ, IJTISP03, IJTISP03-MC

Only the model BS01 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being of model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

#### 1) For BT

#### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.730	-2.5±1	-1.5	0.708
Middle(2441MHz)	-2.200	-3.0±1	-2.0	0.631
Highest(2480MHz)	-2.880	-3.5±1	-2.5	0.562
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.640	0±1	1.0	1.259
Middle(2441MHz)	0.220	-0.5±1	0.5	1.122
Highest(2480MHz)	-0.490	-1.0±1	0	1.000
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.130	0.5±1	1.5	1.413
Middle(2441MHz)	0.700	0±1	1.0	1.259
Highest(2480MHz)	-0.040	-1.0±1	0	1.000

Worst case: π/4DQPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.130	0.5±1	1.5	1.413	0.438	3.0
Middle (2441MHz)	0.700	0±1	1.0	1.259	0.393	
Highest (2480MHz)	-0.040	-1.0±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20201201519E-01