

# TEST REPORT

**Product Name** : Bluetooth Speaker  
**Brand Mark** : NA  
**Model No.** : F2  
**Extension Model** : TY-WSP200, TY-WSP201, OWL-BTSP06,  
BLG-SPLASH, Pro Sound, EPIC 3  
**FCC ID** : N7KF2V2  
**Report Number** : BLA-EMC-202106-A0402  
**Date of Sample Receipt** : 2021/6/1  
**Date of Test** : 2021/6/16 to 2021/6/29  
**Date of Issue** : 2021/6/29  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**KINGTA TECHNOLOGY CO., LTD**

**Floor 2, Building 10/ Floor 4, Building 9, Futing industrial zone, Zhucun,  
Guanlan, Longhua, Shenzhen**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**

**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,  
Shenzhen, Guangdong Province, China**

**TEL: +86-755-23059481**

Compiled by:

*Sven*

Review by:

*Sueels*

Approved by:

*Jmen li*

Date:

2021/6/29



## REPORT REVISE RECORD

Version No.	Date	Description
00	2021/6/29	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>6</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>7</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>7</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT.....</b>	<b>9</b>
<b>8</b>	<b>LABORATORY LOCATION.....</b>	<b>9</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>10</b>
<b>10</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>14</b>
10.1	CONCLUSION .....	14
<b>11</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>15</b>
11.1	LIMITS .....	15
11.2	BLOCK DIAGRAM OF TEST SETUP .....	15
11.3	TEST DATA.....	16
<b>12</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....</b>	<b>17</b>
12.1	LIMITS .....	17
12.2	BLOCK DIAGRAM OF TEST SETUP .....	18
12.3	PROCEDURE .....	18
12.4	TEST DATA.....	20
<b>13</b>	<b>CONDUCTED BAND EDGES MEASUREMENT.....</b>	<b>24</b>
13.1	LIMITS .....	24
13.2	BLOCK DIAGRAM OF TEST SETUP .....	24
13.3	TEST DATA.....	25
<b>14</b>	<b>DWELL TIME.....</b>	<b>26</b>
14.1	LIMITS .....	26
14.2	BLOCK DIAGRAM OF TEST SETUP .....	26
14.3	TEST DATA.....	27
<b>15</b>	<b>HOPPING CHANNEL NUMBER .....</b>	<b>28</b>

15.1	LIMITS .....	28
15.2	BLOCK DIAGRAM OF TEST SETUP .....	28
15.3	TEST DATA.....	28
<b>16</b>	<b>CARRIER FREQUENCIES SEPARATION .....</b>	<b>29</b>
16.1	LIMITS .....	29
16.2	BLOCK DIAGRAM OF TEST SETUP .....	29
16.3	TEST DATA.....	29
<b>17</b>	<b>20DB BANDWIDTH.....</b>	<b>30</b>
17.1	BLOCK DIAGRAM OF TEST SETUP .....	30
17.2	TEST DATA.....	30
<b>18</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>31</b>
18.1	LIMITS .....	31
18.2	BLOCK DIAGRAM OF TEST SETUP .....	31
18.3	TEST DATA.....	32
<b>19</b>	<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....</b>	<b>33</b>
19.1	LIMITS .....	33
19.2	BLOCK DIAGRAM OF TEST SETUP .....	33
19.3	PROCEDURE .....	33
19.4	TEST DATA.....	35
<b>20</b>	<b>RADIATED SPURIOUS EMISSIONS.....</b>	<b>37</b>
20.1	LIMITS .....	37
20.2	BLOCK DIAGRAM OF TEST SETUP .....	38
20.3	PROCEDURE .....	38
20.4	TEST DATA.....	40
<b>21</b>	<b>APPENDIX.....</b>	<b>48</b>
21.1	MAXIMUM CONDUCTED OUTPUT POWER .....	48
21.2	-20DB BANDWIDTH .....	53
21.3	OCCUPIED CHANNEL BANDWIDTH.....	58
21.4	BAND EDGE.....	63
21.5	BAND EDGE(HOPPING).....	70
21.6	CONDUCTED RF SPURIOUS EMISSION .....	77
21.7	CARRIER FREQUENCIES SEPARATION .....	87
21.8	NUMBER OF HOPPING CHANNEL .....	89

21.9	DWELL TIME .....	91
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>		<b>95</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>		<b>97</b>

BlueAsia

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	KINGTA TECHNOLOGY CO., LTD
<b>Address</b>	Floor 2, Building 10/ Floor 4, Building 9, Futing industrial zone, Zhucun, Guanlan, Longhua, Shenzhen
<b>Manufacturer</b>	KINGTA TECHNOLOGY CO., LTD
<b>Address</b>	Floor 2, Building 10/ Floor 4, Building 9, Futing industrial zone, Zhucun, Guanlan, Longhua, Shenzhen
<b>Factory</b>	KINGTA TECHNOLOGY CO., LTD
<b>Address</b>	Floor 2, Building 10/ Floor 4, Building 9, Futing industrial zone, Zhucun, Guanlan, Longhua, Shenzhen
<b>Product Name</b>	Bluetooth Speaker
<b>Test Model No.</b>	F2

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	F2-3266 -2725-MAIN-V1.2
<b>Software Version</b>	F2-3266 V2.0
<b>Operation Frequency:</b>	2402-2480MHz
<b>Modulation Type:</b>	GFSK, $\pi/4$ DQPSK, 8DPSK
<b>Channel Spacing:</b>	1MHz
<b>Number of Channels:</b>	79
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	0 dBi(Provided by the applicant)

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25℃	DC3.7V

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE )
Remark: Full battery is used during all test except ac conducted emission, DH1, DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only the 8-DPSK, of the worst mode would be recorded in this report.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB



## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A
PC	HASEE	K610D	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,  
China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.

## 9 TEST INSTRUMENTS LIST

<b>Test Equipment Of Conducted Spurious Emissions</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal.Date</b>	<b>Cal.Due</b>
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

<b>Test Equipment Of Radiated Emissions which fall in the restricted bands</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal.Date</b>	<b>Cal.Due</b>
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

<b>Test Equipment Of Conducted Band Edges Measurement</b>
---

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Dwell Time					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Hopping Channel Number					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Carrier Frequencies Separation					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11

Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of 20dB Bandwidth**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Peak Output Power**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

**Test Equipment Of Radiated Spurious Emissions**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

## 10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


### 10.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.




## 11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 11.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### 11.2 BLOCK DIAGRAM OF TEST SETUP



### 11.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia



## 12 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX Low channel;TX high channel
<b>Test Mode (Final Test)</b>	TX Low channel;TX high channel
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 12.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 12.2 BLOCK DIAGRAM OF TEST SETUP



## 12.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1:  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

### 12.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Bluetooth Speaker	Distance:	
M/N: F2		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	45.04	-2.09	42.95	74.00	-31.05	peak		
2	*	2390.000	45.26	-0.87	44.39	74.00	-29.61	peak		


\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Horizontal]

**Radiated Emission Measurement**



Site Polarization: **Horizontal** Temperature:  
 Limit: FCC Part15 (PK) Power: Humidity: %  
 EUT: Bluetooth Speaker Distance:  
 M/N: F2  
 Mode: TX-L  
 Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		2310.000	47.17	-2.09	45.08	74.00	-28.92	peak		
2	*	2390.000	49.83	-0.87	48.96	74.00	-25.04	peak		

\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]




\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature:  
 Limit: FCC Part15 (PK) Power: Humidity: %  
 EUT: Bluetooth Speaker Distance:  
 M/N: F2  
 Mode: TX-H  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		2483.500	65.09	-3.84	61.25	74.00	-12.75			peak	
2	*	2483.500	56.94	-3.84	53.10	54.00	-0.90			AVG	
3		2500.000	48.04	-3.78	44.26	74.00	-29.74			peak	

\*:Maximum data x:Over limit !:over margin (Reference Only)

**Test Result: Pass**


### 13 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

#### 13.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

#### 13.2 BLOCK DIAGRAM OF TEST SETUP





### 13.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia


## 14 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 14.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

### 14.2 BLOCK DIAGRAM OF TEST SETUP



### 14.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia


## 15 HOPPING CHANNEL NUMBER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.3
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 15.1 LIMITS

<b>Frequency range(MHz)</b>	<b>Number of hopping channels (minimum)</b>
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

### 15.2 BLOCK DIAGRAM OF TEST SETUP



### 15.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**


## 16 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 16.1 LIMITS

<b>Limit:</b>	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

### 16.2 BLOCK DIAGRAM OF TEST SETUP




### 16.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

## 17 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

### 17.1 BLOCK DIAGRAM OF TEST SETUP



### 17.2 TEST DATA

**Pass: Please Refer To Appendix: For Details**


## 18 CONDUCTED PEAK OUTPUT POWER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 18.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### 18.2 BLOCK DIAGRAM OF TEST SETUP



### 18.3 TEST DATA

**Pass: Please Refer To Appendix: For Details**

BlueAsia



## 19 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT mode
Test Mode (Final Test)	BT mode
Tester	Eason
Temperature	25°C
Humidity	52%

### 19.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 19.2 BLOCK DIAGRAM OF TEST SETUP



Remark  
 E.U.T: Equipment Under Test  
 LISN: Line Impedance Stabilization Network  
 Test table height=0.8m

### 19.3 PROCEDURE


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
  - 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
  - 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
- Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

### 19.4 TEST DATA

[TestMode: BT mode]; [Line: Line][Power:AC120V/60Hz]



**Test Result: Pass**



## 20 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX Low channel;TX middle channel;TX high channel
<b>Test Mode (Final Test)</b>	TX Low channel;TX middle channel;TX high channel
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	52%

### 20.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 20.2 BLOCK DIAGRAM OF TEST SETUP



## 20.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

## 20.4 TEST DATA

[TestMode: TX]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202106-A04
EUT: Bluetooth Speaker	Test Engineer: Sven
M/N: F2	Temperature: 25 °C
S/N:	Humidity: 45%RH
Test Mode: TX	Test Voltage:
Note:	Test Data: 2021-06-11 14:30:17




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	124.211MHz	43.5	30.4	-13.1	7.5	22.9	PK	Ver		
2*	186.413MHz	43.5	29.3	-14.2	8.1	21.2	PK	Ver		
3*	236.125MHz	46.0	40.9	-5.1	18.3	22.6	PK	Ver		
4*	422.486MHz	46.0	40.7	-5.3	13.2	27.5	PK	Ver		
5*	487.234MHz	46.0	37.3	-8.7	9.0	28.3	PK	Ver		
6*	656.135MHz	46.0	35.8	-10.2	4.2	31.6	PK	Ver		

**Test Result: Pass**



[TestMode: TX]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202106-A04
EUT: Bluetooth Speaker	Test Engineer: Sven
M/N: F2	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: TX	Test Voltage:
Note:	Test Data: 2021-06-11 14:28:34




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	43.823MHz	40.0	23.8	-16.2	-0.2	24.0	PK	Hor		
2*	153.796MHz	43.5	23.9	-19.6	0.5	23.4	PK	Hor		
3*	250.190MHz	46.0	25.2	-20.8	2.5	22.7	PK	Hor		
4*	412.544MHz	46.0	27.6	-18.4	0.2	27.4	PK	Hor		
5*	625.459MHz	46.0	32.8	-13.2	1.4	31.4	PK	Hor		
6*	949.924MHz	46.0	37.7	-8.3	2.1	35.6	PK	Hor		

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Vertical]

**Radiated Emission Measurement**



Site: Polarization: **Vertical** Temperature:  
 Limit: FCC Part15 (PK) Power: Humidity: %  
 EUT: Bluetooth Speaker Distance:  
 M/N: F2  
 Mode: TX-L  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4804.000	43.96	3.71	47.67	74.00	-26.33	peak	
2		7206.000	41.98	5.96	47.94	74.00	-26.06	peak	
3	*	9608.000	40.61	9.29	49.90	74.00	-24.10	peak	


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Horizontal]

**Radiated Emission Measurement**



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Bluetooth Speaker	Distance:	
M/N: F2		
Mode: TX-L		
Note:		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	4807.000	48.42	3.71	52.13	74.00	-21.87	peak			
2		7206.000	41.92	5.96	47.88	74.00	-26.12	peak			
3		9608.000	40.25	9.29	49.54	74.00	-24.46	peak			


\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Vertical]

**Radiated Emission Measurement**



Site: Limit: FCC Part15 (PK) EUT: Bluetooth Speaker M/N: F2 Mode: TX-M Note:

Polarization: **Vertical** Temperature: Power: Humidity: % Distance:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		4877.500	45.99	3.37	49.36	74.00	-24.64	peak			
2		7323.000	40.26	6.43	46.69	74.00	-27.31	peak			
3	*	9764.000	40.70	9.63	50.33	74.00	-23.67	peak			


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Horizontal]

**Radiated Emission Measurement**



Site: Limit: FCC Part15 (PK) EUT: Bluetooth Speaker M/N: F2 Mode: TX-M Note:

Polarization: **Horizontal** Temperature: Power: Humidity: % Distance:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	4877.500	48.89	3.37	52.26	74.00	-21.74	peak			
2		7323.000	41.82	6.43	48.25	74.00	-25.75	peak			
3		9764.000	39.90	9.63	49.53	74.00	-24.47	peak			


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]

**Radiated Emission Measurement**



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:  
 EUT: Bluetooth Speaker Power: Humidity: %  
 M/N: F2 Distance:  
 Mode: TX-H  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		4959.750	45.28	3.75	49.03	74.00	-24.97	peak			
2		7440.000	42.04	6.86	48.90	74.00	-25.10	peak			
3	*	9920.000	38.88	10.16	49.04	74.00	-24.96	peak			


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]

**Radiated Emission Measurement**



Site: Limit: FCC Part15 (PK) EUT: Bluetooth Speaker M/N: F2 Mode: TX-H Note:

Polarization: **Horizontal** Temperature: Power: Humidity: % Distance:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	4959.750	47.32	3.75	51.07	74.00	-22.93	peak			
2		7440.000	41.83	6.86	48.69	74.00	-25.31	peak			
3		9920.000	38.89	10.16	49.05	74.00	-24.95	peak			

\*:Maximum data x:Over limit !:over margin

<Reference Only


**Test Result: Pass**

## 21 APPENDIX

### 21.1 MAXIMUM CONDUCTED OUTPUT POWER


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	2.541	2.541	21	Pass
NVNT	1-DH1	2441	Ant1	2.288	2.288	21	Pass
NVNT	1-DH1	2480	Ant1	2.306	2.306	21	Pass
NVNT	2-DH1	2402	Ant1	4.171	4.171	21	Pass
NVNT	2-DH1	2441	Ant1	4.113	4.113	21	Pass
NVNT	2-DH1	2480	Ant1	4.12	4.12	21	Pass
NVNT	3-DH1	2402	Ant1	4.439	4.439	21	Pass
NVNT	3-DH1	2441	Ant1	4.318	4.318	21	Pass
NVNT	3-DH1	2480	Ant1	4.328	4.328	21	Pass

Power NVNT 1-DH1 2402MHz Ant1







Power NVNT 1-DH1 2441MHz Ant1




Power NVNT 1-DH1 2480MHz Ant1




Power NVNT 2-DH1 2402MHz Ant1




Power NVNT 2-DH1 2441MHz Ant1




Power NVNT 2-DH1 2480MHz Ant1




Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1




Power NVNT 3-DH1 2480MHz Ant1




### 21.2 -20DB BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.966	0	Pass
NVNT	1-DH1	2441	Ant1	0.961	0	Pass
NVNT	1-DH1	2480	Ant1	1.017	0	Pass
NVNT	2-DH1	2402	Ant1	1.355	0	Pass
NVNT	2-DH1	2441	Ant1	1.348	0	Pass
NVNT	2-DH1	2480	Ant1	1.356	0	Pass
NVNT	3-DH1	2402	Ant1	1.343	0	Pass
NVNT	3-DH1	2441	Ant1	1.344	0	Pass
NVNT	3-DH1	2480	Ant1	1.344	0	Pass


-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1




-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1




-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1




-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1




-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1




-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1






-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




### 21.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.9131091187
NVNT	1-DH1	2441	Ant1	0.9240635134
NVNT	1-DH1	2480	Ant1	0.892633492
NVNT	2-DH1	2402	Ant1	1.203767497
NVNT	2-DH1	2441	Ant1	1.197920858
NVNT	2-DH1	2480	Ant1	1.199043592
NVNT	3-DH1	2402	Ant1	1.197617681
NVNT	3-DH1	2441	Ant1	1.193440595
NVNT	3-DH1	2480	Ant1	1.188270456


OBW NVNT 1-DH1 2402MHz Ant1




OBW NVNT 1-DH1 2441MHz Ant1




OBW NVNT 1-DH1 2480MHz Ant1




OBW NVNT 2-DH1 2402MHz Ant1




OBW NVNT 2-DH1 2441MHz Ant1




OBW NVNT 2-DH1 2480MHz Ant1




OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1




OBW NVNT 3-DH1 2480MHz Ant1




### 21.4 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	No-Hopping	-56.76	-20	Pass
NVNT	1-DH1	2480	Ant1	No-Hopping	-49.15	-20	Pass
NVNT	2-DH1	2402	Ant1	No-Hopping	-56.45	-20	Pass
NVNT	2-DH1	2480	Ant1	No-Hopping	-48.34	-20	Pass
NVNT	3-DH1	2402	Ant1	No-Hopping	-55.55	-20	Pass
NVNT	3-DH1	2480	Ant1	No-Hopping	-47.14	-20	Pass


Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref



### Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission




### Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref







### Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission




### Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref




### Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission




### Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref




### Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission




### Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Ref




### Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



### Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission




### 21.5 BAND EDGE(HOPPING)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	Hopping	-55.22	-20	Pass
NVNT	1-DH1	2480	Ant1	Hopping	-53.05	-20	Pass
NVNT	2-DH1	2402	Ant1	Hopping	-53.88	-20	Pass
NVNT	2-DH1	2480	Ant1	Hopping	-51.93	-20	Pass
NVNT	3-DH1	2402	Ant1	Hopping	-53.81	-20	Pass
NVNT	3-DH1	2480	Ant1	Hopping	-52.09	-20	Pass


Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref




### Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission




### Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref



### Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission




### Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref







### Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission




### Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref




### Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission




### Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Ref




### Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



### Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Ref




### Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission




### 21.6 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	-36.69	-20	Pass
NVNT	1-DH1	2441	Ant1	-46.62	-20	Pass
NVNT	1-DH1	2480	Ant1	-40.29	-20	Pass
NVNT	2-DH1	2402	Ant1	-36.82	-20	Pass
NVNT	2-DH1	2441	Ant1	-36.3	-20	Pass
NVNT	2-DH1	2480	Ant1	-39.98	-20	Pass
NVNT	3-DH1	2402	Ant1	-34.45	-20	Pass
NVNT	3-DH1	2441	Ant1	-38.47	-20	Pass
NVNT	3-DH1	2480	Ant1	-36.6	-20	Pass


Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref







Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission




### 21.7 CARRIER FREQUENCIES SEPARATION

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2441.0155	2442.037	1.0215	0.961	Pass
NVNT	2-DH1	Ant1	2440.891	2442.073	1.182	0.899	Pass
NVNT	3-DH1	Ant1	2441.125	2442.154	1.029	0.896	Pass


CFS NVNT 1-DH1 2441MHz Ant1



CFS NVNT 2-DH1 2441MHz Ant1



CFS NVNT 3-DH1 2441MHz Ant1







### 21.8 NUMBER OF HOPPING CHANNEL

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass


Hopping No. NVNT 1-DH1 2441MHz Ant1



Hopping No. NVNT 2-DH1 2441MHz Ant1




Hopping No. NVNT 3-DH1 2441MHz Ant1




### 21.9 DWELL TIME

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.378	117.18	310	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.653	256.215	155	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.925	304.2	104	31600	400	Pass


Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



### Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### Conducted Emissions at AC Power Line (150kHz-30MHz)



### Radiated Spurious Emissions





**APPENDIX B: PHOTOGRAPHS OF EUT**

( Reference to the report NO.BLA-EMC-202106-A0401)

**----END OF REPORT----**

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.