

Company: Sierra Wireless, Inc.
 FCC ID: N7NAC775
 Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with Metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Internal 3V power regulator. Refer to schematics
4	Meet the antenna requirements of Section 15.203	Not applicable
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested inside a laptop.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Refer to page 60 of user manual
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	The module is in the form of a PCMCIA card. No adjustment can be made by the user.
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	Refer to RF Exposure_AC775.pdf