



*FCC Part 22 and 24 Class II Permissive Change
Test Report*

**For
800/1900 MHz CDMA DUAL BAND PC CARD**

Model: AirCard 555

FCC ID: N7NACRD555

**Prepared by
SIERRA WIRELESS INC.
13811 WIRELESS WAY
RICHMOND, BC V6V 3A4
CANADA**

Test Date(s): May / June 2002

© 2001 Sierra Wireless, Inc.

This document contains information which is proprietary and confidential to Sierra Wireless, Inc. Disclosure to persons other than the officers, employees, agents, or subcontractors of the Company or licensee of this document without the prior written permission of Sierra Wireless, Inc. is strictly prohibited.

Table of Contents

1 Introduction..... 3
 1.1 Test Summary..... 3
 1.2 Product Description..... 3
 1.3 Test Configuration 4
2 RF Power Output 5
 2.1 Test Procedure..... 5
 2.2 Test Equipment..... 5
 2.3 Test Results 6
3 Radiated Power 13
4 Occupied Bandwidth..... 14
 4.1 Test Procedure..... 14
 4.2 Test Equipment..... 14
 4.3 Test Results 14
5 Out of Band Emissions at Antenna Terminals 17
 5.1 Test Procedure..... 17
 5.2 Test Equipment..... 17
 5.3 Test Results 18
6 Field Strength of Spurious Radiation..... 42
7 Frequency Stability vs Temperature 43
 7.1 Test Procedure..... 43
 7.2 Test Equipment..... 43
 7.3 Test Results 44
8 Frequency Stability vs Voltage..... 45
 8.1 Test Procedure..... 45
 8.2 Test Equipment..... 45
 8.3 Test Results 45

SIERRA WIRELESS, INC.

1 Introduction

1.1 Test Summary

FCC RULE	DESCRIPTION OF TEST	RESULT	PAGE
2.1046	RF Power Output	Complies	6
22.913, 24.232	ERP, EIRP	Complies	*
2.1049	Occupied Bandwidth Emission Designator	Complies 1M25G7D	15
2.1051, 22.901(d) 22.917(f), 24.238(a)	Out of Band Emissions at Antenna Terminals Mobile Emissions In Base Frequency Range	Complies	18
2.1053	Field Strength of Spurious Radiation	Complies	*
2.1055	Frequency Stability vs Temperature	Complies	44
2.1055	Frequency Stability vs Voltage	Complies	45

* Separate Reports are issued.

The following tests:

- 22.913, 24.232 ERP/EIRP Measurement
- 2.1053 Field Strength of Spurious Radiation

were conducted at

Compliance Certification Services, Inc.
561F Monterey Road
Morgan Hill
CA 95037
USA

The remaining tests described in this report were performed at

Sierra Wireless, Inc.
13811 Wireless Way
Richmond, B.C. V6V 3A4
Canada

1.2 Product Description

The Sierra Wireless Inc. model AirCard 555 (FCC ID: N7NACRD555) is a dual band CDMA PCMCIA Radio Card with removable antenna. It was initially certified by the

© 2001 Sierra Wireless, Inc.

The contents of this page are subject to the confidentiality information on page one.

SIERRA WIRELESS, INC.

FCC Part 22 & 24 Test Report	FCC ID: N7NACRD555	June 2002	Page 4 of 45
------------------------------	--------------------	-----------	--------------

Commission on September 25, 2001. The description of all the changes in this Class II Permissive Change application is included in the attached file AC555change.pdf.

EUT Type	Cellular and PCS PCMCIA Card	
Whether quantity(>1) production is planned	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Standards	CMDA	
Types of Emission	1M25F9W	
RF Output Power	824.01-848.97 MHz:	23 dBm(Average)
	1850.00-1909.95 MHz:	23 dBm(Average)
Frequency Range	Cell Band TX 824.01 MHz - 848.97 MHz RX 869.01 MHz - 893.97 MHz	PCS Band TX 1850.00 MHz - 1909.95 MHz RX 1930.00 MHz - 1989.95 MHz
Antenna & Gain	Cell Band ½ wavelength Average Gain: -1.0dBi	PCS Band Full wavelength Average Gain: -2.9dBi
Detachable antenna?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Receiver L.O. frequency	1052.61 – 1077.57 MHz (Cellular) 2113.6 – 2173.6 MHz (PCS)	
External input	<input checked="" type="checkbox"/> Audio <input type="checkbox"/> Digital Data	

1.3 Test Configuration

The radio was tested with radio card installed into laptop.

Item #	Description	Model No.	Serial No.
1	EUT	AC555	E011101002110M4
2	Laptop	IBM ThinkPad iSeries	AA-G2DX7


2 RF Power Output

FCC 2.1046

2.1 Test Procedure

The transmitter output was connected to the Average Power Meter. The output power was adjusted to 23 dBm. The transmitter output was then connected to a calibrated coaxial cable, other end of which was connected to a spectrum analyzer. The resolution and video bandwidths of the spectrum analyzer were set up to 10 MHz and 10 MHz respectively. The peak power at the transmitter output was determined by adding the value of the cable loss to the spectrum analyzer reading in the reference offset level. Test were performed at three frequencies (low, middle, and high channels) in Cellular and PCS bands.

Test Setup



2.2 Test Equipment

Instrument List

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Spectrum Analyzer	Rhode & Schwarz	FSP	100060	2003-05-18
Power Meter	Anritsu	ML2408A	00440086	N/A

SIERRA WIRELESS, INC.

2.3 Test Results

Frequency (MHz)	Average Power (dBm)	Measured Peak Power (dBm)
825.25	23.0	27.06
836.5	23.0	27.70
847.75	23.0	26.93
1851.25	23.0	26.21
1880.0	23.0	26.81
1908.75	23.0	26.61

For more details refer to the attached plots:

• **Cellular Band (CDMA Mode)**

Plot Number	Description
2.1	Low Channel (Ch 8)
2.2	Middle Channel (Ch 383)
2.3	High Channel (Ch 758)

• **PCS Band (CDMA Mode)**



Plot Number	Description
2.4	Low Channel (Ch 25)
2.5	Middle Channel (Ch 600)
2.6	High Channel (Ch 1175)

SIERRA WIRELESS, INC.

Plot 2.1





AC555
 03.Jun 02 15:05
 Ref 20 dBm
 *Att 30 dB
 *RBW 30 kHz
 *VBW 300 Hz
 *SWT 4.5 s
 Marker 1 [T1]
 5.87 dBm
 825.45000000 MHz



Date: 3.JUN.2002 15:05:08

SIERRA WIRELESS, INC.


Plot 2.2



Date: 3.JUN.2002 15:02:18

SIERRA WIRELESS, INC.

Plot 2.3



Date: 3.JUN.2002 14:59:40

SIERRA WIRELESS, INC.

Plot 2.4



AC555
03.Jun 02 15:09
Ref 20.7 dBm



*Att 30 dB

*RBW 30 kHz
*VBW 300 Hz
*SWT 4.5 s

Marker 1 [T1]

6.69 dBm


1.851730000 GHz



Date: 3.JUN.2002 15:09:46

SIERRA WIRELESS, INC.


Plot 2.5



Date: 3.JUN.2002 15:14:19

SIERRA WIRELESS, INC.

Plot 2.6



Date: 3.JUN.2002 15:16:36

SIERRA WIRELESS, INC.

FCC Part 22 & 24 Test Report	FCC ID: N7NACRD555	June 2002	Page 13 of 45
------------------------------	--------------------	-----------	---------------

3 Radiated Power

FCC 22.913 & FCC 24.232

This test was performed at CCS and please refer to the attached CCS Test Report (AC555CCS_report.pdf)


4 Occupied Bandwidth

FCC 2.1049

4.1 Test Procedure

The transmitter output was connected to a calibrated coaxial cable, the other end of which was connected to a spectrum analyzer. The occupied Bandwidth (defined as the 99% Power Bandwidth) was measured with Rohde & Schwarz FSP Spectrum Analyzer.

Test Setup



4.2 Test Equipment


EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Spectrum Analyzer	Rhode & Schwarz	FSP	100060	2003-05-18

4.3 Test Results

See attached plots 4.1 and 4.2. The test results shows that the bandwidth is 1.280 MHz, which is 2.5% higher than the theoretical bandwidth for CDMA – 1.25 MHz. The Emission Designator was determined as 1M25G7D.

SIERRA WIRELESS, INC.


Plot 4.1 Cellular Band (Middle Channel)



Date: 30.MAY.2002 11:12:04

SIERRA WIRELESS, INC.

Plot 4.2 PCS Band (Middle Channel)



Date: 30.MAY.2002 11:17:59

5 Out of Band Emissions at Antenna Terminals

FCC 22.901(d), 22.917(f), 24.238(a)

Out of Band Emissions:

The mean power of emissions must be attenuated below the mean power of the unmodulated carrier(P) on any frequency outside the frequency band by at least $(43 + 10 \log P)$ dB, in this case, -13dBm.


Mobile Emissions in Base Frequency Range:

The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitters operated must be attenuated to a level not exceed -80 dBm at the transmit antenna connector.

5.1 Test Procedure

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. The EUT was scanned for spurious emissions from 1MHz to 20GHz with sufficient bandwidth and video resolution. Data plots were recorded only for the frequency range where out of band emissions at the antenna terminal were detected.

Test Setup



5.2 Test Equipment

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Spectrum Analyzer	Rhode & Schwarz	FSP	100060	2003-05-18

5.3 Test Results

Refer to the attached plots.

- **Cellular Band**

Plot Number	Description
5.1a – 5.1b	Low Channel, 825.25 MHz
5.2a – 5.2b	Middle Channel, 836.50 MHz
5.3a – 5.3d	High Channel, 847.75 MHz

- **PCS Band**


Plot Number	Description
5.4a – 5.4d	Low Channel, 1851.25 MHz
5.5a – 5.5d	Middle Channel, 1880 MHz
5.6a – 5.6d	High Channel, 1908.75 MHz


- **Emission to Base Frequency Range**

Plot Number	Description
5.7a	Low Channel, 825.25 MHz
5.7b	Middle Channel, 836.50 MHz
5.7c	High Channel, 847.75 MHz

SIERRA WIRELESS, INC.

Plot 5.1a

 AC555 *RBW 30 kHz Marker 1 [T1]
03.Jun 02 11:07 *VBW 30 kHz -29.74 dBm
Ref 21 dBm *Att 30 dB *SWT 55 ms 826.066000000 MHz



Date: 3.JUN.2002 11:07:22


SIERRA WIRELESS, INC.

Plot 5.1b



```


AC555                                     *RBW 1 MHz      Marker 1 [T1]
03.Jun 02 11:04                          *VBW 1 MHz      -43.38 dBm
Ref 19 dBm                               *Att 30 dB      *SWT 400 ms    1.64600000 GHz
    
```



Date: 3.JUN.2002 11:04:49

SIERRA WIRELESS, INC.

Plot 5.2a




Date: 3.JUN.2002 11:13:12

SIERRA WIRELESS, INC.

Plot 5.2b




AC555 *RBW 1 MHz Marker 1 [T1]
03.Jun 02 11:24 *VBW 10 MHz -39.84 dBm
Ref 20 dBm *Att 30 dB *SWT 500 ms 1.646000000 GHz



Date: 3.JUN.2002 11:24:23

SIERRA WIRELESS, INC.

Plot 5.3b




Date: 3.JUN.2002 11:30:22

SIERRA WIRELESS, INC.

Plot 5.3c



AC555 *RBW 30 kHz Marker 1 [T1]
03.Jun 02 11:41 *VBW 30 kHz -33.51 dBm
Ref 11 dBm *Att 30 dB *SWT 50 ms 849.052000000 MHz



Date: 3.JUN.2002 11:41:54

SIERRA WIRELESS, INC.

Plot 5.3d



AC555

03.Jun 02 11:43

Ref 11 dBm

*RBW 1 MHz


*VBW 1 MHz

*SWT 500 ms

Marker 1 [T1]

-41.67 dBm

1.680000000 GHz




Date: 3.JUN.2002 11:43:53

SIERRA WIRELESS, INC.

Plot 5.4a

AC555
03.Jun 02 11:52
Ref 1.7 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -48.25 dBm
*SWT 300 ms 111.48000000 MHz




Date: 3.JUN.2002 11:52:43

SIERRA WIRELESS, INC.

Plot 5.4b

AC555 *RBW 1 MHz Marker 1 [T1]
03.Jun 02 11:57 *VBW 1 MHz -59.26 dBm
Ref 1.7 dBm *Att 30 dB *SWT 50 ms 1.039100000 GHz



Date: 3.JUN.2002 11:57:26

SIERRA WIRELESS, INC.


Plot 5.4c



AC555
03.Jun 02 11:47
Ref 20 dBm

*Att 30 dB


*RBW 30 kHz Marker 1 [T1]
*VBW 30 kHz -19.82 dBm
*SWT 50 ms 1.852058000 GHz



Date: 3.JUN.2002 11:47:36

SIERRA WIRELESS, INC.

Plot5.4d




Date: 3.JUN.2002 12:00:44

SIERRA WIRELESS, INC.

Plot 5.5a



AC555
03.Jun 02 12:06
Ref 11.7 dBm
*RBW 100 kHz
*VBW 100 kHz
*Att 30 dB
*SWT 300 ms
Marker 1 [T1]
-48.03 dBm
140.58000000 MHz




Date: 3.JUN.2002 12:06:29

SIERRA WIRELESS, INC.

Plot 5.5b



AC555 *RBW 1 MHz Marker 1 [T1]
03.Jun 02 12:08 *VBW 10 MHz -56.63 dBm
Ref 11.7 dBm *Att 30 dB *SWT 50 ms 1.081600000 GHz




Date: 3.JUN.2002 12:08:43

SIERRA WIRELESS, INC.

Plot 5.5c



AC555
03.Jun 02 12:02
Ref 20 dBm
*Att 30 dB
*RBW 30 kHz
*VBW 30 kHz
*SWT 100 ms
Marker 1 [T1]
-19.55 dBm
1.880816000 GHz



Date: 3.JUN.2002 12:02:56


SIERRA WIRELESS, INC.

Plot 5.5d



AC555
03.Jun 02 12:11
Ref 11.7 dBm *Att 30 dB

*RBW 1 MHz Marker 1 [T1] -42.07 dBm
*VBW 10 MHz
*SWT 500 ms 3.728000000 GHz




Date: 3.JUN.2002 12:11:18

SIERRA WIRELESS, INC.

Plot 5.6a



AC555
03.Jun 02 12:14
Ref 20 dBm
*RBW 100 kHz
*VBW 100 kHz
*Att 30 dB
*SWT 300 ms
Marker 1 [T1]
-51.75 dBm
169.68000000 MHz




Date: 3.JUN.2002 12:14:38

SIERRA WIRELESS, INC.

Plot 5.6b



AC555 *RBW 1 MHz Marker 1 [T1]
03.Jun 02 12:15 *VBW 10 MHz -57.07 dBm
Ref 20 dBm *Att 30 dB *SWT 50 ms 1.12410000 GHz




Date: 3.JUN.2002 12:15:50

SIERRA WIRELESS, INC.

Plot 5.6c




AC555
03.Jun 02 12:13
Ref 20 dBm
*RBW 30 kHz
*VBW 30 kHz
*SWT 100 ms
Marker 1 [T1]
-20.80 dBm
1.909550000 GHz




Date: 3.JUN.2002 12:13:23

SIERRA WIRELESS, INC.

Plot 5.6d


 AC555 *RBW 1 MHz Marker 1 [T1]
03.Jun 02 12:16 *VBW 10 MHz -36.79 dBm
Ref 20 dBm *Att 30 dB *SWT 500 ms 3.800000000 GHz



Date: 3.JUN.2002 12:16:47

SIERRA WIRELESS, INC.


Plot 5.7a



Date: 19.JUN.2002 13:38:18

SIERRA WIRELESS, INC.


Plot 5.7b



Date: 19.JUN.2002 13:38:45

SIERRA WIRELESS, INC.

Plot 5.7c



Date: 19.JUN.2002 13:39:17

6 Field Strength of Spurious Radiation

FCC 2.1053, 22.901(d), 24.238(a)

This test was performed at CCS and please refer to the attached CCS Test Report (AC555CCS_report.pdf)

SIERRA WIRELESS, INC.


7 Frequency Stability vs Temperature

FCC 2.1055

7.1 Test Procedure

The AC555 was placed inside the temperature chamber. After the temperature stabilized for approximately 20 minutes, the transmitting frequency was recorded.

Test Setup



7.2 Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	SERIAL NO.	CAL. DUE DATE
Wireless Test Set	Agilent	8960	GB41070182	2003-06-27
DC Power Supply	Hewlett Packard	E3631A	KR94624200	N/A
Temperature Chamber	Sigma Systems	M30M	7454	N/N

SIERRA WIRELESS, INC.

7.3 Test Results

Transmitting Frequency: 1880 MHz

Temperature (°C)	Frequency (MHz)	Difference (Hz)
-30	1879.995	2.3
-20	1879.994	7.0
-10	1879.995	-6.1
0	1879.994	4.6
10	1879.995	1.2
20	1879.996	3.7
30	1879.995	-2.1
40	1879.994	-5.1
50	1879.994	-3.1

Note: The measured frequency stability vs temperature for the Cellular band is identical (% difference) to the above table since the transmitting frequency is locked to the same oscillator.

SIERRA WIRELESS, INC.

FCC Part 22 & 24 Test Report	FCC ID: N7NACRD555	June 2002	Page 45 of 45
------------------------------	--------------------	-----------	---------------

8 Frequency Stability vs Voltage

FCC 2.1055

8.1 Test Procedure

The AC555 was connected to a DC Power Supply. The voltage was set to 115% of the nominal voltage and was then decreased to 85% of the nominal value. The output frequency was recorded for each voltage setting.

Test Setup

Refer to Section 8.1

8.2 Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	SERIAL NO.	CAL. DUE DATE
Wireless Test Set	Agilent	8960	GB41070182	2003-06-27
DC Power Supply	Hewlett Packard	E3631A	KR94624200	N/A
Temperature Chamber	Sigma Systems	M30M	7454	N/A

8.3 Test Results

Transmitting Frequency : 837 MHz

Vcc (Volts)	Frequency (MHz)	Difference (Hz)
4.0	836.995	-4.5
6.0	836.993	1.4

Transmitting Frequency: 1880 MHz

Vcc (Volts)	Frequency (MHz)	Difference (Hz)
4.0	1879.994	-6.0
6.0	1879.992	-2.2