

FCC SAR Test Report

Report No. : SA150925C05
Applicant : Sierra Wireless Inc.
Address : 13811 Wireless Way, Richmond, BC, Canada
Product : Wireless Modules
FCC ID : N7NEM7455-D2
Brand : Sierra Wireless
Model No. : EM7455
Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE Std 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r01
KDB 248227 D01 v02r02 / KDB 447498 D01 v06
KDB 616217 D04 v01r02 / KDB 941225 D01 v03r01 / KDB 941225 D05 v02r04
Sample Received Date : Sep. 25, 2015
Date of Testing : Sep. 24, 2015 ~ Nov. 06, 2015

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

Evonne Liu
Evonne Liu / Specialist

Approved By :

Gordon Lin
Gordon Lin / Assistant Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	7
3.1 Definition of Specific Absorption Rate (SAR)	7
3.2 SPEAG DASY System	7
3.2.1 Robot.....	8
3.2.2 Probes.....	9
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	10
3.2.5 Device Holder.....	11
3.2.6 System Validation Dipoles.....	11
3.2.7 Tissue Simulating Liquids.....	12
3.3 SAR System Verification	15
3.4 SAR Measurement Procedure	16
3.4.1 Area & Zoom Scan Procedure	16
3.4.2 Volume Scan Procedure.....	16
3.4.3 Power Drift Monitoring.....	17
3.4.4 Spatial Peak SAR Evaluation	17
3.4.5 SAR Averaged Methods	17
4. SAR Measurement Evaluation	18
4.1 EUT Configuration and Setting.....	18
4.2 EUT Testing Position	29
4.2.1 Simultaneous Transmission Possibilities	30
4.3 Tissue Verification	31
4.4 System Validation.....	31
4.5 System Verification.....	32
4.6 Maximum Output Power.....	33
4.6.1 Maximum Conducted Power	33
4.6.2 Measured Conducted Power Result.....	35
4.7 SAR Testing Results	58
4.7.1 SAR Test Reduction Considerations	58
4.7.2 SAR Results for Body Exposure Condition	59
EUT 1 (Thin cover)	59
4.7.3 SAR Measurement Variability.....	69
4.7.4 Simultaneous Multi-band Transmission Evaluation	70
5. Calibration of Test Equipment.....	195
6. Measurement Uncertainty.....	196
7. Information on the Testing Laboratories.....	198
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of EUT and Setup	



Release Control Record

Report No.	Reason for Change	Date Issued
SA150925C05	Initial release	Nov. 09, 2015

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Body SAR _{1g} (W/kg)	
		EUT 1 (Thin cover)	EUT 2 (Thick cover)
PCB	WCDMA II	1.29	1.33
	WCDMA IV	0.99	0.94
	WCDMA V	1.03	1.10
	LTE 2	1.13	0.91
	LTE 4	0.88	0.95
	LTE 5	0.72	0.70
	LTE 7	1.29	1.33
	LTE 12	0.93	0.85
	LTE 13	0.90	0.90
	LTE 25	1.09	1.04
	LTE 26	1.09	0.95
	LTE 30	1.17	1.07
	LTE 41	0.94	1.35
DTS	2.4G WLAN	1.18	-
NII	5.3G WLAN	0.90	-
	5.6G WLAN	1.38	-
	5.8G WLAN	0.92	-
DSS	Bluetooth	0.34	-
DXX	NFC	N/A	N/A
Highest Simultaneous Transmission SAR		Body (W/kg)	
PCB + DTS Ant0 + DTS Ant1		1.58	-
PCB + NII Ant0 + NII Ant1		1.41	-
PCB + DTS Ant0 + DSS Ant1		1.41	-
PCB + NII Ant0 + DSS Ant1		1.52	-

Note:

- The SAR limit (**Head & Body: SAR_{1g} 1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.
- Since the models of T04E have the same WLAN and BT feature, the test data for WLAN SAR in RF Exposure Lab report is referring to SAR report (Test Report No.: SAR.20151007, Issue Date: Oct. 14-15, 2015).

2. Description of Equipment Under Test

EUT Type	Wireless Modules
FCC ID	N7NEM7455-D2
Brand Name	Sierra Wireless
Model Name	EM7455
EUT Configurations	EUT 1 : EUT (Thin cover) + WWAN Module + BT/WLAN Module + NFC Module 1 EUT 2 : EUT (Thick cover) + WWAN Module + BT/WLAN Module + NFC Module 2
Tx Frequency Bands (Unit: MHz)	WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 12 : 699.7 ~ 715.3 (1.4M), 700.5 ~ 714.5 (3M), 701.5 ~ 713.5 (5M), 704 ~ 711 (10M) LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M) LTE Band 25 : 1850.7 ~ 1914.3 (1.4M), 1851.5 ~ 1913.5 (3M), 1852.5 ~ 1912.5 (5M), 1855 ~ 1910 (10M), 1857.5 ~ 1907.5 (15M), 1860 ~ 1905 (20M) LTE Band 26 : 814.7 ~ 848.3 (1.4M), 815.5 ~ 847.5 (3M), 816.5 ~ 846.5 (5M), 819 ~ 844 (10M), 821.5 ~ 841.5 (15M) LTE Band 30 : 2307.5 ~ 2312.5 (5M), 2310 (10M) LTE Band 41 : 2498.5 ~ 2687.5 (5M), 2501 ~ 2685 (10M), 2503.5 ~ 2682.5 (15M), 2506 ~ 2680 (20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 NFC : 13.56
Uplink Modulations	WCDMA : QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK NFC : ASK
Maximum Tune-up Conducted Power (Unit: dBm)	WCDMA Band II : 24.0 WCDMA Band IV : 24.0 WCDMA Band V : 24.0 LTE Band 2 : 24.0 LTE Band 4 : 24.0 LTE Band 5 : 24.0 LTE Band 7 : 23.0 LTE Band 12 : 24.0 LTE Band 13 : 24.0 LTE Band 25 : 24.0 LTE Band 26 : 24.0 LTE Band 30 : 23.0 LTE Band 41 : 23.0 WLAN 2.4G : 15.0 WLAN 5.2G : 13.5 WLAN 5.3G : 13.5 WLAN 5.6G : 13.5 WLAN 5.8G : 13.5 Bluetooth : 11.5
Antenna Type	Fixed Internal Antenna
EUT Stage	Production Unit

Note:

- The EUT is authorized for use in specific End-product. Please refer to below table for more details.

Item	Brand Name	Model Name
Portable Computer - Tablet	Dell	T04E

FCC SAR Test Report

2. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

List of Accessory:

BT/WLAN Module	Brand Name	Intel
	Model Name	8260NGW
NFC Module 1	Brand Name	Wistron NeWeb Corporation
	Model Name	DFCN-4
NFC Module 2	Brand Name	Dell
	Model Name	DWRFID1502

FCC SAR Test Report

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

FCC SAR Test Report




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig-3.2 DASY4



Fig-3.3 DASY5

FCC SAR Test Report

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

FCC SAR Test Report

3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

FCC SAR Test Report

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	


3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

FCC SAR Test Report

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

The following table gives the recipes for tissue simulating liquids.


Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

FCC SAR Test Report

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

FCC SAR Test Report

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

FCC SAR Test Report

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Considerations Related to Proximity Sensor>

The device supports WWAN, WLAN, and Bluetooth capabilities. It is designed with a proximity sensor which can trigger/not trigger power reduction for WCDMA and LTE on Rear Face and Top Side of EUT for SAR compliance. Others RF capability (WLAN and Bluetooth) have no power reduction. The power levels for all wireless technologies and the power reduction please refer to section 4.6 of this report.

Proximity Sensor Triggering Distances (KDB 616217 D04 §6.2)

The proximity sensor triggering distance was determined per KDB 616217 for rear face and applicable edge. Summary for power verification per distance was tabulated in the below table.

EUT 1 (Thin cover)

Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	0	1	2	3	4	5	6	7	8	9	10
WCDMA II	17.6	18.0	17.6	17.5	18.0	17.9	18.0	17.8	17.5	17.9	17.9
WCDMA IV	18.6	18.7	18.7	18.8	18.5	18.6	19.0	18.6	18.8	19.0	18.5
WCDMA V	20.8	20.5	20.9	20.5	21.0	20.8	20.5	20.7	20.7	20.5	20.6
LTE 2	19.0	18.9	18.9	18.8	18.6	18.8	18.8	18.8	18.6	18.6	18.8
LTE 4	18.0	17.8	17.8	17.7	17.6	17.6	17.9	18.0	17.7	17.5	17.7
LTE 5	19.8	19.9	19.5	19.9	19.6	20.0	19.5	19.6	19.7	19.8	19.6
LTE 7	17.7	17.6	17.9	17.6	17.9	17.9	17.8	17.6	17.5	18.0	17.7
LTE 12	19.6	19.8	19.6	19.5	19.9	19.6	19.8	19.5	20.0	19.9	19.6
LTE 13	19.8	19.6	19.6	19.7	19.8	20.0	19.6	20.0	19.6	19.9	20.0
LTE 25	18.8	18.6	19.0	18.7	18.8	18.9	18.7	18.5	18.5	18.6	18.8
LTE 26	20.9	20.8	21.0	20.9	20.9	20.5	20.6	20.8	20.8	20.7	20.6
LTE 30	16.7	16.6	16.9	16.9	17.0	17.0	16.9	16.6	17.0	16.7	17.0
LTE 41	18.5	18.8	18.6	19.0	18.5	18.9	18.8	19.0	19.0	18.6	18.8
Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	11	12	13	14	15	16	17	18	19	20	21
WCDMA II	17.6	17.5	17.7	17.8	17.8	17.8	17.6	18.0	23.9	23.6	23.9
WCDMA IV	18.5	18.7	19.0	18.9	18.6	18.9	18.5	18.9	23.8	23.6	24.0
WCDMA V	20.5	20.6	20.6	21.0	21.0	20.6	20.6	20.6	23.6	23.9	23.5
LTE 2	18.5	18.8	18.6	18.8	19.0	19.0	19.0	18.6	23.6	23.8	23.5
LTE 4	17.5	17.7	18.0	17.8	17.5	17.8	17.5	18.0	23.7	24.0	23.8
LTE 5	19.6	20.0	19.6	19.9	20.0	19.7	20.0	19.7	23.6	23.9	23.6
LTE 7	17.8	17.6	18.0	17.6	17.8	18.0	17.8	17.5	22.5	22.7	22.8
LTE 12	19.6	19.7	19.9	19.8	19.7	19.6	19.5	19.7	23.6	23.5	24.0
LTE 13	20.0	19.9	20.0	19.5	19.7	19.9	19.6	20.0	24.0	23.9	23.8
LTE 25	19.0	18.9	18.9	18.7	18.7	18.8	18.5	18.9	23.7	23.8	24.0
LTE 26	20.6	20.8	20.5	20.8	20.9	20.8	20.7	21.0	23.6	23.9	23.5
LTE 30	16.8	16.9	16.8	16.5	16.5	16.8	16.5	16.8	23.0	22.7	22.7
LTE 41	18.6	18.7	18.8	19.0	18.9	18.7	18.8	19.0	22.5	22.6	23.0
Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	22	23									
WCDMA II	23.8	23.7									
WCDMA IV	23.5	23.7									
WCDMA V	23.9	23.7									
LTE 2	23.5	24.0									
LTE 4	23.8	23.8									
LTE 5	23.7	24.0									
LTE 7	22.9	23.0									
LTE 12	24.0	24.0									
LTE 13	23.7	24.0									
LTE 25	23.8	23.5									
LTE 26	23.7	23.5									
LTE 30	22.8	22.7									
LTE 41	22.9	22.7									


Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	0	1	2	3	4	5	6	7	8	9	10
WCDMA II	17.5	18.0	18.0	18.0	17.9	17.6	17.9	17.7	17.8	17.5	17.5
WCDMA IV	19.0	19.0	18.9	19.0	18.9	18.5	18.7	19.0	18.7	18.5	18.8
WCDMA V	20.5	20.7	20.8	20.8	20.9	20.5	20.6	20.8	20.9	20.9	20.8
LTE 2	18.9	18.9	18.7	18.6	18.5	18.8	18.6	18.9	18.7	18.9	19.0
LTE 4	17.5	17.6	17.9	17.6	17.5	17.9	17.5	17.8	17.9	17.9	17.9
LTE 5	19.7	19.8	20.0	20.0	19.5	19.5	19.8	19.8	19.5	19.7	19.5
LTE 7	17.6	17.6	17.8	17.7	18.0	17.9	17.7	17.7	17.6	17.9	17.8
LTE 12	20.0	19.5	19.7	19.8	19.5	19.8	19.7	19.6	19.6	19.9	19.9
LTE 13	19.9	19.6	19.8	19.9	19.9	19.7	19.6	19.8	19.8	19.6	19.7
LTE 25	18.5	18.9	18.9	18.5	19.0	18.8	18.7	18.5	18.5	18.6	18.9
LTE 26	20.9	21.0	20.7	20.6	20.7	20.5	20.5	20.6	20.8	20.9	20.7
LTE 30	17.0	16.8	16.9	16.6	16.8	16.8	16.7	16.7	17.0	16.8	16.9
LTE 41	18.9	18.9	18.8	18.6	18.8	19.0	18.7	18.8	18.9	18.7	18.7
Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	11	12	13	14	15	16	17	18	19	20	21
WCDMA II	17.7	17.7	17.7	18.0	17.5	18.0	17.9	18.0	17.5	17.7	17.6
WCDMA IV	18.5	18.8	18.5	18.9	18.6	18.9	18.7	18.6	19.0	18.9	18.5
WCDMA V	20.6	20.6	20.5	20.7	20.6	20.8	20.9	20.7	20.7	20.7	20.8
LTE 2	18.8	18.5	18.5	18.7	18.8	18.6	18.5	18.8	18.7	18.9	18.8
LTE 4	17.7	17.7	18.0	17.9	17.8	17.9	17.9	17.7	18.0	18.0	17.8
LTE 5	19.5	19.8	19.6	20.0	19.7	19.5	19.7	19.6	19.6	19.9	19.8
LTE 7	17.6	17.9	17.5	18.0	17.5	17.7	17.6	18.0	17.5	17.6	17.5
LTE 12	19.5	19.5	19.8	20.0	19.8	19.6	19.7	19.9	19.6	19.7	20.0
LTE 13	19.5	19.8	19.5	19.5	19.8	19.7	20.0	19.7	19.8	19.6	20.0
LTE 25	18.7	19.0	18.8	18.5	18.7	18.7	18.5	18.9	19.0	18.6	18.6
LTE 26	20.8	21.0	20.6	20.7	20.9	21.0	20.8	21.0	20.9	20.8	20.9
LTE 30	16.8	16.7	16.8	16.6	16.7	16.9	16.6	16.7	16.5	16.5	16.9
LTE 41	19.0	18.5	18.6	18.6	18.6	18.7	18.6	18.7	18.7	18.8	19.0
Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	22	23	24	25	26	27	28	29	30	31	32
WCDMA II	17.6	17.9	18.0	17.6	17.6	17.6	23.6	23.6	24.0	23.9	23.9
WCDMA IV	19.0	18.6	18.5	18.6	19.0	18.6	23.5	23.7	23.8	23.6	23.9
WCDMA V	20.5	20.6	20.7	20.7	20.6	20.7	23.6	23.7	24.0	23.5	24.0
LTE 2	18.9	18.8	18.9	18.7	18.8	19.0	23.8	23.9	23.8	23.6	23.9
LTE 4	17.7	17.7	17.8	17.7	17.7	17.5	23.5	23.5	23.5	23.6	24.0
LTE 5	20.0	19.6	19.9	20.0	19.6	19.9	23.5	23.6	23.7	24.0	23.7
LTE 7	17.9	18.0	17.6	17.7	17.9	18.0	22.5	22.6	22.8	22.5	22.5
LTE 12	20.0	19.7	19.5	19.9	19.7	19.6	23.6	23.9	23.7	23.9	23.8
LTE 13	19.7	19.9	19.6	19.8	19.9	19.7	23.7	23.6	23.5	23.7	23.7
LTE 25	18.5	18.6	18.9	18.9	18.9	18.7	23.9	23.9	23.5	23.6	23.5
LTE 26	20.7	20.9	20.6	20.9	21.0	20.8	23.8	23.5	23.7	23.8	23.6
LTE 30	16.9	16.6	16.5	16.7	17.0	16.5	22.5	22.9	22.6	22.8	22.7
LTE 41	19.0	19.0	18.8	19.0	18.8	19.0	22.9	22.6	22.7	22.9	22.7

Proximity Sensor Coverage (KDB 616217 D04 §6.3)

Since the proximity sensor is collocated with antenna in one component, the procedure for proximity sensor coverage is not required.

Proximity Sensor Tilt Angle Influences (KDB 616217 D04 §6.4)

The proximity sensor tilt angle influence was determined per KDB 616217 for applicable edge. Summary for proximity sensor tilt angle influence is shown in below.



Orientation	Separation Distance (cm)	Tilt Angle											
		-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°	
Top Edge	2.7	On	On	On	On	On	On	On	On	On	On	On	

FCC SAR Test Report

A D T

EUT 2 (Thick cover)

Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	0	1	2	3	4	5	6	7	8	9	10
WCDMA II	17.9	17.7	17.8	18.0	17.5	17.6	17.7	17.6	17.8	17.9	17.6
WCDMA IV	18.5	18.8	18.5	18.6	18.8	18.5	18.7	18.6	18.9	18.5	18.5
WCDMA V	20.9	20.8	21.0	20.8	20.7	21.0	20.5	20.7	20.5	20.9	21.0
LTE 2	18.9	18.9	18.7	19.0	18.6	18.5	18.5	18.6	18.7	18.6	19.0
LTE 4	18.0	17.6	17.9	17.7	17.6	17.9	17.7	17.6	17.7	17.5	17.9
LTE 5	19.6	19.7	20.0	19.8	19.9	19.6	19.6	20.0	19.9	20.0	19.5
LTE 7	17.9	17.5	17.5	17.7	17.5	17.9	17.5	17.8	17.7	17.6	17.7
LTE 12	20.0	19.8	19.8	19.6	20.0	19.6	19.7	19.8	20.0	19.9	19.6
LTE 13	19.5	20.0	19.8	19.5	20.0	20.0	19.7	19.9	19.9	20.0	20.0
LTE 25	18.5	18.6	18.6	18.6	18.7	19.0	18.5	18.8	18.7	18.8	18.8
LTE 26	21.0	20.6	20.7	20.8	20.8	20.5	20.8	21.0	20.8	20.9	20.7
LTE 30	17.0	16.6	17.0	16.7	16.8	16.7	16.5	16.5	16.5	16.9	16.5
LTE 41	18.5	18.8	19.0	18.7	18.6	18.5	18.7	18.6	18.6	18.8	18.6
Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	11	12	13	14	15	16	17	18	19	20	21
WCDMA II	17.8	17.9	17.7	17.6	17.6	17.5	17.7	24.0	23.7	23.5	23.8
WCDMA IV	18.7	18.9	18.7	18.8	18.8	18.9	18.9	23.6	23.6	23.8	23.9
WCDMA V	20.9	20.8	20.6	20.6	21.0	20.6	20.7	23.6	23.8	23.9	23.7
LTE 2	18.6	18.7	19.0	18.9	18.6	18.6	18.9	24.0	23.6	23.9	23.6
LTE 4	17.5	17.8	17.6	17.5	18.0	17.7	17.5	23.5	23.9	23.7	23.6
LTE 5	19.8	19.6	19.5	19.8	19.5	19.7	19.7	23.6	23.6	23.9	23.5
LTE 7	17.8	17.9	17.5	17.7	17.5	17.7	17.8	23.0	22.7	22.6	22.9
LTE 12	19.6	19.8	19.6	19.7	19.8	19.7	19.7	23.8	23.8	23.8	23.5
LTE 13	19.6	20.0	19.9	19.9	20.0	19.6	19.9	23.5	23.6	23.8	23.8
LTE 25	18.5	18.9	18.7	19.0	18.9	18.7	18.8	23.9	23.8	23.5	23.7
LTE 26	20.6	20.5	20.8	20.5	20.7	20.7	20.8	23.6	23.5	23.7	23.9
LTE 30	16.9	16.9	16.9	16.5	17.0	16.6	16.9	22.9	22.6	22.9	22.9
LTE 41	18.8	18.7	19.0	18.5	18.9	19.0	18.7	22.8	22.6	22.6	23.0
Output Power Verification in dBm for EUT Rear Face											
Distance (mm)	22										
WCDMA II	24.0										
WCDMA IV	23.8										
WCDMA V	23.8										
LTE 2	23.9										
LTE 4	23.5										
LTE 5	23.5										
LTE 7	22.5										
LTE 12	23.8										
LTE 13	23.6										
LTE 25	24.0										
LTE 26	23.8										
LTE 30	22.7										
LTE 41	22.8										


Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	0	1	2	3	4	5	6	7	8	9	10
WCDMA II	18.0	17.5	17.6	17.5	17.7	17.8	17.8	17.8	18.0	17.7	17.7
WCDMA IV	19.0	18.7	18.7	18.6	19.0	18.7	19.0	18.5	18.9	18.6	19.0
WCDMA V	20.9	20.5	20.9	20.8	21.0	20.5	20.8	20.7	20.7	20.7	20.6
LTE 2	18.7	18.9	18.6	18.5	18.9	18.7	18.5	18.5	18.9	18.5	18.8
LTE 4	17.5	17.8	17.7	17.6	17.6	17.6	17.5	17.7	17.6	17.7	17.8
LTE 5	19.6	19.9	19.6	20.0	19.8	19.5	19.7	19.9	19.6	20.0	20.0
LTE 7	17.8	17.7	17.7	17.6	17.6	17.6	17.8	18.0	17.7	18.0	17.9
LTE 12	19.5	19.9	19.8	20.0	19.9	19.8	19.7	19.9	19.8	19.8	19.8
LTE 13	20.0	19.7	19.9	19.9	19.8	19.6	19.5	20.0	19.7	19.7	19.6
LTE 25	18.5	19.0	18.7	18.6	18.9	18.8	19.0	18.9	18.7	18.6	18.5
LTE 26	20.7	21.0	20.8	20.7	21.0	20.8	20.7	21.0	20.5	20.6	20.8
LTE 30	16.7	16.7	16.7	16.7	16.5	17.0	17.0	16.6	16.9	16.7	17.0
LTE 41	18.7	18.8	18.5	19.0	18.5	18.7	18.9	18.5	18.5	18.7	18.8
Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	11	12	13	14	15	16	17	18	19	20	21
WCDMA II	17.6	17.9	18.0	18.0	17.5	17.9	18.0	17.9	17.7	17.5	17.7
WCDMA IV	18.9	19.0	18.9	19.0	18.8	19.0	18.5	18.7	18.8	18.6	19.0
WCDMA V	20.5	20.7	20.7	20.8	20.6	20.7	21.0	20.8	20.9	20.8	20.7
LTE 2	18.7	18.6	18.7	18.8	18.5	18.5	18.9	19.0	18.6	18.6	19.0
LTE 4	17.7	17.7	17.8	18.0	17.5	17.6	17.5	17.9	18.0	17.5	17.5
LTE 5	19.5	19.8	19.6	19.6	19.8	19.5	19.8	19.5	19.8	19.6	19.9
LTE 7	17.8	17.8	17.5	17.9	17.7	17.7	18.0	17.5	17.7	17.9	17.5
LTE 12	20.0	19.7	20.0	20.0	19.7	19.5	19.7	19.8	19.6	19.9	19.8
LTE 13	19.9	19.8	19.7	19.5	19.5	20.0	19.8	19.6	19.6	19.7	19.8
LTE 25	18.6	18.6	18.5	18.8	18.5	18.6	18.9	19.0	18.8	18.7	19.0
LTE 26	20.6	20.7	20.8	21.0	21.0	21.0	20.8	20.5	20.5	21.0	20.5
LTE 30	16.8	16.6	16.8	16.9	16.9	16.6	17.0	17.0	16.7	16.7	16.6
LTE 41	19.0	18.7	18.6	18.5	18.9	18.5	18.7	18.5	18.9	18.5	18.5
Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	22	23	24	25	26	27	28	29	30	31	32
WCDMA II	17.6	17.6	17.6	18.0	17.9	17.8	17.6	17.8	17.8	17.7	23.5
WCDMA IV	18.8	18.5	18.5	19.0	18.8	18.7	19.0	18.5	18.7	19.0	23.5
WCDMA V	20.6	20.6	20.5	20.5	20.6	20.8	20.7	20.8	20.7	20.7	23.8
LTE 2	18.5	18.9	18.7	18.9	19.0	19.0	19.0	18.7	19.0	18.9	23.6
LTE 4	17.7	17.6	17.6	17.9	18.0	17.8	17.5	17.6	17.6	17.8	23.7
LTE 5	19.5	19.5	19.9	19.7	19.8	19.8	19.8	19.7	19.7	19.9	23.6
LTE 7	17.8	17.9	17.7	17.6	17.9	17.8	17.8	17.6	17.5	18.0	22.7
LTE 12	20.0	19.5	19.6	19.5	19.8	19.5	19.8	19.7	19.5	19.5	23.5
LTE 13	19.6	19.5	19.9	19.6	19.7	20.0	19.8	19.7	19.6	19.6	23.6
LTE 25	19.0	18.7	18.5	18.6	18.8	18.9	18.8	18.7	18.5	18.8	23.5
LTE 26	21.0	20.8	20.7	20.5	20.8	20.5	21.0	20.6	21.0	20.9	24.0
LTE 30	16.5	17.0	17.0	17.0	16.5	16.5	16.7	16.6	16.8	16.9	22.7
LTE 41	18.5	18.8	18.9	18.6	18.6	18.9	18.6	18.6	18.5	18.9	22.9
Output Power Verification in dBm for EUT Top Edge											
Distance (mm)	33	34	35	36							
WCDMA II	23.8	23.8	23.6	23.8							
WCDMA IV	24.0	23.9	23.5	23.5							
WCDMA V	23.7	23.5	23.9	23.6							
LTE 2	23.9	24.0	23.8	23.6							
LTE 4	23.9	23.5	23.5	24.0							
LTE 5	23.5	23.5	23.5	23.7							
LTE 7	22.9	22.6	22.9	22.7							
LTE 12	23.5	23.7	23.8	23.6							
LTE 13	24.0	23.6	23.9	23.6							
LTE 25	23.8	23.7	23.7	23.9							
LTE 26	23.7	24.0	23.6	24.0							
LTE 30	22.7	23.0	22.6	22.6							
LTE 41	22.5	22.6	22.5	22.6							

Proximity Sensor Coverage (KDB 616217 D04 §6.3)

Since the proximity sensor is collocated with antenna in one component, the procedure for proximity sensor coverage is not required.

Proximity Sensor Tilt Angle Influences (KDB 616217 D04 §6.4)

The proximity sensor tilt angle influence was determined per KDB 616217 for applicable edge. Summary for proximity sensor tilt angle influence is shown in below.



Orientation	Separation Distance (cm)	Tilt Angle											
		-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°	
Top Edge	3.1	On	On	On	On	On	On	On	On	On	On	On	

FCC SAR Test Report

Summary for Proximity Sensor Triggering Test

EUT 1 (Thin cover)

According to the procedures noticed in KDB 616217 D04, the proximity sensor triggering distance is 1.8 cm for EUT Rear Face and 3.0 cm for Top Side. The separation distance of 3.0 cm determined by the smallest triggering distance on Top Side is used to access the tilt angle influence and the sensor does not release during ± 45 degree. Therefore, the smallest separation distance for tilt angle influence is 2.7 cm for the Top Side.

EUT 2 (Thick cover)

According to the procedures noticed in KDB 616217 D04, the proximity sensor triggering distance is 1.7 cm for EUT Rear Face and 3.1 cm for Top Side. The separation distance of 3.1 cm determined by the smallest triggering distance on Top Side is used to access the tilt angle influence and the sensor does not release during ± 45 degree. Therefore, the smallest separation distance for tilt angle influence is 3.1 cm for the Top Side.

The power reduction is depends on the proximity sensor input. For a steady SAR test, the power reduction was enabled or disabled manually by engineering software during SAR testing.

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for WCDMA and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.

Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
13			V	V		
25	V	V	V	V	V	V
26	V	V	V	V	V	
30			V	V		
41			V	V	V	V

FCC SAR Test Report

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2


Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts	4384 • Ts	5120 • Ts	7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts			20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts			-	-	-
9	13168 • Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

4.2 EUT Testing Position

For full-size tablet, according to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Fig-4.1 Illustration for Tablet Setup

4.2.1 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WCDMA II (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
2	WCDMA IV (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
3	WCDMA V (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
4	LTE 2 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
5	LTE 4 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
6	LTE 5 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
7	LTE 7 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
8	LTE 12 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
9	LTE 13 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
10	LTE 25 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
11	LTE 26 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
12	LTE 30 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
13	LTE 41 (Data) + WLAN Ant 0 (Data) + WLAN Ant 1 (Data)	Yes
14	WCDMA II (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
15	WCDMA IV (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
16	WCDMA V (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
17	LTE 2 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
18	LTE 4 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
19	LTE 5 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
20	LTE 7 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
21	LTE 12 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
22	LTE 13 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
23	LTE 25 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
24	LTE 26 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
25	LTE 30 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes
26	LTE 41 (Data) + WLAN Ant 0 (Data)+ BT Ant 1 (Data)	Yes

Note:

1. The WLAN and Bluetooth can transmit simultaneously.

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Oct. 06, 2015	Body	750	23.2	0.961	54.281	0.96	55.5	0.10	-2.20
Oct. 06, 2015	Body	750	23.2	0.961	54.281	0.96	55.5	0.10	-2.20
Oct. 23, 2015	Body	750	23.1	0.961	54.950	0.96	55.5	0.10	-0.99
Oct. 01, 2015	Body	835	22.6	1.017	54.270	0.97	55.2	4.85	-1.68
Oct. 06, 2015	Body	835	23.3	1.007	54.739	0.97	55.2	3.81	-0.84
Oct. 23, 2015	Body	835	23.3	1.008	54.768	0.97	55.2	3.92	-0.76
Oct. 06, 2015	Body	1750	23.2	1.457	52.268	1.49	53.4	-2.21	-2.12
Oct. 22, 2015	Body	1750	23.2	1.457	52.284	1.49	53.4	-2.21	-2.09
Oct. 01, 2015	Body	1900	23.6	1.570	50.834	1.52	53.3	3.29	-4.63
Oct. 06, 2015	Body	1900	23.2	1.584	51.865	1.52	53.3	4.21	-2.69
Oct. 22, 2015	Body	1900	23.3	1.585	51.894	1.52	53.3	4.28	-2.64
Oct. 01, 2015	Body	2300	23.2	1.833	51.655	1.81	52.9	1.27	-2.35
Oct. 22, 2015	Body	2300	23.2	1.835	52.911	1.81	52.9	1.38	0.02
Nov. 06, 2015	Body	2450	23.1	1.966	52.164	1.95	52.7	0.82	-1.02
Oct. 01, 2015	Body	2600	23.6	2.157	50.910	2.16	52.5	-0.14	-3.03
Oct. 07, 2015	Body	2600	23.1	2.157	51.910	2.16	52.5	-0.14	-1.12
Oct. 22, 2015	Body	2600	23.1	2.169	52.144	2.16	52.5	0.42	-0.68
Nov. 06, 2015	Body	5600	23.2	5.947	47.073	5.77	48.5	3.07	-2.94

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ε _r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Oct. 06, 2015	3650	Body	750	0.961	54.281	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 06, 2015	3971	Body	750	0.961	54.281	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 23, 2015	3650	Body	750	0.961	54.950	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 01, 2015	3971	Body	835	1.017	54.270	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 06, 2015	3650	Body	835	1.007	54.739	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 23, 2015	3650	Body	835	1.008	54.768	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 06, 2015	3650	Body	1750	1.457	52.268	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 22, 2015	3650	Body	1750	1.457	52.284	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 01, 2015	3971	Body	1900	1.570	50.834	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 06, 2015	3650	Body	1900	1.584	51.865	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 22, 2015	3650	Body	1900	1.585	51.894	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 01, 2015	3971	Body	2300	1.833	51.655	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 22, 2015	3650	Body	2300	1.835	52.911	Pass	Pass	Pass	N/A	N/A	N/A
Nov. 06, 2015	3650	Body	2450	1.966	52.164	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 01, 2015	3971	Body	2600	2.157	50.910	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 07, 2015	3650	Body	2600	2.157	51.910	Pass	Pass	Pass	N/A	N/A	N/A
Oct. 22, 2015	3650	Body	2600	2.169	52.144	Pass	Pass	Pass	N/A	N/A	N/A
Nov. 06, 2015	3650	Body	5600	5.947	47.073	Pass	Pass	Pass	N/A	N/A	N/A

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Oct. 06, 2015	Body	750	8.44	2.26	9.04	7.11	1013	3650	1277
Oct. 06, 2015	Body	750	8.44	2.20	8.80	4.27	1013	3971	1431
Oct. 23, 2015	Body	750	8.44	2.06	8.24	-2.37	1013	3650	1277
Oct. 01, 2015	Body	835	9.20	2.40	9.60	4.35	4d121	3971	1431
Oct. 06, 2015	Body	835	9.20	2.34	9.36	1.74	4d121	3650	1277
Oct. 23, 2015	Body	835	9.20	2.17	8.68	-5.65	4d121	3650	1277
Oct. 06, 2015	Body	1750	37.60	9.15	36.60	-2.66	1055	3650	1277
Oct. 22, 2015	Body	1750	37.60	9.16	36.64	-2.55	1055	3650	1277
Oct. 01, 2015	Body	1900	40.50	10.30	41.20	1.73	5d036	3971	1431
Oct. 06, 2015	Body	1900	40.50	10.60	42.40	4.69	5d036	3650	1277
Oct. 22, 2015	Body	1900	40.50	9.88	39.52	-2.42	5d036	3650	1277
Oct. 01, 2015	Body	2300	48.10	12.00	48.00	-0.21	1004	3971	1431
Oct. 22, 2015	Body	2300	48.10	12.80	51.20	6.44	1004	3650	1277
Nov. 06, 2015	Body	2450	51.10	12.80	51.20	0.20	737	3650	1277
Oct. 01, 2015	Body	2600	55.40	13.60	54.40	-1.81	1020	3971	1431
Oct. 07, 2015	Body	2600	55.40	13.50	54.00	-2.53	1020	3650	1277
Oct. 22, 2015	Body	2600	55.40	13.58	54.32	-1.95	1020	3650	1277
Nov. 06, 2015	Body	5600	79.80	7.93	79.30	-0.63	1019	3650	1277

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

FCC SAR Test Report

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	WCDMA Band II (without Power Reduction)	WCDMA Band II (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	24.0	18.0	6.0

Mode	WCDMA Band IV (without Power Reduction)	WCDMA Band IV (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	24.0	19.0	5.0

Mode	WCDMA Band V (without Power Reduction)	WCDMA Band V (with Power Reduction)	Power Reduction (dB)
RMC 12.2K	24.0	21.0	3.0

Mode	LTE 2 (without Power Reduction)	LTE 2 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	19.0	5.0

Mode	LTE 4 (without Power Reduction)	LTE 4 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	18.0	6.0

Mode	LTE 5 (without Power Reduction)	LTE 5 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	20.0	4.0

Mode	LTE 7 (without Power Reduction)	LTE 7 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	23.0	18.0	5.0

Mode	LTE 12 (without Power Reduction)	LTE 12 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	20.0	4.0

Mode	LTE 13 (without Power Reduction)	LTE 13 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	20.0	4.0

FCC SAR Test Report

A D T

Mode	LTE 25 (without Power Reduction)	LTE 25 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	19.0	5.0

Mode	LTE 26 (without Power Reduction)	LTE 26 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	24.0	21.0	3.0

Mode	LTE 30 (without Power Reduction)	LTE 30 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	23.0	17.0	6.0

Mode	LTE 41 (without Power Reduction)	LTE 41 (with Power Reduction)	Power Reduction (dB)
QPSK / 16QAM	23.0	19.0	4.0

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	WCDMA Band II			WCDMA Band IV			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
EUT without Power Reduction (P-Sensor NOT Triggered)										
RMC 12.2K	22.63	22.81	22.76	22.64	22.66	22.61	22.48	22.89	22.51	-
HSDPA Subtest-1	21.75	21.57	21.86	21.60	21.59	21.64	21.39	21.63	21.90	0
HSDPA Subtest-2	21.77	21.59	21.90	21.64	21.62	21.69	21.41	21.66	21.95	0
HSDPA Subtest-3	21.26	21.09	21.39	21.13	21.26	21.18	20.89	21.15	21.44	0.5
HSDPA Subtest-4	21.25	21.08	21.38	21.12	21.11	21.18	20.89	21.15	21.43	0.5
HSUPA Subtest-1	21.55	21.07	21.32	21.36	21.11	21.22	21.50	21.70	22.00	0
HSUPA Subtest-2	20.84	20.74	20.93	20.66	20.63	20.71	20.41	20.68	20.93	2
HSUPA Subtest-3	20.44	20.26	20.53	20.26	20.23	20.36	20.01	20.29	20.59	1
HSUPA Subtest-4	20.72	20.82	21.10	20.61	20.82	20.60	20.45	20.58	20.90	2
HSUPA Subtest-5	21.80	21.70	21.90	21.70	21.60	21.70	21.13	21.17	21.42	0
EUT with Power Reduction (P-Sensor Triggered)										
RMC 12.2K	16.88	17.26	17.16	18.18	18.31	18.13	19.89	20.20	19.95	-
HSDPA Subtest-1	16.48	16.85	16.76	17.52	17.57	17.42	19.20	19.56	19.27	-
HSDPA Subtest-2	16.47	16.82	16.75	17.49	17.54	17.43	19.22	19.61	19.33	-
HSDPA Subtest-3	16.07	16.34	16.22	17.18	17.26	17.11	19.03	19.4	19.12	-
HSDPA Subtest-4	16.06	16.33	16.21	17.17	17.25	17.11	19.02	19.39	19.12	-
HSUPA Subtest-1	16.11	16.32	16.43	17.46	17.30	17.22	19.29	19.43	19.18	-
HSUPA Subtest-2	16.13	16.19	16.19	17.17	17.20	17.13	19.07	19.44	19.24	-
HSUPA Subtest-3	16.05	16.17	16.18	17.18	17.18	17.03	19.24	19.54	19.32	-
HSUPA Subtest-4	16.02	16.16	16.17	17.16	17.17	17.05	19.55	19.83	19.63	-
HSUPA Subtest-5	16.17	16.55	16.45	17.60	17.70	17.50	19.30	19.70	19.40	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 1.4M	1	0	22.95	23.16	23.12	0	21.89	22.10	22.06	1
	1	2	22.48	22.74	22.36	0	21.42	21.68	21.30	1
	1	5	22.70	22.76	22.48	0	21.64	21.70	21.42	1
	3	0	22.49	22.86	22.47	0	21.63	22.00	21.41	1
	3	1	22.40	22.58	22.54	0	21.44	21.72	21.38	1
	3	3	22.46	22.62	22.51	0	21.35	21.76	21.45	1
	6	0	21.98	22.12	21.65	1	20.92	21.06	20.59	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 1.4M	1	0	17.91	18.30	18.20	-	17.77	18.16	18.06	-
	1	2	17.06	17.45	17.35	-	17.20	17.31	17.21	-
	1	5	17.10	17.49	17.39	-	17.18	17.35	17.25	-
	3	0	17.51	17.90	17.80	-	17.37	17.76	17.66	-
	3	1	17.23	17.62	17.52	-	17.19	17.48	17.38	-
	3	3	17.10	17.49	17.39	-	17.21	17.35	17.25	-
	6	0	17.28	17.67	17.57	-	17.22	17.53	17.43	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 3M	1	0	23.04	23.25	23.21	0	21.98	22.19	22.15	1
	1	7	22.57	22.83	22.45	0	21.51	21.77	21.39	1
	1	14	22.79	22.85	22.57	0	21.73	21.79	21.51	1
	8	0	21.93	22.30	21.71	1	20.87	21.24	20.65	2
	8	3	21.74	22.02	21.48	1	20.68	20.96	20.42	2
	8	7	21.65	22.06	21.75	1	20.59	21.00	20.69	2
	15	0	22.07	22.21	21.74	1	21.01	21.15	20.68	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 3M	1	0	17.99	18.38	18.28	-	17.89	18.28	18.18	-
	1	7	17.14	17.53	17.43	-	17.25	17.43	17.33	-
	1	14	17.18	17.57	17.47	-	17.21	17.47	17.37	-
	8	0	17.59	17.98	17.88	-	17.49	17.88	17.78	-
	8	3	17.31	17.70	17.60	-	17.21	17.60	17.50	-
	8	7	17.18	17.57	17.47	-	17.26	17.47	17.37	-
	15	0	17.36	17.75	17.65	-	17.26	17.65	17.55	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 5M	1	0	23.12	23.33	23.29	0	22.06	22.27	22.23	1
	1	12	22.65	22.91	22.53	0	21.59	21.85	21.47	1
	1	24	22.87	22.93	22.65	0	21.81	21.87	21.59	1
	12	0	22.01	22.38	21.79	1	20.95	21.32	20.73	2
	12	6	21.82	22.10	21.56	1	20.76	21.04	20.50	2
	12	13	21.73	22.14	21.83	1	20.67	21.08	20.77	2
	25	0	22.15	22.29	21.82	1	21.09	21.23	20.76	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 5M	1	0	18.05	18.44	18.34	-	17.91	18.30	18.20	-
	1	12	17.20	17.59	17.49	-	17.23	17.45	17.35	-
	1	24	17.24	17.63	17.53	-	17.25	17.49	17.39	-
	12	0	17.65	18.04	17.94	-	17.51	17.90	17.80	-
	12	6	17.37	17.76	17.66	-	17.23	17.62	17.52	-
	12	13	17.24	17.63	17.53	-	17.33	17.49	17.39	-
	25	0	17.42	17.81	17.71	-	17.28	17.67	17.57	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 10M	1	0	23.23	23.44	23.40	0	22.17	22.38	22.34	1
	1	24	22.76	23.02	22.64	0	21.70	21.96	21.58	1
	1	49	22.98	23.04	22.76	0	21.92	21.98	21.70	1
	25	0	22.12	22.49	21.90	1	21.06	21.43	20.84	2
	25	12	21.93	22.21	21.67	1	20.87	21.15	20.61	2
	25	25	21.84	22.25	21.94	1	20.78	21.19	20.88	2
	50	0	22.26	22.40	21.93	1	21.20	21.34	20.87	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 10M	1	0	18.11	18.50	18.40	-	17.99	18.38	18.28	-
	1	24	17.26	17.65	17.55	-	17.33	17.53	17.43	-
	1	49	17.30	17.69	17.59	-	17.32	17.57	17.47	-
	25	0	17.71	18.10	18.00	-	17.59	17.98	17.88	-
	25	12	17.43	17.82	17.72	-	17.31	17.70	17.60	-
	25	25	17.30	17.69	17.59	-	17.43	17.57	17.47	-
	50	0	17.48	17.87	17.77	-	17.36	17.75	17.65	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18675	Mid CH 18900	High CH 19125		Low CH 18675	Mid CH 18900	High CH 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 15M	1	0	23.31	23.52	23.48	0	22.25	22.46	22.42	1
	1	37	22.84	23.10	22.72	0	21.78	22.04	21.66	1
	1	74	23.06	23.12	22.84	0	22.00	22.06	21.78	1
	36	0	22.20	22.57	21.98	1	21.14	21.51	20.92	2
	36	19	22.01	22.29	21.75	1	20.95	21.23	20.69	2
	36	39	21.92	22.33	22.02	1	20.86	21.27	20.96	2
	75	0	22.34	22.48	22.01	1	21.28	21.42	20.95	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 15M	1	0	18.18	18.57	18.47	-	18.00	18.39	18.29	-
	1	37	17.33	17.72	17.62	-	17.38	17.54	17.44	-
	1	74	17.37	17.76	17.66	-	17.35	17.58	17.48	-
	36	0	17.78	18.17	18.07	-	17.60	17.99	17.89	-
	36	19	17.50	17.89	17.79	-	17.32	17.71	17.61	-
	36	39	17.37	17.76	17.66	-	17.48	17.58	17.48	-
	75	0	17.55	17.94	17.84	-	17.37	17.76	17.66	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18700	Mid CH 18900	High CH 19100		Low CH 18700	Mid CH 18900	High CH 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
2 / 20M	1	0	23.40	23.61	23.57	0	22.34	22.55	22.51	1
	1	50	22.93	23.19	22.81	0	21.87	22.13	21.75	1
	1	99	23.15	23.21	22.93	0	22.09	22.15	21.87	1
	50	0	22.29	22.66	22.07	1	21.23	21.60	21.01	2
	50	25	22.10	22.38	21.84	1	21.04	21.32	20.78	2
	50	50	22.01	22.42	22.11	1	20.95	21.36	21.05	2
	100	0	22.43	22.57	22.10	1	21.37	21.51	21.04	2
EUT with Power Reduction (P-Sensor Triggered)										
2 / 20M	1	0	18.24	18.63	18.53	-	18.08	18.47	18.37	-
	1	50	17.39	17.78	17.68	-	17.43	17.62	17.52	-
	1	99	17.43	17.82	17.72	-	17.38	17.66	17.56	-
	50	0	17.84	18.23	18.13	-	17.68	18.07	17.97	-
	50	25	17.56	17.95	17.85	-	17.40	17.79	17.69	-
	50	50	17.43	17.82	17.72	-	17.55	17.66	17.56	-
	100	0	17.61	18.00	17.90	-	17.45	17.84	17.74	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 1.4M	1	0	22.63	22.82	22.61	0	21.62	21.81	21.60	1
	1	2	22.31	22.50	22.29	0	21.30	21.49	21.28	1
	1	5	22.45	22.64	22.43	0	21.34	21.53	21.32	1
	3	0	22.55	22.74	22.53	0	21.44	21.63	21.42	1
	3	1	22.26	22.42	22.28	0	21.31	21.33	21.30	1
	3	3	22.29	22.48	22.27	0	21.28	21.37	21.26	1
	6	0	21.70	21.89	21.68	1	20.69	20.88	20.67	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 1.4M	1	0	17.25	17.36	17.33	-	17.10	17.21	17.18	-
	1	2	16.66	16.77	16.74	-	16.51	16.62	16.59	-
	1	5	16.63	16.74	16.71	-	16.48	16.59	16.56	-
	3	0	17.02	17.13	17.10	-	16.87	16.98	16.95	-
	3	1	16.76	16.87	16.84	-	16.61	16.72	16.69	-
	3	3	16.64	16.75	16.72	-	16.49	16.60	16.57	-
	6	0	16.82	16.93	16.90	-	16.67	16.78	16.75	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 3M	1	0	22.71	22.90	22.69	0	21.70	21.89	21.68	1
	1	7	22.39	22.58	22.37	0	21.38	21.57	21.36	1
	1	14	22.03	22.22	22.01	0	21.02	21.21	21.00	1
	8	0	21.88	22.07	21.86	1	20.87	21.06	20.85	2
	8	3	21.56	21.75	21.54	1	20.55	20.74	20.53	2
	8	7	21.62	21.81	21.60	1	20.61	20.80	20.59	2
	15	0	21.78	21.97	21.76	1	20.77	20.96	20.75	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 3M	1	0	17.31	17.42	17.39	-	17.16	17.27	17.24	-
	1	7	16.72	16.83	16.80	-	16.57	16.68	16.65	-
	1	14	16.69	16.80	16.77	-	16.54	16.65	16.62	-
	8	0	17.08	17.19	17.16	-	16.93	17.04	17.01	-
	8	3	16.82	16.93	16.90	-	16.67	16.78	16.75	-
	8	7	16.70	16.81	16.78	-	16.55	16.66	16.63	-
	15	0	16.88	16.99	16.96	-	16.73	16.84	16.81	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 5M	1	0	22.79	22.98	22.77	0	21.78	21.97	21.76	1
	1	12	22.47	22.66	22.45	0	21.46	21.65	21.44	1
	1	24	22.11	22.30	22.09	0	21.10	21.29	21.08	1
	12	0	21.96	22.15	21.94	1	20.95	21.14	20.93	2
	12	6	21.64	21.83	21.62	1	20.63	20.82	20.61	2
	12	13	21.70	21.89	21.68	1	20.69	20.88	20.67	2
	25	0	21.86	22.05	21.84	1	20.85	21.04	20.83	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 5M	1	0	17.38	17.49	17.46	-	17.27	17.38	17.35	-
	1	12	16.79	16.90	16.87	-	16.68	16.79	16.76	-
	1	24	16.76	16.87	16.84	-	16.65	16.76	16.73	-
	12	0	17.15	17.26	17.23	-	17.04	17.15	17.12	-
	12	6	16.89	17.00	16.97	-	16.78	16.89	16.86	-
	12	13	16.77	16.88	16.85	-	16.66	16.77	16.74	-
	25	0	16.95	17.06	17.03	-	16.84	16.95	16.92	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 10M	1	0	22.88	23.07	22.86	0	21.83	22.02	21.81	1
	1	24	22.06	22.25	22.04	0	21.01	21.20	20.99	1
	1	49	22.20	22.39	22.18	0	21.15	21.34	21.13	1
	25	0	21.45	21.64	21.43	1	20.40	20.59	20.38	2
	25	12	21.13	21.32	21.11	1	20.08	20.27	20.06	2
	25	25	21.19	21.38	21.17	1	20.14	20.33	20.12	2
	50	0	21.35	21.54	21.33	1	20.30	20.49	20.28	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 10M	1	0	17.46	17.57	17.54	-	17.36	17.47	17.44	-
	1	24	16.87	16.98	16.95	-	16.77	16.88	16.85	-
	1	49	16.84	16.95	16.92	-	16.74	16.85	16.82	-
	25	0	17.23	17.34	17.31	-	17.13	17.24	17.21	-
	25	12	16.97	17.08	17.05	-	16.87	16.98	16.95	-
	25	25	16.85	16.96	16.93	-	16.75	16.86	16.83	-
	50	0	17.03	17.14	17.11	-	16.93	17.04	17.01	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 15M	1	0	23.03	23.22	23.01	0	21.98	22.17	21.96	1
	1	37	22.21	22.40	22.19	0	21.16	21.35	21.14	1
	1	74	22.35	22.54	22.33	0	21.30	21.49	21.28	1
	36	0	21.60	21.79	21.58	1	20.55	20.74	20.53	2
	36	19	21.28	21.47	21.26	1	20.23	20.42	20.21	2
	36	39	21.34	21.53	21.32	1	20.29	20.48	20.27	2
	75	0	21.50	21.69	21.48	1	20.45	20.64	20.43	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 15M	1	0	17.51	17.62	17.59	-	17.39	17.50	17.47	-
	1	37	16.92	17.03	17.00	-	16.80	16.91	16.88	-
	1	74	16.89	17.00	16.97	-	16.77	16.88	16.85	-
	36	0	17.28	17.39	17.36	-	17.16	17.27	17.24	-
	36	19	17.02	17.13	17.10	-	16.90	17.01	16.98	-
	36	39	16.90	17.01	16.98	-	16.78	16.89	16.86	-
	75	0	17.08	17.19	17.16	-	16.96	17.07	17.04	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
4 / 20M	1	0	23.15	23.34	23.13	0	22.10	22.29	22.08	1
	1	50	22.33	22.52	22.31	0	21.28	21.47	21.26	1
	1	99	22.47	22.66	22.45	0	21.42	21.61	21.40	1
	50	0	21.72	21.91	21.70	1	20.67	20.86	20.65	2
	50	25	21.40	21.59	21.38	1	20.35	20.54	20.33	2
	50	50	21.46	21.65	21.44	1	20.41	20.60	20.39	2
	100	0	21.62	21.81	21.60	1	20.57	20.76	20.55	2
EUT with Power Reduction (P-Sensor Triggered)										
4 / 20M	1	0	17.57	17.68	17.65	-	17.46	17.57	17.54	-
	1	50	16.98	17.09	17.06	-	16.87	16.98	16.95	-
	1	99	16.95	17.06	17.03	-	16.84	16.95	16.92	-
	50	0	17.34	17.45	17.42	-	17.23	17.34	17.31	-
	50	25	17.08	17.19	17.16	-	16.97	17.08	17.05	-
	50	50	16.96	17.07	17.04	-	16.85	16.96	16.93	-
	100	0	17.14	17.25	17.22	-	17.03	17.14	17.11	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
5 / 1.4M	1	0	22.60	22.89	22.48	0	21.54	21.83	21.42	1
	1	2	22.47	22.83	22.60	0	21.41	21.77	21.54	1
	1	5	22.28	22.51	22.47	0	21.42	21.65	21.61	1
	3	0	22.45	22.76	22.57	0	21.29	21.31	21.30	1
	3	1	22.46	22.85	22.68	0	21.30	21.39	21.36	1
	3	3	22.13	22.87	22.31	0	21.27	21.38	21.35	1
	6	0	21.31	21.77	21.29	1	20.25	20.71	20.23	2
EUT with Power Reduction (P-Sensor Triggered)										
5 / 1.4M	1	0	19.51	19.78	19.59	-	19.34	19.61	19.42	-
	1	2	19.49	19.76	19.57	-	19.32	19.59	19.40	-
	1	5	19.35	19.62	19.43	-	19.18	19.45	19.26	-
	3	0	19.48	19.75	19.56	-	19.31	19.58	19.39	-
	3	1	19.47	19.74	19.55	-	19.30	19.57	19.38	-
	3	3	19.39	19.66	19.47	-	19.22	19.49	19.30	-
	6	0	19.40	19.67	19.48	-	19.23	19.50	19.31	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
5 / 3M	1	0	22.68	22.97	22.56	0	21.62	21.91	21.50	1
	1	7	22.55	22.91	22.68	0	21.49	21.85	21.62	1
	1	14	22.36	22.59	22.55	0	21.30	21.53	21.49	1
	8	0	21.68	21.99	21.80	1	20.62	20.93	20.74	2
	8	3	21.69	22.08	21.91	1	20.63	21.02	20.85	2
	8	7	21.36	22.10	21.54	1	20.30	21.04	20.48	2
	15	0	21.39	21.85	21.37	1	20.33	20.79	20.31	2
EUT with Power Reduction (P-Sensor Triggered)										
5 / 3M	1	0	19.58	19.85	19.66	-	19.41	19.68	19.49	-
	1	7	19.56	19.83	19.64	-	19.39	19.66	19.47	-
	1	14	19.42	19.69	19.50	-	19.25	19.52	19.33	-
	8	0	19.55	19.82	19.63	-	19.38	19.65	19.46	-
	8	3	19.54	19.81	19.62	-	19.37	19.64	19.45	-
	8	7	19.46	19.73	19.54	-	19.29	19.56	19.37	-
	15	0	19.47	19.74	19.55	-	19.30	19.57	19.38	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
5 / 5M	1	0	22.78	23.07	22.66	0	21.72	22.01	21.60	1
	1	12	22.65	23.01	22.78	0	21.59	21.95	21.72	1
	1	24	22.46	22.69	22.65	0	21.40	21.63	21.59	1
	12	0	21.78	22.09	21.90	1	20.72	21.03	20.84	2
	12	6	21.79	22.18	22.01	1	20.73	21.12	20.95	2
	12	13	21.46	22.20	21.64	1	20.40	21.14	20.58	2
	25	0	21.49	21.95	21.47	1	20.43	20.89	20.41	2
EUT with Power Reduction (P-Sensor Triggered)										
5 / 5M	1	0	19.65	19.92	19.73	-	19.58	19.85	19.66	-
	1	12	19.63	19.90	19.71	-	19.56	19.83	19.64	-
	1	24	19.49	19.76	19.57	-	19.42	19.69	19.50	-
	12	0	19.62	19.89	19.70	-	19.55	19.82	19.63	-
	12	6	19.61	19.88	19.69	-	19.54	19.81	19.62	-
	12	13	19.53	19.80	19.61	-	19.46	19.73	19.54	-
	25	0	19.54	19.81	19.62	-	19.47	19.74	19.55	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
5 / 10M	1	0	22.85	23.14	22.73	0	21.79	22.08	21.67	1
	1	24	22.72	23.08	22.85	0	21.66	22.02	21.79	1
	1	49	22.53	22.76	22.72	0	21.47	21.70	21.66	1
	25	0	21.85	22.16	21.97	1	20.79	21.10	20.91	2
	25	12	21.86	22.25	22.08	1	20.80	21.19	21.02	2
	25	25	21.53	22.27	21.71	1	20.47	21.21	20.65	2
	50	0	21.56	22.02	21.54	1	20.50	20.96	20.48	2
EUT with Power Reduction (P-Sensor Triggered)										
5 / 10M	1	0	19.71	19.98	19.79	-	19.64	19.91	19.72	-
	1	24	19.69	19.96	19.77	-	19.62	19.89	19.70	-
	1	49	19.55	19.82	19.63	-	19.48	19.75	19.56	-
	25	0	19.68	19.95	19.76	-	19.61	19.88	19.69	-
	25	12	19.67	19.94	19.75	-	19.60	19.87	19.68	-
	25	25	19.59	19.86	19.67	-	19.52	19.79	19.60	-
	50	0	19.60	19.87	19.68	-	19.53	19.80	19.61	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
7 / 5M	1	0	21.29	21.45	21.44	0	20.25	20.41	20.40	1
	1	12	21.30	21.38	21.27	0	20.26	20.34	20.23	1
	1	24	21.28	21.37	21.25	0	20.24	20.33	20.21	1
	12	0	20.54	20.67	20.40	1	19.50	19.63	19.36	2
	12	6	20.56	20.66	20.41	1	19.52	19.62	19.37	2
	12	13	20.33	20.52	20.34	1	19.29	19.48	19.30	2
	25	0	20.49	20.55	20.43	1	19.45	19.51	19.39	2
EUT with Power Reduction (P-Sensor Triggered)										
7 / 5M	1	0	16.05	16.13	16.06	-	16.04	16.12	16.05	-
	1	12	16.10	16.10	16.11	-	16.09	16.09	16.10	-
	1	24	16.06	16.08	16.07	-	16.05	16.07	16.06	-
	12	0	16.11	16.07	16.09	-	16.10	16.06	16.08	-
	12	6	16.09	16.11	16.10	-	16.08	16.10	16.09	-
	12	13	16.08	16.06	16.05	-	16.07	16.05	16.04	-
	25	0	16.08	16.10	16.09	-	16.07	16.09	16.08	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
7 / 10M	1	0	21.34	21.50	21.49	0	20.30	20.46	20.45	1
	1	24	21.35	21.43	21.32	0	20.31	20.39	20.28	1
	1	49	21.33	21.42	21.30	0	20.29	20.38	20.26	1
	25	0	20.59	20.72	20.45	1	19.55	19.68	19.41	2
	25	12	20.61	20.71	20.46	1	19.57	19.67	19.42	2
	25	25	20.38	20.57	20.39	1	19.34	19.53	19.35	2
	50	0	20.54	20.60	20.48	1	19.50	19.56	19.44	2
EUT with Power Reduction (P-Sensor Triggered)										
7 / 10M	1	0	16.02	16.08	16.01	-	16.03	16.11	16.04	-
	1	24	16.05	16.07	16.06	-	16.08	16.10	16.09	-
	1	49	16.01	16.03	16.02	-	16.04	16.06	16.05	-
	25	0	16.06	16.02	16.07	-	16.09	16.05	16.10	-
	25	12	16.04	16.06	16.05	-	16.07	16.09	16.08	-
	25	25	16.03	16.05	16.01	-	16.06	16.04	16.03	-
	50	0	16.03	16.05	16.04	-	16.06	16.08	16.07	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
7 / 15M	1	0	21.42	21.58	21.57	0	20.38	20.54	20.53	1
	1	37	21.43	21.51	21.40	0	20.39	20.47	20.36	1
	1	74	21.41	21.50	21.38	0	20.37	20.46	20.34	1
	36	0	20.67	20.80	20.53	1	19.63	19.76	19.49	2
	36	19	20.69	20.79	20.54	1	19.65	19.75	19.50	2
	36	39	20.46	20.65	20.47	1	19.42	19.61	19.43	2
	75	0	20.62	20.68	20.56	1	19.58	19.64	19.52	2
EUT with Power Reduction (P-Sensor Triggered)										
7 / 15M	1	0	16.02	16.10	16.03	-	16.01	16.09	16.02	-
	1	37	16.07	16.09	16.08	-	16.06	16.08	16.07	-
	1	74	16.03	16.05	16.04	-	16.02	16.04	16.03	-
	36	0	16.08	16.04	16.09	-	16.07	16.03	16.08	-
	36	19	16.06	16.08	16.07	-	16.05	16.07	16.06	-
	36	39	16.01	16.03	16.02	-	16.02	16.03	16.01	-
	75	0	16.05	16.07	16.06	-	16.04	16.06	16.05	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
7 / 20M	1	0	21.48	21.64	21.63	0	20.44	20.60	20.59	1
	1	50	21.49	21.57	21.46	0	20.45	20.53	20.42	1
	1	99	21.47	21.56	21.44	0	20.43	20.52	20.40	1
	50	0	20.73	20.86	20.59	1	19.69	19.82	19.55	2
	50	25	20.75	20.85	20.60	1	19.71	19.81	19.56	2
	50	50	20.52	20.71	20.53	1	19.48	19.67	19.49	2
	100	0	20.68	20.74	20.62	1	19.64	19.70	19.58	2
EUT with Power Reduction (P-Sensor Triggered)										
7 / 20M	1	0	16.09	16.11	16.10	-	16.07	16.09	16.08	-
	1	50	16.05	16.07	16.06	-	16.03	16.05	16.04	-
	1	99	16.01	16.03	16.02	-	16.05	16.03	16.01	-
	50	0	16.06	16.08	16.07	-	16.04	16.06	16.05	-
	50	25	16.04	16.06	16.05	-	16.02	16.04	16.03	-
	50	50	16.04	16.01	16.02	-	16.03	16.06	16.02	-
	100	0	16.03	16.05	16.04	-	16.01	16.03	16.02	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23017	Mid CH 23095	High CH 23173		Low CH 23017	Mid CH 23095	High CH 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
12 / 1.4M	1	0	22.33	22.34	22.23	0	21.31	21.32	21.21	1
	1	2	22.21	22.22	22.11	0	21.19	21.20	21.09	1
	1	5	22.08	22.09	21.98	0	21.06	21.07	20.96	1
	3	0	22.15	22.16	22.05	0	21.13	21.14	21.03	1
	3	1	22.14	22.15	22.04	0	21.12	21.13	21.02	1
	3	3	22.07	22.08	21.97	0	21.05	21.06	20.95	1
	6	0	21.12	21.13	21.02	1	20.10	20.11	20.01	2
EUT with Power Reduction (P-Sensor Triggered)										
12 / 1.4M	1	0	18.94	19.13	18.88	-	18.84	19.03	18.78	-
	1	2	18.71	18.90	18.65	-	18.61	18.80	18.55	-
	1	5	18.44	18.63	18.38	-	18.34	18.53	18.28	-
	3	0	18.71	18.90	18.65	-	18.61	18.80	18.55	-
	3	1	18.62	18.81	18.56	-	18.52	18.71	18.46	-
	3	3	18.52	18.71	18.46	-	18.42	18.61	18.36	-
	6	0	18.56	18.75	18.50	-	18.46	18.65	18.40	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23025	Mid CH 23095	High CH 23165		Low CH 23025	Mid CH 23095	High CH 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
12 / 3M	1	0	22.41	22.42	22.31	0	21.39	21.40	21.29	1
	1	7	22.29	22.30	22.19	0	21.27	21.28	21.17	1
	1	14	22.16	22.17	22.06	0	21.14	21.15	21.04	1
	8	0	21.23	21.24	21.13	1	20.21	20.22	20.11	2
	8	3	21.22	21.23	21.12	1	20.20	20.21	20.10	2
	8	7	21.15	21.16	21.05	1	20.13	20.14	20.03	2
	15	0	21.20	21.21	21.10	1	20.18	20.19	20.08	2
EUT with Power Reduction (P-Sensor Triggered)										
12 / 3M	1	0	19.06	19.25	19.00	-	18.86	19.05	18.80	-
	1	7	18.83	19.02	18.77	-	18.63	18.82	18.57	-
	1	14	18.56	18.75	18.50	-	18.36	18.55	18.30	-
	8	0	18.83	19.02	18.77	-	18.63	18.82	18.57	-
	8	3	18.74	18.93	18.68	-	18.54	18.73	18.48	-
	8	7	18.64	18.83	18.58	-	18.44	18.63	18.38	-
	15	0	18.68	18.87	18.62	-	18.48	18.67	18.42	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23035	Mid CH 23095	High CH 23155		Low CH 23035	Mid CH 23095	High CH 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
12 / 5M	1	0	22.55	22.56	22.45	0	21.53	21.54	21.43	1
	1	12	22.43	22.44	22.33	0	21.41	21.42	21.31	1
	1	24	22.30	22.31	22.20	0	21.28	21.29	21.18	1
	12	0	21.37	21.38	21.27	1	20.35	20.36	20.25	2
	12	6	21.36	21.37	21.26	1	20.34	20.35	20.24	2
	12	13	21.29	21.30	21.19	1	20.27	20.28	20.17	2
	25	0	21.34	21.35	21.24	1	20.32	20.33	20.22	2
EUT with Power Reduction (P-Sensor Triggered)										
12 / 5M	1	0	19.15	19.34	19.09	-	18.95	19.14	18.89	-
	1	12	18.92	19.11	18.86	-	18.72	18.91	18.66	-
	1	24	18.65	18.84	18.59	-	18.45	18.64	18.39	-
	12	0	18.92	19.11	18.86	-	18.72	18.91	18.66	-
	12	6	18.83	19.02	18.77	-	18.63	18.82	18.57	-
	12	13	18.73	18.92	18.67	-	18.53	18.72	18.47	-
	25	0	18.77	18.96	18.71	-	18.57	18.76	18.51	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23060	Mid CH 23095	High CH 23130		Low CH 23060	Mid CH 23095	High CH 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
12 / 10M	1	0	22.67	22.68	22.57	0	21.65	21.66	21.55	1
	1	24	22.55	22.56	22.45	0	21.53	21.54	21.43	1
	1	49	22.42	22.43	22.32	0	21.40	21.41	21.30	1
	25	0	21.49	21.50	21.39	1	20.47	20.48	20.37	2
	25	12	21.48	21.49	21.38	1	20.46	20.47	20.36	2
	25	25	21.41	21.42	21.31	1	20.39	20.40	20.29	2
	50	0	21.46	21.47	21.36	1	20.44	20.45	20.34	2
EUT with Power Reduction (P-Sensor Triggered)										
12 / 10M	1	0	19.26	19.45	19.20	-	19.06	19.25	19.00	-
	1	24	19.03	19.22	18.97	-	18.83	19.02	18.77	-
	1	49	18.76	18.95	18.70	-	18.56	18.75	18.50	-
	25	0	19.03	19.22	18.97	-	18.83	19.02	18.77	-
	25	12	18.94	19.13	18.88	-	18.74	18.93	18.68	-
	25	25	18.84	19.03	18.78	-	18.64	18.83	18.58	-
	50	0	18.88	19.07	18.82	-	18.68	18.87	18.62	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23205	Mid CH 23230	High CH 23255		Low CH 23205	Mid CH 23230	High CH 23255	
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
13 / 5M	1	0	22.79	22.97	22.86	0	21.73	21.91	21.80	1
	1	12	22.72	22.90	22.79	0	21.66	21.84	21.73	1
	1	24	22.57	22.75	22.64	0	21.51	21.69	21.58	1
	12	0	21.89	22.07	21.96	1	20.83	21.01	20.90	2
	12	6	21.84	22.02	21.91	1	20.78	20.96	20.85	2
	12	13	21.83	22.01	21.90	1	20.77	20.95	20.84	2
	25	0	21.87	22.05	21.94	1	20.81	20.99	20.88	2
EUT with Power Reduction (P-Sensor Triggered)										
13 / 5M	1	0	19.10	19.18	19.15	-	19.07	19.15	19.12	-
	1	12	18.95	19.03	19.00	-	18.92	19.00	18.97	-
	1	24	18.84	18.92	18.89	-	18.81	18.89	18.86	-
	12	0	19.02	19.10	19.07	-	18.99	19.07	19.04	-
	12	6	19.00	19.08	19.05	-	18.97	19.05	19.02	-
	12	13	18.93	19.01	18.98	-	18.90	18.98	18.95	-
	25	0	19.06	19.14	19.11	-	19.03	19.11	19.08	-

Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)
			Mid CH 23230		Mid CH 23230	
			782.0 MHz		782.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)						
13 / 10M	1	0	23.03	0	22.02	1
	1	24	22.96	0	21.95	1
	1	49	22.81	0	21.80	1
	25	0	22.13	1	21.12	2
	25	12	22.08	1	21.07	2
	25	25	22.07	1	21.06	2
	50	0	22.11	1	21.10	2
EUT with Power Reduction (P-Sensor Triggered)						
13 / 10M	1	0	19.23	-	19.08	-
	1	24	19.08	-	18.93	-
	1	49	18.97	-	18.82	-
	25	0	19.15	-	19.00	-
	25	12	19.13	-	18.98	-
	25	25	19.06	-	18.91	-
	50	0	19.19	-	19.04	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26047	Mid CH 26365	High CH 26683		Low CH 26047	Mid CH 26365	High CH 26683	
			1850.7 MHz	1882.5 MHz	1914.3 MHz		1850.7 MHz	1882.5 MHz	1914.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 1.4M	1	0	22.64	22.83	22.59	0	21.63	21.82	21.58	1
	1	2	22.28	22.47	22.23	0	21.27	21.46	21.22	1
	1	5	22.23	22.42	22.18	0	21.22	21.41	21.17	1
	3	0	22.18	22.37	22.13	0	21.17	21.36	21.12	1
	3	1	22.17	22.36	22.12	0	21.16	21.35	21.11	1
	3	3	22.14	22.33	22.09	0	21.13	21.32	21.08	1
	6	0	21.37	21.56	21.32	1	20.36	20.55	20.31	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 1.4M	1	0	18.03	18.24	18.18	-	17.89	18.10	18.04	-
	1	2	17.18	17.39	17.33	-	17.30	17.27	17.27	-
	1	5	17.32	17.53	17.47	-	17.26	17.39	17.33	-
	3	0	17.62	17.83	17.77	-	17.48	17.69	17.63	-
	3	1	17.24	17.45	17.39	-	17.27	17.31	17.26	-
	3	3	17.23	17.44	17.38	-	17.28	17.30	17.29	-
	6	0	17.37	17.58	17.52	-	17.27	17.44	17.38	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26055	Mid CH 26365	High CH 26675		Low CH 26055	Mid CH 26365	High CH 26675	
			1851.5 MHz	1882.5 MHz	1913.5 MHz		1851.5 MHz	1882.5 MHz	1913.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 3M	1	0	22.75	22.94	22.70	0	21.74	21.93	21.69	1
	1	7	22.39	22.58	22.34	0	21.38	21.57	21.33	1
	1	14	22.34	22.53	22.29	0	21.33	21.52	21.28	1
	8	0	21.54	21.73	21.49	1	20.53	20.72	20.48	2
	8	3	21.53	21.72	21.48	1	20.52	20.71	20.47	2
	8	7	21.50	21.69	21.45	1	20.49	20.68	20.44	2
	15	0	21.48	21.67	21.43	1	20.47	20.66	20.42	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 3M	1	0	18.10	18.31	18.25	-	17.99	18.20	18.14	-
	1	7	17.25	17.46	17.40	-	17.33	17.35	17.29	-
	1	14	17.39	17.60	17.54	-	17.28	17.49	17.43	-
	8	0	17.69	17.90	17.84	-	17.58	17.79	17.73	-
	8	3	17.31	17.52	17.46	-	17.31	17.41	17.35	-
	8	7	17.30	17.51	17.45	-	17.38	17.40	17.34	-
	15	0	17.44	17.65	17.59	-	17.33	17.54	17.48	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26065	Mid CH 26365	High CH 26665		Low CH 26065	Mid CH 26365	High CH 26665	
			1852.5 MHz	1882.5 MHz	1912.5 MHz		1852.5 MHz	1882.5 MHz	1912.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 5M	1	0	22.83	23.02	22.78	0	21.82	22.01	21.77	1
	1	12	22.47	22.66	22.42	0	21.46	21.65	21.41	1
	1	24	22.42	22.61	22.37	0	21.41	21.60	21.36	1
	12	0	21.62	21.81	21.57	1	20.61	20.80	20.56	2
	12	6	21.61	21.80	21.56	1	20.60	20.79	20.55	2
	12	13	21.58	21.77	21.53	1	20.57	20.76	20.52	2
	25	0	21.56	21.75	21.51	1	20.55	20.74	20.50	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 5M	1	0	18.15	18.36	18.30	-	18.01	18.22	18.16	-
	1	12	17.30	17.51	17.45	-	17.35	17.37	17.31	-
	1	24	17.44	17.65	17.59	-	17.30	17.51	17.45	-
	12	0	17.74	17.95	17.89	-	17.60	17.81	17.75	-
	12	6	17.36	17.57	17.51	-	17.33	17.43	17.37	-
	12	13	17.35	17.56	17.50	-	17.40	17.42	17.36	-
	25	0	17.49	17.70	17.64	-	17.35	17.56	17.50	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26090	Mid CH 26365	High CH 26640		Low CH 26090	Mid CH 26365	High CH 26640	
			1855.0 MHz	1882.5 MHz	1910.0 MHz		1855.0 MHz	1882.5 MHz	1910.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 10M	1	0	22.93	23.12	22.88	0	21.92	22.11	21.87	1
	1	24	22.57	22.76	22.52	0	21.56	21.75	21.51	1
	1	49	22.52	22.71	22.47	0	21.51	21.70	21.46	1
	25	0	21.72	21.91	21.67	1	20.71	20.90	20.66	2
	25	12	21.71	21.90	21.66	1	20.70	20.89	20.65	2
	25	25	21.68	21.87	21.63	1	20.67	20.86	20.62	2
	50	0	21.66	21.85	21.61	1	20.65	20.84	20.60	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 10M	1	0	18.21	18.42	18.36	-	18.01	18.22	18.16	-
	1	24	17.36	17.57	17.51	-	17.35	17.37	17.31	-
	1	49	17.50	17.71	17.65	-	17.30	17.51	17.45	-
	25	0	17.80	18.01	17.95	-	17.60	17.81	17.75	-
	25	12	17.42	17.63	17.57	-	17.35	17.43	17.37	-
	25	25	17.41	17.62	17.56	-	17.40	17.42	17.36	-
	50	0	17.55	17.76	17.70	-	17.35	17.56	17.50	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26115	Mid CH 26365	High CH 26615		Low CH 26115	Mid CH 26365	High CH 26615	
			1857.5 MHz	1882.5 MHz	1907.5 MHz		1857.5 MHz	1882.5 MHz	1907.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 15M	1	0	23.00	23.19	22.95	0	21.99	22.18	21.94	1
	1	37	22.64	22.83	22.59	0	21.63	21.82	21.58	1
	1	74	22.59	22.78	22.54	0	21.58	21.77	21.53	1
	36	0	21.79	21.98	21.74	1	20.78	20.97	20.73	2
	36	19	21.78	21.97	21.73	1	20.77	20.96	20.72	2
	36	39	21.75	21.94	21.70	1	20.74	20.93	20.69	2
	75	0	21.73	21.92	21.68	1	20.72	20.91	20.67	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 15M	1	0	18.26	18.47	18.41	-	18.09	18.30	18.24	-
	1	37	17.41	17.62	17.56	-	17.43	17.45	17.39	-
	1	74	17.55	17.76	17.70	-	17.38	17.59	17.53	-
	36	0	17.85	18.06	18.00	-	17.68	17.89	17.83	-
	36	19	17.47	17.68	17.62	-	17.40	17.51	17.45	-
	36	39	17.46	17.67	17.61	-	17.45	17.50	17.44	-
	75	0	17.60	17.81	17.75	-	17.43	17.64	17.58	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26140	Mid CH 26365	High CH 26590		Low CH 26140	Mid CH 26365	High CH 26590	
			1860.0 MHz	1882.5 MHz	1905.0 MHz		1860.0 MHz	1882.5 MHz	1905.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
25 / 20M	1	0	23.06	23.25	23.01	0	22.05	22.24	22.00	1
	1	50	22.70	22.89	22.65	0	21.69	21.88	21.64	1
	1	99	22.65	22.84	22.60	0	21.64	21.83	21.59	1
	50	0	21.85	22.04	21.80	1	20.84	21.03	20.79	2
	50	25	21.84	22.03	21.79	1	20.83	21.02	20.78	2
	50	50	21.81	22.00	21.76	1	20.80	20.99	20.75	2
	100	0	21.79	21.98	21.74	1	20.78	20.97	20.73	2
EUT with Power Reduction (P-Sensor Triggered)										
25 / 20M	1	0	18.31	18.52	18.46	-	18.16	18.37	18.31	-
	1	50	17.46	17.67	17.61	-	17.50	17.52	17.46	-
	1	99	17.60	17.81	17.75	-	17.45	17.66	17.60	-
	50	0	17.90	18.11	18.05	-	17.75	17.96	17.90	-
	50	25	17.52	17.73	17.67	-	17.47	17.58	17.52	-
	50	50	17.51	17.72	17.66	-	17.51	17.57	17.51	-
	100	0	17.65	17.86	17.80	-	17.50	17.71	17.65	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26697	Mid CH 26865	High CH 27033		Low CH 26697	Mid CH 26865	High CH 27033	
			814.7 MHz	831.5 MHz	848.3 MHz		814.7 MHz	831.5 MHz	848.3 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
26 / 1.4M	1	0	22.19	22.35	22.29	0	21.15	21.31	21.25	1
	1	2	22.02	22.07	22.01	0	21.07	21.03	21.17	1
	1	5	22.12	22.28	22.22	0	21.08	21.24	21.18	1
	3	0	22.07	22.23	22.17	0	21.03	21.19	21.13	1
	3	1	21.99	22.15	22.09	0	21.05	21.11	21.05	1
	3	3	22.00	22.16	22.10	0	20.96	21.12	21.06	1
	6	0	21.01	21.17	21.11	1	20.07	20.13	20.07	2
EUT with Power Reduction (P-Sensor Triggered)										
26 / 1.4M	1	0	19.81	19.86	19.83	-	19.51	19.60	19.55	-
	1	2	19.54	19.63	19.58	-	19.46	19.55	19.50	-
	1	5	19.46	19.55	19.50	-	19.38	19.47	19.42	-
	3	0	19.49	19.58	19.53	-	19.41	19.50	19.45	-
	3	1	19.44	19.53	19.48	-	19.36	19.45	19.40	-
	3	3	19.36	19.45	19.40	-	19.31	19.37	19.32	-
	6	0	19.46	19.55	19.50	-	19.38	19.47	19.42	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26705	Mid CH 26865	High CH 27025		Low CH 26705	Mid CH 26865	High CH 27025	
			815.5 MHz	831.5 MHz	847.5 MHz		815.5 MHz	831.5 MHz	847.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
26 / 3M	1	0	22.33	22.49	22.43	0	21.29	21.45	21.39	1
	1	7	22.05	22.21	22.15	0	21.01	21.17	21.11	1
	1	14	22.26	22.42	22.36	0	21.22	21.38	21.32	1
	8	0	21.21	21.37	21.31	1	20.17	20.33	20.27	2
	8	3	21.13	21.29	21.23	1	20.09	20.25	20.19	2
	8	7	21.14	21.30	21.24	1	20.10	20.26	20.20	2
	15	0	21.15	21.31	21.25	1	20.11	20.27	20.21	2
EUT with Power Reduction (P-Sensor Triggered)										
26 / 3M	1	0	19.86	19.91	19.88	-	19.66	19.75	19.70	-
	1	7	19.66	19.75	19.70	-	19.61	19.70	19.65	-
	1	14	19.58	19.67	19.62	-	19.53	19.62	19.57	-
	8	0	19.61	19.70	19.65	-	19.56	19.65	19.56	-
	8	3	19.56	19.65	19.60	-	19.51	19.60	19.55	-
	8	7	19.48	19.57	19.52	-	19.43	19.52	19.47	-
	15	0	19.58	19.67	19.62	-	19.53	19.62	19.57	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26715	Mid CH 26865	High CH 27015		Low CH 26715	Mid CH 26865	High CH 27015	
			816.5 MHz	831.5 MHz	846.5 MHz		816.5 MHz	831.5 MHz	846.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
26 / 5M	1	0	22.41	22.57	22.51	0	21.37	21.53	21.47	1
	1	12	22.13	22.29	22.23	0	21.09	21.25	21.19	1
	1	24	22.34	22.50	22.44	0	21.30	21.46	21.40	1
	12	0	21.29	21.45	21.39	1	20.25	20.41	20.35	2
	12	6	21.21	21.37	21.31	1	20.17	20.33	20.27	2
	12	13	21.22	21.38	21.32	1	20.18	20.34	20.28	2
	25	0	21.23	21.39	21.33	1	20.19	20.35	20.29	2
EUT with Power Reduction (P-Sensor Triggered)										
26 / 5M	1	0	19.91	19.96	19.93	-	19.79	19.88	19.83	-
	1	12	19.81	19.90	19.85	-	19.74	19.83	19.78	-
	1	24	19.73	19.82	19.77	-	19.66	19.75	19.70	-
	12	0	19.76	19.85	19.80	-	19.69	19.78	19.73	-
	12	6	19.71	19.80	19.75	-	19.64	19.73	19.68	-
	12	13	19.63	19.72	19.67	-	19.56	19.65	19.60	-
	25	0	19.73	19.82	19.77	-	19.66	19.75	19.70	-

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26740	Mid CH 26865	High CH 26990		Low CH 26740	Mid CH 26865	High CH 26990	
			819.0 MHz	831.5 MHz	844.0 MHz		819.0 MHz	831.5 MHz	844.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
26 / 10M	1	0	22.56	22.72	22.66	0	21.52	21.68	21.62	1
	1	24	22.28	22.44	22.38	0	21.24	21.40	21.34	1
	1	49	22.49	22.65	22.59	0	21.45	21.61	21.55	1
	25	0	21.44	21.60	21.54	1	20.40	20.56	20.50	2
	25	12	21.36	21.52	21.46	1	20.32	20.48	20.42	2
	25	25	21.37	21.53	21.47	1	20.33	20.49	20.43	2
	50	0	21.38	21.54	21.48	1	20.34	20.50	20.44	2
EUT with Power Reduction (P-Sensor Triggered)										
26 / 10M	1	0	19.99	20.08	20.03	-	19.81	19.90	19.85	-
	1	24	19.94	20.03	19.98	-	19.76	19.85	19.80	-
	1	49	19.86	19.95	19.90	-	19.68	19.77	19.72	-
	25	0	19.89	19.98	19.93	-	19.71	19.80	19.75	-
	25	12	19.84	19.93	19.88	-	19.66	19.75	19.70	-
	25	25	19.76	19.85	19.80	-	19.58	19.67	19.62	-
	50	0	19.86	19.95	19.90	-	19.68	19.77	19.72	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26765	Mid CH 26865	High CH 26965		Low CH 26765	Mid CH 26865	High CH 26965	
			821.5 MHz	831.5 MHz	841.5 MHz		821.5 MHz	831.5 MHz	841.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
26 / 15M	1	0	22.68	22.84	22.78	0	21.64	21.80	21.74	1
	1	37	22.40	22.56	22.50	0	21.36	21.52	21.46	1
	1	74	22.61	22.77	22.71	0	21.57	21.73	21.67	1
	36	0	21.56	21.72	21.66	1	20.52	20.68	20.62	2
	36	19	21.48	21.64	21.58	1	20.44	20.60	20.54	2
	36	39	21.49	21.65	21.59	1	20.45	20.61	20.55	2
	75	0	21.50	21.66	21.60	1	20.46	20.62	20.56	2
EUT with Power Reduction (P-Sensor Triggered)										
26 / 15M	1	0	20.07	20.16	20.11	-	19.92	20.01	19.96	-
	1	37	20.02	20.11	20.06	-	19.87	19.96	19.91	-
	1	74	19.94	20.03	19.98	-	19.79	19.88	19.83	-
	36	0	19.97	20.06	20.01	-	19.82	19.91	19.86	-
	36	19	19.92	20.01	19.96	-	19.77	19.86	19.81	-
	36	39	19.84	19.93	19.88	-	19.69	19.78	19.73	-
	75	0	19.94	20.03	19.98	-	19.79	19.88	19.83	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 27685	Mid CH 27710	High CH 27735		Low CH 27685	Mid CH 27710	High CH 27735	
			2307.5 MHz	2310.0 MHz	2312.5 MHz		2307.5 MHz	2310.0 MHz	2312.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)										
30 / 5M	1	0	21.24	21.28	21.20	0	20.21	20.25	20.17	1
	1	12	21.22	21.26	21.18	0	20.19	20.23	20.15	1
	1	24	21.14	21.25	21.13	0	20.02	20.08	20.06	1
	12	0	20.19	20.23	20.15	1	19.16	19.20	19.12	2
	12	6	20.15	20.19	20.11	1	19.12	19.16	19.08	2
	12	13	20.14	20.17	20.05	1	19.02	19.06	19.04	2
	25	0	20.04	20.06	20.00	1	19.01	19.07	19.03	2
EUT with Power Reduction (P-Sensor Triggered)										
30 / 5M	1	0	15.80	15.82	15.81	-	15.72	15.74	15.73	-
	1	12	15.78	15.80	15.79	-	15.70	15.72	15.71	-
	1	24	15.69	15.71	15.70	-	15.61	15.63	15.62	-
	12	0	15.74	15.76	15.75	-	15.66	15.68	15.67	-
	12	6	15.73	15.75	15.74	-	15.65	15.67	15.66	-
	12	13	15.61	15.63	15.62	-	15.53	15.55	15.54	-
	25	0	15.75	15.77	15.76	-	15.67	15.69	15.68	-

Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)
			Mid CH 27710		Mid CH 27710	
			2310.0 MHz		2310.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)						
30 / 10M	1	0	21.42	0	20.37	1
	1	24	21.38	0	20.33	1
	1	49	21.11	0	20.06	1
	25	0	20.35	1	19.30	2
	25	12	20.31	1	19.26	2
	25	25	20.07	1	19.02	2
	50	0	20.16	1	19.11	2
EUT with Power Reduction (P-Sensor Triggered)						
30 / 10M	1	0	16.26	-	16.08	-
	1	24	15.86	-	15.68	-
	1	49	15.53	-	15.35	-
	25	0	15.80	-	15.62	-
	25	12	15.79	-	15.61	-
	25	25	15.55	-	15.37	-
	50	0	15.71	-	15.53	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH	M-CH	M-CH	M-CH	H-CH		L-CH	M-CH	M-CH	M-CH	H-CH	
			39675	40148	40620	41093	41565		39675	40148	40620	41093	41565	
			2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz		2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)														
41 / 5M	1	0	22.23	21.99	22.81	22.41	22.65	0	21.17	20.93	21.75	21.35	21.59	1
	1	12	22.11	21.87	22.71	22.29	22.53	0	21.05	20.81	21.65	21.23	21.47	1
	1	24	21.81	21.57	22.41	21.99	22.23	0	20.75	20.51	21.35	20.93	21.17	1
	12	0	21.15	20.91	21.75	21.33	21.57	1	20.09	20.35	20.69	20.27	20.51	2
	12	6	21.14	20.90	21.74	21.32	21.56	1	20.08	20.34	20.68	20.26	20.50	2
	12	13	21.08	20.84	21.68	21.26	21.50	1	20.02	20.35	20.62	20.20	20.44	2
	25	0	21.07	20.83	21.67	21.25	21.49	1	20.01	20.37	20.61	20.19	20.43	2
EUT with Power Reduction (P-Sensor Triggered)														
41 / 5M	1	0	17.01	17.06	17.11	17.05	17.04	-	17.02	17.06	17.10	17.05	17.04	-
	1	12	17.04	17.06	17.02	17.04	17.01	-	17.06	17.06	17.02	17.04	17.08	-
	1	24	17.01	17.02	17.09	17.03	17.03	-	17.01	17.02	17.09	17.03	17.07	-
	12	0	17.02	17.01	17.07	17.02	17.02	-	17.02	17.03	17.07	17.02	17.06	-
	12	6	17.05	17.01	17.06	17.04	17.03	-	17.05	17.04	17.06	17.04	17.03	-
	12	13	17.04	17.04	17.03	17.02	17.01	-	17.04	17.04	17.03	17.02	17.01	-
	25	0	17.06	17.04	17.06	17.01	17.03	-	17.06	17.04	17.06	17.01	17.03	-

Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH	M-CH	M-CH	M-CH	H-CH		L-CH	M-CH	M-CH	M-CH	H-CH	
			39700	40160	40620	41080	41540		39700	40160	40620	41080	41540	
			2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz		2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)														
41 / 10M	1	0	22.27	22.03	22.85	22.45	22.69	0	21.21	20.97	21.79	21.39	21.63	1
	1	24	22.15	21.91	22.75	22.33	22.57	0	21.09	20.85	21.69	21.27	21.51	1
	1	49	21.85	21.61	22.45	22.03	22.27	0	20.79	20.55	21.39	20.97	21.21	1
	25	0	21.19	20.95	21.79	21.37	21.61	1	20.13	20.39	20.73	20.31	20.55	2
	25	12	21.18	20.94	21.78	21.36	21.60	1	20.12	20.38	20.72	20.30	20.54	2
	25	25	21.12	20.88	21.72	21.30	21.54	1	20.06	20.39	20.66	20.24	20.48	2
	50	0	21.11	20.87	21.71	21.29	21.53	1	20.05	20.41	20.65	20.23	20.47	2
EUT with Power Reduction (P-Sensor Triggered)														
41 / 10M	1	0	17.05	17.02	17.08	17.03	17.06	-	17.05	17.02	17.08	17.03	17.06	-
	1	24	17.04	17.06	17.05	17.04	17.01	-	17.04	17.06	17.05	17.04	17.01	-
	1	49	17.01	17.02	17.03	17.06	17.05	-	17.01	17.02	17.03	17.06	17.05	-
	25	0	17.02	17.01	17.07	17.02	17.02	-	17.03	17.02	17.07	17.02	17.05	-
	25	12	17.05	17.01	17.06	17.04	17.03	-	17.05	17.01	17.06	17.04	17.03	-
	25	25	17.04	17.03	17.03	17.01	17.01	-	17.04	17.03	17.03	17.01	17.01	-
	50	0	17.07	17.04	17.06	17.01	17.03	-	17.07	17.04	17.06	17.01	17.03	-

FCC SAR Test Report

A D T

Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515		L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515	
			2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz		2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)														
41 / 15M	1	0	22.34	22.10	22.92	22.52	22.76	0	21.28	21.04	21.86	21.46	21.70	1
	1	37	22.22	21.98	22.82	22.40	22.64	0	21.16	20.92	21.76	21.34	21.58	1
	1	74	21.92	21.68	22.52	22.10	22.34	0	20.86	20.62	21.46	21.04	21.28	1
	36	0	21.26	21.02	21.86	21.44	21.68	1	20.20	20.46	20.80	20.38	20.62	2
	36	19	21.25	21.01	21.85	21.43	21.67	1	20.19	20.45	20.79	20.37	20.61	2
	36	39	21.19	20.95	21.79	21.37	21.61	1	20.13	20.46	20.73	20.31	20.55	2
	75	0	21.18	20.94	21.78	21.36	21.60	1	20.12	20.48	20.72	20.30	20.54	2
EUT with Power Reduction (P-Sensor Triggered)														
41 / 15M	1	0	17.08	17.05	17.10	17.06	17.03	-	17.07	17.04	17.09	17.05	17.02	-
	1	37	17.05	17.07	17.08	17.05	17.02	-	17.04	17.06	17.07	17.04	17.01	-
	1	74	17.02	17.01	17.06	17.04	17.02	-	17.01	17.02	17.05	17.03	17.02	-
	36	0	17.01	17.02	17.08	17.01	17.01	-	17.02	17.01	17.07	17.02	17.02	-
	36	19	17.06	17.02	17.07	17.05	17.04	-	17.05	17.01	17.06	17.04	17.03	-
	36	39	17.05	17.05	17.04	17.02	17.02	-	17.04	17.04	17.03	17.02	17.01	-
	75	0	17.02	17.05	17.07	17.02	17.04	-	17.05	17.04	17.06	17.01	17.03	-

Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490		L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490	
			2506.0	2549.5	2593.0	2636.5	2680.0		2506.0	2549.5	2593.0	2636.5	2680.0	
			MHz	MHz	MHz	MHz	MHz		MHz	MHz	MHz	MHz	MHz	
EUT without Power Reduction (P-Sensor NOT Triggered)														
41 / 20M	1	0	22.40	22.16	22.98	22.58	22.82	0	21.34	21.10	21.92	21.52	21.76	1
	1	50	22.28	22.04	22.88	22.46	22.70	0	21.22	20.98	21.82	21.40	21.64	1
	1	99	21.98	21.74	22.58	22.16	22.40	0	20.92	20.68	21.52	21.10	21.34	1
	50	0	21.32	21.08	21.92	21.50	21.74	1	20.26	20.52	20.86	20.44	20.68	2
	50	25	21.31	21.07	21.91	21.49	21.73	1	20.25	20.51	20.85	20.43	20.67	2
	50	50	21.25	21.01	21.85	21.43	21.67	1	20.19	20.52	20.79	20.37	20.61	2
	100	0	21.24	21.00	21.84	21.42	21.66	1	20.18	20.54	20.78	20.36	20.60	2
EUT with Power Reduction (P-Sensor Triggered)														
41 / 20M	1	0	17.12	17.06	17.19	17.07	17.02	-	17.11	17.05	17.18	17.06	17.01	-
	1	50	17.06	17.08	17.13	17.06	17.03	-	17.05	17.07	17.12	17.05	17.02	-
	1	99	17.03	17.02	17.11	17.05	17.01	-	17.02	17.01	17.10	17.04	17.01	-
	50	0	17.02	17.03	17.09	17.02	17.02	-	17.01	17.02	17.08	17.01	17.01	-
	50	25	17.07	17.02	17.08	17.06	17.05	-	17.06	17.02	17.07	17.05	17.04	-
	50	50	17.06	17.01	17.05	17.01	17.03	-	17.05	17.05	17.04	17.02	17.02	-
	100	0	17.01	17.06	17.08	17.03	17.05	-	17.01	17.05	17.07	17.02	17.04	-

FCC SAR Test Report

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

4.7.2 SAR Results for Body Exposure Condition

EUT 1 (Thin cover)

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
01	WCDMA II	RMC12.2K	Rear Face	0	9400	w/	18.0	17.26	1.19	0.02	0.831	0.99
	WCDMA II	RMC12.2K	Rear Face	0	9262	w/	18.0	16.88	1.29	0	0.994	1.29
	WCDMA II	RMC12.2K	Rear Face	0	9262	w/	18.0	16.88	1.29	0.07	0.987	1.28
	WCDMA II	RMC12.2K	Rear Face	0	9538	w/	18.0	17.16	1.21	-0.06	0.797	0.97
	WCDMA II	HSDPA Subtest-1	Rear Face	0	9400	w/	18.0	16.85	1.30	0.07	0.723	0.94
	WCDMA II	HSDPA Subtest-1	Rear Face	0	9262	w/	18.0	16.48	1.42	-0.01	0.837	1.19
	WCDMA II	HSDPA Subtest-1	Rear Face	0	9538	w/	18.0	16.76	1.33	0.03	0.702	0.93
	WCDMA II	HSUPA Subtest-5	Rear Face	0	9400	w/	18.0	16.55	1.40	0.09	0.658	0.92
	WCDMA II	HSUPA Subtest-5	Rear Face	0	9262	w/	18.0	16.17	1.52	-0.04	0.774	1.18
	WCDMA II	HSUPA Subtest-5	Rear Face	0	9538	w/	18.0	16.45	1.43	0.01	0.638	0.91
	WCDMA II	RMC12.2K	Rear Face	1.7	9400	w/o	24.0	22.81	1.32	0.06	0.328	0.43
	WCDMA II	RMC12.2K	Right Side	0	9400	w/o	24.0	22.81	1.32	0.03	0.197	0.26
02	WCDMA II	RMC12.2K	Left Side	0	9400	w/o	24.0	22.81	1.32	0.02	0.0581	0.08
	WCDMA II	RMC12.2K	Top Side	0	9400	w/	18.0	17.26	1.19	-0.18	0.519	0.62
	WCDMA II	RMC12.2K	Top Side	2.6	9400	w/o	24.0	22.81	1.32	0.03	0.244	0.32
	WCDMA II	RMC12.2K	Bottom Side	0	9400	w/o	24.0	22.81	1.32	0	0	0.00
	WCDMA IV	RMC12.2K	Rear Face	0	1413	w/	19.0	18.31	1.17	0	0.732	0.86
	WCDMA IV	RMC12.2K	Rear Face	0	1312	w/	19.0	18.18	1.21	0	0.645	0.78
	WCDMA IV	RMC12.2K	Rear Face	0	1513	w/	19.0	18.13	1.22	0	0.811	0.99
	WCDMA IV	RMC12.2K	Rear Face	0	1513	w/	19.0	18.13	1.22	0	0.801	0.98
	WCDMA IV	RMC12.2K	Rear Face	1.7	1413	w/o	24.0	22.66	1.36	0.05	0.341	0.46
	WCDMA IV	RMC12.2K	Right Side	0	1413	w/o	24.0	22.66	1.36	0.01	0.207	0.28
	WCDMA IV	RMC12.2K	Left Side	0	1413	w/o	24.0	22.66	1.36	0.12	0.055	0.07
	WCDMA IV	RMC12.2K	Top Side	0	1413	w/	19.0	18.31	1.17	-0.05	0.737	0.86
03	WCDMA IV	RMC12.2K	Top Side	0	1312	w/	19.0	18.18	1.21	0.1	0.688	0.83
	WCDMA IV	RMC12.2K	Top Side	0	1513	w/	19.0	18.13	1.22	0.11	0.715	0.87
	WCDMA IV	RMC12.2K	Top Side	2.6	1413	w/o	24.0	22.66	1.36	0.04	0.224	0.30
	WCDMA IV	RMC12.2K	Bottom Side	0	1413	w/o	24.0	22.66	1.36	0.12	0	0.00
	WCDMA V	RMC12.2K	Rear Face	0	4182	w/	21.0	20.20	1.20	-0.04	0.65	0.78
	WCDMA V	RMC12.2K	Rear Face	1.7	4182	w/o	24.0	22.89	1.29	-0.01	0.237	0.31
	WCDMA V	RMC12.2K	Right Side	0	4182	w/o	24.0	22.89	1.29	0.15	0.167	0.22
	WCDMA V	RMC12.2K	Left Side	0	4182	w/o	24.0	22.89	1.29	0.12	0.038	0.05
	WCDMA V	RMC12.2K	Top Side	0	4182	w/	21.0	20.20	1.20	0.18	0.749	0.90
	WCDMA V	RMC12.2K	Top Side	0	4132	w/	21.0	19.89	1.29	0.15	0.771	1.00
	WCDMA V	RMC12.2K	Top Side	0	4233	w/	21.0	19.95	1.27	0.15	0.812	1.03
	WCDMA V	RMC12.2K	Top Side	0	4233	w/	21.0	19.95	1.27	0.04	0.802	1.02
	WCDMA V	RMC12.2K	Top Side	2.6	4182	w/o	24.0	22.89	1.29	0.06	0.108	0.14
	WCDMA V	RMC12.2K	Bottom Side	0	4182	w/o	24.0	22.89	1.29	0.12	0	0.00



A D T

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
04	LTE 2	QPSK20M	Rear Face	0	18900	w/	1	0	19.0	18.63	1.09	0.01	0.782	0.85
	LTE 2	QPSK20M	Rear Face	0	18700	w/	1	0	19.0	18.24	1.19	0	0.952	1.13
	LTE 2	QPSK20M	Rear Face	0	18700	w/	1	0	19.0	18.24	1.19	0	0.943	1.12
	LTE 2	QPSK20M	Rear Face	0	19100	w/	1	0	19.0	18.53	1.11	0.01	0.742	0.83
	LTE 2	QPSK20M	Rear Face	0	18900	w/	50	0	19.0	18.23	1.19	0.01	0.735	0.88
	LTE 2	QPSK20M	Rear Face	0	18700	w/	50	0	19.0	17.84	1.31	0.02	0.861	1.12
	LTE 2	QPSK20M	Rear Face	0	19100	w/	50	0	19.0	18.13	1.22	0	0.691	0.84
	LTE 2	QPSK20M	Rear Face	0	18900	w/	100	0	19.0	18.00	1.26	0.01	0.847	1.07
	LTE 2	QPSK20M	Rear Face	1.7	18900	w/o	1	0	24.0	23.61	1.09	0.07	0.278	0.30
	LTE 2	QPSK20M	Rear Face	1.7	18900	w/o	50	0	23.0	22.66	1.08	0.15	0.198	0.21
	LTE 2	QPSK20M	Right Side	0	18900	w/o	1	0	24.0	23.61	1.09	0.06	0.139	0.15
	LTE 2	QPSK20M	Right Side	0	18900	w/o	50	0	23.0	22.66	1.08	-0.06	0.117	0.13
	LTE 2	QPSK20M	Left Side	0	18900	w/o	1	0	24.0	23.61	1.09	0.12	0.062	0.07
	LTE 2	QPSK20M	Left Side	0	18900	w/o	50	0	23.0	22.66	1.08	0.12	0.000	0.00
	LTE 2	QPSK20M	Top Side	0	18900	w/	1	0	19.0	18.63	1.09	-0.11	0.593	0.65
	LTE 2	QPSK20M	Top Side	0	18900	w/	50	0	19.0	18.23	1.19	-0.04	0.536	0.64
	LTE 2	QPSK20M	Top Side	2.6	18900	w/o	1	0	24.0	23.61	1.09	-0.04	0.235	0.26
	LTE 2	QPSK20M	Top Side	2.6	18900	w/o	50	0	23.0	22.66	1.08	0.03	0.173	0.19
	LTE 2	QPSK20M	Bottom Side	0	18900	w/o	1	0	24.0	23.61	1.09	0	0	0.00
	LTE 2	QPSK20M	Bottom Side	0	18900	w/o	50	0	23.0	22.66	1.08	0	0	0.00
05	LTE 4	QPSK20M	Rear Face	0	20175	w/	1	0	18.0	17.68	1.08	0.03	0.669	0.72
	LTE 4	QPSK20M	Rear Face	0	20175	w/	50	0	18.0	17.45	1.14	0.01	0.682	0.77
	LTE 4	QPSK20M	Rear Face	1.7	20175	w/o	1	0	24.0	23.34	1.16	0.06	0.296	0.34
	LTE 4	QPSK20M	Rear Face	1.7	20175	w/o	50	0	23.0	21.91	1.29	0.15	0.223	0.29
	LTE 4	QPSK20M	Right Side	0	20175	w/o	1	0	24.0	23.34	1.16	0.11	0.250	0.29
	LTE 4	QPSK20M	Right Side	0	20175	w/o	50	0	23.0	21.91	1.29	-0.01	0.194	0.25
	LTE 4	QPSK20M	Left Side	0	20175	w/o	1	0	24.0	23.34	1.16	0.12	0.066	0.08
	LTE 4	QPSK20M	Left Side	0	20175	w/o	50	0	23.0	21.91	1.29	0	0.000	0.00
	LTE 4	QPSK20M	Top Side	0	20175	w/	1	0	18.0	17.68	1.08	0.05	0.771	0.83
	LTE 4	QPSK20M	Top Side	0	20050	w/	1	0	18.0	17.57	1.10	0.1	0.758	0.84
	LTE 4	QPSK20M	Top Side	0	20300	w/	1	0	18.0	17.65	1.08	-0.02	0.813	0.88
	LTE 4	QPSK20M	Top Side	0	20300	w/	1	0	18.0	17.65	1.08	0	0.799	0.87
	LTE 4	QPSK20M	Top Side	0	20175	w/	50	0	18.0	17.45	1.14	0.04	0.76	0.86
	LTE 4	QPSK20M	Top Side	0	20050	w/	50	0	18.0	17.34	1.16	0.06	0.728	0.85
	LTE 4	QPSK20M	Top Side	0	20300	w/	50	0	18.0	17.42	1.14	0.05	0.761	0.87
	LTE 4	QPSK20M	Top Side	0	20175	w/	100	0	18.0	17.25	1.19	-0.08	0.734	0.87
06	LTE 4	QPSK20M	Top Side	2.6	20175	w/o	1	0	24.0	23.34	1.16	-0.06	0.259	0.30
	LTE 4	QPSK20M	Top Side	2.6	20175	w/o	50	0	23.0	21.91	1.29	0.1	0.195	0.25
	LTE 4	QPSK20M	Bottom Side	0	20175	w/o	1	0	24.0	23.34	1.16	0	0	0.00
	LTE 4	QPSK20M	Bottom Side	0	20175	w/o	50	0	23.0	21.91	1.29	0	0	0.00
	LTE 5	QPSK10M	Rear Face	0	20525	w/	1	0	20.0	19.98	1.00	0.11	0.657	0.66
	LTE 5	QPSK10M	Rear Face	0	20525	w/	25	0	20.0	19.95	1.01	-0.11	0.664	0.67
	LTE 5	QPSK10M	Rear Face	1.7	20525	w/o	1	0	24.0	23.14	1.22	-0.02	0.119	0.15
	LTE 5	QPSK10M	Rear Face	1.7	20525	w/o	25	0	23.0	22.16	1.21	0.14	0.093	0.11
	LTE 5	QPSK10M	Right Side	0	20525	w/o	1	0	24.0	23.14	1.22	0.03	0.099	0.12
	LTE 5	QPSK10M	Right Side	0	20525	w/o	25	0	23.0	22.16	1.21	0.02	0.074	0.09
	LTE 5	QPSK10M	Left Side	0	20525	w/o	1	0	24.0	23.14	1.22	0.09	0	0.00
	LTE 5	QPSK10M	Left Side	0	20525	w/o	25	0	23.0	22.16	1.21	0.01	0	0.00
06	LTE 5	QPSK10M	Top Side	0	20525	w/	1	0	20.0	19.98	1.00	-0.13	0.71	0.71
	LTE 5	QPSK10M	Top Side	0	20525	w/	25	0	20.0	19.95	1.01	-0.15	0.712	0.72
	LTE 5	QPSK10M	Top Side	2.6	20525	w/o	1	0	24.0	23.14	1.22	0.02	0.075	0.09
	LTE 5	QPSK10M	Top Side	2.6	20525	w/o	25	0	23.0	22.16	1.21	-0.06	0.063	0.08
	LTE 5	QPSK10M	Bottom Side	0	20525	w/o	1	0	24.0	23.14	1.22	0	0	0.00
LTE 5	QPSK10M	Bottom Side	0	20525	w/o	25	0	23.0	22.16	1.21	0	0	0	0.00



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
07	LTE 7	QPSK20M	Rear Face	0	21100	w/	1	0	18.0	16.11	1.55	0	0.727	1.12
	LTE 7	QPSK20M	Rear Face	0	20850	w/	1	0	18.0	16.09	1.55	0.08	0.801	1.24
	LTE 7	QPSK20M	Rear Face	0	21350	w/	1	0	18.0	16.10	1.55	0.04	0.726	1.12
	LTE 7	QPSK20M	Rear Face	0	21100	w/	50	0	18.0	16.08	1.56	0.02	0.778	1.21
	LTE 7	QPSK20M	Rear Face	0	20850	w/	50	0	18.0	16.06	1.56	0.05	0.824	1.29
	LTE 7	QPSK20M	Rear Face	0	20850	w/	50	0	18.0	16.06	1.56	0.15	0.818	1.28
	LTE 7	QPSK20M	Rear Face	0	21350	w/	50	0	18.0	16.07	1.56	0.01	0.766	1.19
	LTE 7	QPSK20M	Rear Face	0	21100	w/	100	0	18.0	16.05	1.57	0	0.707	1.11
	LTE 7	QPSK20M	Rear Face	1.7	21100	w/o	1	0	23.0	21.64	1.37	0.09	0.146	0.20
	LTE 7	QPSK20M	Rear Face	1.7	21100	w/o	50	0	22.0	20.86	1.30	0	0.117	0.15
	LTE 7	QPSK20M	Right Side	0	21100	w/o	1	0	23.0	21.64	1.37	0.08	0.064	0.09
	LTE 7	QPSK20M	Right Side	0	21100	w/o	50	0	22.0	20.86	1.30	0.06	0.049	0.06
	LTE 7	QPSK20M	Left Side	0	21100	w/o	1	0	23.0	21.64	1.37	0.03	0	0.00
	LTE 7	QPSK20M	Left Side	0	21100	w/o	50	0	22.0	20.86	1.30	0.01	0	0.00
	LTE 7	QPSK20M	Top Side	0	21100	w/	1	0	18.0	16.11	1.55	0.09	0.676	1.04
	LTE 7	QPSK20M	Top Side	0	20850	w/	1	0	18.0	16.09	1.55	0.08	0.688	1.07
	LTE 7	QPSK20M	Top Side	0	21350	w/	1	0	18.0	16.10	1.55	0.04	0.688	1.07
	LTE 7	QPSK20M	Top Side	0	21100	w/	50	0	18.0	16.08	1.56	0.1	0.712	1.11
	LTE 7	QPSK20M	Top Side	0	20850	w/	50	0	18.0	16.06	1.56	0.08	0.716	1.12
	LTE 7	QPSK20M	Top Side	0	21350	w/	50	0	18.0	16.07	1.56	0.01	0.719	1.12
	LTE 7	QPSK20M	Top Side	0	21100	w/	100	0	18.0	16.05	1.57	0.1	0.68	1.07
	LTE 7	QPSK20M	Top Side	2.6	21100	w/o	1	0	23.0	21.64	1.37	-0.04	0.114	0.16
	LTE 7	QPSK20M	Top Side	2.6	21100	w/o	50	0	22.0	20.86	1.30	0.06	0.092	0.12
	LTE 7	QPSK20M	Bottom Side	0	21100	w/o	1	0	23.0	21.64	1.37	0	0	0.00
	LTE 7	QPSK20M	Bottom Side	0	21100	w/o	50	0	22.0	20.86	1.30	0	0	0.00
08	LTE 12	QPSK10M	Rear Face	0	23095	w/	1	0	20.0	19.45	1.14	0.02	0.49	0.56
	LTE 12	QPSK10M	Rear Face	0	23095	w/	25	0	20.0	19.22	1.20	0	0.478	0.57
	LTE 12	QPSK10M	Rear Face	1.7	23095	w/o	1	0	24.0	22.68	1.36	0.08	0.181	0.25
	LTE 12	QPSK10M	Rear Face	1.7	23095	w/o	25	0	23.0	21.50	1.41	0.07	0.146	0.21
	LTE 12	QPSK10M	Right Side	0	23095	w/o	1	0	24.0	22.68	1.36	0.07	0.147	0.20
	LTE 12	QPSK10M	Right Side	0	23095	w/o	25	0	23.0	21.50	1.41	0.01	0.086	0.12
	LTE 12	QPSK10M	Left Side	0	23095	w/o	1	0	24.0	22.68	1.36	0.01	0.035	0.05
	LTE 12	QPSK10M	Left Side	0	23095	w/o	25	0	23.0	21.50	1.41	0.06	0.000	0.00
	LTE 12	QPSK10M	Top Side	0	23095	w/	1	0	20.0	19.45	1.14	0.07	0.752	0.85
	LTE 12	QPSK10M	Top Side	0	23060	w/	1	0	20.0	19.26	1.19	0.01	0.726	0.86
	LTE 12	QPSK10M	Top Side	0	23130	w/	1	0	20.0	19.20	1.20	0.02	0.730	0.88
	LTE 12	QPSK10M	Top Side	0	23095	w/	25	0	20.0	19.22	1.20	0.02	0.733	0.88
	LTE 12	QPSK10M	Top Side	0	23060	w/	25	0	20.0	19.03	1.25	0.02	0.743	0.93
	LTE 12	QPSK10M	Top Side	0	23130	w/	25	0	20.0	18.97	1.27	0.06	0.702	0.89
	LTE 12	QPSK10M	Top Side	0	23095	w/	50	0	20.0	19.07	1.24	0.03	0.697	0.86
	LTE 12	QPSK10M	Top Side	2.6	23095	w/o	1	0	24.0	22.68	1.36	0.07	0.058	0.08
09	LTE 12	QPSK10M	Top Side	2.6	23095	w/o	50	0	23.0	21.50	1.41	-0.05	0.055	0.08
	LTE 12	QPSK10M	Bottom Side	0	23095	w/o	1	0	24.0	22.68	1.36	0	0	0.00
	LTE 12	QPSK10M	Bottom Side	0	23095	w/o	50	0	23.0	21.50	1.41	0	0	0.00
	LTE 13	QPSK10M	Rear Face	0	23230	w/	1	0	20.0	19.23	1.19	0.06	0.702	0.84
	LTE 13	QPSK10M	Rear Face	0	23230	w/	25	0	20.0	19.15	1.22	0.08	0.676	0.82
	LTE 13	QPSK10M	Rear Face	1.7	23230	w/o	1	0	24.0	23.03	1.25	0.01	0.161	0.20
	LTE 13	QPSK10M	Rear Face	1.7	23230	w/o	25	0	23.0	22.13	1.22	-0.05	0.142	0.17
	LTE 13	QPSK10M	Right Side	0	23230	w/o	1	0	24.0	23.03	1.25	0.03	0.107	0.13
	LTE 13	QPSK10M	Right Side	0	23230	w/o	25	0	23.0	22.13	1.22	0.05	0.097	0.12
	LTE 13	QPSK10M	Left Side	0	23230	w/o	1	0	24.0	23.03	1.25	0.01	0.01	0.01
	LTE 13	QPSK10M	Left Side	0	23230	w/o	25	0	23.0	22.13	1.22	0.00	0.00	0.00
	LTE 13	QPSK10M	Top Side	0	23230	w/	1	0	20.0	19.23	1.19	0.03	0.755	0.90
	LTE 13	QPSK10M	Top Side	0	23230	w/	1	0	20.0	19.23	1.19	0.04	0.742	0.89
	LTE 13	QPSK10M	Top Side	0	23230	w/	25	0	20.0	19.15	1.22	0.16	0.733	0.89
	LTE 13	QPSK10M	Top Side	0	23230	w/	50	0	20.0	19.19	1.21	0.11	0.694	0.84
	LTE 13	QPSK10M	Top Side	2.6	23230	w/o	1	0	24.0	23.03	1.25	-0.05	0.079	0.10
	LTE 13	QPSK10M	Top Side	2.6	23230	w/o	25	0	23.0	22.13	1.22	0.14	0.067	0.08
	LTE 13	QPSK10M	Bottom Side	0	23230	w/o	1	0	24.0	23.03	1.25	0	0	0.00
	LTE 13	QPSK10M	Bottom Side	0	23230	w/o	25	0	23.0	22.13	1.22	0	0	0.00



A D T

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
10	LTE 25	QPSK20M	Rear Face	0	26365	w/	1	0	19.0	18.52	1.12	0.02	0.77	0.86
	LTE 25	QPSK20M	Rear Face	0	26140	w/	1	0	19.0	18.31	1.17	0.01	0.835	0.98
	LTE 25	QPSK20M	Rear Face	0	26590	w/	1	0	19.0	18.46	1.13	0.06	0.713	0.81
	LTE 25	QPSK20M	Rear Face	0	26365	w/	50	0	19.0	18.11	1.23	0.03	0.693	0.85
	LTE 25	QPSK20M	Rear Face	0	26140	w/	50	0	19.0	17.90	1.29	0	0.844	1.09
	LTE 25	QPSK20M	Rear Face	0	26140	w/	50	0	19.0	17.90	1.29	0	0.831	1.07
	LTE 25	QPSK20M	Rear Face	0	26590	w/	50	0	19.0	18.05	1.24	0.07	0.665	0.83
	LTE 25	QPSK20M	Rear Face	0	26365	w/	100	0	19.0	17.86	1.30	0.01	0.808	1.05
	LTE 25	QPSK20M	Rear Face	1.7	26365	w/o	1	0	24.0	23.25	1.19	0	0.381	0.45
	LTE 25	QPSK20M	Rear Face	1.7	26365	w/o	50	0	23.0	22.04	1.25	0.06	0.267	0.33
	LTE 25	QPSK20M	Right Side	0	26365	w/o	1	0	24.0	23.25	1.19	0.13	0.198	0.24
	LTE 25	QPSK20M	Right Side	0	26365	w/o	50	0	23.0	22.04	1.25	0.09	0.155	0.19
	LTE 25	QPSK20M	Left Side	0	26365	w/o	1	0	24.0	23.25	1.19	0.12	0.0684	0.08
	LTE 25	QPSK20M	Left Side	0	26365	w/o	50	0	23.0	22.04	1.25	0.03	0.0572	0.07
	LTE 25	QPSK20M	Top Side	0	26365	w/	1	0	19.0	18.52	1.12	0.09	0.542	0.61
	LTE 25	QPSK20M	Top Side	0	26365	w/	50	0	19.0	18.11	1.23	0.08	0.451	0.55
	LTE 25	QPSK20M	Top Side	2.6	26365	w/o	1	0	24.0	23.25	1.19	0.06	0.289	0.34
	LTE 25	QPSK20M	Top Side	2.6	26365	w/o	50	0	23.0	22.04	1.25	0.09	0.203	0.25
	LTE 25	QPSK20M	Bottom Side	2.6	26365	w/o	1	0	24.0	23.25	1.19	0	0	0.00
	LTE 25	QPSK20M	Bottom Side	2.6	26365	w/o	50	0	23.0	22.04	1.25	0	0	0.00
11	LTE 26	QPSK15M	Rear Face	0	26865	w/	1	0	21.0	20.16	1.21	0.14	0.748	0.91
	LTE 26	QPSK15M	Rear Face	0	26765	w/	1	0	21.0	20.07	1.24	0.11	0.735	0.91
	LTE 26	QPSK15M	Rear Face	0	26965	w/	1	0	21.0	20.11	1.23	0.12	0.73	0.90
	LTE 26	QPSK15M	Rear Face	0	26865	w/	36	0	21.0	20.06	1.24	-0.18	0.766	0.95
	LTE 26	QPSK15M	Rear Face	0	26765	w/	36	0	21.0	19.97	1.27	-0.11	0.783	0.99
	LTE 26	QPSK15M	Rear Face	0	26965	w/	36	0	21.0	20.01	1.26	-0.11	0.801	1.01
	LTE 26	QPSK15M	Rear Face	0	26865	w/	75	0	21.0	20.03	1.25	-0.12	0.754	0.94
	LTE 26	QPSK15M	Rear Face	1.7	26865	w/o	1	0	24.0	22.84	1.31	-0.01	0.129	0.17
	LTE 26	QPSK15M	Rear Face	1.7	26865	w/o	36	0	23.0	21.72	1.34	0.13	0.099	0.13
	LTE 26	QPSK15M	Right Side	0	26865	w/o	1	0	24.0	22.84	1.31	0.07	0.127	0.17
	LTE 26	QPSK15M	Right Side	0	26865	w/o	36	0	23.0	21.72	1.34	0.1	0.095	0.13
	LTE 26	QPSK15M	Left Side	0	26865	w/o	1	0	24.0	22.84	1.31	0.04	0.042	0.05
	LTE 26	QPSK15M	Left Side	0	26865	w/o	36	0	23.0	21.72	1.34	0	0	0.00
	LTE 26	QPSK15M	Top Side	0	26865	w/	1	0	21.0	20.16	1.21	0.14	0.775	0.94
	LTE 26	QPSK15M	Top Side	0	26765	w/	1	0	21.0	20.07	1.24	0.15	0.83	1.03
	LTE 26	QPSK15M	Top Side	0	26965	w/	1	0	21.0	20.11	1.23	0.11	0.825	1.01
	LTE 26	QPSK15M	Top Side	0	26865	w/	36	0	21.0	20.06	1.24	0.11	0.796	0.99
	LTE 26	QPSK15M	Top Side	0	26765	w/	36	0	21.0	19.97	1.27	0.15	0.813	1.03
	LTE 26	QPSK15M	Top Side	0	26965	w/	36	0	21.0	20.01	1.26	-0.1	0.864	1.09
	LTE 26	QPSK15M	Top Side	0	26965	w/	36	0	21.0	20.01	1.26	-0.08	0.852	1.07
12	LTE 26	QPSK15M	Top Side	0	26865	w/	75	0	21.0	20.03	1.25	0.13	0.805	1.01
	LTE 26	QPSK15M	Top Side	2.6	26865	w/o	1	0	24.0	22.84	1.31	-0.1	0.086	0.11
	LTE 26	QPSK15M	Top Side	2.6	26865	w/o	36	0	23.0	21.72	1.34	-0.06	0.069	0.09
	LTE 26	QPSK15M	Bottom Side	0	26865	w/o	1	0	24.0	22.84	1.31	0	0	0.00
	LTE 26	QPSK15M	Bottom Side	0	26865	w/o	36	0	23.0	21.72	1.34	0	0	0.00
	LTE 30	QPSK10M	Rear Face	0	27710	w/	1	0	17.0	16.26	1.19	0.01	0.871	1.03
	LTE 30	QPSK10M	Rear Face	0	27710	w/	25	0	17.0	15.80	1.32	0.06	0.865	1.14
	LTE 30	QPSK10M	Rear Face	0	27710	w/	50	0	17.0	15.71	1.35	0	0.869	1.17
	LTE 30	QPSK10M	Rear Face	0	27710	w/	50	0	17.0	15.71	1.35	0	0.851	1.15
	LTE 30	QPSK10M	Rear Face	1.7	27710	w/o	1	0	23.0	21.42	1.44	0.05	0.26	0.37
	LTE 30	QPSK10M	Rear Face	1.7	27710	w/o	25	0	22.0	20.35	1.46	0.09	0.210	0.31
	LTE 30	QPSK10M	Right Side	0	27710	w/o	1	0	23.0	21.42	1.44	0.05	0.105	0.15
	LTE 30	QPSK10M	Right Side	0	27710	w/o	25	0	22.0	20.35	1.46	0.03	0.086	0.13
	LTE 30	QPSK10M	Left Side	0	27710	w/o	1	0	23.0	21.42	1.44	0.12	0.065	0.09
	LTE 30	QPSK10M	Left Side	0	27710	w/o	25	0	22.0	20.35	1.46	0	0.000	0.00
	LTE 30	QPSK10M	Top Side	0	27710	w/	1	0	17.0	16.26	1.19	0.09	0.705	0.84
	LTE 30	QPSK10M	Top Side	0	27710	w/	25	0	17.0	15.80	1.32	0.08	0.676	0.89
	LTE 30	QPSK10M	Top Side	0	27710	w/	50	0	17.0	15.71	1.35	0.02	0.657	0.88
	LTE 30	QPSK10M	Top Side	2.6	27710	w/o	1	0	23.0	21.42	1.44	-0.02	0.157	0.23
	LTE 30	QPSK10M	Top Side	2.6	27710	w/o	25	0	22.0	20.35	1.46	0.08	0.129	0.19
	LTE 30	QPSK10M	Bottom Side	0	27710	w/o	1	0	23.0	21.42	1.44	0	0.000	0.00
	LTE 30	QPSK10M	Bottom Side	0	27710	w/o	25	0	22.0	20.35	1.46	0	0.000	0.00



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Rear Face	0	40620	w/	1	0	19.0	17.19	1.52	0.03	0.365	0.55
	LTE 41	QPSK20M	Rear Face	0	40620	w/	50	0	19.0	17.09	1.55	0.04	0.415	0.64
	LTE 41	QPSK20M	Rear Face	1.7	40620	w/o	1	0	23.0	22.98	1.00	0.07	0.105	0.11
	LTE 41	QPSK20M	Rear Face	1.7	40620	w/o	50	0	22.0	21.92	1.02	-0.07	0.083	0.08
	LTE 41	QPSK20M	Right Side	0	40620	w/o	1	0	23.0	22.98	1.00	0.09	0.043	0.04
	LTE 41	QPSK20M	Right Side	0	40620	w/o	50	0	22.0	21.92	1.02	0.04	0.033	0.03
	LTE 41	QPSK20M	Left Side	0	40620	w/o	1	0	23.0	22.98	1.00	0	0.000	0.00
	LTE 41	QPSK20M	Left Side	0	40620	w/o	50	0	22.0	21.92	1.02	0	0.000	0.00
	LTE 41	QPSK20M	Top Side	0	40620	w/	1	0	19.0	17.19	1.52	0.01	0.582	0.88
	LTE 41	QPSK20M	Top Side	0	39750	w/	1	0	19.0	17.12	1.54	0.05	0.553	0.85
	LTE 41	QPSK20M	Top Side	0	40185	w/	1	0	19.0	17.06	1.56	0.09	0.574	0.90
	LTE 41	QPSK20M	Top Side	0	41055	w/	1	0	19.0	17.07	1.56	0.08	0.524	0.82
	LTE 41	QPSK20M	Top Side	0	41490	w/	1	0	19.0	17.02	1.58	0.07	0.513	0.81
	LTE 41	QPSK20M	Top Side	0	40620	w/	50	0	19.0	17.09	1.55	0.04	0.591	0.92
	LTE 41	QPSK20M	Top Side	0	39750	w/	50	25	19.0	17.07	1.56	0.02	0.522	0.81
13	LTE 41	QPSK20M	Top Side	0	40185	w/	50	0	19.0	17.03	1.57	0.03	0.596	0.94
	LTE 41	QPSK20M	Top Side	0	40185	w/	50	0	19.0	17.03	1.57	0.01	0.589	0.93
	LTE 41	QPSK20M	Top Side	0	41055	w/	50	25	19.0	17.06	1.56	0	0.560	0.88
	LTE 41	QPSK20M	Top Side	0	41490	w/	50	25	19.0	17.05	1.57	-0.01	0.589	0.92
	LTE 41	QPSK20M	Top Side	0	40620	w/	100	0	19.0	17.08	1.56	0.03	0.593	0.92
	LTE 41	QPSK20M	Top Side	2.6	40620	w/o	1	0	23.0	22.98	1.00	-0.03	0.068	0.07
	LTE 41	QPSK20M	Top Side	2.6	40620	w/o	50	0	22.0	21.92	1.02	0.1	0.054	0.06
	LTE 41	QPSK20M	Bottom Side	0	40620	w/o	1	0	23.0	22.98	1.00	0	0	0.00
	LTE 41	QPSK20M	Bottom Side	0	40620	w/o	50	0	22.0	21.92	1.02	0	0	0.00

Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
30	2.4G WLAN	802.11b	Top Side	0	11	0	15.0	14.93	1.02	0.04	0.034	0.03
31	5.6G WLAN	802.11a	Top Side	0	104	0	13.5	13.50	1.00	-0.02	0.140	0.14

Note: Only the test this 2.4G / 5G WLAN item for SPLSR Analysis are presented in the report.

FCC SAR Test Report

A D T

EUT 2 (Thick cover)

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WCDMA II	RMC12.2K	Rear Face	0	9400	w/	18.0	17.26	1.19	0.02	0.316	0.37
	WCDMA II	RMC12.2K	Rear Face	1.6	9400	w/o	24.0	22.81	1.32	0.07	0.099	0.13
	WCDMA II	RMC12.2K	Right Side	0	9400	w/o	24.0	22.81	1.32	-0.05	0.219	0.29
	WCDMA II	RMC12.2K	Left Side	0	9400	w/o	24.0	22.81	1.32	0.12	0.057	0.07
	WCDMA II	RMC12.2K	Top Side	0	9400	w/	18.0	17.26	1.19	0.03	0.923	1.09
14	WCDMA II	RMC12.2K	Top Side	0	9262	w/	18.0	16.88	1.29	0.11	1.03	1.33
	WCDMA II	RMC12.2K	Top Side	0	9262	w/	18.0	16.88	1.29	0.11	0.98	1.27
	WCDMA II	RMC12.2K	Top Side	0	9538	w/	18.0	17.16	1.21	0.02	0.932	1.13
	WCDMA II	HSDPA Subtest-1	Top Side	0	9400	w/	18.0	16.85	1.30	-0.10	0.804	1.05
	WCDMA II	HSDPA Subtest-1	Top Side	0	9262	w/	18.0	16.48	1.42	0.03	0.881	1.25
	WCDMA II	HSDPA Subtest-1	Top Side	0	9538	w/	18.0	16.76	1.33	-0.04	0.81	1.08
	WCDMA II	HSUPA Subtest-5	Top Side	0	9400	w/	18.0	16.55	1.40	-0.09	0.768	1.07
	WCDMA II	HSUPA Subtest-5	Top Side	0	9262	w/	18.0	16.17	1.52	0.13	0.806	1.23
	WCDMA II	HSUPA Subtest-5	Top Side	0	9538	w/	18.0	16.45	1.43	0.01	0.775	1.11
	WCDMA II	RMC12.2K	Top Side	3	9400	w/o	24.0	22.81	1.32	-0.01	0.107	0.14
	WCDMA II	RMC12.2K	Bottom Side	0	9400	w/o	24.0	22.81	1.32	0	0.00	0
	WCDMA IV	RMC12.2K	Rear Face	0	1413	w/	19.0	18.31	1.17	0.03	0.38	0.45
	WCDMA IV	RMC12.2K	Rear Face	1.6	1413	w/o	24.0	22.66	1.36	-0.07	0.322	0.44
	WCDMA IV	RMC12.2K	Right Side	0	1413	w/o	24.0	22.66	1.36	0.06	0.167	0.23
	WCDMA IV	RMC12.2K	Left Side	0	1413	w/o	24.0	22.66	1.36	0.12	0.062	0.08
	WCDMA IV	RMC12.2K	Top Side	0	1413	w/	19.0	18.31	1.17	0.01	0.765	0.90
15	WCDMA IV	RMC12.2K	Top Side	0	1312	w/	19.0	18.18	1.21	0.18	0.777	0.94
	WCDMA IV	RMC12.2K	Top Side	0	1513	w/	19.0	18.13	1.22	0.06	0.748	0.91
	WCDMA IV	RMC12.2K	Top Side	3	1413	w/o	24.0	22.66	1.36	0.02	0.244	0.33
	WCDMA IV	RMC12.2K	Bottom Side	0	1413	w/o	24.0	22.66	1.36	0	0.00	0
	WCDMA V	RMC12.2K	Rear Face	0	4182	w/	21.0	20.20	1.20	0.01	0.752	0.90
	WCDMA V	RMC12.2K	Rear Face	0	4132	w/	21.0	19.89	1.29	0.04	0.601	0.78
	WCDMA V	RMC12.2K	Rear Face	0	4233	w/	21.0	19.95	1.27	-0.09	0.652	0.83
	WCDMA V	RMC12.2K	Rear Face	1.6	4182	w/o	24.0	22.89	1.29	0.04	0.12	0.15
	WCDMA V	RMC12.2K	Right Side	0	4182	w/o	24.0	22.89	1.29	0.14	0.085	0.11
	WCDMA V	RMC12.2K	Left Side	0	4182	w/o	24.0	22.89	1.29	0	0.00	0
16	WCDMA V	RMC12.2K	Top Side	0	4182	w/	21.0	20.20	1.20	-0.12	0.917	1.10
	WCDMA V	RMC12.2K	Top Side	0	4182	w/	21.0	20.20	1.20	0.12	0.908	1.09
	WCDMA V	RMC12.2K	Top Side	0	4132	w/	21.0	19.89	1.29	-0.08	0.845	1.09
	WCDMA V	RMC12.2K	Top Side	0	4233	w/	21.0	19.95	1.27	0.06	0.804	1.02
	WCDMA V	RMC12.2K	Top Side	3	4182	w/o	24.0	22.89	1.29	0	0.049	0.06
	WCDMA V	RMC12.2K	Bottom Side	0	4182	w/o	24.0	22.89	1.29	0	0.00	0



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Rear Face	0	18900	w/	1	0	19.0	18.63	1.09	-0.18	0.283	0.31
	LTE 2	QPSK20M	Rear Face	0	18900	w/	50	0	19.0	18.23	1.19	-0.05	0.268	0.32
	LTE 2	QPSK20M	Rear Face	1.6	18900	w/o	1	0	24.0	23.54	1.11	-0.02	0.193	0.21
	LTE 2	QPSK20M	Rear Face	1.6	18900	w/o	50	0	23.0	21.66	1.36	0.15	0.132	0.18
	LTE 2	QPSK20M	Right Side	0	18900	w/o	1	0	24.0	23.54	1.11	-0.04	0.373	0.41
	LTE 2	QPSK20M	Right Side	0	18900	w/o	50	0	23.0	21.66	1.36	0.09	0.267	0.36
	LTE 2	QPSK20M	Left Side	0	18900	w/o	1	0	24.0	23.54	1.11	0.12	0.082	0.09
	LTE 2	QPSK20M	Left Side	0	18900	w/o	50	0	23.0	21.66	1.36	0.11	0.069	0.09
17	LTE 2	QPSK20M	Top Side	0	18900	w/	1	0	19.0	18.63	1.09	0.16	0.84	0.91
	LTE 2	QPSK20M	Top Side	0	18900	w/	1	0	19.0	18.63	1.09	0.15	0.82	0.89
	LTE 2	QPSK20M	Top Side	0	18700	w/	1	0	19.0	18.24	1.19	-0.06	0.768	0.91
	LTE 2	QPSK20M	Top Side	0	19100	w/	1	0	19.0	18.53	1.11	0.15	0.643	0.72
	LTE 2	QPSK20M	Top Side	0	18900	w/	50	0	19.0	18.23	1.19	-0.11	0.699	0.83
	LTE 2	QPSK20M	Top Side	0	18700	w/	50	0	19.0	17.84	1.31	0.06	0.617	0.81
	LTE 2	QPSK20M	Top Side	0	19100	w/	50	0	19.0	18.13	1.22	-0.02	0.601	0.73
	LTE 2	QPSK20M	Top Side	0	18900	w/	100	0	19.0	18.00	1.26	-0.01	0.703	0.89
	LTE 2	QPSK20M	Top Side	3	18900	w/o	1	0	24.0	23.54	1.11	0	0.202	0.22
	LTE 2	QPSK20M	Top Side	3	18900	w/o	50	0	23.0	21.66	1.36	0.05	0.144	0.20
	LTE 2	QPSK20M	Bottom Side	0	18900	w/o	1	0	24.0	23.54	1.11	0	0	0.00
	LTE 2	QPSK20M	Bottom Side	0	18900	w/o	50	0	23.0	21.66	1.36	0	0	0.00
	LTE 4	QPSK20M	Rear Face	0	20175	w/	1	0	18.0	17.68	1.08	0.05	0.446	0.48
	LTE 4	QPSK20M	Rear Face	0	20175	w/	50	0	18.0	17.45	1.14	-0.02	0.399	0.45
	LTE 4	QPSK20M	Rear Face	1.6	20175	w/o	1	0	24.0	23.34	1.16	0.06	0.322	0.37
	LTE 4	QPSK20M	Rear Face	1.6	20175	w/o	50	0	23.0	21.91	1.29	0	0.239	0.31
	LTE 4	QPSK20M	Right Side	0	20175	w/o	1	0	24.0	23.34	1.16	0.12	0.2	0.23
	LTE 4	QPSK20M	Right Side	0	20175	w/o	50	0	23.0	21.91	1.29	0.07	0.146	0.19
	LTE 4	QPSK20M	Left Side	0	20175	w/o	1	0	24.0	23.34	1.16	0.12	0.052	0.06
	LTE 4	QPSK20M	Left Side	0	20175	w/o	50	0	23.0	21.91	1.29	0	0	0.00
18	LTE 4	QPSK20M	Top Side	0	20175	w/	1	0	18.0	17.68	1.08	0.1	0.879	0.95
	LTE 4	QPSK20M	Top Side	0	20175	w/	1	0	18.0	17.68	1.08	0.11	0.871	0.94
	LTE 4	QPSK20M	Top Side	0	20050	w/	1	0	18.0	17.57	1.10	0.04	0.809	0.89
	LTE 4	QPSK20M	Top Side	0	20300	w/	1	0	18.0	17.65	1.08	-0.12	0.859	0.93
	LTE 4	QPSK20M	Top Side	0	20175	w/	50	0	18.0	17.45	1.14	0.03	0.793	0.90
	LTE 4	QPSK20M	Top Side	0	20050	w/	50	0	18.0	17.34	1.16	0.09	0.806	0.94
	LTE 4	QPSK20M	Top Side	0	20300	w/	50	0	18.0	17.42	1.14	0.07	0.802	0.92
	LTE 4	QPSK20M	Top Side	0	20175	w/	100	0	18.0	17.25	1.19	0.05	0.795	0.94
	LTE 4	QPSK20M	Top Side	3	20175	w/o	1	0	24.0	23.34	1.16	0.01	0.311	0.36
	LTE 4	QPSK20M	Top Side	3	20175	w/o	50	0	23.0	21.91	1.29	0.1	0.232	0.30
	LTE 4	QPSK20M	Bottom Side	0	20175	w/o	1	0	24.0	23.34	1.16	0	0	0.00
	LTE 4	QPSK20M	Bottom Side	0	20175	w/o	50	0	23.0	21.91	1.29	0	0	0.00
	LTE 5	QPSK10M	Rear Face	0	20525	w/	1	0	20.0	19.98	1.00	0.03	0.463	0.47
	LTE 5	QPSK10M	Rear Face	0	20525	w/	25	0	20.0	19.95	1.01	-0.06	0.438	0.44
	LTE 5	QPSK10M	Rear Face	1.6	20525	w/o	1	0	24.0	22.61	1.38	-0.03	0.121	0.17
	LTE 5	QPSK10M	Rear Face	1.6	20525	w/o	25	0	23.0	21.14	1.53	0.09	0.096	0.15
	LTE 5	QPSK10M	Right Side	0	20525	w/o	1	0	24.0	22.61	1.38	-0.08	0.107	0.15
	LTE 5	QPSK10M	Right Side	0	20525	w/o	25	0	23.0	21.14	1.53	-0.08	0.081	0.12
	LTE 5	QPSK10M	Left Side	0	20525	w/o	1	0	24.0	22.61	1.38	0.02	0.021	0.03
	LTE 5	QPSK10M	Left Side	0	20525	w/o	25	0	23.0	21.14	1.53	0	0	0.00
19	LTE 5	QPSK10M	Top Side	0	20525	w/	1	0	20.0	19.98	1.00	-0.02	0.697	0.70
	LTE 5	QPSK10M	Top Side	0	20525	w/	25	0	20.0	19.95	1.01	-0.02	0.593	0.60
	LTE 5	QPSK10M	Top Side	3	20525	w/o	1	0	24.0	22.61	1.38	0.04	0.05	0.07
	LTE 5	QPSK10M	Top Side	3	20525	w/o	25	0	23.0	21.14	1.53	-0.01	0.039	0.06
	LTE 5	QPSK10M	Bottom Side	0	20525	w/o	1	0	24.0	22.61	1.38	0	0	0.00
	LTE 5	QPSK10M	Bottom Side	0	20525	w/o	25	0	23.0	21.14	1.53	0	0	0.00

FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 7	QPSK20M	Rear Face	0	21100	w/	1	0	18.0	16.11	1.55	0.02	0.417	0.64
	LTE 7	QPSK20M	Rear Face	0	21100	w/	50	0	18.0	16.08	1.56	-0.03	0.461	0.72
	LTE 7	QPSK20M	Rear Face	1.6	21100	w/o	1	0	23.0	21.64	1.37	0.09	0.13	0.18
	LTE 7	QPSK20M	Rear Face	1.6	21100	w/o	50	0	22.0	20.86	1.30	-0.04	0.105	0.14
	LTE 7	QPSK20M	Right Side	0	21100	w/o	1	0	23.0	21.64	1.37	0.03	0.034	0.05
	LTE 7	QPSK20M	Right Side	0	21100	w/o	50	0	22.0	20.86	1.30	0.08	0.041	0.05
	LTE 7	QPSK20M	Left Side	0	21100	w/o	1	0	23.0	21.64	1.37	0	0	0.00
	LTE 7	QPSK20M	Left Side	0	21100	w/o	50	0	22.0	20.86	1.30	0	0	0.00
20	LTE 7	QPSK20M	Top Side	0	21100	w/	1	0	18.0	16.11	1.55	0.03	0.859	1.33
	LTE 7	QPSK20M	Top Side	0	21100	w/	1	0	18.0	16.11	1.55	0.02	0.851	1.32
	LTE 7	QPSK20M	Top Side	0	20850	w/	1	0	18.0	16.09	1.55	0.15	0.747	1.16
	LTE 7	QPSK20M	Top Side	0	21350	w/	1	0	18.0	16.10	1.55	0.08	0.781	1.21
	LTE 7	QPSK20M	Top Side	0	21100	w/	50	0	18.0	16.08	1.56	-0.07	0.795	1.24
	LTE 7	QPSK20M	Top Side	0	20850	w/	50	0	18.0	16.06	1.56	-0.05	0.738	1.15
	LTE 7	QPSK20M	Top Side	0	21350	w/	50	0	18.0	16.07	1.56	0.05	0.751	1.17
	LTE 7	QPSK20M	Top Side	0	21100	w/	100	0	18.0	16.05	1.57	0.06	0.756	1.18
	LTE 7	QPSK20M	Top Side	3	21100	w/o	1	0	23.0	21.64	1.37	0.06	0.123	0.17
	LTE 7	QPSK20M	Top Side	3	21100	w/o	50	0	22.0	20.86	1.30	-0.07	0.098	0.13
	LTE 7	QPSK20M	Bottom Side	0	21100	w/o	1	0	23.0	21.64	1.37	0	0	0.00
	LTE 7	QPSK20M	Bottom Side	0	21100	w/o	50	0	22.0	20.86	1.30	0	0	0.00
	LTE 12	QPSK10M	Rear Face	0	23095	w/	1	0	20.0	19.45	1.14	0.03	0.469	0.53
	LTE 12	QPSK10M	Rear Face	0	23095	w/	25	0	20.0	19.22	1.20	-0.04	0.423	0.51
	LTE 12	QPSK10M	Rear Face	1.6	23095	w/o	1	0	24.0	22.68	1.36	-0.09	0.146	0.20
	LTE 12	QPSK10M	Rear Face	1.6	23095	w/o	25	0	23.0	21.50	1.41	0.02	0.116	0.16
	LTE 12	QPSK10M	Right Side	0	23095	w/o	1	0	24.0	22.68	1.36	-0.06	0.11	0.15
	LTE 12	QPSK10M	Right Side	0	23095	w/o	25	0	23.0	21.50	1.41	-0.08	0.1	0.14
	LTE 12	QPSK10M	Left Side	0	23095	w/o	1	0	24.0	22.68	1.36	0.01	0.043	0.06
	LTE 12	QPSK10M	Left Side	0	23095	w/o	25	0	23.0	21.50	1.41	-0.03	0.015	0.02
21	LTE 12	QPSK10M	Top Side	0	23095	w/	1	0	20.0	19.45	1.14	-0.1	0.745	0.85
	LTE 12	QPSK10M	Top Side	0	23060	w/	1	0	20.0	19.26	1.19	0.02	0.643	0.76
	LTE 12	QPSK10M	Top Side	0	23130	w/	1	0	20.0	19.20	1.20	0.05	0.646	0.78
	LTE 12	QPSK10M	Top Side	0	23095	w/	25	0	20.0	19.22	1.20	0.09	0.657	0.79
	LTE 12	QPSK10M	Top Side	0	23095	w/	50	0	20.0	19.07	1.24	0.12	0.628	0.78
	LTE 12	QPSK10M	Top Side	3	23095	w/o	1	0	24.0	22.68	1.36	0.14	0.05	0.07
	LTE 12	QPSK10M	Top Side	3	23095	w/o	25	0	23.0	21.50	1.41	0.01	0.046	0.06
	LTE 12	QPSK10M	Bottom Side	0	23095	w/o	1	0	24.0	22.68	1.36	0	0	0.00
	LTE 12	QPSK10M	Bottom Side	0	23095	w/o	25	0	23.0	21.50	1.41	0	0	0.00
	LTE 13	QPSK10M	Rear Face	0	23230	w/	1	0	20.0	19.23	1.19	0.05	0.514	0.61
	LTE 13	QPSK10M	Rear Face	0	23230	w/	25	0	20.0	19.15	1.22	0.03	0.483	0.59
	LTE 13	QPSK10M	Rear Face	1.6	23230	w/o	1	0	24.0	23.03	1.25	0.03	0.135	0.17
	LTE 13	QPSK10M	Rear Face	1.6	23230	w/o	25	0	23.0	22.13	1.22	0.03	0.129	0.16
	LTE 13	QPSK10M	Right Side	0	23230	w/o	1	0	24.0	23.03	1.25	0.16	0.127	0.16
	LTE 13	QPSK10M	Right Side	0	23230	w/o	25	0	23.0	22.13	1.22	0.13	0.120	0.15
	LTE 13	QPSK10M	Left Side	0	23230	w/o	1	0	24.0	23.03	1.25	0	0.037	0.05
	LTE 13	QPSK10M	Left Side	0	23230	w/o	25	0	23.0	22.13	1.22	0.01	0.020	0.02
22	LTE 13	QPSK10M	Top Side	0	23230	w/	1	0	20.0	19.23	1.19	-0.11	0.752	0.90
	LTE 13	QPSK10M	Top Side	0	23230	w/	25	0	20.0	19.15	1.22	0.11	0.703	0.85
	LTE 13	QPSK10M	Top Side	0	23230	w/	50	0	20.0	19.19	1.21	0.04	0.737	0.89
	LTE 13	QPSK10M	Top Side	3	23230	w/o	1	0	24.0	23.03	1.25	0.02	0.064	0.08
	LTE 13	QPSK10M	Top Side	3	23230	w/o	25	0	23.0	22.13	1.22	0.06	0.055	0.07
	LTE 13	QPSK10M	Bottom Side	0	23230	w/o	1	0	24.0	23.03	1.25	0	0	0.00
	LTE 13	QPSK10M	Bottom Side	0	23230	w/o	25	0	23.0	22.13	1.22	0	0	0.00



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 25	QPSK20M	Rear Face	0	26365	w/	1	0	19.0	18.52	1.12	-0.01	0.278	0.31
	LTE 25	QPSK20M	Rear Face	0	26365	w/	50	0	19.0	18.11	1.23	0	0.248	0.30
	LTE 25	QPSK20M	Rear Face	1.6	26365	w/o	1	0	24.0	23.25	1.19	0.11	0.175	0.21
	LTE 25	QPSK20M	Rear Face	1.6	26365	w/o	50	0	23.0	22.04	1.38	0.07	0.125	0.17
	LTE 25	QPSK20M	Right Side	0	26365	w/o	1	0	24.0	23.25	1.19	-0.03	0.373	0.44
	LTE 25	QPSK20M	Right Side	0	26365	w/o	50	0	23.0	22.04	1.38	0.08	0.273	0.38
	LTE 25	QPSK20M	Left Side	0	26365	w/o	1	0	24.0	23.25	1.19	0.12	0.081	0.10
	LTE 25	QPSK20M	Left Side	0	26365	w/o	50	0	23.0	22.04	1.38	0.11	0.063	0.08
	LTE 25	QPSK20M	Top Side	0	26365	w/	1	0	19.0	18.52	1.12	-0.02	0.802	0.90
23	LTE 25	QPSK20M	Top Side	0	26140	w/	1	0	19.0	18.31	1.17	0.08	0.888	1.04
	LTE 25	QPSK20M	Top Side	0	26140	w/	1	0	19.0	18.31	1.17	0.11	0.878	1.03
	LTE 25	QPSK20M	Top Side	0	26590	w/	1	0	19.0	18.46	1.13	0.12	0.644	0.73
	LTE 25	QPSK20M	Top Side	0	26365	w/	50	0	19.0	18.11	1.23	-0.11	0.719	0.88
	LTE 25	QPSK20M	Top Side	0	26140	w/	50	0	19.0	17.90	1.29	-0.11	0.712	0.92
	LTE 25	QPSK20M	Top Side	0	26590	w/	50	0	19.0	18.05	1.24	-0.05	0.701	0.87
	LTE 25	QPSK20M	Top Side	0	26365	w/	100	0	19.0	17.86	1.30	0.02	0.764	0.99
	LTE 25	QPSK20M	Top Side	3	26365	w/o	1	0	24.0	23.25	1.19	0.01	0.177	0.21
	LTE 25	QPSK20M	Top Side	3	26365	w/o	50	0	23.0	22.04	1.38	0.03	0.123	0.17
	LTE 25	QPSK20M	Bottom Side	0	26365	w/o	1	0	24.0	23.25	1.19	0	0	0.00
	LTE 25	QPSK20M	Bottom Side	0	26365	w/o	50	0	23.0	22.04	1.38	0	0	0.00
	LTE 26	QPSK15M	Rear Face	0	26865	w/	1	0	21.0	20.16	1.21	-0.11	0.498	0.60
	LTE 26	QPSK15M	Rear Face	0	26865	w/	36	0	21.0	20.06	1.24	0.04	0.453	0.56
	LTE 26	QPSK15M	Rear Face	1.6	26865	w/o	1	0	24.0	22.84	1.31	-0.04	0.139	0.18
	LTE 26	QPSK15M	Rear Face	1.6	26865	w/o	36	0	23.0	21.72	1.34	-0.04	0.111	0.15
	LTE 26	QPSK15M	Right Side	0	26865	w/o	1	0	24.0	22.84	1.31	-0.07	0.13	0.17
	LTE 26	QPSK15M	Right Side	0	26865	w/o	36	0	23.0	21.72	1.34	-0.03	0.096	0.13
	LTE 26	QPSK15M	Left Side	0	26865	w/o	1	0	24.0	22.84	1.31	0.01	0.015	0.02
	LTE 26	QPSK15M	Left Side	0	26865	w/o	36	0	23.0	21.72	1.34	0	0	0.00
24	LTE 26	QPSK15M	Top Side	0	26865	w/	1	0	21.0	20.16	1.21	-0.11	0.782	0.95
	LTE 26	QPSK15M	Top Side	0	26765	w/	1	0	21.0	20.07	1.24	0.12	0.752	0.93
	LTE 26	QPSK15M	Top Side	0	26965	w/	1	0	21.0	20.11	1.23	0.14	0.720	0.88
	LTE 26	QPSK15M	Top Side	0	26865	w/	36	0	21.0	20.06	1.24	-0.01	0.613	0.76
	LTE 26	QPSK15M	Top Side	0	26865	w/	75	0	21.0	20.03	1.25	0.02	0.602	0.75
	LTE 26	QPSK15M	Top Side	3	26865	w/o	1	0	24.0	22.84	1.31	-0.01	0.056	0.07
	LTE 26	QPSK15M	Top Side	3	26865	w/o	36	0	23.0	21.72	1.34	-0.12	0.044	0.06
	LTE 26	QPSK15M	Bottom Side	0	26865	w/o	1	0	24.0	22.84	1.31	0	0	0.00
	LTE 26	QPSK15M	Bottom Side	0	26865	w/o	36	0	23.0	21.72	1.34	0	0	0.00
	LTE 30	QPSK10M	Rear Face	0	27710	w/	1	0	17.0	16.26	1.19	0.03	0.511	0.61
	LTE 30	QPSK10M	Rear Face	0	27710	w/	25	0	17.0	15.80	1.32	0.01	0.489	0.64
	LTE 30	QPSK10M	Rear Face	1.6	27710	w/o	1	0	23.0	21.42	1.44	-0.09	0.216	0.31
	LTE 30	QPSK10M	Rear Face	1.6	27710	w/o	25	0	22.0	20.35	1.46	0.05	0.172	0.25
	LTE 30	QPSK10M	Right Side	0	27710	w/o	1	0	23.0	21.42	1.44	-0.05	0.068	0.10
	LTE 30	QPSK10M	Right Side	0	27710	w/o	25	0	22.0	20.35	1.46	0.08	0.055	0.08
	LTE 30	QPSK10M	Left Side	0	27710	w/o	1	0	23.0	21.42	1.44	0.11	0.068	0.10
	LTE 30	QPSK10M	Left Side	0	27710	w/o	25	0	22.0	20.35	1.46	0.11	0.058	0.08
25	LTE 30	QPSK10M	Top Side	0	27710	w/	1	0	17.0	16.26	1.19	-0.1	0.901	1.07
	LTE 30	QPSK10M	Top Side	0	27710	w/	1	0	17.0	16.26	1.19	0.11	0.891	1.06
	LTE 30	QPSK10M	Top Side	0	27710	w/	25	0	17.0	15.80	1.32	0.05	0.805	1.06
	LTE 30	QPSK10M	Top Side	0	27710	w/	50	0	17.0	15.71	1.35	0.09	0.786	1.06
	LTE 30	QPSK10M	Top Side	3	27710	w/o	1	0	23.0	21.42	1.44	0.01	0.167	0.24
	LTE 30	QPSK10M	Top Side	3	27710	w/o	25	0	22.0	20.35	1.46	0.03	0.136	0.20
	LTE 30	QPSK10M	Bottom Side	0	27710	w/o	1	0	23.0	21.42	1.44	0	0	0.00
	LTE 30	QPSK10M	Bottom Side	0	27710	w/o	25	0	22.0	20.35	1.46	0	0	0.00



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	Power Reduction	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Rear Face	0	40620	w/	1	0	19.0	17.19	1.52	0.03	0.348	0.53
	LTE 41	QPSK20M	Rear Face	0	40620	w/	50	0	19.0	17.09	1.55	0.08	0.300	0.47
	LTE 41	QPSK20M	Rear Face	1.6	40620	w/o	1	0	23.0	22.98	1.00	0.09	0.078	0.08
	LTE 41	QPSK20M	Rear Face	1.6	40620	w/o	50	0	22.0	21.92	1.02	0.02	0.065	0.07
	LTE 41	QPSK20M	Right Side	0	40620	w/o	1	0	23.0	22.98	1.00	-0.05	0.039	0.04
	LTE 41	QPSK20M	Right Side	0	40620	w/o	50	0	22.0	21.92	1.02	0.08	0.031	0.03
	LTE 41	QPSK20M	Left Side	0	40620	w/o	1	0	23.0	22.98	1.00	0	0	0.00
	LTE 41	QPSK20M	Left Side	0	40620	w/o	50	0	22.0	21.92	1.02	0	0	0.00
	LTE 41	QPSK20M	Top Side	0	40620	w/	1	0	19.0	17.19	1.52	-0.04	0.685	1.04
	LTE 41	QPSK20M	Top Side	0	39750	w/	1	0	19.0	17.12	1.54	0.01	0.557	0.86
	LTE 41	QPSK20M	Top Side	0	40185	w/	1	0	19.0	17.06	1.56	-0.05	0.659	1.03
	LTE 41	QPSK20M	Top Side	0	41055	w/	1	0	19.0	17.07	1.56	0.03	0.688	1.07
26	LTE 41	QPSK20M	Top Side	0	41490	w/	1	0	19.0	17.02	1.58	-0.1	0.858	1.35
	LTE 41	QPSK20M	Top Side	0	41490	w/	1	0	19.0	17.02	1.58	0.12	0.852	1.34
	LTE 41	QPSK20M	Top Side	0	40620	w/	50	0	19.0	17.09	1.55	0.03	0.731	1.13
	LTE 41	QPSK20M	Top Side	0	39750	w/	50	25	19.0	17.07	1.56	0.06	0.716	1.12
	LTE 41	QPSK20M	Top Side	0	40185	w/	50	0	19.0	17.03	1.57	0.15	0.648	1.02
	LTE 41	QPSK20M	Top Side	0	41055	w/	50	25	19.0	17.06	1.56	0.12	0.699	1.09
	LTE 41	QPSK20M	Top Side	0	41490	w/	50	25	19.0	17.05	1.57	0.18	0.831	1.30
	LTE 41	QPSK20M	Top Side	0	40620	w/	100	0	19.0	17.08	1.56	0.17	0.619	0.96
	LTE 41	QPSK20M	Top Side	3	40620	w/o	1	0	23.0	22.98	1.00	0	0.075	0.08
	LTE 41	QPSK20M	Top Side	3	40620	w/o	50	0	22.0	21.92	1.02	0.08	0.064	0.07
	LTE 41	QPSK20M	Bottom Side	0	40620	w/o	1	0	23.0	22.98	1.00	0	0	0.00
	LTE 41	QPSK20M	Bottom Side	0	40620	w/o	50	0	22.0	21.92	1.02	0	0	0.00

4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

EUT 1 (Thin cover)

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WCDMA II	RMC12.2K	Rear Face	9262	0.994	0.987	1.01	N/A	N/A	N/A	N/A
WCDMA IV	RMC12.2K	Rear Face	1513	0.811	0.801	1.01	N/A	N/A	N/A	N/A
WCDMA V	RMC12.2K	Top Side	4233	0.812	0.802	1.01	N/A	N/A	N/A	N/A
LTE 2	QPSK20M	Rear Face	18700	0.952	0.943	1.01	N/A	N/A	N/A	N/A
LTE 4	QPSK20M	Top Side	20300	0.813	0.799	1.02	N/A	N/A	N/A	N/A
LTE 7	QPSK20M	Rear Face	20850	0.945	0.938	1.01	N/A	N/A	N/A	N/A
LTE 25	QPSK20M	Rear Face	26140	0.844	0.831	1.02	N/A	N/A	N/A	N/A
LTE 26	QPSK15M	Top Side	26965	0.864	0.852	1.01	N/A	N/A	N/A	N/A
LTE 30	QPSK10M	Rear Face	27710	0.869	0.851	1.02	N/A	N/A	N/A	N/A

EUT 2 (Thick cover)

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WCDMA II	RMC12.2K	Top Side	9262	1.03	0.98	1.05	N/A	N/A	N/A	N/A
WCDMA V	RMC12.2K	Top Side	4182	0.917	0.908	1.01	N/A	N/A	N/A	N/A
LTE 2	QPSK20M	Top Side	18900	0.84	0.82	1.02	N/A	N/A	N/A	N/A
LTE 4	QPSK20M	Top Side	20175	0.879	0.871	1.01	N/A	N/A	N/A	N/A
LTE 7	QPSK20M	Top Side	21100	0.859	0.851	1.01	N/A	N/A	N/A	N/A
LTE 25	QPSK20M	Top Side	26140	0.888	0.878	1.01	N/A	N/A	N/A	N/A
LTE 30	QPSK10M	Top Side	27710	0.901	0.891	1.01	N/A	N/A	N/A	N/A
LTE 41	QPSK20M	Top Side	41490	0.858	0.852	1.01	N/A	N/A	N/A	N/A

4.7.4 Simultaneous Multi-band Transmission Evaluation

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
WLAN (DTS)	2.462	15.0	Body	5	0.40
WLAN (NII)	5.7	13.5	Body	5	0.40
BT (DSS)	2.48	11.5	Body	5	0.40

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

EUT 1 (Thin cover)

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	WCDMA II + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.29	0.50	1.18	2.97	Analyzed as below
			Left Side	0.08	0.25	0.25	0.58	Σ SAR < 1.6, Not required
			Right Side	0.26	0.40	0.40	1.06	Σ SAR < 1.6, Not required
			Top Side	0.62	0.03	0.93	1.58	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
2	WCDMA II + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.29	0.98	0.69	2.96	Analyzed as below
			Left Side	0.08	0.61	0.40	1.09	Σ SAR < 1.6, Not required
			Right Side	0.26	0.40	0.40	1.06	Σ SAR < 1.6, Not required
			Top Side	0.62	0.14	1.38	2.14	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
3	WCDMA II + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.29	0.50	0.34	2.13	Analyzed as below
			Left Side	0.08	0.25	0.09	0.42	Σ SAR < 1.6, Not required
			Right Side	0.26	0.40	0.40	1.06	Σ SAR < 1.6, Not required
			Top Side	0.62	0.03	0.26	0.91	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
4	WCDMA II + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.29	0.98	0.34	2.61	Analyzed as below
			Left Side	0.40	0.61	0.09	1.1	Σ SAR < 1.6, Not required
			Right Side	0.26	0.40	0.40	1.06	Σ SAR < 1.6, Not required
			Top Side	0.62	0.14	0.26	1.02	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
5	WCDMA IV + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.99	0.50	1.18	2.67	Analyzed as below
			Left Side	0.07	0.25	0.25	0.57	Σ SAR < 1.6, Not required
			Right Side	0.28	0.40	0.40	1.08	Σ SAR < 1.6, Not required
			Top Side	0.87	0.03	0.93	1.83	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
6	WCDMA IV + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.99	0.98	0.69	2.66	Analyzed as below
			Left Side	0.07	0.61	0.40	1.08	Σ SAR < 1.6, Not required
			Right Side	0.28	0.40	0.40	1.08	Σ SAR < 1.6, Not required
			Top Side	0.87	0.14	1.38	2.39	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
7	WCDMA IV + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.99	0.50	0.34	1.83	Analyzed as below
			Left Side	0.07	0.25	0.09	0.41	Σ SAR < 1.6, Not required
			Right Side	0.28	0.40	0.40	1.08	Σ SAR < 1.6, Not required
			Top Side	0.87	0.03	0.26	1.16	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
8	WCDMA IV + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.99	0.98	0.34	2.31	Analyzed as below
			Left Side	0.07	0.61	0.09	0.77	Σ SAR < 1.6, Not required
			Right Side	0.28	0.40	0.40	1.08	Σ SAR < 1.6, Not required
			Top Side	0.87	0.14	0.26	1.27	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
9	WCDMA V + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.78	0.50	1.18	2.46	Analyzed as below
			Left Side	0.05	0.25	0.25	0.55	Σ SAR < 1.6, Not required
			Right Side	0.22	0.40	0.40	1.02	Σ SAR < 1.6, Not required
			Top Side	1.03	0.03	0.93	1.99	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
10	WCDMA V + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.78	0.98	0.69	2.45	Analyzed as below
			Left Side	0.05	0.61	0.40	1.06	Σ SAR < 1.6, Not required
			Right Side	0.22	0.40	0.40	1.02	Σ SAR < 1.6, Not required
			Top Side	1.03	0.14	1.38	2.55	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
11	WCDMA V + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.78	0.50	0.34	1.62	Analyzed as below
			Left Side	0.05	0.25	0.09	0.39	Σ SAR < 1.6, Not required
			Right Side	0.22	0.40	0.40	1.02	Σ SAR < 1.6, Not required
			Top Side	1.03	0.03	0.26	1.32	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
12	WCDMA V + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.78	0.98	0.34	2.1	Analyzed as below
			Left Side	0.05	0.61	0.09	0.75	Σ SAR < 1.6, Not required
			Right Side	0.22	0.40	0.40	1.02	Σ SAR < 1.6, Not required
			Top Side	1.03	0.14	0.26	1.43	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
13	LTE 2 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.13	0.50	1.18	2.81	Analyzed as below
			Left Side	0.07	0.25	0.25	0.57	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.65	0.03	0.93	1.61	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
14	LTE 2 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.13	0.98	0.69	2.80	Analyzed as below
			Left Side	0.07	0.61	0.40	1.08	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.65	0.14	1.38	2.17	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
15	LTE 2 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.13	0.50	0.34	1.97	Analyzed as below
			Left Side	0.07	0.25	0.09	0.41	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.65	0.03	0.26	0.94	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
16	LTE 2 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.13	0.98	0.34	2.45	Analyzed as below
			Left Side	0.07	0.61	0.09	0.77	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.65	0.14	0.26	1.05	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
17	LTE 4 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.77	0.50	1.18	2.45	Analyzed as below
			Left Side	0.08	0.25	0.25	0.58	Σ SAR < 1.6, Not required
			Right Side	0.29	0.40	0.40	1.09	Σ SAR < 1.6, Not required
			Top Side	0.88	0.03	0.93	1.84	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
18	LTE 4 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.77	0.98	0.69	2.44	Analyzed as below
			Left Side	0.08	0.61	0.40	1.09	Σ SAR < 1.6, Not required
			Right Side	0.29	0.40	0.40	1.09	Σ SAR < 1.6, Not required
			Top Side	0.88	0.14	1.38	2.40	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
19	LTE 4 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.77	0.50	0.34	1.61	Analyzed as below
			Left Side	0.08	0.25	0.09	0.42	Σ SAR < 1.6, Not required
			Right Side	0.29	0.40	0.40	1.09	Σ SAR < 1.6, Not required
			Top Side	0.88	0.03	0.26	1.17	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
20	LTE 4 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.77	0.98	0.34	2.09	Analyzed as below
			Left Side	0.08	0.61	0.09	0.78	Σ SAR < 1.6, Not required
			Right Side	0.29	0.40	0.40	1.09	Σ SAR < 1.6, Not required
			Top Side	0.88	0.14	0.26	1.28	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
21	LTE 5 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.67	0.50	1.18	2.35	Analyzed as below
			Left Side	0.00	0.25	0.25	0.50	Σ SAR < 1.6, Not required
			Right Side	0.12	0.40	0.40	0.92	Σ SAR < 1.6, Not required
			Top Side	0.72	0.03	0.93	1.68	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
22	LTE 5 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.67	0.98	0.69	2.34	Analyzed as below
			Left Side	0.00	0.61	0.40	1.01	Σ SAR < 1.6, Not required
			Right Side	0.12	0.40	0.40	0.92	Σ SAR < 1.6, Not required
			Top Side	0.72	0.14	1.38	2.24	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
23	LTE 5 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.67	0.50	0.34	1.51	Σ SAR < 1.6, Not required
			Left Side	0.00	0.25	0.09	0.34	Σ SAR < 1.6, Not required
			Right Side	0.12	0.40	0.40	0.92	Σ SAR < 1.6, Not required
			Top Side	0.72	0.03	0.26	1.01	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
24	LTE 5 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.67	0.98	0.34	1.99	Analyzed as below
			Left Side	0.00	0.61	0.09	0.70	Σ SAR < 1.6, Not required
			Right Side	0.12	0.40	0.40	0.92	Σ SAR < 1.6, Not required
			Top Side	0.72	0.14	0.26	1.12	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
25	LTE 7 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.29	0.50	1.18	2.97	Analyzed as below
			Left Side	0.00	0.25	0.25	0.50	Σ SAR < 1.6, Not required
			Right Side	0.09	0.40	0.40	0.89	Σ SAR < 1.6, Not required
			Top Side	1.12	0.03	0.93	2.08	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
26	LTE 7 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.29	0.98	0.69	2.96	Analyzed as below
			Left Side	0.00	0.61	0.40	1.01	Σ SAR < 1.6, Not required
			Right Side	0.09	0.40	0.40	0.89	Σ SAR < 1.6, Not required
			Top Side	1.12	0.14	1.38	2.64	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
27	LTE 7 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.29	0.50	0.34	2.13	Analyzed as below
			Left Side	0.00	0.25	0.09	0.34	Σ SAR < 1.6, Not required
			Right Side	0.09	0.40	0.40	0.89	Σ SAR < 1.6, Not required
			Top Side	1.12	0.03	0.26	1.41	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
28	LTE 7 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.29	0.98	0.34	2.61	Analyzed as below
			Left Side	0.00	0.61	0.09	0.70	Σ SAR < 1.6, Not required
			Right Side	0.09	0.40	0.40	0.89	Σ SAR < 1.6, Not required
			Top Side	1.12	0.14	0.26	1.52	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
29	LTE 12 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.57	0.50	1.18	2.25	Analyzed as below
			Left Side	0.05	0.25	0.25	0.55	Σ SAR < 1.6, Not required
			Right Side	0.20	0.40	0.40	1.00	Σ SAR < 1.6, Not required
			Top Side	0.93	0.03	0.93	1.89	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
30	LTE 12 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.57	0.98	0.69	2.24	Analyzed as below
			Left Side	0.05	0.61	0.40	1.06	Σ SAR < 1.6, Not required
			Right Side	0.20	0.40	0.40	1.00	Σ SAR < 1.6, Not required
			Top Side	0.93	0.14	1.38	2.45	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
31	LTE 12 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.57	0.50	0.34	1.41	Σ SAR < 1.6, Not required
			Left Side	0.05	0.25	0.09	0.39	Σ SAR < 1.6, Not required
			Right Side	0.20	0.40	0.40	1.00	Σ SAR < 1.6, Not required
			Top Side	0.93	0.03	0.26	1.22	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
32	LTE 12 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.57	0.98	0.34	1.89	Analyzed as below
			Left Side	0.05	0.61	0.09	0.75	Σ SAR < 1.6, Not required
			Right Side	0.20	0.40	0.40	1.00	Σ SAR < 1.6, Not required
			Top Side	0.93	0.14	0.26	1.33	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
33	LTE 13 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.84	0.50	1.18	2.52	Analyzed as below
			Left Side	0.01	0.25	0.25	0.51	Σ SAR < 1.6, Not required
			Right Side	0.13	0.40	0.40	0.93	Σ SAR < 1.6, Not required
			Top Side	0.90	0.03	0.93	1.86	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
34	LTE 13 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.84	0.98	0.69	2.51	Analyzed as below
			Left Side	0.01	0.61	0.40	1.02	Σ SAR < 1.6, Not required
			Right Side	0.13	0.40	0.40	0.93	Σ SAR < 1.6, Not required
			Top Side	0.90	0.14	1.38	2.42	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
35	LTE 13 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.84	0.50	0.34	1.68	Analyzed as below
			Left Side	0.01	0.25	0.09	0.35	Σ SAR < 1.6, Not required
			Right Side	0.13	0.40	0.40	0.93	Σ SAR < 1.6, Not required
			Top Side	0.90	0.03	0.26	1.19	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
36	LTE 13 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.84	0.98	0.34	2.16	Analyzed as below
			Left Side	0.01	0.61	0.09	0.71	Σ SAR < 1.6, Not required
			Right Side	0.13	0.40	0.40	0.93	Σ SAR < 1.6, Not required
			Top Side	0.90	0.14	0.26	1.3	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
37	LTE 25 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.09	0.50	1.18	2.77	Analyzed as below
			Left Side	0.08	0.25	0.25	0.58	Σ SAR < 1.6, Not required
			Right Side	0.24	0.40	0.40	1.04	Σ SAR < 1.6, Not required
			Top Side	0.61	0.03	0.93	1.57	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
38	LTE 25 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.09	0.98	0.69	2.76	Analyzed as below
			Left Side	0.08	0.61	0.40	1.09	Σ SAR < 1.6, Not required
			Right Side	0.24	0.40	0.40	1.04	Σ SAR < 1.6, Not required
			Top Side	0.61	0.14	1.38	2.13	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
39	LTE 25 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.09	0.50	0.34	1.93	Analyzed as below
			Left Side	0.08	0.25	0.09	0.42	Σ SAR < 1.6, Not required
			Right Side	0.24	0.40	0.40	1.04	Σ SAR < 1.6, Not required
			Top Side	0.61	0.03	0.26	0.90	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
40	LTE 25 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.09	0.98	0.34	2.41	Analyzed as below
			Left Side	0.08	0.61	0.09	0.78	Σ SAR < 1.6, Not required
			Right Side	0.24	0.40	0.40	1.04	Σ SAR < 1.6, Not required
			Top Side	0.61	0.14	0.26	1.01	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
41	LTE 26 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.01	0.50	1.18	2.69	Analyzed as below
			Left Side	0.05	0.25	0.25	0.55	Σ SAR < 1.6, Not required
			Right Side	0.17	0.40	0.40	0.97	Σ SAR < 1.6, Not required
			Top Side	1.09	0.03	0.93	2.05	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
42	LTE 26 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.01	0.98	0.69	2.68	Analyzed as below
			Left Side	0.05	0.61	0.40	1.06	Σ SAR < 1.6, Not required
			Right Side	0.17	0.40	0.40	0.97	Σ SAR < 1.6, Not required
			Top Side	1.09	0.14	1.38	2.61	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
43	LTE 26 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.01	0.50	0.34	1.85	Analyzed as below
			Left Side	0.05	0.25	0.09	0.39	Σ SAR < 1.6, Not required
			Right Side	0.17	0.40	0.40	0.97	Σ SAR < 1.6, Not required
			Top Side	1.09	0.03	0.26	1.38	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
44	LTE 26 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.01	0.98	0.34	2.33	Analyzed as below
			Left Side	0.05	0.61	0.09	0.75	Σ SAR < 1.6, Not required
			Right Side	0.17	0.40	0.40	0.97	Σ SAR < 1.6, Not required
			Top Side	1.09	0.14	0.26	1.49	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
45	LTE 30 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	1.17	0.50	1.18	2.85	Analyzed as below
			Left Side	0.09	0.25	0.25	0.59	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.89	0.03	0.93	1.85	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
46	LTE 30 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	1.17	0.98	0.69	2.84	Analyzed as below
			Left Side	0.09	0.61	0.40	1.10	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.89	0.14	1.38	2.41	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
47	LTE 30 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	1.17	0.50	0.34	2.01	Analyzed as below
			Left Side	0.09	0.25	0.09	0.43	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.89	0.03	0.26	1.18	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
48	LTE 30 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	1.17	0.98	0.34	2.49	Analyzed as below
			Left Side	0.09	0.61	0.09	0.79	Σ SAR < 1.6, Not required
			Right Side	0.15	0.40	0.40	0.95	Σ SAR < 1.6, Not required
			Top Side	0.89	0.14	0.26	1.29	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
49	LTE 41 + WLAN Ant 0 (DTS) + WLAN Ant 1 (DTS)	Body	Rear Face	0.64	0.50	1.18	2.32	Analyzed as below
			Left Side	0.00	0.25	0.25	0.50	Σ SAR < 1.6, Not required
			Right Side	0.04	0.40	0.40	0.84	Σ SAR < 1.6, Not required
			Top Side	0.94	0.03	0.93	1.90	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
50	LTE 41 + WLAN Ant 0 (NII) + WLAN Ant 1 (NII)	Body	Rear Face	0.64	0.98	0.69	2.31	Analyzed as below
			Left Side	0.00	0.61	0.40	1.01	Σ SAR < 1.6, Not required
			Right Side	0.04	0.40	0.40	0.84	Σ SAR < 1.6, Not required
			Top Side	0.94	0.14	1.38	2.46	Analyzed as below
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
51	LTE 41 + WLAN Ant 0 (DTS) + BT (DSS) Ant 1	Body	Rear Face	0.64	0.50	0.34	1.48	Σ SAR < 1.6, Not required
			Left Side	0.00	0.25	0.09	0.34	Σ SAR < 1.6, Not required
			Right Side	0.04	0.40	0.40	0.84	Σ SAR < 1.6, Not required
			Top Side	0.94	0.03	0.26	1.23	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required
52	LTE 41 + WLAN Ant 0 (NII) + BT (DSS) Ant 1	Body	Rear Face	0.64	0.98	0.34	1.96	Analyzed as below
			Left Side	0.00	0.61	0.09	0.70	Σ SAR < 1.6, Not required
			Right Side	0.04	0.40	0.40	0.84	Σ SAR < 1.6, Not required
			Top Side	0.94	0.14	0.26	1.34	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.40	0.40	0.80	Σ SAR < 1.6, Not required

FCC SAR Test Report

<SAR to Peak Location Separation Ratio Analysis>

The simultaneous transmitting antennas in each operating mode and exposure condition combination are considered one pair at a time to determine the SPLSR. When SAR is measured for both antennas in the pair, the peak location separation distance is computed by the following formula.

$$\text{Peak Location Separation Distance} = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

Where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the area or zoom scans.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna. Due to curvatures on the SAM phantom, when SAR is estimated for one of the antennas in an antenna pair, the measured peak SAR location will be translated onto the test device to determine the peak location separation for the antenna pair.

The SPLSR is determined by the following formula.

$$\text{SPLSR} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{R_i}$$

Where SAR_1 and SAR_2 are the highest reported or estimated SAR for each antenna in the pair, and R_i is the separation distance between the peak SAR locations for the antenna pair in mm.

When the SPLSR is ≤ 0.04 , the simultaneous transmission SAR is not required. Otherwise, the enlarged zoom scan and volume scan post-processing procedures will be performed.


FCC SAR Test Report

A D T


EUT 1 (Thin cover)

WCDMA II

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	220.0	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	188.7	0.02	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	218.9	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	191.4	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9400	Body	Top side	0.62	-0.04	9	0.16	237.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9400	Body	Top side	0.62	-0.04	9	0.16	180.6	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	220.0	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	188.4	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	218.9	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA II Ch9262	Body	Rear Face	1.29	7.88	8.08	0.3	188.4	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



WCDMA IV


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	222.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	191.1	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Top Side	0.87	0	8.8	0.14	229.1	0.00	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Top Side	0.87	0	8.8	0.14	210.5	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	221.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	193.8	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Top Side	0.87	0	8.8	0.14	235.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Top Side	0.87	0	8.8	0.14	178.6	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	222.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	190.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	221.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA IV Ch1513	Body	Rear Face	0.99	7.84	8.32	0.3	190.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



WCDMA V


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	203.9	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	169.7	0.02	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4233	Body	Top side	1.03	-0.24	5.96	0.06	201.1	0.01	SPLSR ≤ 0.04, Not required
802.11 Ch11 Ant0			0.03	2.2	-14	0.24			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4233	Body	Top side	1.03	-0.24	5.96	0.06	182.2	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11_Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11_Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	203.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116_Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	172.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4233	Body	Top side	1.03	-0.24	5.96	0.06	207.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4233	Body	Top side	1.03	-0.24	5.96	0.06	150.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	203.9	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	169.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	203.5	0.01	SPLSR ≤ 0.04, Not required
802.11a 5.6G Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
WCDMA V Ch4182	Body	Rear Face	0.78	8.6	6.2	0.24	169.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a 5.6G Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



LTE 2


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	216.7	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	186.3	0.02	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18900	Body	Top side	0.65	0.24	9.2	0.17	232.8	0.00	SPLSR ≤ 0.04, Not required
802.11b Ch11_Ant0			0.03	2.2	-14	0.24			



The diagram shows a top-down view of a device with two antennas. A green box labeled '802.11b_Ant0' points to a small antenna on the left. An orange box labeled 'LTE 2' points to a larger antenna on the right. A blue rectangular area represents the SAR measurement volume, extending from the left antenna towards the right. A red arrow indicates the direction of the incident electromagnetic wave, pointing from the left towards the antennas.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18900	Body	Top side	0.65	0.24	9.2	0.17	214.5	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



The diagram shows a top-down view of a device with two antennas. A green box labeled '802.11b_Ant1' points to a small antenna on the left. An orange box labeled 'LTE 2' points to a larger antenna on the right. A blue rectangular area represents the SAR measurement volume, extending from the left antenna towards the right. A red arrow indicates the direction of the incident electromagnetic wave, pointing from the left towards the antennas.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	215.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	189.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18900	Body	Top side	0.65	0.24	9.2	0.17	239.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18900	Body	Top side	0.65	0.24	9.2	0.17	182.6	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	216.7	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	185.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	215.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 2 Ch18700	Body	Rear Face	1.13	7.54	7.83	0.27	185.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



LTE 4


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	231.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	198.5	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R_{is} , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20300	Body	Top side	0.88	-0.16	9	0.15	231.2	0.00	SPLSR $\leq$ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			



The diagram shows a top-down view of a device with two antennas. A green box labeled '802.11b_Ant0' points to an antenna on the left. An orange box labeled 'LTE 4' points to an antenna on the right. The device is shown with a coordinate system (x, y, z) and a color-coded SAR field distribution.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R_{is} , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20300	Body	Top side	0.88	-0.16	9	0.15	212.6	0.01	SPLSR $\leq$ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



The diagram shows a top-down view of a device with two antennas. A green box labeled '802.11b_Ant1' points to an antenna on the left. An orange box labeled 'LTE 4' points to an antenna on the right. The device is shown with a coordinate system (x, y, z) and a color-coded SAR field distribution.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	230.3	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	201.3	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20300	Body	Top side	0.88	-0.16	9	0.15	237.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20300	Body	Top side	0.88	-0.16	9	0.15	180.5	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	231.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	198.6	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	230.3	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 4 Ch20175	Body	Rear Face	0.77	8.48	9.08	0.27	198.6	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



LTE5


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	205.8	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	171.7	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE5 Ch20525	Body	Top Side	0.72	0.04	5.8	0.06	199.2	0.00	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			



The figure shows a 3D visualization of the SAR field distribution for the device. Two specific areas are highlighted: '802.11b_Ant0' (indicated by a green box and arrow) and 'LTE 5' (indicated by an orange box and arrow). The plot shows the spatial distribution of the electromagnetic field, with color-coded regions representing different SAR values. The device is shown in a horizontal orientation, and the field distribution is concentrated around the antenna locations.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE5 Ch20525	Body	Top Side	0.72	0.04	5.8	0.06	180.5	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




The figure shows a 3D visualization of the SAR field distribution for the device. Two specific areas are highlighted: '802.11b_Ant1' (indicated by a green box and arrow) and 'LTE 5' (indicated by an orange box and arrow). The plot shows the spatial distribution of the electromagnetic field, with color-coded regions representing different SAR values. The device is shown in a horizontal orientation, and the field distribution is concentrated around the antenna locations.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	205.4	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	174.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Top side	0.72	0.04	5.8	0.06	205.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Top side	0.72	0.04	5.8	0.06	148.6	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	205.4	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 5 Ch20525	Body	Rear Face	0.67	8.6	6.4	0.3	171.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth_Ch 39			0.34	7.75	-10.76	0.62			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report


A D T

LTE 7

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	189.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	155.4	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch21350	Body	Top side	1.12	-0.16	5.6	0.13	197.4	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch21350	Body	Top side	1.12	-0.16	5.6	0.13	178.6	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	189.1	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The figure shows a 3D visualization of the SAR field distribution for two antennas. The left antenna, labeled '802.11a_Ant 0', shows a localized field with a peak SAR value of 0.98 W/kg. The right antenna, labeled 'LTE 7', shows a more extensive field with a peak SAR value of 1.29 W/kg. The plot includes a color scale and a 3D coordinate system.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	158.2	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The figure shows a 3D visualization of the SAR field distribution for two antennas. The left antenna, labeled '802.11a_Ant 1', shows a localized field with a peak SAR value of 0.69 W/kg. The right antenna, labeled 'LTE 7', shows a more extensive field with a peak SAR value of 1.29 W/kg. The plot includes a color scale and a 3D coordinate system.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch21350	Body	Top side	1.12	-0.16	5.6	0.13	203.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch21350	Body	Top side	1.12	-0.16	5.6	0.13	146.5	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	189.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	155.3	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	189.1	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 7 Ch20850	Body	Rear Face	1.29	8.32	4.76	0.57	155.3	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report


A D T

LTE 12

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	216.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	184.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23060	Body	Top side	0.93	-0.2	6.56	0.15	207.0	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23060	Body	Top side	0.93	-0.2	6.56	0.15	188.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	215.4	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The figure shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 0' points to a high-intensity region on the left. An orange box labeled 'LTE 12' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck, with color-coded regions representing different SAR levels (red for highest, yellow/orange for intermediate, and blue for lower levels).

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	187.0	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The figure shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 1' points to a high-intensity region on the left. An orange box labeled 'LTE 12' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck, with color-coded regions representing different SAR levels (red for highest, yellow/orange for intermediate, and blue for lower levels).


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23060	Body	Top side	0.93	-0.2	6.56	0.15	213.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23060	Body	Top side	0.93	-0.2	6.56	0.15	156.1	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	216.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 12 Ch23095	Body	Rear Face	0.57	8.1	7.64	0.25	184.1	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



LTE 13


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	207.8	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	173.7	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Top side	0.9	-0.44	6.6	0.1	207.7	0.00	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Top side	0.9	-0.44	6.6	0.1	188.7	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	207.4	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	176.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Top side	0.9	-0.44	6.6	0.1	213.6	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			



The figure shows a 3D visualization of the SAR field distribution for two antennas. On the left, a green box labeled '802.11a_Ant0' points to a small, localized field. On the right, an orange box labeled 'LTE 13' points to a larger, more elongated field. The fields are shown in a cross-section of a human body model, with color gradients indicating the intensity of the SAR values.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Top side	0.9	-0.44	6.6	0.1	156.5	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




The figure shows a 3D visualization of the SAR field distribution for two antennas. On the left, a green box labeled '802.11a_Ant1' points to a small, localized field. On the right, an orange box labeled 'LTE 13' points to a larger, more elongated field. The fields are shown in a cross-section of a human body model, with color gradients indicating the intensity of the SAR values.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	207.8	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	173.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	207.4	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 13 Ch23230	Body	Rear Face	0.84	8.64	6.6	0.31	173.9	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



LTE 25


Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	216.9	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	184.7	0.02	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	216.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The figure shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 0' points to a high-intensity region on the left. An orange box labeled 'LTE 25' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck, with the SAR field represented by a color gradient from blue (low) to red (high).

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	187.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The figure shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 1' points to a high-intensity region on the left. An orange box labeled 'LTE 25' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck, with the SAR field represented by a color gradient from blue (low) to red (high).


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26365	Body	Top side	0.61	-0.04	8.6	0.12	233.5	0.00	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26365	Body	Top side	0.61	-0.04	8.6	0.12	176.6	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	216.9	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	184.6	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	216.1	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 25 Ch26140	Body	Rear Face	1.09	8.16	7.69	0.28	184.6	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report


A D T

LTE26

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	205.3	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	171.7	0.02	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Top side	1.09	0	5.8	0.06	199.2	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Top side	1.09	0	5.8	0.06	180.5	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	204.8	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The figure shows a SAR field distribution plot for the rear face of the device. Two antennas are highlighted: 802.11a_Ant 0 (green box) and LTE 26 (orange box). The plot shows the spatial distribution of the SAR field, with the highest values concentrated around the antennas. The background is a dark blue color, and the SAR field is represented by a color gradient from blue to red.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	174.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The figure shows a SAR field distribution plot for the rear face of the device. Two antennas are highlighted: 802.11a_Ant 1 (green box) and LTE 26 (orange box). The plot shows the spatial distribution of the SAR field, with the highest values concentrated around the antennas. The background is a dark blue color, and the SAR field is represented by a color gradient from blue to red.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Top side	1.09	0	5.8	0.06	205.5	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Top side	1.09	0	5.8	0.06	148.6	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	205.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	171.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	204.8	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 26 Ch26965	Body	Rear Face	1.01	8.44	6.4	0.28	171.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report


A D T

LTE30

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	192.7	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	161.7	0.02	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Top side	0.89	-0.52	5.36	0.12	195.5	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Top side	0.89	-0.52	5.36	0.12	176.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	191.8	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The image shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 0' points to a high-intensity region on the left. An orange box labeled 'LTE 30' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	164.5	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The image shows a 3D visualization of the SAR field distribution for two antennas. A green box labeled '802.11a_Ant 1' points to a high-intensity region on the left. An orange box labeled 'LTE 30' points to a high-intensity region on the right. The background is a dark, semi-transparent model of a human head and neck.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Top side	0.89	-0.52	5.36	0.12	201.2	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Top side	0.89	-0.52	5.36	0.12	144.1	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	192.7	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	161.2	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	58.8	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	191.8	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 30 Ch27710	Body	Rear Face	1.17	7.48	5.36	0.4	161.2	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			




FCC SAR Test Report


A D T

LTE 41

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	215.1	0.01	SPLSR ≤ 0.04, Not required
802.11b ch11 Ant0			0.5	2.43	-13.23	0.15			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	188.3	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Rear Face	0.5	2.43	-13.23	0.15	66.8	0.03	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			1.18	8.64	-10.77	0.25			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40185	Body	Top side	0.94	0.41	5.61	0.06	196.9	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant0			0.03	2.2	-14	0.24			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40185	Body	Top side	0.94	0.41	5.61	0.06	178.6	0.01	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11b Ch11 Ant0	Body	Top Side	0.03	2.2	-14	0.24	25.7	0.04	SPLSR ≤ 0.04, Not required
802.11b Ch11 Ant1			0.93	0.32	-12.25	0.11			



FCC SAR Test Report


A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	213.3	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



The figure shows a 3D visualization of the SAR field distribution for two antennas. On the left, '802.11a_Ant 0' is highlighted with a green box, showing a localized field. On the right, 'LTE 41' is highlighted with an orange box, showing a more extensive field. A coordinate system with x, y, and z axes is visible in the center of the plot.

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	191.0	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			



The figure shows a 3D visualization of the SAR field distribution for two antennas. On the left, '802.11a_Ant 1' is highlighted with a green box, showing a localized field. On the right, 'LTE 41' is highlighted with an orange box, showing a more extensive field. A coordinate system with x, y, and z axes is visible in the center of the plot.


FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	75.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant1			0.69	8.6	-11.05	0.27			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40185	Body	Top side	0.94	0.41	5.61	0.06	203.7	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant0			0.14	-0.05	-14.75	0.35			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40185	Body	Top side	0.94	0.41	5.61	0.06	146.9	0.02	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch104 Ant0	Body	Top side	0.14	-0.05	-14.75	0.35	57.1	0.03	SPLSR ≤ 0.04, Not required
802.11a Ch104 Ant1			1.38	-0.45	-9.05	0.29			




FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	213.3	0.01	SPLSR ≤ 0.04, Not required
802.11a Ch116 Ant0			0.98	1.3	-12.8	0.2			



Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
LTE 41 Ch40620	Body	Rear Face	0.64	6.36	7.92	0.24	187.4	0.01	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			



FCC SAR Test Report

A D T

Conditions	Exposure Condition	Test Position	SAR Value (W/kg)	Coordinates			Peak Location Separation Distance (R _i , mm)	SPLSR	Simultaneous Transmission SAR Test
				x	y	z			
802.11a Ch116 Ant0	Body	Rear Face	0.98	1.3	-12.8	0.2	67.8	0.02	SPLSR ≤ 0.04, Not required
Bluetooth Ch39			0.34	7.75	-10.76	0.62			

Test Engineer : Chiajui Fu, and Terry Huang

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1013	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D835V2	4d121	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D1750V2	1055	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D1900V2	5d036	Jan. 26, 2015	1 Year
System Validation Dipole	SPEAG	D2300V2	1004	Jan. 27, 2015	1 Year
System Validation Dipole	SPEAG	D2450V2	737	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D2600V2	1020	Aug. 19, 2015	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Aug. 28, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 23, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3971	Mar. 26, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1431	Mar. 20, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1277	Jul. 22, 2015	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY50266628	Dec. 05, 2013	2 Years
Radio Communication Analyzer	Anritsu	MT8820C	6201300638	Jul. 29, 2015	1 Year
MXG Analog Signal Generator	Agilent	N5181A	MY50143868	Jul. 06, 2015	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 06, 2015	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 06, 2015	1 Year
Thermometer	YFE	YF-160A	110600361	Feb. 26, 2015	1 Year
Power Amplifier	AR	551G4	339656	Dec. 18, 2014	1 Year
Power Amplifier	mini-circuits	ZVE-8G	05770420A	Dec. 18, 2014	1 Year
Attenuator	Woken	00800A1G01L-03	N/A	Dec. 17, 2014	1 Year
Directional Coupler	Woken	0110A05602O-10	11122702	Dec. 17, 2014	1 Year

6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 11.2 %	± 10.4 %	
Expanded Uncertainty (K=2)						± 22.4 %	± 20.8 %	

Uncertainty budget for frequency range 300 MHz to 3 GHz

FCC SAR Test Report

A D T

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	√3	1	1	3.9	3.9	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	4.0	Rectangular	√3	1	1	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 12.3 %	± 11.5 %	
Expanded Uncertainty (K=2)						± 24.6 %	± 23.0 %	

Uncertainty budget for frequency range 3 GHz to 6 GHz

FCC SAR Test Report

7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan HwaYa EMC/RF/Safety/Telecom Lab:

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232

Fax: 886-3-327-0892

Taiwan LinKo EMC/RF Lab:

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180

Fax: 886-2-2605-1924

Taiwan HsinChu EMC/RF Lab:

Add: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343

Fax: 886-3-593-5342

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The road map of all our labs can be found in our web site also.

---END---



Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.



Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.



Appendix C. Calibration Certificate for Probe and Dipole

The SPEAG calibration certificates are shown as follows.



Appendix D. Photographs of EUT and Setup