FCC RF Test Report

APPLICANT : Sierra Wireless Inc.

EQUIPMENT: Radio Module

BRAND NAME : AirPrime

MODEL NAME : EM7565-9

FCC ID : N7NEM75L

STANDARD : FCC 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Sep. 19, 2017 and testing was completed on Oct. 06, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-E and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 1 of 20 Report Issued Date : Oct. 12, 2017

Report Version

Report Template No.: BU5-FWLTE Version 1.0

1190

: Rev. 01

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAI	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Feature of Equipment Under Test	5
	1.4	Modification of EUT	5
	1.5	Testing Site	6
	1.6	Applied Standards	6
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Test Mode	7
	2.2	Connection Diagram of Test System	8
	2.3	Support Unit used in test configuration and system	8
	2.4	Measurement Results Explanation Example	
	2.5	Frequency List of Low/Middle/High Channels	9
3	TES	T RESULT	10
	3.1	Conducted Output Power Measurement	10
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	11
	3.3	Emissions Mask Measurement	12
	3.4	Emissions Mask – Out Of Band Emissions Measurement	14
	3.5	Field Strength of Spurious Radiation Measurement	15
	3.6	Frequency Stability Measurement	17
4	LIST	OF MEASURING EQUIPMENT	19
5	UNC	ERTAINTY OF EVALUATION	20
ΑP	PEND	DIX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	DIX B. TEST RESULTS OF RADIATED TEST	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 2 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG791919D	Rev. 01	Initial issue of report	Oct. 12, 2017

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 3 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	FCC < 50+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	FCC < 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 46.11 dB at 2448.000 MHz for FCC
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 4 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 1.0

1 General Description

1.1 Applicant

Sierra Wireless Inc.

13811 Wireless Way Richmond, BC Canada V6V 3A4

1.2 Manufacturer

Sierra Wireless Inc.

13811 Wireless Way Richmond, BC Canada V6V 3A4

1.3 Feature of Equipment Under Test

WCDMA/LTE

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

SPORTON INTERNATIOINAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 5 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

1.5 Testing Site

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.						
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,						
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.						
lest Site Location	TEL: +886-3-327-3456						
	FAX: +886-3-328-4978						
Toot Site No	Sporton	Site No.					
Test Site No.	TH05-HY	03CH07-HY					

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA / EIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 6 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

Test Configuration of Equipment Under Test

Test Mode 2.1

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.


		Bandwidth (MHz)			Modulation		RB#			Test Channel						
Test Items	Band	1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	1	Half	Full	L	М	Н
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	٧	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v			v	v	>	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v		v	v		v
Emission masks - Out of band emissions	26	v	v	v	٧	v	-		v	v	v			v	V	v
Frequency Stability	26				v	v	-	v					v	v	v	
Radiated Spurious Emission	26	v	v	v	v	v	-	v			v			v	٧	v
Note	 The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. 															

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L

: 7 of 20 Page Number Report Issued Date: Oct. 12, 2017 Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$

$$= 4.2 + 10 = 14.2 (dB)$$

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 8 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report No.: FG791919D

Report Template No.: BU5-FWLTE Version 1.0

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List											
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest							
15	Channel	26765	-	-							
15	Frequency	821.5	-	-							
10	Channel	-	26740	-							
10	Frequency	-	819	-							
5	Channel	26715	26740	26765							
5	Frequency	816.5	819	821.5							
3	Channel	26705	26740	26775							
S	Frequency	815.5	819	822.5							
1.4	Channel	26697	26740	26783							
1.4	Frequency	814.7	819	823.3							

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 9 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 1.0

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 10 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 11 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

- (a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
- (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 $\log_{10}(f/6.1)$ decibels or 50 + 10 $\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
- (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 12 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 13 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 1.0

3.4 Emissions Mask - Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 14 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report No.: FG791919D

Report Template No.: BU5-FWLTE Version 1.0

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43+10log₁₀(P[Watts]) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 16 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report No.: FG791919D

Report Template No.: BU5-FWLTE Version 1.0

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three
 hours. Power was applied and the maximum change in frequency was recorded within one
 minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.


3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
- 2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
- 3. The variation in frequency was measured for the worst case.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 17 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 18 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 1.0

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 11, 2016	Sep. 19, 2017 ~ Oct. 04, 2017	Oct. 10, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 04, 2016	Sep. 19, 2017 ~ Oct. 04, 2017	Nov. 03, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30°C ~70°C	Aug. 28, 2017	Sep. 19, 2017 ~ Oct. 04, 2017	Aug. 27, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890089	1V~20V 0.5A~5A	Jan. 12, 2017	Sep. 19, 2017 ~ Oct. 04, 2017	Jan. 11, 2018	Conducted (TH05-HY)
Coupler	Warison	1-18GHz 20 dB 25WSM A Directiona I Coupler	#B	1G~18GHz	Feb. 20, 2017	Sep. 19, 2017 ~ Oct. 04, 2017	Feb. 19, 2018	Conducted (TH05-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	N/A	Sep. 23, 2017 ~ Oct. 06, 2017	N/A	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 23, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Aug. 22, 2018	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00 101800-30- 10P	1590075	1GHz ~ 18GHz	Apr. 25, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Apr. 24, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Mar. 13, 2018	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MX E)	MY5329005 3	20Hz to 26.5GHz	Jan. 12, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Jan. 11, 2018	Radiation (03CH07-HY)
Horn Antenna	ESCO	3117	00066584	1GHz~18GHz	Sep. 06, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Sep. 05, 2018	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Sep. 23, 2017 ~ Oct. 06, 2017	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Sep. 23, 2017 ~ Oct. 06, 2017	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA91705 84	18GHz- 40GHz	Nov. 08, 2016	Sep. 23, 2017 ~ Oct. 06, 2017	Nov. 07, 2017	Radiation (03CH07-HY)
Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	Jul. 17, 2018	Radiation (03CH07-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 22, 2017	Sep. 23, 2017 ~ Oct. 06, 2017	May 21, 2018	Radiation (03CH07-HY)

SPORTON INTERNATIOINAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 19 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 1.0

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	3.05
Confidence of 95% (U = 2Uc(y))	3.05

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

	rance and the second se
Measuring Uncertainty for a Level of	2.44
Confidence of 95% (U = 2Uc(y))	3.44

SPORTON INTERNATIOINAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: N7NEM75L Page Number : 20 of 20
Report Issued Date : Oct. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 1.0



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 26 Maximum Average Power [dBm]											
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
15	1	0		22.79	-	-					
15	1	37		22.65	-	-					
15	1	74		22.58	-	-					
15	36	0	QPSK	21.73	-	-					
15	36	20		21.69	-	-					
15	36	39		21.69	-	-					
15	75	0		21.76	1	-					
15	1	0		21.97	-	-					
15	1	37		21.95	-	-					
15	1	74		21.88	-	-					
15	36	0	16-QAM	20.74	-	-					
15	36	20		20.71	-	-					
15	36	39		20.68	-	-					
15	75	0		20.74	-	-					
15	1	0		20.97	-	-					
15	1	37		20.90	-	-					
15	1	74		20.81	-	-					
15	36	0	64-QAM	19.72	-	-					
15	36	20		19.74	-	-					
15	36	39		19.71	-	-					
15	75	0		19.75	-	-					
10	1	0		-	22.66	-					
10	1	25		-	22.61	-					
10	1	49		-	22.58	-					
10	25	0	QPSK	-	21.66	-					
10	25	12		-	21.63	-					
10	25	25		-	21.57	-					
10	50	0		-	21.59	-					
10	1	0		-	21.95	-					
10	1	25		-	21.90	-					
10	1	49		-	21.93	-					
10	25	0	16-QAM	-	20.65	-					
10	25	12		-	20.63	-					
10	25	25		-	20.58	-					
10	50	0		-	20.64	-					

10	1	0		-	20.82	-
10	1	25		-	20.76	-
10	1	49		-	20.80	-
10	25	0	64-QAM	-	19.67	-
10	25	12		-	19.66	-
10	25	25		-	19.57	-
10	50	0		-	19.64	-

LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	BW [MHz] RB Size RB Offset Mod Lowest Middle Highest									
5	1	0		22.63	22.58	22.68				
5	1	12		22.67	22.55	22.60				
5	1	24		22.54	22.51	22.59				
5	12	0	QPSK	21.68	21.61	21.71				
5	12	7		21.74	21.62	21.71				
5	12	13		21.73	21.57	21.64				
5	25	0		21.73	21.63	21.69				
5	1	0		21.95	21.92	21.94				
5	1	12		22.02	21.86	21.92				
5	1	24		21.87	21.85	21.88				
5	12	0	16-QAM	20.67	20.63	20.72				
5	12	7		20.78	20.64	20.71				
5	12	13		20.72	20.59	20.66				
5	25	0		20.73	20.61	20.67				
5	1	0		20.87	20.76	20.89				
5	1	12		20.88	20.70	20.94				
5	1	24		20.86	20.74	20.82				
5	12	0	64-QAM	19.80	19.61	19.71				
5	12	7		19.71	19.60	19.81				
5	12	13		19.62	19.51	19.74				
5	25	0		19.67	19.58	19.80				
3	1	0		22.60	22.58	22.72				
3	1	8		22.58	22.54	22.70				
3	1	14		22.65	22.52	22.69				
3	8	0	QPSK	21.66	21.60	21.80				
3	8	4		21.68	21.61	21.81				
3	8	7		21.72	21.55	21.78				
3	15	0		21.64	21.59	21.78				
3	1	0		21.92	21.89	22.03				
3	1	8		21.93	21.91	22.05				
3	1	14		22.00	21.83	21.98				
3	8	0	16-QAM	20.70	20.64	20.83				
3	8	4		20.72	20.65	20.86				
3	8	7		20.78	20.62	20.83				
3	15	0		20.65	20.59	20.81				

3	1	0		20.85	20.71	20.95
3	1	8		20.76	20.76	20.92
3	1	14		20.86	20.68	20.92
3	8	0	64-QAM	19.68	19.64	19.79
3	8	4		19.70	19.64	19.82
3	8	7		19.75	19.61	19.78
3	15	0		19.66	19.63	19.81



LTE Band 26 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest		
1.4	1	0		22.54	22.51	22.65		
1.4	1	3		22.63	22.57	22.72		
1.4	1	5		22.54	22.49	22.65		
1.4	3	0	QPSK	22.60	22.54	22.70		
1.4	3	1		22.65	22.60	22.75		
1.4	3	3		22.61	22.56	22.71		
1.4	6	0		21.58	21.54	21.69		
1.4	1	0	16-QAM	21.88	21.81	21.93		
1.4	1	3		21.96	21.88	22.02		
1.4	1	5		21.88	21.79	21.95		
1.4	3	0		21.63	21.60	21.76		
1.4	3	1		21.68	21.63	21.79		
1.4	3	3		21.64	21.55	21.72		
1.4	6	0		20.68	20.62	20.80		
1.4	1	0		20.74	20.69	20.88		
1.4	1	3		20.79	20.72	20.93		
1.4	1	5		20.70	20.69	20.85		
1.4	3	0	64-QAM	20.75	20.70	20.87		
1.4	3	1		20.81	20.75	20.91		
1.4	3	3		20.78	20.70	20.86		
1.4	6	0		19.62	19.56	19.71		


LTE Band 26_Part 90S


Peak-to-Average Ratio

Mode						
Mod.	QP	SK	160	Limit: 13dB		
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	-	-	-	-		
Middle CH	4.58	5.39	5.45	6.14	PASS	
Highest CH	-	-	-	-]	
Mode		LTE Band	26 / 10MHz			
Mode Mod.	640	LTE Band	26 / 10MHz		Limit: 13dB	
	64C 1RB		26 / 10MHz		Limit: 13dB Result	
Mod.		AM	26 / 10MHz -	-		
Mod. RB Size	1RB	PAM Full RB	26 / 10MHz - -	-		

Report No.: FG791919D

TEL: 886-3-327-3456 FAX: 886-3-328-4978






26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.24	1.23	3.06	2.99	4.84	4.87	-	-	14.24	14.51	-	-
Middle CH	1.23	1.23	3.04	3.04	4.92	4.94	9.81	9.71	-	-	-	-
Highest CH	1.24	1.23	2.99	3.03	4.92	4.86	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	26dB BV	V(MHz)				
BW	1.4MHz		3MHz		5M	lHz	101	ИHz	15N	ИHz	201	ЛHz
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.24	-	3.02	-	4.8	-	-	-	14.39	-	-	-
Middle CH	1.23	-	3.02	-	4.99	-	9.81	-	-	-	-	-
Highest CH	1.23	-	3.02	-	4.86	-	-	-	-	-	-	-

Report No.: FG791919D


TEL: 886-3-327-3456 FAX: 886-3-328-4978




LTE Band 26 Lowest Channel / 3MHz / QPSK Lowest Channel / 3MHz / 16QAM W V William I Ref Lovel 90.00 dbm Offset 10.80 db = RBW 100 kHz
Att 30 db SWT 19 µs = VBW 300 kHz Mode Auto FFT
SGL Count 100/100 15.41 dgr 816.33320 MH 26.00 di 3.056900000 MH 14.57 dB 10 dBm 267 273. -10 dBm 50 d8m Type | Ref | Trc | Type Ref Trc
 X-value
 Y-value
 Function

 816.3332 MHz
 15.41 dBm
 ndB down
 Middle Channel / 3MHz / QPSK Middle Channel / 3MHz / 16QAM TIME V W V 15.26 dBi 820.18080 Mi-26.00 d 3.039000000 Mi-269 CF 819.0 MHz Span 6.0 MHz Y-value 1 14.83 dBm 2 -11.04 dBm 1 -11.31 dBm Function m ndB down Type | Ref | Trc | Date 2 OCT 2017 13:55:23 Date: 2 OCT 2017 13:55:34 Highest Channel / 3MHz / QPSK Highest Channel / 3MHz / 16QAM THE V William V Offset 10.80 d8 • RBW 100 kHz SWT 19 μs • VBW 300 kHz Mode Auto FFT 15.99 dB 823.00350 AN 15.11 dBr 823,30320 MH CF 822.5 MH Function Result 2.991 MHz Type | Ref | Trc | Type | Ref | Trc | X-value Y-value Function 823.3032 MHz 15.11 dBm ndB down

TEL: 886-3-327-3456 FAX: 886-3-328-4978





: A26S-8 of 48

LTE Band 26 Lowest Channel / 1.4MHz / 64QAM Lowest Channel / 3MHz / 64QAM W V William I 270. 30.d8A 50 d8m -60 dBm Type | Ref | Trc |
 X-value
 Y-value
 Function

 814.9378 MHz
 12.10 dBm
 ndB down
 Middle Channel / 1.4MHz / 64QAM Middle Channel / 3MHz / 64QAM TIME TO SERVICE TO SER W V Ref Level 30.00 dBm

Att 30 dS

SGL Count 190/100

1Pk Max 13,40 dB 819,10350 MI 26,00 d 1,229000000 MI 667 15:30 dBn 819:87510 MH 26:00 dl 3:621000000 MH 271. CF 819.0 MH CF 819.0 MHz
 Y-value
 Function

 2
 13.40 dBm
 ndB down

 2
 -12.68 dBm
 ndB

 2
 -12.98 dBm
 Q factor
 Type | Ref | Trc | Date 2 OCT 2017 15:31:56 Date 2 OCT 2017 15 20 05 Highest Channel / 1.4MHz / 64QAM Highest Channel / 3MHz / 64QAM Ε ∀ Will W 00 dBm Offset 30 d8 SWT 10.80 dB **RBW** 30 kHz 63.2 μs **VBW** 100 kHz **Mode** Auto FFT .80 dB • RBW 100 kHz 19 µs • VBW 300 kHz Mode Auto FFT MITII 14,43 dBn 823,53700 MH 12.41 dBr 822.84130 Mi-30 dBm CF 822.5 MHz
 X-value
 Y-value
 Eunction

 822.8413 MHz
 12.41 dBm
 nd8 down

 822.693 MHz
 -13.66 dBm
 nd8

 823.921 MHz
 -13.44 dBm
 Q factor


 Marker
 Trc
 X-value
 Y-value
 Function


 M1
 1
 623.537 MHz
 14.43 dBm
 nd8 down

 T1
 1
 821.0135 MHz
 -11.64 dBm
 nd8

 T2
 1
 824.0285 MHz
 -11.25 dBm
 Q factor
 Type | Ref | Trc | Function Result

TEL: 886-3-327-3456 FAX: 886-3-328-4978





Date: 2.OCT.2017 15:27:35

: A26S-11 of 48

Occupied Bandwidth


Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.72	2.71	4.5	4.47	-	-	13.43	13.37	-	-
Middle CH	1.08	1.09	2.71	2.72	4.49	4.48	9.09	9.03	-	-	-	-
Highest CH	1.09	1.1	2.72	2.72	4.51	4.5	-	-	1	-	-	-

Report No.: FG791919D

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.09	-	2.73	-	4.52	-	-	-	13.49	-	-	-
Middle CH	1.1	-	2.72	-	4.46	-	9.01	-	-	-	-	-
Highest CH	1.09	-	2.72	-	4.49	-	-	-	-	-	-	-


SPORTON INTERNATIONAL INC. Page Number : A26S-12 of 48


TEL: 886-3-327-3456 FAX: 886-3-328-4978




1.085314685 MHz

TEL: 886-3-327-3456 FAX: 886-3-328-4978 1.099388699 MHz








Date: 2.OCT.2017 14:10:14

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Date: 2.OCT.2017 14:10:04


: A26S-16 of 48




Date: 2.OCT.2017 15:21:10

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Date: 2.OCT.2017 15:33:01





Conducted Band Edge

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A26S-20 of 48

